Tuscola Energy, Inc.

920 North Water Street, Suite 213 Bay City, Michigan 48708 DEQ-AQD NOV 28 2018 SAGINAW BAY

11/26/18

Mr. Matt Karl Air Quality Division Saginaw Bay District Office 401 Ketchum Street, Suite B Bay City, MI 48708

Re:

Response to November 5, 2018 Violation Notice: SRN P0202

Dear Mr. Karl

Below I have provided our responses to the Violation Notice.

Response to SRN P0202

Allegation	Response
PTI 9-11	The wind shroud has deteriorated over time and has caused it to tilt
FGFACILITY SC IV.2 – The	slightly. A new shroud has been made and will replace the old shroud.
wind shroud at the top of	Should be replaced by the end of November.
the flare was tilted and in	
bad shape.	
PTI 9-11	The well had been shut down. We replaced the gasket, but are waiting
FGFACILITY SC IV.3 – Visible	on the new lid.
vapor / mist was coming	
from the oil tank thief	
hatch	

Response to SRN P0199

Allegation	Response
PTI 6-11	The broken pipe was glued and put back together this summer. We
FGFACILITY SC IV.3 - The	have a new employee doing well inspections and he should be able to
line from the separator	find these problems soon after they happen.
pressure relief valve to the	
flare was broken off at the	
separator.	

Response to SRN N7954

Response

PTI 14-09E FGOILPRODUCTION SC IV.2 - The vent line from the separator pressure relief valve was open to the atmosphere. It should be connected directly to the flare.	The pressure relief valve will be connected before we begin producing from the McPherson well again. The well is currently hung up.
PTI 14-09D & E FGOILPRODUCTION SC II.1 – Data indicated the H2S feed rate to the flare exceeded the limit of 310 lbs per day, 21 times between June 17 and August 17, 2018.	This limit exceedance was first brought to the attention of Ben by myself. I was instructed to let him know when I noticed something that didn't make sense and that is exactly what I did. I showed Ben the data and even he couldn't make sense of it. We had made no changes in the operations of the well and all of a sudden it had begun to show 0.0 for 7-8 hours in the morning on some days starting on June 17 th . We had not exceeded our limit in 2018 until June 17 th .
August 17, 2016.	The meter also showed gas flows after we had shut the well in to increase the flare height. During the quarterly calibrations done by Trend Services, they mentioned that they had to clean some oil out of a tube in the meter. They think that is why it was giving off inaccurate readings.
	I do not believe that we exceeded the limit on any day.

Response to SRN N1586

Allegation	Response
PTI 20-12B	The wind shroud has deteriorated over time and has caused it to tilt
FGOILPRODUCTION SC IV.2	slightly. A new shroud has been made and will replace the old shroud.
– The wind shroud at the	Replacing the shroud has been on our list of things to do, but we didn't
top of the flare was tilted	plan on doing it until after we had the McPherson and B1/B2 flares
and in bad shape.	raised. We should have the new shroud installed by December 10 th .
PTI 20-12B	The drip tank is currently bypassed. We are looking to purchase a used
FGOILPRODUCTION SC IV.2	propane tank to replace the old drip tank. We are also looking to
- A spill was noted by the	purchase a few more drip tanks in case we have more drip tanks that
drip tank for the produced	spring leaks so they can easily be replaced. We should have the new
gas going to the flare. The	tanks in early December.
tank is bypassed.	

Please contact me if you have any questions.

Respectfully submitted,

Tuscola Energy, Inc.

By:

Jeffrey M. Adler - President