

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY  
AIR QUALITY DIVISION**

September 2, 2016

**PERMIT TO INSTALL  
85-84E**

**ISSUED TO**  
The C. Reiss Coal Company

**LOCATED AT**  
1010 3<sup>rd</sup> Avenue North  
Escanaba, Michigan

**IN THE COUNTY OF**  
Delta

**STATE REGISTRATION NUMBER**  
D0053

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

**August 12, 2016**

DATE PERMIT TO INSTALL APPROVED:

**September 2, 2016**

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

**PERMIT TO INSTALL**

**Table of Contents**

<b>Section</b>	<b>Page</b>
Alphabetical Listing of Common Abbreviations / Acronyms .....	2
General Conditions .....	3
Special Conditions .....	5
Emission Unit Summary Table.....	5
Special Conditions for EU-COALSCREENING.....	6
Special Conditions for EU-MATERIALS .....	8
Special Conditions for EU-BARGELOADING .....	10
Special Conditions for EU-WATERPUMP .....	12
Flexible Group Summary Table .....	14
Special Conditions for FG-DUSTGROUP .....	15

**Common Abbreviations / Acronyms**

<b>Common Acronyms</b>		<b>Pollutant / Measurement Abbreviations</b>	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO <sub>2</sub> e	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H <sub>2</sub> S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO <sub>x</sub>	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM10	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO <sub>2</sub>	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
  
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
  
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

**SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Installation Date / Modification Date	Flexible Group ID
EU-COALSCREENING	Coal screening plant with loading hopper and associated storage piles including conveyors and loading systems subject to New Source Performance Standards in 40 CFR Part 60 Subpart Y.	7-10-1984/ 9-2-2016	FG-DUSTGROUP
EU-MATERIALS	Transfer and storage of two groups of materials as defined below:  <b>No dust group:</b> logs, cut lumber, plywood, railroad ties, steel and steel products, pig iron, and chipped tires. <b>Potential dust group:</b> limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, lump and pelletized iron ore & copper ore.	7-10-1984/ 6-6-1988, 6-20-1991, 9-2-2016	FG-DUSTGROUP
EU-BARGELOADING	Self-loading barges and/or temporary box hopper and stacking conveyor (with diesel engine/generator <100 HP combined) loading material from stockpiles onto barges for transfer to off-site locations. The transfer of two groups of materials as defined below:  <b>No dust group:</b> logs, cut lumber, plywood, railroad ties, steel and steel products, pig iron, and chipped tires. <b>Potential dust group:</b> limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, lump and pelletized iron ore & copper ore.	7-2-2012/ 9-2-2016	FG-DUSTGROUP
EU-WATERPUMP	Diesel water pump (77.5 HP) for use as a backup to an electric water pump that supplies water to dust control portable spray towers and also to a dust control water truck. The portable towers and/or truck are used on an "as needed" basis as dictated by weather conditions, amount of materials in storage, and vehicular activity.	7-30-2004/ 12-18-2012	N/A

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.

**The following conditions apply to: EU-COALSCREENING**

**DESCRIPTION:** Coal screening plant with loading hopper and associated storage piles including conveyors and loading systems subject to New Source Performance Standards in 40 CFR Part 60 Subpart Y.

**Flexible Group ID:** FG-DUSTGROUP

**POLLUTION CONTROL EQUIPMENT:** Control of fugitive dust emissions through work practices, enclosure, and conveyor discharge chute.

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Visible Emissions	20 percent opacity	Test protocol*	EU-COALSCREENING	SC V.1	40 CFR 60.254(a)
*Test protocol shall specify averaging time.					

**II. MATERIAL LIMITS**

N/A

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall operate and maintain EU-COALSCREENING according to a *Fugitive Dust Control Plan for the Material Handling Operations at The C. Reiss Coal Company Dock 2 in Escanaba, Michigan*, for all coal screening and associated handling operations and screened coal storage areas. The permittee shall keep a copy of the *Fugitive Dust Control Plan* at the facility and make it available to the AQD District Supervisor upon request. **(R 336.1201, R 336.1901)**
2. The permittee shall not operate the coal screening plant in EU-COALSCREENING unless the wind speed is under 35 miles per hour. **(R 336.1201, R 336.1901)**
3. The permittee shall minimize the drop distance when unloading to EU-COALSCREENING storage piles throughout the entire unloading process. The drop distance shall be specified in the *Fugitive Dust Control Plan*. **(R 336.1201, R 336.1901)**
4. The permittee shall not operate the storage piles of EU-COALSCREENING unless fugitive emissions from the storage piles are controlled as described in the *Fugitive Dust Control Plan*. **(R 336.1201, R 336.1301, R 336.1901)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall equip and maintain the hopper portion of the coal screening plant in EU-COALSCREENING with a three sided enclosure to limit emissions of fugitive dust. **(R 336.1201, R 336.1301, R 336.1901)**
2. The permittee shall equip and maintain a chute on the discharge portion of the coal screening plant of EU-COALSCREENING to limit emissions of fugitive dust. **(R 336.1201, R 336.1301, R 336.1901)**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee has provided an initial performance test for an affected facility regulated under Standards of Performance for New Stationary Sources, 40 CFR Subparts A and Y. Until the affected facility is reconstructed or modified, additional performance tests are not required unless requested by the AQD. Visible emission observation procedures must have prior approval by the AQD. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD within 60 days following the last date of the evaluation. **(40 CFR 60.250(b), 40 CFR 60.255(a), 40 CFR 60.257)**

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep, in a satisfactory manner, records and information associated with the *Fugitive Dust Control Plan* as required by SC III.1. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> **(R 336.1201, R 336.1901)**
2. The permittee shall keep, in a satisfactory manner, records and information associated with the activity and control for each storage pile in EU-COALSCREENING as required by SC III.4. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> **(R 336.1201, R 336.1901)**

#### **VII. REPORTING**

N/A

#### **VIII. STACK/VENT RESTRICTIONS**

N/A

#### **IX. OTHER REQUIREMENTS**

1. The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and Y, as they apply to EU-COALSCREENING. **(40 CFR Part 60 Subparts A & Y)**

#### **Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).



**The following conditions apply to: EU - MATERIALS**

**DESCRIPTION:** Transfer and storage of two groups of materials as defined below:

**No dust group:** logs, cut lumber, plywood, railroad ties, steel and steel products, pig iron, and chipped tires.

**Potential dust group:** limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, lump and pelletized iron ore & copper ore.

**Flexible Group ID:** FG-DUSTGROUP

**POLLUTION CONTROL EQUIPMENT:** Control of fugitive dust emissions through work practices.

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Visible Emissions	10 percent opacity at wind speed <25 mph	Test protocol*	EU-MATERIALS	GC 13	R 336.1301(1)(c)
2. Visible Emissions	20 percent opacity at wind speed ≥25 mph	Test protocol*	EU-MATERIALS	GC 13	R 336.1301(1)(c)

\*Test protocol shall specify averaging time.

**II. MATERIAL LIMITS**

N/A

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall operate and maintain EU-MATERIALS according to a *Fugitive Dust Control Plan for the Material Handling Operations at The C. Reiss Coal Company Dock 2 in Escanaba, Michigan*, for all material handling operations and material storage areas, all plant roadways, and the plant yard. The permittee shall keep a copy of the *Fugitive Dust Control Plan* at the facility and make it available to the AQD District Supervisor upon request. **(R 336.1201, R 336.1901)**
2. The permittee shall minimize the drop distance when unloading limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, or lump and pelletized iron ore & copper ore to EU-MATERIALS storage piles throughout the entire unloading process. The drop distance shall be specified in the *Fugitive Dust Control Plan*. **(R 336.1201, R 336.1901)**
3. The permittee shall not operate the storage piles of EU-MATERIALS unless fugitive emissions from the storage piles are controlled as described in the *Fugitive Dust Control Plan*. **(R 336.1201, R 336.1301, R 336.1901)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

N/A

**V. TESTING/SAMPLING**

N/A

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall keep, in a satisfactory manner, records and information associated with the *Fugitive Dust Control Plan* as required by SC III.1. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> (R 336.1201, R336.1901)
2. The permittee shall keep, in a satisfactory manner, records and information associated with the activity and control for each storage pile in EU-MATERIALS as required by SC III.3. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> (R 336.1201, R 336.1901)

**VII. REPORTING**

N/A

**VIII. STACK/VENT RESTRICTIONS**

N/A

**IX. OTHER REQUIREMENTS**

N/A

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**The following conditions apply to: EU-BARGELOADING**

**DESCRIPTION:** Self-loading barges and/or temporary box hopper and stacking conveyor (with diesel engine/generator <100 HP combined) loading material from stockpiles onto barges for transfer to off-site locations. The transfer of two groups of materials as defined below:

**No dust group:** logs, cut lumber, plywood, railroad ties, steel and steel products, pig iron, and chipped tires.

**Potential dust group:** limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, lump and pelletized iron ore & copper ore.

**Flexible Group ID:** FG-DUSTGROUP

**POLLUTION CONTROL EQUIPMENT:** Control fugitive dust emissions through work practices.

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Visible Emissions	10 percent opacity at wind speed <25 mph	Test protocol*	EU-BARGELOADING	GC 13	R 336.1301(1)(c)
2. Visible Emissions	20 percent opacity at wind speed ≥25 mph	Test protocol*	EU-BARGELOADING	GC 13	R 336.1301(1)(c)

\*Test protocol shall specify averaging time.

**II. MATERIAL LIMITS**

N/A

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall not retain the diesel powered portable box hopper and stacking conveyor in EU-BARGELOADING at the site for more than 12 consecutive months. **(40 CFR Part 60 Subpart IIII, 40 CFR Part 63 Subpart ZZZZ)**
2. The permittee shall operate and maintain the portable box hopper and stacking conveyor in EU-BARGELOADING according to a *Fugitive Dust Control Plan for the Material Handling Operations at The C. Reiss Coal Company Dock 2 in Escanaba, Michigan*, for all material handling operations and material storage areas, all plant roadways, and the plant yard. The permittee shall keep a copy of the *Fugitive Dust Control Plan* at the facility and make it available to the AQD District Supervisor upon request. **(R 336.1201, R 336.1901)**
3. The permittee shall minimize the drop distance from the portable box hopper and stacking conveyor or self-loading barge equipment when loading limestone, rock salt, wood chips, wood pulp, sawdust, pelletized or solidified biomass fuel, trap rock, armor rock, railroad ballast, aggregate, washed or unwashed sand & gravel, metallurgical coke, petroleum coke, unscreened coal, slag and slag products, or lump and pelletized iron ore & copper ore throughout the entire barge loading process. The drop distance shall be specified in the *Fugitive Dust Control Plan*. **(R 336.1201, R 336.1901)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

N/A

**V. TESTING/SAMPLING**

N/A

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep, in a satisfactory manner, records and information associated with the *Fugitive Dust Control Plan* as required by SC III.2. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> **(R 336.1205, R 336.1901)**
2. The permittee shall keep, in a satisfactory manner, records and information associated with the presence on site of the portable box hopper and stacking conveyor in EU-BARGELOADING as required by SC III.1. The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> **(R 336.1205, 40 CFR Part 60 Subpart IIII, 40 CFR Part 63 Subpart ZZZZ)**

**VII. REPORTING**

N/A

**VIII. STACK/VENT RESTRICTIONS**

N/A

**IX. OTHER REQUIREMENTS**

N/A

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**The following conditions apply to: EU-WATERPUMP**

**DESCRIPTION:** Diesel water pump (77.5 HP) for use as a backup to an electric water pump that supplies water to dust control portable spray towers and also to a dust control water truck. The portable towers and/or truck are used on an "as needed" basis as dictated by weather conditions, amount of materials in storage, and vehicular activity.

**Flexible Group ID:** N/A

**POLLUTION CONTROL EQUIPMENT:** N/A

**I. EMISSION LIMITS**

N/A

**II. MATERIAL LIMITS**

N/A

**III. PROCESS/OPERATIONAL RESTRICTIONS**

N/A

**IV. DESIGN/EQUIPMENT PARAMETERS**

N/A

**V. TESTING/SAMPLING**

N/A

**VI. MONITORING/RECORDKEEPING**

N/A

**VII. REPORTING**

N/A

**VIII. STACK/VENT RESTRICTIONS**

N/A

**IX. OTHER REQUIREMENTS**

1. The permittee shall comply with all provisions of the National Emission Standards for Hazardous Air Pollutants as specified in 40 CFR Part 63 Subparts A and ZZZZ, as they apply to EU-WATERPUMP. **(40 CFR Part 63 Subparts A & ZZZZ)**

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**FLEXIBLE GROUP SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FG-DUSTGROUP	Flexible group of emission units necessitating a wind speed monitor. Opacity limits or operational restrictions of these emission units are contingent on wind speed.	EU-COALSCREENING, EU-MATERIALS, and EU-BARGELOADING

**The following conditions apply to: FG-DUSTGROUP**

**DESCRIPTION:** Flexible group of emission units necessitating a wind speed monitor. Opacity limits or operational restrictions of these emission units are contingent on wind speed.

**Emission Units:** EU-COALSCREENING, EU-MATERIALS, and EU-BARGELOADING

**POLLUTION CONTROL EQUIPMENT:** N/A

**I. EMISSION LIMITS**

N/A

**II. MATERIAL LIMITS**

N/A

**III. PROCESS/OPERATIONAL RESTRICTIONS**

N/A

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall calibrate, maintain and operate in a satisfactory manner, a device to monitor and record the wind speed on site at the facility on a continuous basis. **(R 336.1201, R 336.1301, R 336.1901)**

**V. TESTING/SAMPLING**

N/A

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall continuously monitor and record, in a satisfactory manner, the wind speeds on site at the facility. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1201, R 336.1301, R 336.1901)**
2. The permittee shall keep, in a satisfactory manner, a log of the downtime of the wind speed monitoring device. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1201, R 336.1301, R 336.1901)**



**VII. REPORTING**

N/A

**VIII. STACK/VENT RESTRICTIONS**

N/A

**IX. OTHER REQUIREMENTS**

N/A

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).