## MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

February 27, 2007

# PERMIT TO INSTALL

114-95A



LOCATED AT 28178 Hayes Road Roseville, Michigan

IN THE COUNTY OF Macomb

## STATE REGISTRATION NUMBER B5635

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: February 13, 2007			
DATE PERMIT TO INSTALL APPROVED:	SIGNATURE:		
February 27, 2007			
DATE PERMIT VOIDED:	SIGNATURE:		
DATE PERMIT REVOKED:	SIGNATURE:		

## PERMIT TO INSTALL

## Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	
General Conditions	4
Emission Unit Identification	6
Flexible Group Identification	6
Flexible Group Special Conditions	6

### **Common Abbreviations / Acronyms**

		Pollutant/Measurement Abbreviations			
Common Acronyms					
AQD ANSI	Air Quality Division American National Standards Institute	Btu °C			
BACT	Best Available Control Technology	co	Degrees Celsius Carbon Monoxide		
CAA	Clean Air Act	dscf			
CAA CEM			Dry standard cubic foot		
	Continuous Emission Monitoring	dscm °F	Dry standard cubic meter		
CFR	Code of Federal Regulations		Degrees Fahrenheit Grains		
COM EPA	Continuous Opacity Monitoring	gr Lla			
EU	Environmental Protection Agency Emission Unit	Hg	Mercury Hour		
FG		hr LLS			
	Flexible Group	H <sub>2</sub> S	Hydrogen Sulfide		
GACS	Gallon of Applied Coating Solids	hp	Horsepower		
GC	General Condition	lb	Pound		
HAP	Hazardous Air Pollutant	m	Meter		
HVLP	High Volume Low Pressure *	mg	Milligram		
ID	Identification	mm	Millimeter		
LAER	Lowest Achievable Emission Rate	MM	Million		
MACT	Maximum Achievable Control	MW	Megawatts		
MAERS	Technology Michigan Air Emissions Reporting	NOx	Oxides of Nitrogen		
	System				
MAP	Malfunction Abatement Plan	PM	Particulate Matter		
MDEQ	Michigan Department of Environmental Quality	PM- 10	Particulate Matter less than 10 microns diameter		
MIOSHA	Michigan Occupational Safety & Health	pph	Pound per hour		
	Administration	PPI			
MSDS	Material Safety Data Sheet	ppm	Parts per million		
NESHA P	National Emission Standard for Hazardous Air Pollutants	ppmv	Parts per million by volume		
NSPS	New Source Performance Standards	ppmw	Parts per million by weight		
NSR	New Source Review	psia	Pounds per square inch absolute		
PS	Performance Specification	psig	Pounds per square inch gauge		
PSD	Prevention of Significant Deterioration	scf	Standard cubic feet		
PTE	Permanent Total Enclosure	sec	Seconds		
PTI	Permit to Install	SO <sub>2</sub>	Sulfur Dioxide		
RACT	Reasonable Available Control	THC	Total Hydrocarbons		
	Technology		-		
ROP	Renewable Operating Permit	tpy	Tons per year		
SC	Special Condition Number	μg	Microgram		
SCR	Selective Catalytic Reduction	VOC	Volatile Organic Compounds		
SRN	State Registration Number	yr	Year		
TAC	Toxic Air Contaminant				
VE	Visible Emissions				

\* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

#### GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **[R336.1201(1)]**
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **[R336.1201(4)]**
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. [R336.1201(6)(b)]
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. [R336.1201(8), Section 5510 of Act 451, PA 1994]
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **[R336.1219]**
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **[R336.1901]**
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition required in Rule 912(5). [R336.1912]

- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R336.1303. **[R336.1301]** 
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this permit to install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R336.1370(2). **[R336.1370]**
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R336.2001 and R336.2003, under any of the conditions listed in R336.2001. **[R336.2001]**

#### SPECIAL CONDITIONS

#### **Emission Unit Identification**

Emission Unit ID Emission Unit Description		Stack Identification	
	Natural gas-fired aluminum melting furnace #5	NA	
EUFURNACE5	East with a bath capacity of 3,000 lbs and a		
	melting capacity of 600 lbs per hour.		
	Natural gas-fired aluminum melting furnace #6		
EUFURNACE6	West with a bath capacity of 3,000 lbs and a	NA	
	melting capacity of 600 lbs per hour.		
Changes to the equipment described in this table are subject to the requirements of R336.1201,			
except as allowed by R336.1278 to R336.1290.			

#### Flexible Group Identification

Flexible Group ID Emission Units Included in Flexible Group		Stack Identification
FGMELTING	EUFURNACE5 and EUFURNACE6	
FGFACILITY	All process equipment at the facility including equipment covered by other permits, grand- fathered equipment and exempt equipment.	

#### The following conditions apply to: FGMELTING

#### **Emission Limits**

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
1.1	Particulate	FGMELTING	0.10 lb/1000 lbs of exhaust gases on a dry gas basis	Test Protocol	GC 13	R336.1331

#### Material Usage Limits

1.2 The permittee shall not charge fluxing materials in FGMELTING. [R336.1225]

#### The following conditions apply to: FGFACILITY

2.1 The permittee shall melt only clean charge, customer returns, or internal scrap, as defined by 40 CFR Part 63 Subpart RRR. This condition is necessary to avoid requirements of 40 CFR Part 63 Subpart RRR, National Emission Standards for Secondary Aluminum Production. [R336.1224 and R336.1225, 40 CFR Part 63 Subpart RRR]

2.2 The permittee shall not install or operate any sweat furnace, thermal chip dryer, or scrap dryer / delacquering kiln / decoating kiln at any location in the facility. This condition is necessary to avoid requirements of 40 CFR Part 63 Subpart RRR, National Emission Standards for Secondary Aluminum Production. [40 CFR Part 63 Subpart RRR]

#### Recordkeeping/Reporting/Notification

2.3 The permittee shall keep records of the monthly tonnage of aluminum melted in tons per month. Such records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1205 (3), R336.1225]**