SUPPLEMENT TO PERMIT NO. 292-96 Timber Products Michigan Munising, Michigan

January 2, 1997

GENERAL CONDITIONS

- 1. Rule 201(1) The process or process equipment covered by this permit shall not be reconstructed, relocated, altered, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule.
- 2. Rule 201(4) If the installation, reconstruction, relocation, or alteration of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the person to whom this permit was issued, or the designated authorized agent, shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, reconstruction, relocation, or alteration of the equipment allowed by this Permit to Install.
- 3. Rule 201(6)(a) If this Permit to Install is issued for a process or process equipment located at a stationary source which is subject to a Renewable Operating Permit pursuant to Rule 210, trial operation is allowed if the equipment performs in accordance with the terms and conditions of this Permit to Install and until the appropriate terms and conditions of this Permit to Install have been incorporated into the Renewable Operating Permit as a modification pursuant to Rule 216 or upon renewal pursuant to Rule 217. Upon incorporation of the appropriate terms and conditions into the Renewable Operating Permit, this Permit to Install shall become void.
- 4. Rules 201(6)(b)(i) or 216(1)(a)(v)(A) Except as provided in General Condition No. 3, operation of the process or process equipment is allowed if, not more than 30 days after completion of the installation, construction, reconstruction, relocation, alteration, or modification authorized by this Permit to Install, the person to whom this Permit to Install was issued, or the authorized agent pursuant to Rule 204, notifies the District Supervisor, Air Quality Division, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, alteration, or modification is considered to occur not later than commencement of trial operation of the process or process equipment.
- 5. Rule 201(6)(b)(ii) Except as provided in General Condition No. 3, not more than 18 months after completion of the installation, construction, reconstruction, relocation, alteration, or modification authorized by this Permit to Install, the person to whom this permit was issued, or the authorized agent pursuant to Rule 204, shall notify the District Supervisor, Air Quality Division, in writing, of the status of compliance of the process or process equipment with the terms and conditions of the Permit to Install. The notification shall include all of the following:

Timber Products Michigan Permit No. 292-96 Page 2 01/02/97

- A. The results of all testing, monitoring, and recordkeeping performed to determine the actual emissions from the process or process equipment and to demonstrate compliance with the terms and conditions of the Permit to Install.
- B. A schedule of compliance for the process or process equipment as described in Rule 119(a).
- C. A statement, signed by the person owning or operating the process or process equipment, that, based on information and belief formed after reasonable inquiry, the statements and information in the notification are true, accurate, and complete.
- 6. Rule 201(7) and Section 5510 of Act 451, P.A. 1994 The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Departments' rules or the Clean Air Act.
- 7. Rule 219 The terms and conditions of this permit to install shall apply to any person or legal entity that now or hereafter owns or operates the process equipment at the location authorized by this permit to install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required in Rule 219(a), (b), and (c). The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality.
- 8. Rule 901 Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property.
- 9. Rule 912 The owner or operator of a source, process, or process equipment shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant in excess of standards for more than one hour, or of any air contaminant in excess of standards for more than two hours, as required in this rule, to the District Supervisor, Air Quality Division. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the District Supervisor within 10 days, with the information required in this rule.
- Approval of this permit does not exempt the person to whom this permit was issued from complying with any future regulations which may be promulgated under Part 55 of Act 451, P.A. 1994.
- 11. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 12. Operation of this equipment may be subject to other requirements of Part 55 of Act 451, P.A. 1994, and the rules promulgated thereunder.

Timber Products Michigan Permit No. 292-96 Page 3 01/02/97

SPECIAL CONDITIONS

- 13. Visible emissions from Boilers #1, #2, #3 and #4 shall not exceed a 6-minute average of 20% opacity, except as specified in Rule 301(1)(a).
- 14. Rule 331 The particulate emission from wood-fired Boiler #1 shall not exceed 0.50 pounds per 1000 pounds of exhaust gases, corrected to 50% excess air.
- 15. Rule 331 The particulate emission from wood-fired Boiler #2 shall not exceed 0.50 pounds per 1000 pounds of exhaust gases, corrected to 50% excess air.
- 16. Rule 331 The particulate emission from wood-fired Boiler #3 shall not exceed 0.50 pounds per 1000 pounds of exhaust gases, corrected to 50% excess air.
- 17. Rule 331 The particulate emission from wood-fired Boiler #4 shall not exceed 0.50 pounds per 1000 pounds of exhaust gases, corrected to 50% excess air.
- 18. Wood fuel usage in Boilers #1, #2, #3, and #4 combined shall not exceed 44,500 tons per year, based on a 12-month rolling average calculated at the end of each calendar month.
- 19. Permittee shall maintain monthly records of the 12-month rolling average wood fuel usage for Boilers #1, #2, #3, and #4 combined to demonstrate compliance with the wood fuel usage limitation of Condition 18. Permittee may calculate the wood fuel usage using the measured surrogate parameter of boiler feedwater flow, with a conversion factor of 3.0 pounds of boiler feedwater per pound of wood fuel. All such 12-month rolling average records shall contain both the measured boiler feedwater flow and the corresponding calculated wood fuel usage rate. These records shall be kept on file for a period of at least two years and be made available to the Air Quality Division upon request.
- 20. Used oil shall be burned only in Boiler #3.
- 21. Permittee shall not burn more than two gallons per hour, nor more than 160 gallons per month, of used oil in Boiler #3. Used oil shall be limited to on-site generated used oil.
- 22. Permittee shall record the amount of used oil burned in Boiler #3 for each calendar month. All such records shall be kept on file for a period of at least two years and made available to the Air Quality Division upon request.
- 23. Permittee shall not burn used oil in Boiler #3 if the level of total halogen content of the used oil exceeds 1000 parts per million.
- 24. Within 120 days after written notification from the District Supervisor, applicant shall submit an analysis of the used oil fired in Boiler #3.
- 25. Exhaust gases from Boiler #3 shall be discharged unobstructed vertically upwards to the ambient air from a stack with a maximum diameter of 36 inches at an exit point not less than 60 feet above ground level.

Timber Products Michigan Permit No. 292-96 Page 4 01/02/97

- 26. Exhaust gases from Boiler #4 shall be discharged unobstructed vertically upwards to the ambient air from a stack with a maximum diameter of 54 inches at an exit point not less than 55 feet above ground level.
- 27. Visible emissions from the sawmill, veneer mill, planer, and hydraulic ladder shall not exceed a 6-minute average of 20% opacity, except as specified in Rule 301(1)(a).
- 28. Rule 331 The particulate emission from the sawmill, veneer mill, planer, and hydraulic ladder shall not exceed 0.10 pounds per 1000 pounds of exhaust gases. This limit applies to each exhaust point separately.
- 29. Verification of particulate emission rates from Boilers #1, #2, #3, #4, and from individual exhaust points at the sawmill, veneer mill, planer, and hydraulic ladder by testing, at owner's expense, in accordance with Department requirements, may be required for operating approval. Verification of emission rates includes the submittal of a complete report of the test results. If testing is required, stack testing procedures and the location of stack testing ports must have prior approval by the Air Quality Division, and results shall be submitted within 120 days of the written requirement for such verification.
- 30. Permittee shall not operate Boiler #1, #2, #3, #4, sawmill, veneer mill, planer, or hydraulic ladder unless its respective dust collector is installed and operating properly.
- 31. Collected dust shall be removed from the dust collectors as necessary to maintain the dust collectors at the required operating efficiency.
- 32. The disposal of collected air contaminants and/or waste powder adhesive shall be performed in a manner which minimizes the introduction of air contaminants to the outer air.
- 33. Permittee shall not use more than 5,000 pounds per month of adhesive in the veneer splicing operation.
- 34. Permittee shall maintain records to verify that adhesive usage is in compliance with the usage limit of Condition 33. These records shall be kept on file for a period of at least two years and made available to the Air Quality Division upon request.
- 34. Permittee shall not substitute any adhesive for that described in this permit which would result in an appreciable change in the quality or any appreciable increase in the quantity of the emission of an air contaminant, without prior notification to and approval by the Air Quality Division.