SUPPLEMENT to PERMIT No. 124-01 Paint Work, Inc. Warren, Michigan June 6, 2001

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, altered, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. [R 336.1201(1)]
- 2. If the installation, reconstruction, relocation, or alteration of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the person to whom this permit was issued, or the designated authorized agent, shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, PO Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, reconstruction, relocation, or alteration of the equipment allowed by this Permit to Install. [R 336.1201(4)]
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. [R 336.1201(6)(b)]
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. [R 336.1201(8), Section 5510 of Act 451, PA 1994]
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. [R 336.1219]
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. [R 336.1901]
- 7. The owner or operator of a source, process, or process equipment shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant in excess of standards for more than one hour, or of any air contaminant in excess of standards for more than two hours, as required in this rule, to the District Supervisor, Air Quality Division. The notice shall be provided no later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the District Supervisor within ten days, with the information required in this rule. [R 336.1912]

Paint Work, Inc. Permit No. 124-01 Page 2 of 8 June 6, 2001

- 8. Approval of this permit does not exempt the person to whom this permit was issued from complying with any future applicable requirements which may be promulgated under Part 55 of Act 451, PA 1994 of the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of Act 451, PA 1994, and the rules promulgated thereunder.
- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, a person shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. [R 336.1301]
- 12. A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - a) A visible emission limit specified by an applicable federal new source performance standard.
 - b) A visible emission limit specified as a condition of this permit to install.
- 13. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). [R 336.1370]
- 14. Except as allowed by Rule 285 (a), (b), and (c), applicant shall not substitute any fuels, coatings, nor raw materials for those described in the application and allowed by this permit, nor make changes to the process or process equipment described in the application, without prior notification to and approval by the Air Quality Division. [R 336.1201(1)]
- 15. The Department may require the applicant to conduct acceptable performance tests, at the applicant's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. [R 336.2001]

SPECIAL CONDITIONS

Emission Unit Identification

Emission Unit (EU)	Emission Unit Description	Stack ID	
	Booth No. 1 (Line No. 1)	SV_Booth_01-01	
EU_Line-01	BOOTH NO. 1 (LINE NO. 1)	SV_Booth_01-02	
	Electric Oven (Bake Line)	SV_ElectricOven	
EU_Line-02	Booth No. 3	SV_Booth_03	
	Natural Gas Oven	SV_NatGasOven	

Flexible Group Identification

Flexible Group (FG)	Emission Units Included in Flexible Group
FG_Lines	EU_Line-01 and EU_Line-02
FG_SS	The Stationary Source (All Permitted, Exempted, and Grandfathered Emission Units)

EU Line-01

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirements
1.	VOCs	EU_Line-01	≤ 2,000 Pounds	Per Calendar Month	Special Condition Nos. 3 and 4	R336.1225, R336.1702(d)
2.	VOCs	EU_Line-01	≤ 10 Tons	Per 12-Month Rolling Time Period	Special Condition Nos. 3 and 4	R336.1205, R336.1702(d)

Recordkeeping/Reporting/Notification

- 3. The permittee shall keep the following information on a calendar month basis for the EU_Line-01:
 - a) Gallons (with water) of each material (material (paint, coating, catalyst, reducer, cleanup solvent, etc.) used.
 - b) The VOC content, in pounds per gallon, of each material used.
 - VOC mass emission calculations determining the monthly emission rate in tons per month.
 - d) VOC mass emission calculations determining the yearly emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1225, R336.1702(a & d), R336.1901]

Paint Work, Inc. Permit No. 124-01 Page 4 of 8 June 6, 2001

- 4. The permittee shall keep the following information on a calendar month basis for the use of clean-up and purge solvents associated with the EU_Line-01:
 - a) Gallons of each solvent used and reclaimed.
 - b) The VOC content, in pounds per gallon, of each solvent used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per month.
 - d) VOC mass emission calculations determining the yearly emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1225, R336.1702(a & d), R336.1901]

Stacks/Vents Restrictions

5. The exhaust gases from the EU_Line-01 shall be discharged unobstructed vertically upwards to the ambient air from stacks with the dimensions listed in the table below.

Process Equipment	Stack ID	Minimum Stack Height (feet)	Maximum Stack Diameter (inches)	Applicable Requirements	
Booth No. 1	SV_Booth_01-01	29.0	24.0	R336.1225, R336.1901,	
				40 CFR 52.21 Subparts (c) & (d)	
Booth No. 1	SV_Booth_01-02	29.0	24.0	R336.1225, R336.1901,	
				40 CFR 52.21 Subparts (c) & (d)	
Electric Oven	SV_ElectricOven	22.5	18.0	R336.1225, R336.1901,	
				40 CFR 52.21 Subparts (c) & (d)	

EU Line-02

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirements
6.	VOCs	EU_Line-02	\leq 2,000 Pounds	Per Calendar Month	Special Condition Nos. 8 and 9	R336.1225, R336.1702(d)
7.	VOCs	EU_Line-02	≤ 10 Tons	Per 12-Month Rolling Time Period	Special Condition Nos. 8 and 9	R336.1205, R336.1702(d)

Paint Work, Inc. Permit No. 124-01 Page 5 of 8 June 6, 2001

Recordkeeping/Reporting/Notification

- 8. The permittee shall keep the following information on a calendar month basis for the EU_Line-02:
 - a) Gallons (with water) of each material used.
 - b) The VOC content, in pounds per gallon, of each material used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per month.
 - d) VOC mass emission calculations determining the yearly emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1225, R336.1702(a & d), R336.1901]

- 9. The permittee shall keep the following information on a calendar month basis for the use of clean-up and purge solvents associated with the EU_Line-02:
 - a) Gallons of each solvent used and reclaimed.
 - b) The VOC content, in pounds per gallon, of each solvent used.
 - VOC mass emission calculations determining the monthly emission rate in tons per month.
 - d) VOC mass emission calculations determining the yearly emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1225, R336.1702(a & d), R336.1901]

Stacks/Vents Restrictions

10. The exhaust gases from the EU_Line-02 shall be discharged unobstructed vertically upwards to the ambient air from stacks with the dimensions listed in the following table.

Process Equipment	Stack ID	Minimum Stack Height (feet)	Maximum Stack Diameter (inches)	Applicable Requirements	
Booth No. 3	SV_Booth-03	29.0	36.0	R336.1225, R336.1901,	
				40 CFR 52.21 Subparts (c) & (d)	
Natural Gas	SV_NatGasOven	24.5	12.0	R336.1225, R336.1901,	
Oven				40 CFR 52.21 Subparts (c) & (d)	

FG Lines

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirements
11.	VOCs	FG_Lines	126.7 Pounds	Per Calendar Day	Special Condition Nos. 19	R336.1225, R336.1702(d)

Process/Operational Limits

- 12. The permittee shall recover and reclaim, recycle, or dispose of, in accordance with all applicable regulations, a minimum of 36 percent by weight of all purge solvents used for the FG_Lines. [R336.1225, R336.1702(a), R336.1901]
- 13. All waste material shall be captured and stored in closed containers and shall be disposed of in an acceptable manner in compliance with all applicable rules and regulations. [R336.1225, R336.1702, R336.1901]
- 14. The disposal of spent filters shall be performed in a manner, which minimizes the introduction of air contaminants to the outer air. [R336.331, R336.1901]

Equipment

- 15. The permittee shall not operate the booth portions of the FG_Lines unless all respective exhaust filters are installed and operating properly. [R336.1301, R336.1331, R336.1901, R336.1910]
- 16. The permittee shall equip and maintain the booth booth portions of the FG_Lines with High Volume Low Pressure (HVLP) or equivalent technology with comparable transfer efficiency. For HVLP applicators the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig) and the permittee shall keep test caps available for pressure testing. [R336.1702(a)]

Testing

17. The VOC content, water content, and density of any material as applied and as received shall be determined using federal Reference Test Method 24. Alternatively, for waterborne materials, the VOC content may be determined from formulation data upon written approval by the Air Quality Division District Supervisor. If the Method 24 and the formulation values should

Paint Work, Inc. Permit No. 124-01 Page 7 of 8 June 6, 2001

differ, then the Method 24 results shall be used to determine compliance. [R336.1225, R336.1702, R336.1901]

Recordkeeping/Reporting/Notification

- 18. The permittee shall maintain a current listing form the manufacturer of the chemical composition of each coating, catalyst, reducer, cleanup solvent, *etc.*, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. [R336.1225, R336.1702, R336.1901]
- 19. The permittee shall keep the following information on a calendar day basis for the FG_Lines:
 - a) Gallons (with water) of each material used.
 - b) The VOC content, in pounds per gallon, of each material used.
 - c) VOC mass emission calculations determining the daily emission rate in pounds per day.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1225, R336.1702(a & d), R336.1901]

FG SS

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirements
20.	Each Individual HAP	FG_SS	< 9.0 Tons	Per 12-Month Rolling Time Period	Special Condition No. 24	R336.205(3)
21.	Aggregate HAPs	FG_SS	< 22.5 Tons	Per 12-Month Rolling Time Period	Special Condition No. 24	R336.205(3)

Testing

22. The HAP content of any material as applied and as received shall be determined using manufacturer's formulation data. Upon request of the Air Quality Division District Supervisor, the HAP content of the manufacturer's formulation data shall be verified using Method 311. [R336.1225, R336.1901]

Recordkeeping/Reporting/Notification

23. The permittee shall maintain a current listing form the manufacturer of the chemical composition of each material including the weight percent of each component. The data may consist of

Paint Work, Inc. Permit No. 124-01 Page 8 of 8 June 6, 2001

Material Safety Data Sheets, manufacturer's formulation data, or both. [R336.1225, R336.1702, R336.1901]

- 24. The permittee shall keep the following information on a calendar month basis for the stationary source:
 - a) Gallons or pounds of each material used.
 - b) Where applicable, the gallons or pounds of each material reclaimed.
 - c) The HAP content, in pounds per gallon or pounds per pound, of each material used.
 - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per month.
 - e) Individual and aggregate HAP emission calculations determining the yearly emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month.

The records are for the purpose of compliance demonstration and shall be kept in the format approved by the Air Quality Division District Supervisor. All records shall be kept on file for a period of at least five years and be made available to the Department upon request. [R336.1205(3), R336.1225, R336.1702(a & d), R336.1901]