# MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

December 5, 2006

## PERMIT TO INSTALL 343-06

**ISSUED TO** 

Nissan Technical Center North America, Inc.

**LOCATED AT** 

39001 Sunrise Drive Farmington Hills, Michigan

IN THE COUNTY OF

Oakland

## STATE REGISTRATION NUMBER N7727

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

November 16, 2006				
DATE PERMIT TO INSTALL APPROVED:	SIGNATURE:			
December 5, 2006				
DATE PERMIT VOIDED:	SIGNATURE:			
DATE PERMIT REVOKED:	SIGNATURE:			

## PERMIT TO INSTALL

## **Table of Contents**

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Emission Unit Identification	5
Emission Unit Special Conditions	5

## **Common Abbreviations / Acronyms**

	Common Acronyms	Pollutant/Measurement Abbreviations		
AQD	Air Quality Division	Btu	British Thermal Unit	
BACT	Best Available Control Technology	°C	Degrees Celsius	
CAA	Clean Air Act	CO	Carbon Monoxide	
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot	
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter	
COM	Continuous Opacity Monitoring	°F	Degrees Fahrenheit	
EPA			Grains	
EU	Environmental Protection Agency Emission Unit	gr Hg	Mercury	
FG	Flexible Group	hr	Hour	
GACS	-	H <sub>2</sub> S		
	Gallon of Applied Coating Solids General Condition	_	Hydrogen Sulfide	
GC		hp	Horsepower	
HAP	Hazardous Air Pollutant	lb	Pound	
HVLP	High Volume Low Pressure *	m	Meter	
ID	Identification	mg	Milligram	
LAER	Lowest Achievable Emission Rate	mm	Millimeter	
MACT	Maximum Achievable Control Technology	MM	Million	
MAERS	Michigan Air Emissions Reporting System	MW	Megawatts	
MAP	Malfunction Abatement Plan	ng	Nanogram	
MDEQ	Michigan Department of Environmental Quality	NOx	Oxides of Nitrogen	
MSDS	Material Safety Data Sheet	PM	Particulate Matter	
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM-10	Particulate Matter less than 10 microns diameter	
NSPS	New Source Performance Standards	pph	Pounds per hour	
NSR	New Source Review	ppm	Parts per million	
PS	Performance Specification	ppmv	Parts per million by volume	
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight	
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute	
PTI	Permit to Install	psig	Pounds per square inch gauge	
RACT	Reasonably Available Control Technology	scf	Standard cubic feet	
ROP	Renewable Operating Permit	sec	Seconds	
SC	Special Condition	$SO_2$	Sulfur Dioxide	
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons	
SRN	State Registration Number	tpy	Tons per year	
TAC	Toxic Air Contaminant	μg	Microgram	
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound	
VE	Visible Emissions	yr	Year	

<sup>\*</sup> For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

#### **GENERAL CONDITIONS**

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. [R336.1201(1)]
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. [R336.1201(4)]
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. [R336.1201(6)(b)]
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. [R336.1201(8), Section 5510 of Act 451, PA 1994]
- 5. The AQD District Supervisor shall be notified, in writing, of a change in ownership or operational control of the stationary source or emission unit(s) authorized by this Permit to Install pursuant to R336.1219. The notification shall include all of the information required by R336.1219(1)(a) and (b). In addition, a new owner or operator must submit a written statement pursuant to R336.1219(1)(c), agreeing to and accepting the terms and conditions of this Permit to Install, and shall notify the AQD District Supervisor of any change in the contact person for this Pemit to Install. [R336.1219]
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. [R336.1901]
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). [R336.1912]
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.

- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law nor does it affect any liability for past violations under the Natural Resources and Environmental Protection Act, 1994 PA 451.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R336.1303. [R336.1301]
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this permit to install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R336.1370(2). [R336.1370]
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R336.2001 and R336.2003, under any of the conditions listed in R336.2001. [R336.2001]

#### SPECIAL CONDITIONS

## **Emission Unit Identification**

<b>Emission Unit ID</b>	Emission Unit Description	Stack Identification			
EUTESTCELLS	2 dynamometer engine test cells using diesel,	SVTESTCELL1			
	gasoline, and ethanol fuels, including blends of	SVTESTCELL2			
	gasoline and ethanol. For the purposes of this				
	permit, gasoline/ethanol blends with an ethanol				
	content of less than 85% will be treated as gasoline				
	and an ethanol content of 85% or greater will be				
	treated as ethanol. The engines may be controlled by				
	catalytic converters or uncontrolled.				
Changes to the equipment described in this table are subject to the requirements of R336.1201, except as					
allowed by R336.1278 through R336.1290.					

### The following conditions apply to: EUTESTCELLS

#### **Emission Limits**

LIIIS	mission Limits						
	Pollutant	Equipment	Limit	Tin	ne Period	Testing/ Monitoring Method	Applicable Requirement(s)
1.1a	NOx	EUTESTCELLS	89 tpy	12-month r	olling time	See below,	R336.1205
				period as d	etermined at the	and SC 1.6	
				end of each	calendar month.		
1.1b	CO	EUTESTCELLS	89 tpy	12-month r	olling time	See below,	R336.1205
				period as d	etermined at the	and SC 1.7	
				end of each	calendar month.		
	The permittee shall calculate NOx and CO emissions from EUTESTCELLS based on fuel usage data per						
	Special Condition 1.7, and the worst-case emission fa				actor from testing	per General Cor	ndition No. 13, if
	required by	the Department, and	d the emi	ssion factors	below:		
	Gasoline Er	mission Factor for U	ncontroll	ed Engines	Gasoline Emission Factor for Controlled Engines		
	NOx = 1.02	lb/gallon gasoline		_	NOx = 0.0176  lb/	gallon gasoline	
	CO = 3.121	b/gallon gasoline			CO = 0.0940  lb/g	allon gasoline	
	Ethanol Em	ission Factor for Un	controlle	d Engines	Ethanol Emission	Factor for Controlled Engines	
	NOx = 0.92	0 lb/gallon gasoline		-	NOx = 0.0158  lb/	gallon gasoline	
	CO = 1.871	b/gallon gasoline			CO = 0.0564  lb/g	allon gasoline	
	Diesel Emis	ssion Factor for Unc	ontrolled	Engines			
	NOx = 0.604	4 lb/gallon diesel		-			
	CO = 0.130	lb/gallon diesel					

### **Material Usage Limits**

- 1.2 The diesel usage for EUTESTCELLS shall not exceed 578,000 gallons per 12-month rolling time period as determined at the end of each calendar month. [R336.1205, R336.1225, R336.1702(a)]
- 1.3 The gasoline usage for EUTESTCELLS shall not exceed 57,000 gallons for uncontrolled engines per 12-month rolling time period as determined at the end of each calendar month, or 450,000 gallons for controlled engines per 12-month rolling time period as determined at the end of each calendar month. [R336.1205, R336.1225, R336.1702(a)]

1.4 The ethanol usage for EUTESTCELLS shall not exceed 95,000 gallons for uncontrolled engines per 12-month rolling time period as determined at the end of each calendar month, or 658,000 gallons for controlled engines per 12-month rolling time period as determined at the end of each calendar month. [R336.1205, R336.1225, R336.1702(a)]

### Recordkeeping/Reporting/Notification

- 1.5 The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. [R336.1205, R336.1225, R336.1702(a)]
- 1.6 The permittee shall keep, in a satisfactory manner, monthly and previous 12-month NOx emission calculation records for EUTESTCELLS, as required by SC 1.1a. The permittee shall keep all records on file for a period of at least five years and make them available to the Department upon request. [R336.1205]
- 1.7 The permittee shall keep, in a satisfactory manner, monthly and previous 12-month CO emission calculation records for EUTESTCELLS, as required by SC 1.1b. The permittee shall keep all records on file for a period of at least five years and make them available to the Department upon request. [R336.1205]
- 1.8 The permittee shall keep, in a satisfactory manner, monthly and previous 12-month fuel use records for EUTESTCELLS. The records shall specify the fuel usage for engines equipped with catalytic converters and the fuel usage for uncontrolled engines, as well as the type of fuel used. All records shall be kept on file for a period of at least five years and made available to the Department upon request. [R336.1205, R336.1225, R336.1702 (a)]

#### **Stack/Vent Restrictions**

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement(s)			
1.9a	SVTESTCELL1	14	39	R336.1225			
1.9b	SVTESTCELL2	14	39	R336.1225			
	The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.						