
MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

May 11, 2009

PERMIT TO INSTALL

No. 74-09



STATE REGISTRATION NUMBER N8262

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: **3/31/2009**

DATE PERMIT TO INSTALL APPROVED: SIGNATURE: 5/11/2009 SIGNATURE: DATE PERMIT VOIDED: SIGNATURE: DATE PERMIT REVOKED: SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table	5
Special Conditions for EUBURNOFF	6

Common Abbreviations / Acronyms

Common Acronyms			Pollutant/Measurement Abbreviations		
AQD Air Quality Division		BTU	British Thermal Unit		
ANSI	American National Standards Institute	°C	Degrees Celsius		
BACT	Best Available Control Technology	со	Carbon Monoxide		
CAA	Clean Air Act	dscf	Dry standard cubic foot		
CEM	Continuous Emission Monitoring	dscm	Dry standard cubic meter		
CFR	Code of Federal Regulations	°F	Degrees Fahrenheit		
СОМ	Continuous Opacity Monitoring	gr	Grains		
EPA	Environmental Protection Agency	Hg	Mercury		
EU	Emission Unit	hr	Hour		
FG	Flexible Group	H_2S	Hydrogen Sulfide		
GACS	Gallon of Applied Coating Solids	hp	Horsepower		
GC	General Condition	lb	Pound		
HAP	Hazardous Air Pollutant	m	Meter		
HVLP	High Volume Low Pressure *	mg	Milligram		
ID	Identification	mm	Millimeter		
LAER	Lowest Achievable Emission Rate	MM	Million		
MACT	Maximum Achievable Control Technology	MW	Megawatts		
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram		
MAP	Malfunction Abatement Plan	NOx	Oxides of Nitrogen		
MDEQ	Michigan Department of Environmental Quality	РМ	Particulate Matter		
MIOSHA	Michigan Occupational Safety & Health Administration	PM10	PM less than 10 microns diameter		
MSDS	Material Safety Data Sheet	PM2.5	PM less than 2.5 microns diameter		
NESHAP	National Emission Standard for Hazardous Air Pollutants	pph	Pound per hour		
NSPS	New Source Performance Standards	ppm	Parts per million		
NSR	New Source Review	ppmv	Parts per million by volume		
PS	Performance Specification	ppmw	Parts per million by weight		
PSD	Prevention of Significant Deterioration	psia	Pounds per square inch absolute		
PTE	Permanent Total Enclosure	psig	Pounds per square inch gauge		
PTI	Permit to Install	scf	Standard cubic feet		
RACT	Reasonably Available Control Technology	sec	Seconds		
ROP	Renewable Operating Permit	SO ₂	Sulfur Dioxide		
SC	Special Condition	THC	Total Hydrocarbons		
SCR	Selective Catalytic Reduction	tpy	Tons per year		
SRN	State Registration Number	μg	Microgram		
TAC	Toxic Air Contaminant	VOC	Volatile Organic Compounds		
TEQ	Toxicity Equivalence Quotient	yr	Year		
VE	Visible Emissions				

VE Visible Emissions
 * For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

- The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The AQD District Supervisor shall be notified, in writing, of a change in ownership or operational control of the stationary source or emission unit(s) authorized by this Permit to Install pursuant to R 336.1219. The notification shall include all of the information required by R 336.1219(1)(a) and (b). In addition, a new owner or operator must submit a written statement pursuant to R 336.1219(1)(c), agreeing to and accepting the terms and conditions of this Permit to Install, and shall notify the AQD District Supervisor of any change in the contact person for this Permit to Install. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. (R 336.2001)

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID				
EUBURNOFF	A batch type natural gas-fired burnoff oven with a secondary chamber or afterburner, used to remove cured paints, coatings, oil or grease from metal parts by thermal decomposition in a primary chamber.					
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.						

The following conditions apply to: EUBURNOFF

DESCRIPTION: A batch type natural gas-fired burnoff oven with a secondary chamber or afterburner, used to remove cured paints, coatings, oil or grease from metal parts by thermal decomposition in a primary chamber.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: The burnoff oven is equipped with a secondary chamber/afterburner.

I. EMISSION LIMITS

1. There shall be no visible emissions from EUBURNOFF. (R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))

II. MATERIAL LIMITS

- 1. The permittee shall burn only natural gas in EUBURNOFF. (R 336.1901)
- 2. The permittee shall not process any material in EUBURNOFF other than cured paints, coatings, oil or grease on metal parts, racks and/or hangers. (R 336.1224, R 336.1225, R 336.1901)

III. PROCESS/OPERATIONAL RESTRICTIONS

- 1. The permittee shall not use EUBURNOFF for the thermal destruction or removal of rubber, plastics, uncured paints, or any other materials containing sulfur or halogens (chlorine, fluorine, bromine, etc.) such as plastisol, polyvinyl chloride (PVC), or Teflon. (R 336.1224, R 336.1225, R 336.1901)
- 2. The permittee shall not load any transformer cores, which may be contaminated with PCB-containing dielectric fluid, wire or parts coated with lead or rubber, or any waste materials such as paint sludge or waste powder coatings into EUBURNOFF. (R 336.1224, R 336.1225, R 336.1901)

IV. DESIGN/EQUIPMENT PARAMETERS

- 1. The permittee shall not operate EUBURNOFF unless a secondary chamber or afterburner is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of the secondary chamber or afterburner includes maintaining a minimum temperature of 1400°F and a minimum retention time of 0.5 seconds. (R 336.1224, R 336.1225, R 336.1301, R 336.1901, R 336.1910)
- 2. The permittee shall not operate EUBURNOFF unless an automatic temperature control system for the primary chamber and secondary chamber or afterburner is installed, maintained, and operated in a satisfactory manner. (R 336.1224, R 336.1225, R 336.1301, R 336.1901, R 336.1910)
- 3. The permittee shall not operate EUBURNOFF unless an interlock system that shuts down the primary chamber burner when the secondary chamber or afterburner is not operating properly, is installed, maintained and operated in a satisfactory manner. (R 336.1224, R 336.1225, R 336.1301, R 336.1901, R 336.1910)

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to continuously monitor the temperature in the burnoff oven secondary chamber or afterburner and record the temperature at least once every 15 minutes. (R 336.1224, R 336.1225, R 336.1301, R 336.1901, R 336.1910)
- 2. The permittee shall calibrate the thermocouples associated with the primary and secondary chambers at least once per year. (R 336.1224, R 336.1225, R 336.1301, R 336.1901)
- 3. The permittee shall keep, in a satisfactory manner, temperature data records for the burnoff oven secondary chamber or afterburner. All records shall be kept on file for a period of at least five years and made available to the Department upon request. (R 336.1910, R 336.1912)
- 4. The permittee shall keep, in a satisfactory manner, records of the date, duration, and description of any malfunction of the control equipment, any maintenance performed and any testing results for EUBURNOFF. All records shall be kept on file for a period of at least five years and made available to the Department upon request. (R 336.1224, R 336.1225, R 336.1301, R 336.1901, R 336.1910)
- 5. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material (cured coating, oil or grease) processed in EUBURNOFF, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file for a period of at least five years and made available to the Department upon request. (R 336.1224, R 336.1225, R 336.1901)

VII. <u>REPORTING</u>

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVBURNOFF	10	30	R 336.1224, R 336.1225, R 336.1901

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).