

**MICHIGAN DEPARTMENT OF NATURAL RESOURCES AND ENVIRONMENT
AIR QUALITY DIVISION**

May 21, 2010

PERMIT TO INSTALL
No. 81-10

ISSUED TO
Endura Plating Technology

LOCATED AT
42268 Yearego Drive
Sterling Heights, Michigan 48134

IN THE COUNTY OF
Macomb

STATE REGISTRATION NUMBER
P0097

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Natural Resources and Environment. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: April 29, 2010	
DATE PERMIT TO INSTALL APPROVED: May 21, 2010	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Flexible Group Summary Table	5
Special Conditions for FGELESSNILINE	5

Common Abbreviations / Acronyms

Common Acronyms		Pollutant/Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
ANSI	American National Standards Institute	°C	Degrees Celsius
BACT	Best Available Control Technology	CO	Carbon Monoxide
CAA	Clean Air Act	dscf	Dry standard cubic foot
CEM	Continuous Emission Monitoring	dscm	Dry standard cubic meter
CFR	Code of Federal Regulations	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfunction Abatement Plan	NO _x	Oxides of Nitrogen
MDNRE	Michigan Department of Natural Resources and Environment (Department)	PM	Particulate Matter
MIOSHA	Michigan Occupational Safety & Health Administration	PM10	PM less than 10 microns diameter
MSDS	Material Safety Data Sheet	PM2.5	PM less than 2.5 microns diameter
NESHAP	National Emission Standard for Hazardous Air Pollutants	pph	Pound per hour
NSPS	New Source Performance Standards	ppm	Parts per million
NSR	New Source Review	ppmv	Parts per million by volume
PS	Performance Specification	ppmw	Parts per million by weight
PSD	Prevention of Significant Deterioration	psia	Pounds per square inch absolute
PTE	Permanent Total Enclosure	psig	Pounds per square inch gauge
PTI	Permit to Install	scf	Standard cubic feet
RACT	Reasonably Available Control Technology	sec	Seconds
ROP	Renewable Operating Permit	SO ₂	Sulfur Dioxide
SC	Special Condition	THC	Total Hydrocarbons
SCR	Selective Catalytic Reduction	tpy	Tons per year
SRN	State Registration Number	µg	Microgram
TAC	Toxic Air Contaminant	VOC	Volatile Organic Compounds
TEQ	Toxicity Equivalence Quotient	yr	Year
VE	Visible Emissions		

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Natural Resources and Environment, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Natural Resources and Environment. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUELETROCLEAN	Surface preparation tank controlled by a common packed bed wet scrubber system.	FGELESSNILINE
EUELECTROLESSNIA	Electro less nickel plating tank electrically heated and agitated to promote electro less nickel plating. The tank is controlled by a common packed bed wet scrubber system.	FGELESSNILINE
EUELECTROLESSNIB	Electro less nickel plating tank electrically heated and agitated to promote electro less nickel plating. The tank is controlled by a common packed bed wet scrubber system.	FGELESSNILINE
EUELECTROLESSNIC	Electro less nickel plating tank electrically heated and agitated to promote electro less nickel plating. The tank is controlled by a common packed bed wet scrubber system.	FGELESSNILINE
EUNITRICSTRIP	Nitric acid rack stripping tank for stripping defective parts or racks used in the electro less nickel plating process. The tank is controlled by a common packed bed wet scrubber system.	FGELESSNILINE
EUCAUSTICSTRIP	Caustic strip tank for stripping defective parts or racks used in the electro less nickel plating process. The tank is controlled by a common packed bed wet scrubber system.	FGELESSNILINE

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGELESSNILINE	Electro less nickel plating line with common packed bed wet scrubber system for control.	EUELETROCLEAN, EUELECTROLESSNIA, EUELECTROLESSNIB, EUELECTROLESSNIC, EUNITRICSTRIP, EUCAUSTICSTRIP

The following conditions apply to: FGELESSNILINE

DESCRIPTION: Electro less nickel plating line with common packed bed wet scrubber system for control.

Emission Units: EUELETROCLEAN, EUELECTROLESSNIA, EUELECTROLESSNIB, EUELECTROLESSNIC, EUNITRICSTRIP, EUCAUSTICSTRIP

POLLUTION CONTROL EQUIPMENT: packed bed wet scrubber system for control

I. EMISSION LIMITS

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Nickel	0.0009 lb/hr	According to Method	FGELESSNILINE	GC 13	R 336.1225
2. Nitric Acid	1.2 lb/hr	According to Method	FGELESSNILINE	GC 13	R 336.1225

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. Within 30 calendar days after start-up of FGELESSNILINE, the permittee shall submit to the AQD District Supervisor, an approvable operation and maintenance plan. The plan shall contain all information specified by the manufacturer which includes the following: **(R 336.1224, R 336.1225, R 336.1331, R 336.1702, R 336.1901, R 336.1910)**
 - a) Operation and maintenance criteria for all tanks in FGELESSNILINE, add-on control device(s), and for the process and control device(s) monitoring equipment as well as a standardized checklist to document the operation and maintenance of the equipment;
 - b) The work practice standards for the add-on control device(s) and monitoring equipment;
 - c) Procedures to be followed to ensure that equipment or process malfunctions due to poor maintenance or other preventable conditions do not occur; and
 - d) A systematic procedure for identifying process equipment, add-on control device(s) and monitoring equipment malfunctions and for implementing corrective actions to address such malfunctions.

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate FGELESSNILINE unless the packed bed scrubber system with mist eliminator is installed, maintained, and operated in a satisfactory manner. **(R 336.1224, R 336.1225, R 336.1331, R 336.1702, R 336.1901)**
2. The permittee shall equip and maintain the packed bed scrubber system with mist eliminator with a differential pressure monitoring device and a liquid flow indicator. **(R 336.1224, R 336.1225, R 336.1331, R 336.1702, R 336.1901)**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall perform inspections of the packed bed scrubber system as follows: **(R 336.1224, R 336.1225, R 336.1331, R 336.1702, R 336.1901, R 336.1910)**
- a) Determine pressure drop across the packed bed scrubber on a daily basis. If the pressure drop across the control varies by more than ± 1 inch of water gauge, from the pressure drop specified by the manufacturer or as determined during compliance testing, the permittee shall document the variation, and review the operation and maintenance procedures. The permittee shall document any corrective action.
 - b) Determine liquid flow rate on a daily basis. If the liquid flow rate varies from the liquid flow rate specified by the manufacturer to maintain proper operation of the scrubber system, the permittee shall document the variation, and review the operation and maintenance procedures. The permittee shall document any corrective action.
 - c) Visually inspect the packed bed scrubber, on a quarterly basis, to ensure there is proper drainage, and no evidence of chemical attack on the structural integrity of the control device.
 - d) Visually inspect the back portion of the mist eliminator, on a quarterly basis, to ensure that it is dry and there is no breakthrough.
 - e) Visually inspect ductwork from tanks to the packed bed scrubber, on a quarterly basis, to ensure there are no leaks.

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVELESSNILINE	24	27	R 336.1225

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).