# MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

May 8, 2012

PERMIT TO INSTALL 182-11A

ISSUED TO Gerdau Special Steel North America

> LOCATED AT 3000 East Front Street Monroe, Michigan

IN THE COUNTY OF

Monroe

# STATE REGISTRATION NUMBER B7061

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: April 23, 2012

DATE PERMIT TO INSTALL APPROVED: May 8, 2012	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

# **PERMIT TO INSTALL**

# **Table of Contents**

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table	5
Special Conditions for EUTEMPBOILER	5

## **Common Abbreviations / Acronyms**

Common Acronyms			Pollutant/Measurement Abbreviations		
AQD	Air Quality Division	BTU	British Thermal Unit		
ANSI	American National Standards Institute	°C	Degrees Celsius		
BACT	Best Available Control Technology	со	Carbon Monoxide		
CAA	Clean Air Act	dscf	Dry standard cubic foot		
CEM	Continuous Emission Monitoring	dscm	Dry standard cubic meter		
CFR	Code of Federal Regulations	°F	Degrees Fahrenheit		
СОМ	Continuous Opacity Monitoring	gr	Grains		
EPA	Environmental Protection Agency	Hg	Mercury		
EU	Emission Unit	hr	Hour		
FG	Flexible Group	H <sub>2</sub> S	Hydrogen Sulfide		
GACS	Gallon of Applied Coating Solids	hp	Horsepower		
GC	General Condition	lb	Pound		
HAP	Hazardous Air Pollutant	m	Meter		
HVLP	High Volume Low Pressure *	mg	Milligram		
ID	Identification	mm	Millimeter		
LAER	Lowest Achievable Emission Rate	MM	Million		
MACT	Maximum Achievable Control Technology	MW	Megawatts		
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram		
MAP	Malfunction Abatement Plan	NOx	Oxides of Nitrogen		
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter		
MIOSHA	Michigan Occupational Safety & Health Administration	PM10	PM less than or equal to 10 microns diameter		
MSDS	Material Safety Data Sheet	PM2.5	PM less than or equal 2.5 microns diameter		
NESHAP	National Emission Standard for Hazardous Air Pollutants	pph	Pound per hour		
NSPS	New Source Performance Standards	ppm	Parts per million		
NSR	New Source Review	ppmv	Parts per million by volume		
PS	Performance Specification	ppmw	Parts per million by weight		
PSD	Prevention of Significant Deterioration	psia	Pounds per square inch absolute		
PTE	Permanent Total Enclosure	psig	Pounds per square inch gauge		
PTI	Permit to Install	scf	Standard cubic feet		
RACT	Reasonably Available Control Technology	sec	Seconds		
ROP	Renewable Operating Permit	SO <sub>2</sub>	Sulfur Dioxide		
SC	Special Condition	THC	Total Hydrocarbons		
SCR	Selective Catalytic Reduction	tpy	Tons per year		
SRN	State Registration Number	μg	Microgram		
TAC	Toxic Air Contaminant	VOC	Volatile Organic Compounds		
TEQ	Toxicity Equivalence Quotient	yr	Year		
VE	Visible Emissions				

\* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

### **GENERAL CONDITIONS**

- The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. (R 336.1301)
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
- Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. (R 336.2001)

## SPECIAL CONDITIONS

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Installation Date / Modification Date	Flexible Group ID	
EUTEMPBOILER	One (1) natural gas-fired packaged boiler with a maximum heat input of 56 MMBtu/hr and controlled by a low NOx burner.	PTI Issuance*	NA	
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.				

# The following conditions apply to: EUTEMPBOILER

**DESCRIPTION:** One (1) natural gas-fired packaged boiler with a maximum heat input of 56 MMBtu/hr.

Flexible Group ID: NA

**POLLUTION CONTROL EQUIPMENT:** Low NOx burner.

### I. EMISSION LIMITS

NA

# II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Natural Gas	54,624 cubic feet/hr	90 days	EUTEMPBOILER	SC VI.2	R 336.1205, R 336.1225

2. The permittee shall burn only pipeline quality natural gas in EUTEMPBOILER. (R 336.1205, R 336.1224, R 336.1225, R 336.1702, 40 CFR Part 60 Subpart Dc)

# III. PROCESS/OPERATIONAL RESTRICTIONS

 The permittee shall operate EUTEMPBOILER in accordance with manufacturer's recommendations for safe and proper operation to minimize emissions during periods of startup, shutdown and malfunction. (R 336.1912)

### IV. DESIGN/EQUIPMENT PARAMETERS

1. The heat input capacity of EUTEMPBOILER shall not exceed a maximum of 56 million BTU per hour. (R 336.1205(1)(a))

Gerdau Special Steel North America (B7061) Permit No. 182-11A

- 2. The permittee shall not operate EUTEMPBOILER unless a low NOx burner is installed, maintained, and operated in a satisfactory manner. (R 336.1205)
- 3. The permittee shall install, calibrate, maintain, and operate in a satisfactory manner a device to monitor and record the fuel use for EUTEMPBOILER on a daily basis. (R 336.1205(1)(a), R 336.1225)

## V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

# VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1205(1)(a) & (3), R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))
- 2. The permittee shall keep, in a satisfactory manner, daily and monthly fuel use records for EUTEMPBOILER. The records must indicate the total amount of fuel used in EUTEMPBOILER. All records shall be kept on file and made available to the Department upon request. (R 336.1205(1)(a), 40 CFR 60.48c(g))
- 3. The permittee shall keep, in a satisfactory manner, records of the date, duration, and description of any malfunction of the control equipment, any maintenance performed and any testing results for EUTEMPBOILER. All records shall be kept on file and made available to the Department upon request. (R 336.1702(a), R 336.1910)

### VII. <u>REPORTING</u>

1. The permittee shall submit the following notifications to the AQD District Supervisor in accordance with 40 CFR 60.48c:

a) A notification of the date when construction was commenced, submitted no later than 30 calendar days after such date.

b) A notification of the actual date of startup of the source, submitted within 30 calendar days after such date.

c) The design heat input capacity of EUTEMPBOILER and identification of fuels to be combusted in the boiler. (40 CFR 60.48c(a))

### VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. EUTEMPBOILER	36.0	19.0	R 336.1225, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d)

## IX. OTHER REQUIREMENTS

- The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and Dc, as they apply to EUTEMPBOILER. (40 CFR Part 60 Subparts A & Dc)
- 2. This permittee shall notify the District Office 14 days prior to or after the start-up date of EUTEMPBOILER and upon the termination of this permit. The permit shall be terminated not more than 90 days from the start-up date of EUTEMPBOILER or no later than December 31, 2012. To continue operation of EUTEMPBOILER at this site after 90 days from the start-up date or after December 31, 2012, the permittee must apply for and receive a new PTI. (Act 451 324.5503(c))

### Footnotes:

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).