MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

August 17, 2012

PERMIT TO INSTALL 73-11A

ISSUED TODykema Excavators, Inc.

LOCATED AT 1730 Three Mile Road Grand Rapids, Michigan

IN THE COUNTY OF Kent

STATE REGISTRATION NUMBER N6762

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: August 3, 2012			
DATE PERMIT TO INSTALL APPROVED: August 17, 2012	SIGNATURE:		
DATE PERMIT VOIDED:	SIGNATURE:		
DATE PERMIT REVOKED:	SIGNATURE:		

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table	5
Special Conditions for EUCRUSHING	5
Special Conditions for EUTRUCKTRAFFIC	8
Special Conditions for EUSTORAGE	10
Flexible Group Summary Table	12
Special Conditions for FGFACILITY	12
Appendix A	14
Appendix B	15
Appendix C	16

Common Abbreviations / Acronyms

Common Acronyms			Pollutant / Measurement Abbreviations		
AQD Air Quality Division		BTU	British Thermal Unit		
BACT	Best Available Control Technology	°C	Degrees Celsius		
CAA	Clean Air Act	СО	Carbon Monoxide		
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot		
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter		
CO ₂ e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit		
COM	Continuous Opacity Monitoring	gr	Grains		
EPA	Environmental Protection Agency	Hg	Mercury		
EU	Emission Unit	hr	Hour		
FG	Flexible Group	H ₂ S	Hydrogen Sulfide		
GACS	Gallon of Applied Coating Solids	hp	Horsepower		
GC	General Condition	lb	Pound		
GHGs	Greenhouse Gases	kW	Kilowatt		
HAP	Hazardous Air Pollutant	m	Meter		
HVLP	High Volume Low Pressure *	mg	Milligram		
ID	Identification	mm	Millimeter		
LAER	Lowest Achievable Emission Rate	MM	Million		
MACT	Maximum Achievable Control Technology	MW	Megawatts		
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram		
MAP	Malfunction Abatement Plan	NO _x	Oxides of Nitrogen		
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter		
MSDS	Material Safety Data Sheet	PM10	PM less than 10 microns diameter		
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM less than 2.5 microns diameter		
NSPS	New Source Performance Standards	pph	Pounds per hour		
NSR	New Source Review	ppm	Parts per million		
PS	Performance Specification	ppmv	Parts per million by volume		
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight		
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute		
PTI	Permit to Install	psig	Pounds per square inch gauge		
RACT	Reasonably Available Control Technology	scf	Standard cubic feet		
ROP	Renewable Operating Permit	sec	Seconds		
SC	Special Condition	SO ₂	Sulfur Dioxide		
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons		
SRN	State Registration Number	tpy	Tons per year		
TAC	Toxic Air Contaminant	μg	Microgram		
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound		
VE	Visible Emissions	yr	Year		

^{*} For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. (R 336.2001)

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUCRUSHING	A combination of portable process equipment (screens, crushers, feeders, conveyors, etc.) used to reduce larger materials down to smaller sizes, classify and sort materials into various product types, material handling and transporting of material to storage areas. Control methods include water sprays and wet suppression.	FGFACILITY
EUTRUCKTRAFFIC	Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area.	FGFACILITY
EUSTORAGE	Open area stock piles of various material sizes and product types. Water spray of material products are used when necessary for material storage piles.	FGFACILITY
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as		

allowed by R 336.1278 to R 336.1290.

The following conditions apply to: EUCRUSHING

<u>DESCRIPTION</u>: Portable non-metallic crusher including crushers, screens, feeders, conveyors, etc.

Flexible Group ID: FGFACILITY

POLLUTION CONTROL EQUIPMENT: Water sprays and wet suppression

I. <u>EMISSION LIMITS</u>

- 1. Visible emissions from the drop point and transfer point portions of EUCRUSHING shall not exceed 10 percent opacity. (R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d), 40 CFR 60.670)
- 2. The permittee shall not operate any portion of EUCRUSHING unless each portion of EUCRUSHING meets the specific opacity limit listed in Appendix A of this permit. (R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d), 40 CFR 60.670)

II. MATERIAL LIMITS

1. The permittee shall not process any asbestos tailing or asbestos containing waste materials in EUCRUSHING pursuant to the National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 61 Subpart M. (40 CFR Part 61 Subpart M)

2. The permittee shall not process more than 2,000,000 tons of material through EUCRUSHING per 12-month rolling time period, as determined at the end of each calendar month, per site. (R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))

III. PROCESS/OPERATIONAL RESTRICTIONS

- 1. The permittee shall not operate EUCRUSHING unless the fugitive dust control plan for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. (R 336.1371, R 336.1901)
- 2. The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and OOO, as they apply to EUCRUSHING. (40 CFR Part 60 Subparts A & OOO)

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any portion of EUCRUSHING unless the equipment's specified control device is installed, maintained and operated in a satisfactory manner as listed in Appendix A. (R 336.1901, R 336.1910, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. Within 60 days after achieving maximum production rate, but not later than 180 days after commencement of trial operation, the permittee shall evaluate visible emissions from EUCRUSHING, at owner's expense, in accordance with federal Standards of Performance for New Stationary Sources 40 CFR Part 60 Subparts A and OOO. The permittee must have prior approval from the AQD for visible emission observation procedures. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD within 45 days following the last date of the evaluation. (R 336.1301, 40 CFR Part 60 Subparts A & OOO)

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))
- 2. The permittee shall keep daily and monthly records of the amount of material processed through EUCRUSHING for each site. Further the permittee shall calculate on a monthly basis, the yearly throughput rate based upon the most recent 12-month rolling time period for each site. The permittee shall keep records of the amount of material processed on file and make them available to the Department upon request. (R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))

VII. REPORTING

1. The permittee shall provide written notification of construction and operation to comply with the federal Standards of Performance for New Stationary Sources, 40 CFR 60.7. The permittee shall submit this notification to the AQD District Supervisor within the time frames specified in 40 CFR 60.7. (40 CFR 60.7)

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

1. Within 45 days of issuance of this permit, the permittee shall label all equipment using the company ID Numbers in Appendix A, according to a method acceptable to the AQD District Supervisor. Labels shall be in a conspicuous location on the equipment. Within seven days of completing the labeling, the permittee shall notify the AQD District Supervisor, in writing, as to the date the labeling was completed. (R 336.1201)

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUTRUCKTRAFFIC

<u>DESCRIPTION</u>: Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area.

Flexible Group ID: FGFACILITY

POLLUTION CONTROL EQUIPMENT: Fugitive Dust Control Plan

I. EMISSION LIMITS

1. Visible emissions from all wheel loaders and all truck traffic, operated in conjunction with EUTRUCKTRAFFIC, shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). (R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUTRUCKTRAFFIC unless the fugitive dust control plan for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. (R 336.1371, R 336.1372, Act 451 324.5524)

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

<u>Footnotes:</u> ¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUSTORAGE

DESCRIPTION: Open area stock piles of various material sizes and product types.

Flexible Group ID: FGFACILITY

POLLUTION CONTROL EQUIPMENT: Water spray of material products is used when necessary for material

storage piles

I. EMISSION LIMITS

1. Visible emissions from each of the material storage piles maintained under EUSTORAGE shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). (R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUSTORAGE unless the fugitive dust control plan for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. (R 336.1371, R 336.1372, Act 451 324.5524)

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

Dykema Excavators, Inc (N6762) Permit No. 73-11A

August 17, 2012 Page 11 of 16

IX. OTHER REQUIREMENTS

NA

Footnotes: ¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGFACILITY	All process equipment source-wide including	EUCRUSHING,
	equipment covered by other permits, grand-fathered	EUTRUCKTRAFFIC,
	equipment and exempt equipment.	EUSTORAGE

The following conditions apply Source-Wide to: FGFACILITY

POLLUTION CONTROL EQUIPMENT: Water sprays, Fugitive Dust Control Plan

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

- 1. The permittee shall not operate FGFACILITY unless the preventive maintenance plan specified in Appendix C has been implemented and is maintained. (R 336.1301, R 336.1303, R 336.1331, R 336.1910)
- 2. The permittee shall not relocate FGFACILITY to any new geographical site in Michigan unless all of the following criteria are met:
 - a. FGFACILITY shall not have any outstanding unresolved violations of any of the MDEQ Air Pollution Control rules, order, or permits; or federal air quality regulations.
 - b. The installation of FGFACILITY at the geographical site shall be of a temporary nature lasting not more than 12 consecutive months.
 - c. The permittee shall provide a notice of intent to relocate along with a proposed site plan to the AQD district office not less than 10 days prior to the scheduled relocation identifying the proposed new geographical site and the probable duration at the new site. The permittee shall use Relocation Notice Form EQP5757 for this submittal. The permittee shall clearly identify all residential or commercial establishments and places of public assembly within 1,000 feet of the proposed site of FGFACILITY on the proposed site plan.
 - d. The permittee shall not locate FGFACILITY within 500 feet of a residential or commercial establishment or a place of public assembly unless prior written site approval is obtained from the AQD district office.
 - e. The permittee shall clearly post a copy of this approved permit and permit conditions in the operator's office or work station and shall post the permit number on the equipment where it is clearly visible from the operator's office or work station.

f. The permittee shall not relocate FGFACILITY to any geographical site for which there is a known controversy. (Act 451 324.5505, R 336.1201, R 336.1205, R 336.1901)

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

1. The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and OOO, as they apply to FGFACILITY. (40 CFR Part 60 Subparts A & OOO)

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

APPENDIX A

Equipment Description	ID Number	Serial Number	Opacity Limit (Percent)	Control Device
36" conveyor	M-148	7248-60-36-1	10	Residual moisture
36" conveyor	M-149	7248-60-36-2	10	Residual moisture
36" conveyor	M-150	7248-60-36-3	10	Residual moisture
36" conveyor	M-151	7249-40-36	10	Residual moisture
Telsmith Cone crusher	M-152	505M2710	15	Water spray
24" conveyor	M-155	N/A	10	Water spray
Magnet conveyor	M-156	MCB11273	10	Water spray
Telsmith Jaw Crusher	M-160	22M8113	15	Water spray
36" conveyor	M-167	MCB11127	10	Water spray
McClosky conveyor	M-165	MCB366011154	10	Residual moisture

APPENDIX B Fugitive Dust Control Plan

I. Site Roadways / Plant Yard

- A. The dust on the site roadways and the plant yard shall be controlled by applications of water, calcium chloride or other acceptable and approved fugitive dust control compounds. Applications of dust suppressants shall be done as often as necessary to meet all applicable emission limits. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.
- B. All paved roadways and the plant yards shall be swept as needed between applications.
- C. Any material spillage on roads shall be cleaned up immediately.

II. Plant

The drop distance at each transfer point shall be reduced to the minimum the equipment can achieve.

III. Storage Piles

- A. Stockpiling of all nonmetallic minerals shall be performed to minimize drop distance and control potential dust problems.
- B. Stockpiles shall be watered on an as needed basis in order to meet the opacity limit of 5 percent. Equipment to apply water or dust suppressant shall be available at the site or on call for use at the site within a given operating day. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.

IV. Truck Traffic

On-site vehicles shall be loaded to prevent their contents from dropping, leaking, blowing or otherwise escaping. This shall be accomplished by loading so that no part of the load shall come in contact within 6 inches of the top of any side board, side panel or tailgate. Otherwise, the truck shall be tarped.

V. AQD/MDEQ Inspection

The provisions and procedures of this plan are subject to adjustment by written notification from the AQD if, following an inspection, the AQD finds the fugitive dust requirements and/or permitted emission limits are not being met.

APPENDIX C

Preventive Maintenance Plan

To assure proper operation of the particulate and dust emission control equipment, the permittee shall institute the following preventive maintenance program at the facility.

Water Sprays

Water sprays shall be installed so as to minimize possible damage from processed material.

Repairs due to damage shall take place immediately.

The water spray system shall be inspected weekly. Routine repairs and/or maintenance shall be made as needed.

A record shall be kept for the inspections and repairs made to the water spray system.

All records shall be kept in a format acceptable to the AQD District Supervisor. All records shall be kept on file for a period of at least five years and made available to the Department upon request.

The provisions and procedures of this plan are subject to adjustment if following an inspection and written notification the AQD finds the fugitive dust requirements and/or permitted emission limits are not being met.