

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

January 10, 2017

PERMIT TO INSTALL
132-16

ISSUED TO
MLC Research and Development, LLC

LOCATED AT
130 S Leja Drive
Vicksburg, Michigan

IN THE COUNTY OF
Kalamazoo

STATE REGISTRATION NUMBER
P0728

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: July 19, 2016	
DATE PERMIT TO INSTALL APPROVED: January 10, 2017	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EUBURNER.....	6
Special Conditions for EUROTARYDRYER	8
Special Conditions for EUFOODPROCESS.....	10
Flexible Group Summary Table	12
Special Conditions for FGFACILITY	13

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO _{2e}	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H ₂ S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO _x	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM ₁₀	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM _{2.5}	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO ₂	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Installation Date / Modification Date	Flexible Group ID
EUBURNER	10 MMBTU/hr natural gas fired boiler.	TBD	FGFACILITY
EUROTARYDRYER	A direct fired rotary drum dryer. The drum is fired from EUBURNER and is controlled with a 7.5 diameter cyclone collector.	TBD	FGFACILITY
EUFOODPROCESS	Process equipment for drying fruits, vegetables, pomaces, and byproducts. This equipment consists of a, a two vibratory control sieves, a finished hopper/bin, and a hammer mill. All of this equipment exhausts to a dust collection baghouse.	TBD*	FGFACILITY
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.			

The following conditions apply to: EUBURNER

DESCRIPTION: 10 MMBTU/hr natural gas fired boiler.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT:

There are not any control devices used directly on EUBURNER. Hot gases from EUBURNER are directed to EUROTARYDRYER, which is direct fired, and is controlled by a cyclonic collector.

I. EMISSION LIMITS

(See emission limits for EUROTARYDRYER below)

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1.Natural gas	86 Million cubic feet per year	12 month rolling time period as determined at the end of each calendar month	EUBURNER	SC VI.1	R 336.1205

2. The permittee shall burn only natural gas in EUBURNER. (R 336.1205)

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The heat release capacity of EUBURNER shall not exceed 10 MMBtu/hr. (R 336.1205, 40 CFR Part 60 Subpart Dc)

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall keep records of the natural gas usage, in million cubic feet, on a rolling 12-month time period, as determined at the end of each calendar month. (R 336.1205, 40 CFR Part 60, Subpart Dc)

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

(Exhaust gases from the boiler are exhausted through the EUROTARYDRYER stack. See stack/vent restrictions for EUROTARYDRYER).

IX. OTHER REQUIREMENTS

1. The permittee shall comply with all applicable requirements of 40 CFR Part 60 Subpart Dc, Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units.
2. The permittee shall comply with all applicable requirements of 40 CFR Part 60 Subpart Dc, Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units.

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUROTARYDRYER

DESCRIPTION: A direct fired rotary drum dryer. The rotary drum dryer is heated via the exhaust from EUBURNER.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT:

A 7.5 diameter cyclonic collector to control PM.

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. PM	0.01 lb per 1,000 pounds of exhaust gases.	Test Protocol*	EUROTARYDRYER	GC 13	R 336.1331 R 336.1205(3)
2. PM	1.0 pph	Test Protocol*	EUROTARYDRYER	GC 13	R 336.1205(3)
3. PM-10	0.25 pph	Test Protocol*	EUROTARYDRYER	GC 13	R 336.1205(3)
4. Visible Emissions	10% opacity	6 minute average	EUROTARYDRYER	SC VI.1	R 336.1301

* The Test Protocol will specify the averaging period

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall only combust natural gas in EUBURNER. **(R 336.1205)**
2. The permittee shall not operate EUROTARYDRYER unless the cyclonic collector is installed and is operating properly. **(R 336.1205)**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall conduct daily visible emissions observations, either by a certified or a non-certified reader, as required in Emission Limit SC I.4. If visible emissions are observed, a USEPA Method 9 certified visible emissions observation, which is a 6-minute average reading consisting of 15 second data points, shall be conducted by a certified reader. Records shall include the visible emissions observations (date, time, name of reader, whether the reader is certified or not), causes of abnormal opacity, corrective actions, and the results of such actions. The permittee shall keep all records on file at the facility for a period of at least five years and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVROTARYDRYER	25	60	R 336.1225

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUFOODPROCESS

DESCRIPTION: Process equipment for drying fruits, vegetables, and fruit pomace. This equipment consists of a, a two vibratory control sieves, a finished hopper/bin, and a hammer mill. All of this equipment exhausts to a dust collection baghouse.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT:

Cartridge fabric filter dust collector using Hemi-Pleat cartridges.

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. PM	0.01 lb per 1,000 pounds of exhaust gases.	Test Protocol*	EUFOODPROCESS	GC 13	R 336.1205(3)
2. PM	0.32 pph	Test Protocol*	EUFOODPROCESS	GC 13	R 336.1205(3)
3. PM-10	0.08 pph	Test Protocol*	EUFOODPROCESS	GC 13	R 336.1205(3)
4. Visible Emissions	10% opacity	6 minute average	EUFOODPROCESS	SC VI.1	R 336.1301
* The Test Protocol will specify the averaging period					

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUFOODPROCESS unless the fabric filter collector is installed and is operating properly. Proper operation of the fabric filter means compliance with all manufacturer recommendations with respect to collector inspection and maintenance, and filter replacement. **(R 336.1205(3))**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall conduct daily visible emissions observations, either by a certified or a non-certified reader, as required in Emission Limit SC I.4. If visible emissions are observed, a USEPA Method 9 certified visible emissions observation, which is a 6-minute average reading consisting of 15 second data points, shall be conducted by a certified reader. Records shall include the visible emissions observations (date, time, name of reader, whether the reader is certified or not), causes of abnormal opacity, corrective actions, and the results of such actions. The permittee shall keep all records on file at the facility for a period of at least five years and make them available to the Department upon request. **(R 336.1301, R 336.1331, R 336.1910)**
2. The permittee shall maintain records of the following information for the fabric filter collector:
 - a. The fabric collector manufacturers specific recommendations for proper operation of the fabric filter including:
 - i. Inspection frequency
 - ii. Recommended spare parts
 - iii. Measurements or parameters used to determine filter replacement.
 - b. Inspection dates
 - c. Filter and/or spare parts replacement dates.**(R 336.1911)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVFOODPROCESS	18	60	R 336.1225

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.	EUROTARYDRYER, EUBURNER, EUFOODPROCES

The following conditions apply to: FGFACILITY

DESCRIPTION: All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.

Emission Units:

POLLUTION CONTROL EQUIPMENT:

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. All materials produced	4.0 ton per hour	Daily average		FGFACILITY	R 336.1301

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall store all raw materials received at the facility in enclosed tanks or storage buildings and which are protected from outdoor weather conditions. **(R 336.1301)**.
2. The permittee shall only process materials in FGFACILITY which are used for human and/or animal consumption. **(R 336.1203)**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall maintain records of the amount and type of raw materials process by FGFACILITY on a daily basis. **(R336.1203)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

1. Upon written notification from the AQD district supervisor, the permittee shall develop, and submit for approval, an odor management plan for FGFACILITY. Such plan shall address all odor producing sources, and measures to mitigate/eliminate the generation of odors and shall be submitted no later than 45 days after written notification from the AQD. **(R 336.1203)**

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).