MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

November 22, 2016

PERMIT TO INSTALL

153-16

ISSUED TO

Paslin Company

LOCATED AT

25411 Ryan Road Warren, Michigan

IN THE COUNTY OF

Macomb

STATE REGISTRATION NUMBER

P0739

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

| REQUIRED BY RULE 203: |
|-------------------------------|
| SIGNATURE: Anutholist Caretin |
| SIGNATURE: |
| SIGNATURE: |
| |

PERMIT TO INSTALL

Table of Contents

| Section | Page |
|---|------|
| Alphabetical Listing of Common Abbreviations / Acronyms | 2 |
| General Conditions | 3 |
| Special Conditions | 5 |
| Flexible Group Summary Table | 5 |
| Special Conditions for FG-Facility | 6 |

Common Abbreviations / Acronyms

| | Common Acronyms | Pollutant / Measurement Abbreviations | | | | |
|---|--|---------------------------------------|---|--|--|--|
| AQD | Air Quality Division | acfm | Actual cubic feet per minute | | | |
| BACT | Best Available Control Technology | BTU | British Thermal Unit | | | |
| CAA | Clean Air Act | °C | Degrees Celsius | | | |
| CAM | Compliance Assurance Monitoring | СО | Carbon Monoxide | | | |
| CEM | Continuous Emission Monitoring | CO ₂ e | Carbon Dioxide Equivalent | | | |
| CFR | Code of Federal Regulations | dscf | Dry standard cubic foot | | | |
| СОМ | Continuous Opacity Monitoring | dscm | Dry standard cubic meter | | | |
| Department/ | Michigan Department of Environmental | °F | Degrees Fahrenheit | | | |
| department | Quality | gr | Grains | | | |
| EU | Emission Unit | HAP | Hazardous Air Pollutant | | | |
| FG | Flexible Group | Hg | Mercury | | | |
| GACS | Gallons of Applied Coating Solids | hr | Hour | | | |
| GC | General Condition | HP | Horsepower | | | |
| GHGs | Greenhouse Gases | H ₂ S | Hydrogen Sulfide | | | |
| HVLP | High Volume Low Pressure* | kW | Kilowatt | | | |
| ID | Identification | lb | Pound | | | |
| IRSL | Initial Risk Screening Level | m | Meter | | | |
| ITSL | Initial Threshold Screening Level | mg | Milligram | | | |
| LAER | Lowest Achievable Emission Rate | mm | Millimeter | | | |
| MACT | Maximum Achievable Control Technology | MM | Million | | | |
| MAERS | Michigan Air Emissions Reporting System | MW | Megawatts | | | |
| MAP | Malfunction Abatement Plan | NMOC | Non-methane Organic Compounds | | | |
| MDEQ | Michigan Department of Environmental | NO _x | Oxides of Nitrogen | | | |
| | Quality | ng | Nanogram | | | |
| MSDS NA | Material Safety Data Sheet Not Applicable | PM | Particulate Matter | | | |
| NAAQS | National Ambient Air Quality Standards | PM10 | Particulate Matter equal to or less than 10 microns in diameter | | | |
| NESHAP | National Emission Standard for Hazardous | | Particulate Matter equal to or less than 2.5 | | | |
| | Air Pollutants | PM2.5 | microns in diameter | | | |
| NSPS | New Source Performance Standards | pph | Pounds per hour | | | |
| NSR | New Source Review | ppm | Parts per million | | | |
| PS | Performance Specification | ppmv | Parts per million by volume | | | |
| PSD | Prevention of Significant Deterioration | ppmw | Parts per million by weight | | | |
| PTE | Permanent Total Enclosure | psia | Pounds per square inch absolute | | | |
| PTI | Permit to Install | psig | Pounds per square inch gauge | | | |
| RACT | Reasonable Available Control Technology | scf | Standard cubic feet | | | |
| ROP | Renewable Operating Permit | sec | Seconds | | | |
| SC | Special Condition | SO ₂ | Sulfur Dioxide | | | |
| SCR | Selective Catalytic Reduction | TAC | Toxic Air Contaminant | | | |
| SNCR | Selective Non-Catalytic Reduction | Temp | Temperature | | | |
| SRN | State Registration Number | THC | Total Hydrocarbons | | | |
| TEQ | Toxicity Equivalence Quotient | tpy | Tons per year | | | |
| USEPA/EPA | United States Environmental Protection Agency | μg | Microgram | | | |
| VE | Visible Emissions | μm VOC | Micrometer or Micron | | | |
| V L | VISIDIC LIIIISSIUIIS | | Volatile Organic Compounds Year | | | |
| *For HVI P applicators, the pressure measured at the gun air can shall not exceed 10 psig | | | | | | |

^{*}For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

Paslin Company (P0739)

November 22, 2016

Permit No. 153-16

Page 3 of 7

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

November 22, 2016 Page 4 of 7

Paslin Company (P0739) Permit No. 153-16

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. (R 336.2001)

SPECIAL CONDITIONS

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| Flexible Group ID | Flexible Group Description | Associated Emission Unit IDs |
|-------------------|--|---------------------------------|
| | All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment. | |

The following conditions apply Source-Wide to: FG-Facility

<u>DESCRIPTION</u>: All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.

POLLUTION CONTROL EQUIPMENT:

I. <u>EMISSION LIMITS</u>

| | Pollutant | Limit | Time Period / Operating Scenario | Equipment | Testing / Monitoring Method | Underlying Applicable Requirements |
|----|---------------------------|-------------------------|---|-------------|-----------------------------------|--|
| 1. | Each Individual HAP | Less than 9.0 tpy * | 12-month rolling time period as determined at the end of each calendar month | FG-Facility | SC VI.3 | R 336.1205(3) |
| 2. | Aggregate HAPs | Less than 22.5 tpy * | 12-month rolling time period as determined at the end of each calendar month | FG-Facility | SC VI.3 | R 336.1205(3) |

^{*} Beginning on PTI Issuance Date of this permit, and continuing for the first 12 calendar months, this limit applies to the cumulative total HAP emissions. Thereafter, the limit shall become a 12-month rolling limit.

II. MATERIAL LIMITS

N/A

III. PROCESS/OPERATIONAL RESTRICTIONS

N/A

IV. DESIGN/EQUIPMENT PARAMETERS

N/A

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. (R 336.1205(3))

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1225, R 336.1205(3))
- 2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1205(3))
- 3. The permittee shall keep the following information on a calendar month basis for FGFACILITY:
 - a) Gallons or pounds of each HAP containing material used.
 - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
 - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
 - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
 - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month. For the first month following permit issuance, the calculations shall include the summation of emissions from the 11-month period immediately preceding the issuance date. For each month thereafter, calculations shall include the summation of emissions for the appropriate number of months prior to permit issuance plus the months following permit issuance for a total of 12 consecutive months.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1205(3))

VII. REPORTING

N/A

VIII. STACK/VENT RESTRICTIONS

N/A

IX. OTHER REQUIREMENTS

NA