

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

September 14, 2017

PERMIT TO INSTALL
123-17

ISSUED TO
Brink Wood Products

LOCATED AT
1175 76th Street SW
Byron Center, Michigan

IN THE COUNTY OF
Kent

STATE REGISTRATION NUMBER
P0827

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

August 4, 2017

DATE PERMIT TO INSTALL APPROVED:

September 14, 2017

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

| Section | Page |
|---|-------------|
| Alphabetical Listing of Common Abbreviations / Acronyms | 2 |
| General Conditions | 3 |
| Special Conditions | 5 |
| Emission Unit Summary Table..... | 5 |
| Special Conditions for EUTUBGRINDER | 5 |
| Appendices | 7 |

Common Abbreviations / Acronyms

| Common Acronyms | | Pollutant / Measurement Abbreviations | |
|---------------------------|--|--|---|
| AQD | Air Quality Division | acfm | Actual cubic feet per minute |
| BACT | Best Available Control Technology | BTU | British Thermal Unit |
| CAA | Clean Air Act | °C | Degrees Celsius |
| CAM | Compliance Assurance Monitoring | CO | Carbon Monoxide |
| CEM | Continuous Emission Monitoring | CO _{2e} | Carbon Dioxide Equivalent |
| CFR | Code of Federal Regulations | dscf | Dry standard cubic foot |
| COM | Continuous Opacity Monitoring | dscm | Dry standard cubic meter |
| Department/ department | Michigan Department of Environmental Quality | °F | Degrees Fahrenheit |
| EU | Emission Unit | gr | Grains |
| FG | Flexible Group | HAP | Hazardous Air Pollutant |
| GACS | Gallons of Applied Coating Solids | Hg | Mercury |
| GC | General Condition | hr | Hour |
| GHGs | Greenhouse Gases | HP | Horsepower |
| HVLP | High Volume Low Pressure* | H ₂ S | Hydrogen Sulfide |
| ID | Identification | kW | Kilowatt |
| IRSL | Initial Risk Screening Level | lb | Pound |
| ITSL | Initial Threshold Screening Level | m | Meter |
| LAER | Lowest Achievable Emission Rate | mg | Milligram |
| MACT | Maximum Achievable Control Technology | mm | Millimeter |
| MAERS | Michigan Air Emissions Reporting System | MM | Million |
| MAP | Malfunction Abatement Plan | MW | Megawatts |
| MDEQ | Michigan Department of Environmental Quality | NMOC | Non-methane Organic Compounds |
| MSDS | Material Safety Data Sheet | NO _x | Oxides of Nitrogen |
| NA | Not Applicable | ng | Nanogram |
| NAAQS | National Ambient Air Quality Standards | PM | Particulate Matter |
| NESHAP | National Emission Standard for Hazardous Air Pollutants | PM ₁₀ | Particulate Matter equal to or less than 10 microns in diameter |
| NSPS | New Source Performance Standards | PM _{2.5} | Particulate Matter equal to or less than 2.5 microns in diameter |
| NSR | New Source Review | pph | Pounds per hour |
| PS | Performance Specification | ppm | Parts per million |
| PSD | Prevention of Significant Deterioration | ppmv | Parts per million by volume |
| PTE | Permanent Total Enclosure | ppmw | Parts per million by weight |
| PTI | Permit to Install | psia | Pounds per square inch absolute |
| RACT | Reasonable Available Control Technology | psig | Pounds per square inch gauge |
| ROP | Renewable Operating Permit | scf | Standard cubic feet |
| SC | Special Condition | sec | Seconds |
| SCR | Selective Catalytic Reduction | SO ₂ | Sulfur Dioxide |
| SNCR | Selective Non-Catalytic Reduction | TAC | Toxic Air Contaminant |
| SRN | State Registration Number | Temp | Temperature |
| TEQ | Toxicity Equivalence Quotient | THC | Total Hydrocarbons |
| USEPA/EPA | United States Environmental Protection Agency | tpy | Tons per year |
| VE | Visible Emissions | µg | Microgram |
| | | µm | Micrometer or Micron |
| | | VOC | Volatile Organic Compounds |
| | | yr | Year |

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| Emission Unit ID | Emission Unit Description (Process Equipment & Control Devices) | Flexible Group ID |
|--|---|-------------------|
| EUTUBGRINDER | Vermeer 7000 tub grinder for grinding waste wood form furniture factories, including plywood and particle board, as well as associated material handling. The grinder is portable. Emissions from the grinder and conveyor are controlled by water spray. | NA |
| Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290. | | |

The following conditions apply to: EUTUBGRINDER

DESCRIPTION: Vermeer 7000 tub grinder for grinding waste wood form furniture factories, including plywood and particle board, as well as associated material handling. The grinder is portable.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Emissions from the grinder and conveyor are controlled by water spray.

I. EMISSION LIMITS

1. Visible emissions from the grinder portion of EUTUBGRINDER shall not exceed a six-minute average of five (5) percent opacity. **(R 336.1301, 40 CFR 52.21(c) & (d))**
2. Visible emissions from all wheel loaders and all truck traffic, operated in conjunction with EUTUBGRINDER shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, 40 CFR 52.21(c) & (d))**
3. Visible emissions from each storage pile associated with EUTUBGRINDER shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, 40 CFR 52.21(c) & (d))**

II. MATERIAL LIMITS

1. The permittee shall not process more than 7,500 tons of scrap wood through the grinder portion of EUTUBGRINDER per 12-month rolling time period, as determined at the end of each calendar month. **(R 336.1205, 40 CFR 52.21(c) and (d))**
2. The permittee shall grind only scrap wood in the grinder portion of EUTUBGRINDER. Scrap wood does not contain asbestos, is not painted with lead paint, does not contain plastic that is not adhered to the surface of the wood, and does not contain other non-wood materials that could generate odors or visible emissions. **(R 336.1301, R 336.1901, 40 CFR Part 61 Subpart M)**

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUTUBGRINDER unless the program for continuous fugitive emissions control for all plant roadways, the plant yard, all storage piles, and all material handling operations specified in Appendix A has been implemented and is maintained. **(R 336.1301, R 336.1371, R 336.1901)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate the grinder portion of EUTUBGRINDER unless the associated water sprays on the conveyor and the tub grinder are installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes applying sufficient water to the scrap wood prior to and during grinding to eliminate dust emissions from the grinder and conveyor. **(R 336.1301, R 336.1910, 40 CFR 52.21(c) and (d))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep, in a satisfactory manner, records of the amount of scrap wood ground in the grinder portion of EUTUBGRINDER for each calendar month, and each 12-month rolling time period, as determined at the end of each calendar month. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1205, 40 CFR 52.21(c) and (d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

APPENDIX A: Nuisance Management Plan for Fugitive Dust Control

I. Plant

The drop distance at each transfer point throughout the plant shall be reduced to the minimum the equipment can achieve.

II. Truck Traffic

On-site vehicles shall be loaded to prevent their contents from dropping, leaking, blowing or otherwise escaping. The trucks leaving the facility shall be tarped.

III. Site Roadways and the Plant Yard

- (a) The dust on the site roadways and the plant yard shall be controlled by applications of water, calcium chloride or other acceptable and approved fugitive dust control compounds. Applications of dust suppressants shall be done as often as necessary to meet an opacity limit of five percent.
- (b) All paved roadways and the plant yards shall be swept as needed between applications of dust suppressants.
- (c) Any material spillage on roads shall be cleaned up immediately.
- (d) A record of all applications of dust suppressants and roadway and the plant yard sweepings shall be kept on file for the most recent five-year period and be made available to the AQD upon request.

IV. Storage Piles

- (a) Stockpiling of all nonmetallic minerals shall be performed to minimize drop distance and control potential dust problems.
- (b) Stockpiles shall be watered on an as needed basis in order to meet an opacity limit of five percent. Equipment to apply water or dust suppressant shall be available at the site, or on call for use at the site, within a given operating day.
- (c) A record of all watering shall be kept on file for the most recent five-year period and be made available to the AQD upon request.

V. AQD/MDEQ Inspection

The provisions and procedures of this plan are subject to adjustment by written notification from the AQD, if following an inspection, the AQD finds the fugitive dust requirements and/or the permitted opacity limits are not being met.