# MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

December 11, 2017

PERMIT TO INSTALL 160-17

**ISSUED TO**OilGear

LOCATED AT 1424 International Drive Traverse City, Michigan

IN THE COUNTY OF Grand Traverse

RIS PENINSULAS

# STATE REGISTRATION NUMBER P0874

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:  November 14, 2017			
December 11, 2017	SIGNATURE:		
DATE PERMIT VOIDED:	SIGNATURE:		
DATE PERMIT REVOKED:	SIGNATURE:		

# **PERMIT TO INSTALL**

# **Table of Contents**

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table	5
Flexible Group Summary Table	5
Special Conditions for FGCLEAN	6

 OilGear (P0874)
 December 11, 2017

 Permit No. 160-17
 Page 2 of 7

# **Common Abbreviations / Acronyms**

BACT B CAA C	Common Acronyms  Air Quality Division  Best Available Control Technology	acfm	ollutant / Measurement Abbreviations  Actual cubic feet per minute
BACT B CAA C	•	acım	ACTUAL CUDIC TEEL DEL MINUTE
CAA C	best Available Control Technology	DTU	·
	Noon Air Aot	BTU	British Thermal Unit
CAM	Clean Air Act	°C	Degrees Celsius
	Compliance Assurance Monitoring	CO	Carbon Monoxide
	Continuous Emission Monitoring	CO <sub>2</sub> e	Carbon Dioxide Equivalent
	Code of Federal Regulations	dscf	Dry standard cubic foot
	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
	Michigan Department of Environmental	°F	Degrees Fahrenheit
•	Quality Emission Unit	gr HAP	Grains Hazardous Air Pollutant
_	Flexible Group		
	Sallons of Applied Coating Solids	Hg	Mercury
	Seneral Condition	hr	Hour
	Greenhouse Gases	HP	Horsepower
		H <sub>2</sub> S	Hydrogen Sulfide
	ligh Volume Low Pressure*	kW	Kilowatt
	dentification	lb	Pound
	nitial Risk Screening Level	m	Meter
	nitial Threshold Screening Level	mg	Milligram
	owest Achievable Emission Rate	mm	Millimeter
T	Maximum Achievable Control echnology	MM	Million
S	Michigan Air Emissions Reporting System	MW	Megawatts
	Malfunction Abatement Plan	NMOC	Non-methane Organic Compounds
	Michigan Department of Environmental	$NO_x$	Oxides of Nitrogen
	Quality	ng	Nanogram
	Material Safety Data Sheet	PM	Particulate Matter
	Not Applicable	PM10	Particulate Matter equal to or less than 10 microns in diameter
NESHAP N	National Ambient Air Quality Standards  National Emission Standard for  National Emission Standard for  National Emission Standard for	PM2.5	Particulate Matter equal to or less than 2.5
	New Source Performance Standards	nnh	microns in diameter Pounds per hour
	New Source Review	pph ppm	Parts per million
	Performance Specification	ppmv	Parts per million by volume
PSD P	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE P	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI P	Permit to Install	psig	Pounds per square inch gauge
	Reasonable Available Control Technology	scf	Standard cubic feet
	Renewable Operating Permit	sec	Seconds
sc s	Special Condition	$SO_2$	Sulfur Dioxide
	Selective Catalytic Reduction	TAC	Toxic Air Contaminant
	Selective Non-Catalytic Reduction	Temp	Temperature
	State Registration Number	THC	Total Hydrocarbons
	oxicity Equivalence Quotient	tpy	Tons per year
	Inited States Environmental Protection	μg	Microgram
	Agency	μm	Micrometer or Micron
VE V	/isible Emissions	VOC	Volatile Organic Compounds
		yr	Year

<sup>\*</sup>For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

OilGear (P0874) December 11, 2017
Permit No. 160-17 Page 3 of 7

#### **GENERAL CONDITIONS**

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))

- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

OilGear (P0874) December 11, 2017
Permit No. 160-17 Page 4 of 7

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. (R 336.1301)

- a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
- b) A visible emission limit specified by an applicable federal new source performance standard.
- c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. (R 336.2001)

OilGear (P0874) December 11, 2017
Permit No. 160-17 Page 5 of 7

## **SPECIAL CONDITIONS**

# **EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUBOOTH1	A spray booth used to clean pump and valve parts using a spray-applied cleaner. The booth is equipped with particulate filters.	FGCLEAN
EUBOOTH2	A spray booth used to clean pump and valve parts using a spray- applied cleaner. The booth is equipped with particulate filters.	FGCLEAN

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.

# **FLEXIBLE GROUP SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGCLEAN	Two spray booths used to clean pump and valve parts using a spray-applied cleaner prior to repair operations.	EUBOOTH1, EUBOOTH2
	The booths are equipped with particulate filters.	

OilGear (P0874) December 11, 2017
Permit No. 160-17 Page 6 of 7

## The following conditions apply to: FGCLEAN

**<u>DESCRIPTION</u>**: Two spray booths used to clean pump and valve parts using spray-applied cleaner prior to repair operations. The booths are equipped with particulate filters.

Emission Unit IDs: EUBOOTH1, EUBOOTH2

POLLUTION CONTROL EQUIPMENT: NA

#### I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOCs	10.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGCLEAN	SC VI.2	R 336.1702

#### **II. MATERIAL LIMITS**

NA

#### III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. (R 336.1224, R 336.1370)

## IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any emission unit in FGCLEAN unless all respective exhaust filters are installed, maintained and operated in a satisfactory manner. (R 336.1301, R 336.1910)

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

# VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor and make them available by the end of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. (R 336.1225, R 336.1702(a))

OilGear (P0874) December 11, 2017
Permit No. 160-17 Page 7 of 7

- 2. The permittee shall keep the following information on a monthly basis for FGCLEAN:
  - a) Gallons of spray-applied cleaner used.
  - b) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - c) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
  - d) Hours of operations.

The permittee shall keep the records on file at the facility, in a format acceptable to the AQD District Supervisor, and make them available to the Department upon request. (R 336.1702(a))

## VII. REPORTING

NA

## VIII. STACK/VENT RESTRICTIONS

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-BOOTHS <sup>a</sup>	24	13	R 336.1225,
			40 CFR 52.21(c) & (d)
<sup>a</sup> This stack/vent discharges horizontally out of the building.			

## IX. OTHER REQUIREMENTS

NA

# Footnotes:

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).