

Michigan Department of Natural Resources and Environment
Air Quality Division

EFFECTIVE DATE: January 18, 2011

ISSUED TO

Graphics Packaging

State Registration Number (SRN): B1534

LOCATED AT

79 East Fountain Street, Battle Creek, Michigan 49016

RENEWABLE OPERATING PERMIT

Permit Number: MI-ROP-B1534-2011

Expiration Date: January 18, 2016

Administratively Complete ROP Renewal Application Due Between July 18, 2014 and July 18, 2015

This Renewable Operating Permit (ROP) is issued in accordance with and subject to Section 5506(3) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). Pursuant to Michigan Air Pollution Control Rule 210(1), this ROP constitutes the permittee's authority to operate the stationary source identified above in accordance with the general conditions, special conditions and attachments contained herein. Operation of the stationary source and all emission units listed in the permit are subject to all applicable future or amended rules and regulations pursuant to Act 451 and the federal Clean Air Act.

SOURCE-WIDE PERMIT TO INSTALL

Permit Number: MI-PTI-B1534-2011

This Permit to Install (PTI) is issued in accordance with and subject to Section 5505(5) of Act 451. Pursuant to Michigan Air Pollution Control Rule 214a, the terms and conditions herein, identified by the underlying applicable requirement citation of Rule 201(1)(a), constitute a federally enforceable PTI. The PTI terms and conditions do not expire and remain in effect unless the criteria of Rule 201(6) are met. Operation of all emission units identified in the PTI is subject to all applicable future or amended rules and regulations pursuant to Act 451 and the federal Clean Air Act.

Michigan Department of Natural Resources and Environment

Mary A. Douglas, Kalamazoo District Supervisor

TABLE OF CONTENTS

AUTHORITY AND ENFORCEABILITY	3
A. GENERAL CONDITIONS	4
Permit Enforceability	4
General Provisions	4
Equipment & Design	5
Emission Limits	5
Testing/Sampling	5
Certification & Reporting	6
Permit Shield.....	7
Revisions	8
Reopenings.....	8
Renewals	9
Stratospheric Ozone Protection	9
Risk Management Plan.....	9
Emission Trading	9
Permit To Install (PTI)	10
B. SOURCE-WIDE CONDITIONS	11
C. EMISSION UNIT CONDITIONS	12
EMISSION UNIT SUMMARY TABLE	12
EUBLR001	13
EUPAPERMACH1	16
EUPAPERMACH2	19
EUSTARCHSILO	21
D. FLEXIBLE GROUP CONDITIONS	23
FLEXIBLE GROUP SUMMARY TABLE	23
FGCOLDCLEANERS.....	24
E. NON-APPLICABLE REQUIREMENTS.....	26
APPENDICES.....	27
Appendix 1: Abbreviations and Acronyms	27
Appendix 2. Schedule of Compliance	28
Appendix 3. Monitoring Requirements	28
Appendix 4. Recordkeeping.....	29
Appendix 5. Testing Procedures	31
Appendix 6. Permits to Install	31
Appendix 7. Emission Calculations	31
Appendix 8. Reporting	31
Appendix 9. Malfunction Abatement Plan	31

AUTHORITY AND ENFORCEABILITY

For the purpose of this permit, the **permittee** is defined as any person who owns or operates an emission unit at a stationary source for which this permit has been issued. The **department** is defined in Rule 104(d) as the Director of the Michigan Department of Natural Resources and Environment (MDNRE) or his or her designee.

The permittee shall comply with all specific details in the permit terms and conditions and the cited underlying applicable requirements. All terms and conditions in this ROP are both federally enforceable and state enforceable unless otherwise footnoted. Certain terms and conditions are applicable to most stationary sources for which an ROP has been issued. These general conditions are included in Part A of this ROP. Other terms and conditions may apply to a specific emission unit, several emission units which are represented as a flexible group, or the entire stationary source which is represented as a source-wide group. Special conditions are identified in Parts B, C, D and/or the appendices.

In accordance with Rule 213(2)(a), all underlying applicable requirements will be identified for each ROP term or condition. All terms and conditions that are included in a PTI, are streamlined or subsumed, or is state only enforceable will be noted as such.

In accordance with Section 5507 of Act 451, the permittee has included in the ROP application a compliance certification, a schedule of compliance, and a compliance plan. For applicable requirements with which the source is in compliance, the source will continue to comply with these requirements. For applicable requirements with which the source is not in compliance, the source will comply with the detailed schedule of compliance requirements that are incorporated as an appendix in this ROP. Furthermore, for any applicable requirements effective after the date of issuance of this ROP, the stationary source will meet the requirements on a timely basis, unless the underlying applicable requirement requires a more detailed schedule of compliance.

Issuance of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.

A. GENERAL CONDITIONS

Permit Enforceability

- All conditions in this permit are both federally enforceable and state enforceable unless otherwise noted. **(R 336.1213(5))**
- Those conditions that are hereby incorporated in a state only enforceable Source-wide PTI pursuant to Rule 201(2)(d) are designated by footnote one. **(R 336.1213(5)(a), R336.1214a(5))**
- Those conditions that are hereby incorporated in federally enforceable Source-wide PTI No. MI-PTI-B1534-pursuant to Rule 201(2)(c) are designated by footnote two. **(R 336.1213(5)(b), R 336.1214a(3))**

General Provisions

1. The permittee shall comply with all conditions of this ROP. Any ROP noncompliance constitutes a violation of Act 451, and is grounds for enforcement action, for ROP revocation or revision, or for denial of the renewal of the ROP. All terms and conditions of this ROP that are designated as federally enforceable are enforceable by the Administrator of the United States Environmental Protection Agency (USEPA) and by citizens under the provisions of the federal Clean Air Act (CAA). Any terms and conditions based on applicable requirements which are designated as "state only" are not enforceable by the USEPA or citizens pursuant to the CAA. **(R 336.1213(1)(a))**
2. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this ROP. **(R 336.1213(1)(b))**
3. This ROP may be modified, revised, or revoked for cause. The filing of a request by the permittee for a permit modification, revision, or termination, or a notification of planned changes or anticipated noncompliance does not stay any ROP term or condition. This does not supersede or affect the ability of the permittee to make changes, at the permittee's own risk, pursuant to Rule 215 and Rule 216. **(R 336.1213(1)(c))**
4. The permittee shall allow the department, or an authorized representative of the department, upon presentation of credentials and other documents as may be required by law and upon stating the authority for and purpose of the investigation, to perform any of the following activities: **(R 336.1213(1)(d))**
 - a. Enter, at reasonable times, a stationary source or other premises where emissions-related activity is conducted or where records must be kept under the conditions of the ROP.
 - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the ROP.
 - c. Inspect, at reasonable times, any of the following:
 - i. Any stationary source.
 - ii. Any emission unit.
 - iii. Any equipment, including monitoring and air pollution control equipment.
 - iv. Any work practices or operations regulated or required under the ROP.
 - d. As authorized by Section 5526 of Act 451, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the ROP or applicable requirements.
5. The permittee shall furnish to the department, within a reasonable time, any information the department may request, in writing, to determine whether cause exists for modifying, revising, or revoking the ROP or to determine compliance with this ROP. Upon request, the permittee shall also furnish to the department copies of any records that are required to be kept as a term or condition of this ROP. For information which is claimed

by the permittee to be confidential, consistent with the requirements of the 1976 PA 442, MCL §15.231 et seq., and known as the Freedom of Information Act, the person may also be required to furnish the records directly to the USEPA together with a claim of confidentiality. **(R 336.1213(1)(e))**

6. A challenge by any person, the Administrator of the USEPA, or the department to a particular condition or a part of this ROP shall not set aside, delay, stay, or in any way affect the applicability or enforceability of any other condition or part of this ROP. **(R 336.1213(1)(f))**
7. The permittee shall pay fees consistent with the fee schedule and requirements pursuant to Section 5522 of Act 451. **(R 336.1213(1)(g))**
8. This ROP does not convey any property rights or any exclusive privilege. **(R 336.1213(1)(h))**

Equipment & Design

9. Any collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
10. Any air cleaning device shall be installed, maintained, and operated in a satisfactory manner and in accordance with the Michigan Air Pollution Control rules and existing law. **(R 336.1910)**

Emission Limits

11. Except as provided in Subrules 2, 3, and 4 of Rule 301, states in part; "a person shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of a density greater than the most stringent of Rule 301(1)(a) or (b) unless otherwise specified in this ROP." The grading of visible emissions shall be determined in accordance with Rule 303. **(R 336.1301(1) in pertinent part):**
 - a. A 6-minute average of 20 percent opacity, except for one 6-minute average per hour of not more than 27 percent opacity.
 - b. A limit specified by an applicable federal new source performance standard.
12. The permittee shall not cause or permit the emission of an air contaminant or water vapor in quantities that cause, alone or in reaction with other air contaminants, either of the following:
 - a. Injurious effects to human health or safety, animal life, plant life of significant economic value, or property.¹ **(R 336.1901(a))**
 - b. Unreasonable interference with the comfortable enjoyment of life and property.¹ **(R 336.1901(b))**

Testing/Sampling

13. The department may require the owner or operator of any source of an air contaminant to conduct acceptable performance tests, at the owner's or operator's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001(1). **(R 336.2001)**
14. Any required performance testing shall be conducted in accordance with Rule 1001(2), Rule 1001(3) and Rule 1003. **(R 336.2001(2), R 336.2001(3), R 336.2003(1))**
15. Any required test results shall be submitted to the Air Quality Division (AQD) in the format prescribed by the applicable reference test method within 60 days following the last date of the test. **(R 336.2001(4))**

Monitoring/Recordkeeping

16. Records of any periodic emission or parametric monitoring required in this ROP shall include the following information specified in Rule 213(3)(b)(i), where appropriate: **(R 336.1213(3)(b))**
 - a. The date, location, time, and method of sampling or measurements.
 - b. The dates the analyses of the samples were performed.
 - c. The company or entity that performed the analyses of the samples.
 - d. The analytical techniques or methods used.
 - e. The results of the analyses.
 - f. The related process operating conditions or parameters that existed at the time of sampling or measurement.
17. All required monitoring data, support information and all reports, including reports of all instances of deviation from permit requirements, shall be kept and furnished to the department upon request for a period of not less than 5 years from the date of the monitoring sample, measurement, report or application. Support information includes all calibration and maintenance records and all original strip-chart recordings, or other original data records, for continuous monitoring instrumentation and copies of all reports required by the ROP. **(R 336.1213(1)(e), R 336.1213(3)(b)(ii))**

Certification & Reporting

18. Except for the alternate certification schedule provided in Rule 213(3)(c)(iii)(B), any document required to be submitted to the department as a term or condition of this ROP shall contain an original certification by a responsible official which states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete. **(R 336.1213(3)(c))**
19. A responsible official shall certify to the appropriate AQD District Office and to the USEPA that the stationary source is and has been in compliance with all terms and conditions contained in the ROP except for deviations that have been or are being reported to the appropriate AQD District Office pursuant to Rule 213(3)(c). This certification shall include all the information specified in Rule 213(4)(c)(i) through (v) and shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the certification are true, accurate, and complete. The USEPA address is: USEPA, Air Compliance Data - Michigan, Air and Radiation Division, 77 West Jackson Boulevard, Chicago, Illinois 60604. **(R 336.1213(4)(c))**
20. The certification of compliance shall be submitted annually for the term of this ROP as detailed in the special conditions, or more frequently if specified in an applicable requirement or in this ROP. **(R 336.1213(4)(c))**
21. The permittee shall promptly report any deviations from ROP requirements and certify the reports. The prompt reporting of deviations from ROP requirements is defined in Rule 213(3)(c)(ii) as follows, unless otherwise described in this ROP: **(R 336.1213(3)(c))**
 - a. For deviations that exceed the emissions allowed under the ROP, prompt reporting means reporting consistent with the requirements of Rule 912 as detailed in Condition 25. All reports submitted pursuant to this paragraph shall be promptly certified as specified in Rule 213(3)(c)(iii).
 - b. For deviations which exceed the emissions allowed under the ROP and which are not reported pursuant to Rule 912 due to the duration of the deviation, prompt reporting means the reporting of all deviations in the semiannual reports required by Rule 213(3)(c)(i). The report shall describe reasons for each deviation and the actions taken to minimize or correct each deviation.
 - c. For deviations that do not exceed the emissions allowed under the ROP, prompt reporting means the reporting of all deviations in the semiannual reports required by Rule 213(3)(c)(i). The report shall describe the reasons for each deviation and the actions taken to minimize or correct each deviation.

22. For reports required pursuant to Rule 213(3)(c)(ii), prompt certification of the reports is described in Rule 213(3)(c)(iii) as either of the following: **(R 336.1213(3)(c))**
 - a. Submitting a certification by a responsible official with each report which states that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.
 - b. Submitting, within 30 days following the end of a calendar month during which one or more prompt reports of deviations from the emissions allowed under the ROP were submitted to the department pursuant to Rule 213(3)(c)(ii), a certification by a responsible official which states that, "based on information and belief formed after reasonable inquiry, the statements and information contained in each of the reports submitted during the previous month were true, accurate, and complete". The certification shall include a listing of the reports that are being certified. Any report submitted pursuant to Rule 213(3)(c)(ii) that will be certified on a monthly basis pursuant to this paragraph shall include a statement that certification of the report will be provided within 30 days following the end of the calendar month.
23. Semiannually for the term of the ROP as detailed in the special conditions, or more frequently if specified, the permittee shall submit certified reports of any required monitoring to the appropriate AQD District Office. All instances of deviations from ROP requirements during the reporting period shall be clearly identified in the reports. **(R 336.1213(3)(c)(i))**
24. On an annual basis, the permittee shall report the actual emissions, or the information necessary to determine the actual emissions, of each regulated air pollutant as defined in Rule 212(6) for each emission unit utilizing the emissions inventory forms provided by the department. **(R 336.1212(6))**
25. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the appropriate AQD District Office. The notice shall be provided not later than two business days after the start-up, shutdown, or discovery of the abnormal conditions or malfunction. Notice shall be by any reasonable means, including electronic, telephonic, or oral communication. Written reports, if required under Rule 912, must be submitted to the appropriate AQD District Supervisor within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal conditions or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5) and shall be certified by a responsible official in a manner consistent with the CAA. **(R 336.1912)**

Permit Shield

26. Compliance with the conditions of the ROP shall be considered compliance with any applicable requirements as of the date of ROP issuance, if either of the following provisions is satisfied: **(R 336.1213(6)(a)(i), R 336.1213(6)(a)(ii))**
 - a. The applicable requirements are included and are specifically identified in the ROP.
 - b. The permit includes a determination or concise summary of the determination by the department that other specifically identified requirements are not applicable to the stationary source.

Any requirements identified in Part E of this ROP have been identified as non-applicable to this ROP and are included in the permit shield.

27. Nothing in this ROP shall alter or affect any of the following:
 - a. The provisions of Section 303 of the CAA, emergency orders, including the authority of the USEPA under Section 303 of the CAA. **(R 336.1213(6)(b)(i))**
 - b. The liability of the owner or operator of this source for any violation of applicable requirements prior to or at the time of this ROP issuance. **(R 336.1213(6)(b)(ii))**
 - c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the CAA. **(R 336.1213(6)(b)(iii))**

- d. The ability of the USEPA to obtain information from a source pursuant to Section 114 of the CAA. **(R 336.1213(6)(b)(iv))**
28. The permit shield shall not apply to provisions incorporated into this ROP through procedures for any of the following:
- a. Operational flexibility changes made pursuant to Rule 215. **(R 336.1215(5))**
 - b. Administrative Amendments made pursuant to Rule 216(1)(a)(i)-(iv). **(R 336.1216(1)(b)(iii))**
 - c. Administrative Amendments made pursuant to Rule 216(1)(a)(v) until the amendment has been approved by the department. **(R 336.1216(1)(c)(iii))**
 - d. Minor Permit Modifications made pursuant to Rule 216(2). **(R 336.1216(2)(f))**
 - e. State-Only Modifications made pursuant to Rule 216(4) until the changes have been approved by the department. **(R 336.1216(4)(e))**
29. Expiration of this ROP results in the loss of the permit shield. If a timely and administratively complete application for renewal is submitted not more than 18 months, but not less than 6 months, before the expiration date of the ROP, but the department fails to take final action before the end of the ROP term, the existing ROP does not expire until the renewal is issued or denied, and the permit shield shall extend beyond the original ROP term until the department takes final action. **(R 336.1217(1)(c), R 336.1217(1)(a))**

Revisions

30. For changes to any process or process equipment covered by this ROP that do not require a revision of the ROP pursuant to Rule 216, the permittee must comply with Rule 215. **(R 336.1215, R 336.1216)**
31. A change in ownership or operational control of a stationary source covered by this ROP shall be made pursuant to Rule 216(1). **(R 336.1219(2))**
32. For revisions to this ROP, an administratively complete application shall be considered timely if it is received by the department in accordance with the time frames specified in Rule 216. **(R 336.1210(9))**
33. Pursuant to Rule 216(1)(b)(iii), Rule 216(2)(d) and Rule 216(4)(d), after a change has been made, and until the department takes final action, the permittee shall comply with both the applicable requirements governing the change and the ROP terms and conditions proposed in the application for the modification. During this time period, the permittee may choose to not comply with the existing ROP terms and conditions that the application seeks to change. However, if the permittee fails to comply with the ROP terms and conditions proposed in the application during this time period, the terms and conditions in the ROP are enforceable. **(R 336.1216(1)(c)(iii), R 336.1216(2)(d), R 336.1216(4)(d))**

Reopenings

34. A ROP shall be reopened by the department prior to the expiration date and revised by the department under any of the following circumstances:
- a. If additional requirements become applicable to this stationary source with three or more years remaining in the term of the ROP, but not if the effective date of the new applicable requirement is later than the ROP expiration date. **(R 336.1217(2)(a)(i))**
 - b. If additional requirements pursuant to Title IV of the CAA become applicable to this stationary source. **(R 336.1217(2)(a)(ii))**
 - c. If the department determines that the ROP contains a material mistake, information required by any applicable requirement was omitted, or inaccurate statements were made in establishing emission limits or the terms or conditions of the ROP. **(R 336.1217(2)(a)(iii))**
 - d. If the department determines that the ROP must be revised to ensure compliance with the applicable requirements. **(R 336.1217(2)(a)(iv))**

Renewals

35. For renewal of this ROP, an administratively complete application shall be considered timely if it is received by the department not more than 18 months, but not less than 6 months, before the expiration date of the ROP. **(R 336.1210(7))**

Stratospheric Ozone Protection

36. If the permittee is subject to Title 40 of the Code of Federal Regulations (CFR), Part 82 and services, maintains, or repairs appliances except for motor vehicle air conditioners (MVAC), or disposes of appliances containing refrigerant, including MVAC and small appliances, or if the permittee is a refrigerant reclaiming, appliance owner or a manufacturer of appliances or recycling and recovery equipment, the permittee shall comply with all applicable standards for recycling and emissions reduction pursuant to 40 CFR, Part 82, Subpart F.
37. If the permittee is subject to 40 CFR, Part 82, and performs a service on motor (fleet) vehicles when this service involves refrigerant in the MVAC, the permittee is subject to all the applicable requirements as specified in 40 CFR, Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed by the original equipment manufacturer. The term MVAC as used in Subpart B does not include the air-tight sealed refrigeration system used for refrigerated cargo or an air conditioning system on passenger buses using Hydrochlorofluorocarbon-22 refrigerant.

Risk Management Plan

38. If subject to Section 112(r) of the CAA and 40 CFR, Part 68, the permittee shall register and submit to the USEPA the required data related to the risk management plan for reducing the probability of accidental releases of any regulated substances listed pursuant to Section 112(r)(3) of the CAA as amended in 40 CFR, Part 68.130. The list of substances, threshold quantities, and accident prevention regulations promulgated under 40 CFR, Part 68, do not limit in any way the general duty provisions under Section 112(r)(1).
39. If subject to Section 112(r) of the CAA and 40 CFR, Part 68, the permittee shall comply with the requirements of 40 CFR, Part 68, no later than the latest of the following dates as provided in 40 CFR, Part 68.10(a):
- June 21, 1999,
 - Three years after the date on which a regulated substance is first listed under 40 CFR, Part 68.130, or
 - The date on which a regulated substance is first present above a threshold quantity in a process.
40. If subject to Section 112(r) of the CAA and 40 CFR, Part 68, the permittee shall submit any additional relevant information requested by any regulatory agency necessary to ensure compliance with the requirements of 40 CFR, Part 68.
41. If subject to Section 112(r) of the CAA and 40 CFR, Part 68, the permittee shall annually certify compliance with all applicable requirements of Section 112(r) as detailed in Rule 213(4)(c)). **(40 CFR, Part 68)**

Emission Trading

42. Emission averaging and emission reduction credit trading are allowed pursuant to any applicable interstate or regional emission trading program that has been approved by the Administrator of the USEPA as a part of Michigan's State Implementation Plan. Such activities must comply with Rule 215 and Rule 216. **(R 336.1213(12))**

Permit To Install (PTI)

43. The process or process equipment included in this permit shall not be reconstructed, relocated, or modified unless a PTI authorizing such action is issued by the department, except to the extent such action is exempt from the PTI requirements by any applicable rule. ² **(R 336.1201(1))**
44. The department may, after notice and opportunity for a hearing, revoke PTI terms or conditions if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of the PTI or is violating the department's rules or the CAA. ² **(R 336.1201(8), Section 5510 of Act 451)**
45. The terms and conditions of a PTI shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by the PTI. If a new owner or operator submits a written request to the department pursuant to Rule 219 and the department approves the request, this PTI will be amended to reflect the change of ownership or operational control. The request must include all of the information required by Subrules (1)(a), (b) and (c) of Rule 219. The written request shall be sent to the appropriate AQD District Supervisor, MDNRE. ² **(R 336.1219)**
46. If the installation, reconstruction, relocation, or modification of the equipment for which PTI terms and conditions have been approved has not commenced within 18 months, or has been interrupted for 18 months, the applicable terms and conditions from that PTI shall become void unless otherwise authorized by the department. Furthermore, the person to whom that PTI was issued, or the designated authorized agent, shall notify the department via the supervisor, Permit Section, MDNRE, AQD, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, reconstruction, relocation, or modification of the equipment allowed by the terms and conditions from that PTI. ² **(R 336.1201(4))**

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

²This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

B. SOURCE-WIDE CONDITIONS

Part B outlines the Source-Wide Terms and Conditions that apply to this stationary source. The permittee is subject to these special conditions for the stationary source in addition to the general conditions in Part A and any other terms and conditions contained in this ROP.

The permittee shall comply with all specific details in the special conditions and the underlying applicable requirements cited. If a specific condition type does not apply to this source, NA (not applicable) has been used in the table. If there are no Source-Wide Conditions, this section will be left blank.

C. EMISSION UNIT CONDITIONS

Part C outlines terms and conditions that are specific to individual emission units listed in the Emission Unit Summary Table. The permittee is subject to the special conditions for each emission unit in addition to the General Conditions in Part A and any other terms and conditions contained in this ROP.

The permittee shall comply with all specific details in the special conditions and the underlying applicable requirements cited. If a specific condition type does not apply, NA (not applicable) has been used in the table. If there are no conditions specific to individual emission units, this section will be left blank.

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date/ Modification Date	Flexible Group ID
EUBLR001	A 185 MM BTU per hour; 140,000 pound per hour Babcock and Wilcox boiler for the production of process steam and electricity. Natural gas is the primary fuel; however, the boiler can also be dual fired with No. 6 fuel oil.	01-01-1954/ 01-01-1970	NA
EUPAPERMACH1	Paper Machine No. 1 is used to manufacture paperboard stock, and includes wet and paperboard coater 1 and drying oven 1.	01-01-1935/ 03-01-1998	NA
EUPAPERMACH2	Paper Machine No. 2 is used to manufacture paperboard stock, and includes wet and paperboard coater 2 and drying oven 2.	01-01-1935/ NA	NA
EUSTARCHSILO	Storage silo for process starch.	02-01-1999/ NA	NA
EUCOLDCLEANERS	Any cold cleaner that is grandfathered or exempt from Rule 201 pursuant to Rule 278 and Rule 281(h), or Rule 285(r)(iv). Existing cold cleaners were placed into operation prior to July 1, 1979. New cold cleaners were placed into operation on or after July 1, 1979.	01-01-1985/ NA	FGCOLDCLEANERS

EUBLR001
EMISSION UNIT CONDITIONS

DESCRIPTION

A 185 MM BTU per hour, 140,000 pound per hour Babcock and Wilcox boiler for the production of process steam and electricity. Natural gas is the primary fuel; however, the boiler can also be dual fired with No. 6 fuel oil.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. Sulfur Dioxide	280 pounds ²	Per hour	EUBLR001	VI.8	R 336.1201(3)
2. Sulfur Dioxide	6,720 pounds ²	Per calendar day	EUBLR001	VI.6	R 336.1205(3)
3. Sulfur Dioxide	470 tons ²	Per 12-month rolling time period as determined at the end of each calendar month	EUBLR001	VI.10	R 336.1205(3)
4. Nitrogen Oxides	55 pounds ²	Per hour	EUBLR001	V.4	R 336.1205(3)
5. Nitrogen Oxides	215 tons ²	Per 12-month rolling time period as determined at the end of each calendar month	EUBLR001	VI.7	R 336.1213(2)
6. Opacity	10 percent ²	6-minute average when firing with fuel oil	EUBLR001	VI.4	R 336.1301(1)(c)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. Fuel Oil	4.0 million gallons ²	Per 12-month rolling time period as determined at the end of each calendar month	EUBLR001	VI.2	R 336.1205(3)
2. Natural Gas	1,536 million cubic feet ²	Per 12-month rolling time period as determined at the end of each calendar month	EUBLR001	VI.9	R 336.1213(2)

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The maximum sulfur content in fuel oil shall not exceed 1.5% or the equivalent of 1.67 pounds of sulfur dioxide per million BTU of heat input. The maximum sulfur content in fuel is defined as the average sulfur content in all fuels burned, including natural gas, at any one time in EUBLR001. The sulfur content shall be calculated on the basis of 18,000 BTU per pound of liquid fuels.² **(R 336.1401(1) - Table 42)**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1213(3)(b)(ii))**

1. Annual testing of the percent sulfur content in the fuel oil burned in EUBLR001 shall be performed using ASTM D4294, ASTM D129, ASTM D4057, ASTM D2622, or an ASTM test method approved by AQD. The first test shall be performed within the calendar year of permit issuance and subsequent tests shall be performed once each 12 months thereafter. Test results, including test method used, shall be submitted to the AQD within 60 days of completing the test. **(R 336.1213(3))**.
2. Annual testing of density and heat content in BTU per gallon or BTU per pound of fuel oil using an approved test method shall be performed. **(R 336.1213(3))**
3. The permittee shall test EUBLR001 for nitrogen oxides during the term of this permit if the facility returns to dual fuel fired operation of EUBLR001. The testing shall be performed under dual fuel operation at maximum fuel oil usage. **(R 336.1213(3))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1213(3)(b)(ii))**

1. The permittee shall continuously monitor and record the natural gas consumption rate, in million cubic feet. The permittee shall also record the total natural gas consumption rate for each calendar day.² **(R 336.1201(3))**
2. The permittee shall continuously monitor and record the fuel oil consumption rate, in gallons. The permittee shall also record the total fuel oil consumption rate for each calendar day, month, and 12-month rolling time period.² **(R 336.1201(3))**
3. The permittee shall maintain a complete record of fuel oil specifications and/or a fuel oil analysis for each delivery, or storage tank, of fuel oil in order to demonstrate compliance with the percent sulfur limit in fuel oil. These records may include purchase records for ASTM specification fuel oil, specifications or analyses provided by the vendor at the time of delivery, analytical results from laboratory testing, or any other records adequate to demonstrate compliance with the percent sulfur limit in fuel oil. **(R 336.1213(3))**
4. To ensure proper operation when firing residual fuel oil (residual fuel oil means fuel oil grades no. 3 through no. 6), the permittee shall perform and record the results of a six-minute visible emission check of SVBLR001 immediately after each start-up occurrence and at least once per calendar day thereafter during maximum routine operating conditions. If visible emissions are observed, the permittee shall implement the monitoring program listed in Appendix 3A. **(R 336.1213(3))**
5. The permittee shall monitor and record the actual hours of operation for each calendar day. **(R 336.1213(3))**
6. The permittee shall calculate and record the sulfur dioxide emission rate for each calendar day that fuel oil is fired. **(R 336.1213(3))**

7. The permittee shall calculate and record the nitrogen oxides emission rate for each calendar month. The permittee shall also calculate and record the 12-month rolling time period emission rate as determined at the end of each calendar month. **(R 336.1213(3))**
8. The permittee shall calculate and record the pounds per hour sulfur dioxide emission rate and pounds per million Btu emission rate for each calendar day that fuel oil is fired. **(R 336.1213(3))**
9. The permittee shall calculate on a monthly basis the natural gas consumption rate in million cubic feet, and determine the 12-month rolling time period consumption rate. **(R 336.1213(3))**
10. The permittee shall calculate and record emission rates for sulfur dioxide for each calendar month and each 12-month rolling time period as determined at the end of each calendar month. **(R 336.1213(3))**

See Appendix 4

VII. REPORTING

1. Prompt reporting of deviations pursuant to General Conditions 21 and 22 of Part A. **(R 336.1213(3)(c)(ii))**
2. Semiannual reporting of monitoring and deviations pursuant to General Condition 23 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for reporting period July 1 to December 31 and September 15 for reporting period January 1 to June 30. **(R 336.1213(3)(c)(i))**
3. Annual certification of compliance pursuant to General Conditions 19 and 20 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for the previous calendar year. **(R 336.1213(4)(c))**

See Appendix 8

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVBLR001	48 ²	86 ²	R 336.1201(3)

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).
²This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

**EUPAPERMACH1
 EMISSION UNIT CONDITIONS**

DESCRIPTION

Paper Machine No. 1 is used to manufacture paperboard stock, and includes wet and paperboard coater 1 and drying oven 1.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. Parafinic Oil (CAS # 64742-52-5)	8.20 pounds per hour ¹	Monthly Calculation	EUPAPERMACH1	VI.7	R 336.1225
2. Parafinic Oil (CAS # 64742-52-5)	35.5 tons ¹	Per 12-month rolling time period as determined at the end of each calendar month	EUPAPERMACH1	VI.3	R 336.1225
3. Acetaldehyde	0.25 pounds per hour ¹	Monthly Calculation	EUPAPERMACH1	VI.7	R 336.1225
4. Acetaldehyde	1.08 tons ¹	Per 12-month rolling time period as determined at the end of each calendar month	EUPAPERMACH1	VI.6	R 336.1225
5. VOC*	173.74 pounds per calendar day ²	Monthly Calculation	EUPAPERMACH1	SC VI.8	R 336.1205(3), R 336.1702(a), R 336.1225
6. VOC*	31.71 tons ²	Per 12-month rolling time period as determined at the end of each calendar month	EUPAPERMACH1	VI.9	R 336.1205(3), R 336.1702(a), R 336.1225
7. VOC*	0.05 pounds per gallon of coating, minus water, as applied ²	Monthly Average	EUPAPERMACH1	VI.2b, VI.4	R 336.1702(a)
8. Hazardous Air Pollutants (HAPs)	3.77 tons per year for any individual HAP ²	Per 12-month rolling time period as determined at the end of each calendar month	EUPAPERMACH1	VI.5, VI.6	R 336.1205(3)
9. Hazardous Air Pollutants (HAPs)	4.85 tons per year for any combination of HAPs ²	Per 12-month rolling time period as determined at the end of each calendar month	EUPAPERMACH1	VI.5, VI.6	R 336.1205(3)

* The total VOC emission rate includes VOC content from all coatings, cleaning solvents, parafinic oil and acetaldehyde usage.

II. MATERIAL LIMIT(S)

Material	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
NA	NA	NA	NA	NA	NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1213(3)(b)(ii))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1213(3)(b)(ii))**

1. The permittee shall monitor and record the actual hours of operation of EUPAPERMACH1 for each calendar month.² **(R 336.1201(3))**
2. The permittee shall monitor and record the following information for each coating on a monthly basis:²
 - a. A list that identifies each coating.
 - b. The volatile organic compound content of each coating in pounds per gallon (minus water) as applied.
 - c. The usage rate of each coating.

The records shall be kept in a format acceptable to the AQD District Supervisor and shall be made available to the Department upon request.² **(R 336.1201(3))**

3. The permittee shall record usage rates and calculate emission rates of volatile organic compounds (including coatings, cleaning solvents, acetaldehyde and parafinic oil) for each calendar month and each 12-month rolling time period, as determined at the end of each calendar month. All required calculations shall be completed by the 15th day of the calendar month for the previous calendar month.² **(R 336.1201(3))**
4. The permittee shall keep a material safety data sheet and/or a material specification sheet for each coating used or mixed. At a minimum, these records must include information regarding the volatile organic compound content, water content, density, solids weight fraction and solids volume fraction.² **(R 336.1201(3))**
5. The permittee shall monitor and record the following information for each material containing hazardous air pollutions on a monthly basis:²
 - a. A list that identifies each HAP containing material, including CAS numbers.
 - b. A list of each HAP contained in the material.
 - c. The HAP content for each HAP contained in each material.
 - d. The usage rate of each HAP containing material.

The records shall be kept in a format acceptable to the AQD District Supervisor and shall be made available to the Department upon request.² **(R 336.1201(3))**

6. The permittee shall calculate emission rates of individual and total hazardous air pollutants for each calendar month and each 12-month rolling time period as determined at the end of each calendar month.² **(R 336.1201(3))**
7. The permittee shall calculate the hourly emission rate of parafinic oil and acetaldehyde monthly using the hours of operation and amount used for that month. **(R 336.1213(3))**
8. The permittee shall calculate the daily VOC emission rate. **(R 336.1213(3))**
9. The permittee shall calculate the VOC emission rate for each 12-month rolling time period as determined at the end of each calendar month. **(R 336.1213(3))**

VII. REPORTING

1. Prompt reporting of deviations pursuant to General Conditions 21 and 22 of Part A. **(R 336.1213(3)(c)(ii))**
2. Semiannual reporting of monitoring and deviations pursuant to General Condition 23 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for reporting period July 1 to December 31 and September 15 for reporting period January 1 to June 30. **(R 336.1213(3)(c)(i))**
3. Annual certification of compliance pursuant to General Conditions 19 and 20 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for the previous calendar year. **(R 336.1213(4)(c))**

See Appendix 8

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVWETEND-A	10.0 ¹	35.0 ¹	R 336.1225
2. SVWETEND-B	31.5 ¹	34.0 ¹	R 336.1225
3. SVWETEND-C	6.6 ¹	33.5 ¹	R 336.1225
4. SVWETEND-D	10.8 ¹	34.0 ¹	R 336.1225
5. SVOVEN-1*	20.0 ¹	52.0 ¹	R 336.1225
6. SVHEATEXCHANGER	18.0 ¹	70.0 ¹	R 336.1225

* SVOVEN-1 may be discharged horizontally through a goose-neck T stack.

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).
² This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

**EUPAPERMACH2
 EMISSION UNIT CONDITIONS**

DESCRIPTION

Paper Machine No. 2 is used to manufacture paperboard stock, and includes wet and paperboard coater 2 and drying oven 2.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. VOC	Volume-weighted average of 2.9 pounds per gallon of coating, minus water, as applied	Based upon a calendar day averaging period	EUPAPERMACH2	VI.3b	R 336.1610(2)(f) - Table 63

II. MATERIAL LIMIT(S)

Material	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. NA	NA	NA	NA	NA	NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1213(3)(b)(ii))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1213(3)(b)(ii))

1. The permittee shall monitor and record the actual hours of operation of EUPAPERMACH2 for each calendar month. **(R 336.1213(3))**
2. The permittee shall keep a material safety data sheet and/or a material specification sheet for each coating used or mixed. At a minimum, these records must include information regarding the volatile organic compound content, water content, density, solids weight fraction and solids volume fraction. **(R 336.1213(3))**
3. The permittee shall monitor and record the following information for each calendar day:
 - a. Maintain a list that identifies each coating used.
 - b. Record the volatile organic compound content, in pounds per gallon, minus water, as applied, for each coating used.
 - c. Record the daily usage rate of each coating used.

The records shall be kept in a format acceptable to the AQD District Supervisor and shall be made available to the Department upon request. **(R 336.1610(6))**

See Appendix 4.A.

4. If a coating with a volatile organic compound content greater than 2.9 pounds per gallon, minus water, as applied, is used during a calendar day, the permittee shall monitor and record the information, as required by R 336.2040(12)(a) and R 336.2041, for that calendar day. **(R 336.1610(6))**

See Appendix 4.B.

VII. REPORTING

1. Prompt reporting of deviations pursuant to General Conditions 21 and 22 of Part A. **(R 336.1213(3)(c)(ii))**
2. Semiannual reporting of monitoring and deviations pursuant to General Condition 23 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for reporting period July 1 to December 31 and September 15 for reporting period January 1 to June 30. **(R 336.1213(3)(c)(i))**
3. Annual certification of compliance pursuant to General Conditions 19 and 20 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for the previous calendar year. **(R 336.1213(4)(c))**

See Appendix 8

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
NA	NA	NA	NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

²This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

**EUSTARCHSILO
 EMISSION UNIT CONDITIONS**

DESCRIPTION

Storage silo for process starch.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

Baghouse

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. Particulate	0.10 pounds per 1,000 pounds of exhaust gases, calculated on a dry gas basis	Test Protocol	EUSTARCHSILO	General Condition 13	R 336.1331, Table 31 J

II. MATERIAL LIMIT(S)

Material	Limit	Time Period/ Operating Scenario	Equipment	Monitoring/ Testing Method	Underlying Applicable Requirements
1. NA	NA	NA	NA	NA	NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1213(3)(b)(ii))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1213(3)(b)(ii))

NA

VII. REPORTING

1. Prompt reporting of deviations pursuant to General Conditions 21 and 22 of Part A. **(R 336.1213(3)(c)(ii))**
2. Semiannual reporting of monitoring and deviations pursuant to General Condition 23 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for reporting period July 1 to December 31 and September 15 for reporting period January 1 to June 30. **(R 336.1213(3)(c)(i))**
3. Annual certification of compliance pursuant to General Conditions 19 and 20 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for the previous calendar year. **(R 336.1213(4)(c))**

See Appendix 8

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
NA	NA	NA	NA

IX. OTHER REQUIREMENT(S)

1. The permittee shall perform a visible emission check during filling operations. If visible emissions are observed, the permittee shall cease filling operations until preventative maintenance can be completed. The results shall be recorded in the baghouse maintenance log. **(R 336.1213(3))**

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).
² This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

D. FLEXIBLE GROUP CONDITIONS

Part D outlines the terms and conditions that apply to more than one emission unit. The permittee is subject to the special conditions for each flexible group in addition to the General Conditions in Part A and any other terms and conditions contained in this ROP.

The permittee shall comply with all specific details in the special conditions and the underlying applicable requirements cited. If a specific condition type does not apply, NA (not applicable) has been used in the table. If there are no special conditions that apply to more than one emission unit, this section will be left blank.

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGCOLDCLEANERS	Any cold cleaner that is grandfathered or exempt from Rule 201 pursuant to Rule 278 and Rule 281(h), or Rule 285(r)(iv). Existing cold cleaners were placed into operation prior to July 1, 1979. New cold cleaners were placed into operation on or after July 1, 1979.	EUCOLDCLEANERS

FGCOLDCLEANERS FLEXIBLE GROUP CONDITIONS

DESCRIPTION

Any cold cleaner that is grandfathered or exempt from Rule 201 pursuant to Rule 278 and Rule 281(h), or Rule 285(r)(iv). Existing cold cleaners were placed into operation prior to July 1, 1979. New cold cleaners were placed into operation on or after July 1, 1979.

Emission Unit: EUCOLDCLEANERS

I. EMISSION LIMIT(S)

NA

II. MATERIAL LIMIT(S)

1. The permittee shall not use cleaning solvents containing more than five percent by weight of the following halogenated compounds: methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, chloroform, or any combination thereof. **(R 336.1213(2))**

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. Cleaned parts shall be drained for no less than 15 seconds or until dripping ceases. **(R 336.1611(2)(b), R 336.1707(3)(b))**
2. The permittee shall perform routine maintenance on each cold cleaner as recommended by the manufacturer. **(R 336.1213(3))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The cold cleaner must meet one of the following design requirements:
 - a. The air/vapor interface of the cold cleaner is no more than ten square feet. **(R 336.1281(h))**
 - b. The cold cleaner is used for cleaning metal parts and the emissions are released to the general in-plant environment. **(R 336.1285(r)(iv))**
2. The cold cleaner shall be equipped with a device for draining cleaned parts. **(R 336.1611(2)(b), R 336.1707(3)(b))**
3. All new and existing cold cleaners shall be equipped with a cover and the cover shall be closed whenever parts are not being handled in the cold cleaner. **(R 336.1611(2)(a), R 336.1707(3)(a))**
4. The cover of a new cold cleaner shall be mechanically assisted if the Reid vapor pressure of the solvent is more than 0.3 psia or if the solvent is agitated or heated. **(R 336.1707(3)(a))**
5. If the Reid vapor pressure of any solvent used in a new cold cleaner is greater than 0.6 psia; or, if any solvent used in a new cold cleaner is heated above 120 degrees fahrenheit, then the cold cleaner must comply with at least one of the following provisions:
 - a. The cold cleaner must be designed such that the ratio of the freeboard height to the width of the cleaner is equal to or greater than 0.7. **(R 336.1707(2)(a))**
 - b. The solvent bath must be covered with water if the solvent is insoluble and has a specific gravity of more than 1.0. **(R 336.1707(2)(b))**
 - c. The cold cleaner must be controlled by a carbon adsorption system, condensation system, or other method of equivalent control approved by the AQD. **(R 336.1707(2)(c))**

V. TESTING/SAMPLING

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1213(3)(b)(ii))**

1. For each new cold cleaner in which the solvent is heated, the solvent temperature shall be monitored and recorded at least once each calendar week during routine operating conditions. **(R 336.1213(3))**
2. The permittee shall maintain the following information on file for each cold cleaner: **(R 336.1213(3))**
 - a. A serial number, model number, or other unique identifier for each cold cleaner.
 - b. The date the unit was installed, manufactured or that it commenced operation.
 - c. The air/vapor interface area for any unit claimed to be exempt under Rule 281(h).
 - d. The applicable Rule 201 exemption.
 - e. The Reid vapor pressure of each solvent used.
 - f. If applicable, the option chosen to comply with Rule 707(2).
3. The permittee shall maintain written operating procedures for each cold cleaner. These written procedures shall be posted in an accessible, conspicuous location near each cold cleaner. **(R 336.1611(3), R 336.1707(4))**
4. As noted in Rule 611(2)(c) and Rule 707(3)(c), if applicable, an initial demonstration that the waste solvent is a safety hazard shall be made prior to storage in non-closed containers. If the waste solvent is a safety hazard and is stored in non-closed containers, verification that the waste solvent is disposed of so that not more than 20 percent, by weight, is allowed to evaporate into the atmosphere shall be made on a monthly basis. **(R 336.1213(3), R 336.1611(2)(c), R 336.1707(3)(c))**

VII. REPORTING

1. Prompt reporting of deviations pursuant to General Conditions 21 and 22 of Part A. **(R 336.1213(3)(c)(ii))**
2. Semiannual reporting of monitoring and deviations pursuant to General Condition 23 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for reporting period July 1 to December 31 and September 15 for reporting period January 1 to June 30. **(R 336.1213(3)(c)(i))**
3. Annual certification of compliance pursuant to General Conditions 19 and 20 of Part A. The report shall be postmarked or received by the appropriate AQD District Office by March 15 for the previous calendar year. **(R 336.1213(4)(c))**

See Appendix 8

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

E. NON-APPLICABLE REQUIREMENTS

At the time of the ROP issuance, the AQD has determined that no non-applicable requirements have been identified for incorporation into the permit shield provision set forth in the General Conditions in Part A pursuant to Rule 213(6)(a)(ii).

APPENDICES

Appendix 1: Abbreviations and Acronyms

The following is an alphabetical listing of abbreviations/acronyms that may be used in this permit.

AQD	Air Quality Division	MM	Million
acfm	Actual cubic feet per minute	MSDS	Material Safety Data Sheet
BACT	Best Available Control Technology	MW	Megawatts
BTU	British Thermal Unit	NA	Not Applicable
°C	Degrees Celsius	NAAQS	National Ambient Air Quality Standards
CAA	Federal Clean Air Act	NESHAP	National Emission Standard for Hazardous Air Pollutants
CAM	Compliance Assurance Monitoring	NMOC	Non-methane Organic Compounds
CEM	Continuous Emission Monitoring	NOx	Oxides of Nitrogen
CFR	Code of Federal Regulations	NSPS	New Source Performance Standards
CO	Carbon Monoxide	NSR	New Source Review
COM	Continuous Opacity Monitoring	PM	Particulate Matter
department	Michigan Department of Natural Resources and Environment	PM-10	Particulate Matter less than 10 microns in diameter
dscf	Dry standard cubic foot	pph	Pound per hour
dscm	Dry standard cubic meter	ppm	Parts per million
EPA	United States Environmental Protection Agency	ppmv	Parts per million by volume
EU	Emission Unit	ppmw	Parts per million by weight
°F	Degrees Fahrenheit	PS	Performance Specification
FG	Flexible Group	PSD	Prevention of Significant Deterioration
GACS	Gallon of Applied Coating Solids	psia	Pounds per square inch absolute
gr	Grains	psig	Pounds per square inch gauge
HAP	Hazardous Air Pollutant	PeTE	Permanent Total Enclosure
Hg	Mercury	PTI	Permit to Install
hr	Hour	RACT	Reasonable Available Control Technology
HP	Horsepower	ROP	Renewable Operating Permit
H ₂ S	Hydrogen Sulfide	SC	Special Condition
HVLP	High Volume Low Pressure *	scf	Standard cubic feet
ID	Identification (Number)	sec	Seconds
IRSL	Initial Risk Screening Level	SCR	Selective Catalytic Reduction
ITSL	Initial Threshold Screening Level	SO ₂	Sulfur Dioxide
LAER	Lowest Achievable Emission Rate	SRN	State Registration Number
lb	Pound	TAC	Toxic Air Contaminant
m	Meter	Temp	Temperature
MACT	Maximum Achievable Control Technology	THC	Total Hydrocarbons
MAERS	Michigan Air Emissions Reporting System	tpy	Tons per year
MAP	Malfunction Abatement Plan	µg	Microgram
MDNRE	Michigan Department of Natural Resources and Environment	VE	Visible Emissions
mg	Milligram	VOC	Volatile Organic Compounds
mm	Millimeter	yr	Year

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 pounds per square inch gauge (psig).

Appendix 2. Schedule of Compliance

The permittee certified in the ROP application that this stationary source is in compliance with all applicable requirements and the permittee shall continue to comply with all terms and conditions of this ROP. A Schedule of Compliance is not required. **(R 336.1213(4)(a), R 336.1119(a)(ii))**

Appendix 3. Monitoring Requirements

The following monitoring procedures, methods, or specifications are the details to the monitoring requirements identified and referenced in EUBLR001.

A. Monitoring Requirements for EUBLR001

The permittee shall use the following approved formats and procedures for the record keeping requirements referenced in EUBLR001 when firing residual fuel oil (residual fuel oil means fuel oil grades No. 3 through No. 6) unless an alternative format is approved by the AQD District Supervisor.

1. The permittee shall perform and record the results of a six-minute visible emission check of SVBLR001 immediately after each start-up occurrence and at least once per calendar day thereafter during maximum routine operating conditions. **(R 336.1213(3))**
2. If visible emissions are observed at start-up or during maximum routine operating conditions, the permittee shall then perform and record the results of a six-minute visible emission check of SVBLR001 at least once every 30 minutes thereafter, until visible emissions are no longer observable or until visible emissions are observable for more than 2 hours. **(R 336.1213(3))**
3. If visible emissions are still observable within 2 hours of the initial observance, the permittee shall proceed with the Malfunction Abatement Plan in Appendix 9A and perform and record the results of a Federal Reference Test Method 9 visible emission observation of SVBLR001 within 2 hours; or the permittee shall cease firing of fuel oil and revert to firing natural gas. **(R 336.1213(3))**
4. If a Federal Reference Test Method 9 visible emission observation is performed and indicates a violation of the opacity standard specified in R 336.1301 (See General Condition 11.a), the permittee shall immediately notify the AQD as required in General Condition No. 21 of Part A. **(R 336.1213(3))**
5. If a Federal Reference Test Method 9 visible emission observation is performed and indicates that the opacity from EUBLR001 is in compliance with R 336.1301, then the permittee may continue to fire residual fuel oil and cease making visible emission checks until such time that residual fuel oil start-up occurs again.

NOTE: The purpose of the six-minute visible emission check is to verify (yes or no) whether visible emissions are observed. Therefore, the permittee should record a positive or negative response for each visible emission check that is performed.

Appendix 5. Testing Procedures

Specific testing requirement plans, procedures, and averaging times are detailed in the appropriate Source-Wide, Emission Unit and/or Flexible Group Special Conditions. Therefore, this appendix is not applicable.

Appendix 6. Permits to Install

The following table lists any PTIs issued since the effective date of previously issued ROP No. MI-ROP-B1534-2006a. This includes any PTI that were incorporated into the Source-wide PTI No MI-PTI-B1534-2006a through amendments or modifications and any PTI that remained off-permit until this ROP renewal.

Permit to Install Number	Description of Equipment	Corresponding Emission Unit(s) or Flexible Group(s)
MI-PTI-B1534-2006a	Boiler, Paper Machine No. 1, Paper Machine No. 2, starch silo, and cold cleaners	EUBLR001, EUPAPERMACH1, EUPAPERMACH2, EUSTARCHSILO, FGCOLDCLEANER

Appendix 7. Emission Calculations

Specific emission calculations to be used with monitoring, testing or recordkeeping data are detailed in the appropriate Source-Wide, Emission Unit and/or Flexible group Special Conditions. Therefore, this appendix is not applicable.

Appendix 8. Reporting

A. Annual, Semiannual, and Deviation Certification Reporting

The permittee shall use the MDNRE Report Certification form (EQP 5736) and MDNRE Deviation Report form (EQP 5737) for the annual, semiannual and deviation certification reporting referenced in the Reporting Section of the Source-Wide, Emission Unit and/or Flexible Group Special Conditions. Alternative formats must meet the provisions of Rule 213(4)(c) and Rule 213(3)(c)(i), respectively, and be approved by the AQD District Supervisor.

B. Other Reporting

Specific reporting requirement formats and procedures are detailed in Part A or the appropriate Source-Wide, Emission Unit and/or Flexible Group Special Conditions. Therefore, Part B of this appendix is not applicable.

Appendix 9. Malfunction Abatement Plan

A. Malfunction Abatement Plan for EUBLR001

If the opacity exceeds the limits set forth in EUBLR001, or if visible emissions are observed for more than two hours using the methods set forth in Appendix 3A, the permittee shall implement the following procedures:

1. Determine the cause of the visible emissions within four hours of discovery;
2. Identify possible corrective measures within eight hours of discovery; and
3. Implement the most practically feasible corrective measure which will reduce/eliminate the visible emissions within 48 hours of discovery; or
4. Stop firing residual fuel oil and convert to firing natural gas.