

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY  
AIR QUALITY DIVISION**

November 22, 2017

**PERMIT TO INSTALL**  
387-94D

**ISSUED TO**  
Buckeye Terminals, LLC – Marshall Terminal

**LOCATED AT**  
12451 Old US 27 South  
Marshall, Michigan

**IN THE COUNTY OF**  
Calhoun

**STATE REGISTRATION NUMBER**  
B9052

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>September 28, 2017</b>	
DATE PERMIT TO INSTALL APPROVED: <b>November 22, 2017</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

## PERMIT TO INSTALL

### Table of Contents

<b>Section</b>	<b>Page</b>
Alphabetical Listing of Common Abbreviations / Acronyms .....	2
General Conditions .....	3
Special Conditions .....	5
Emission Unit Summary Table.....	5
Special Conditions for EULOADRACK .....	6
Flexible Group Summary Table .....	9
Special Conditions for FGIFRTANKS .....	9
Special Conditions for FGFIXEDROOFTANKS .....	12
Special Conditions for FGFACILITY .....	14

**Common Abbreviations / Acronyms**

<b>Common Acronyms</b>		<b>Pollutant / Measurement Abbreviations</b>	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO <sub>2e</sub>	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H <sub>2</sub> S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO <sub>x</sub>	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM <sub>10</sub>	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM <sub>2.5</sub>	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO <sub>2</sub>	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
  
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
  
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

**SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Process Equipment &amp; Control Devices)</b>	<b>Flexible Group ID</b>
EULOADRACK	Truck loading rack equipped with a Vapor Combustion Unit (VCU).	NA
EU-TANK28-1	1,260,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS
EU-TANK28-2	1,260,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS
EU-TANK28-3	1,260,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS
EU-TANK28-4	1,260,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS
EU-TANK75-5	3,360,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS
EU-TANK1-7	42,000 gallon gasoline/ethanol/distillate or petroleum contact water tank with Internal Floating Roof	FGIFRTANKS
EU-TANK75-6	3,360,000 gallon diesel tank with fixed roof	FGFIXEDROOFTANKS
EU-TANK8A	10,000 gallon additive tank with fixed roof	FGFIXEDROOFTANKS
EU-TANK9A	10,000 gallon slop tank with fixed roof	FGFIXEDROOFTANKS
EU-80-10	4,200,000 gallon gasoline/ethanol/distillate tank with Internal Floating Roof	FGIFRTANKS

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.

**The following conditions apply to: EULOADRACK**

**DESCRIPTION:** Truck loading rack equipped with a Vapor Combustion Unit (VCU).

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT:** Vapor Combustion Unit

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	75.5 tpy	12-month rolling time period as determined at the end of each calendar month.	EULOADRACK emissions through VCU	SC VI.1, SC VI.2	R 336.1205(1)(a)
2. VOC	35 mg/L of gasoline loaded	Continuous	EULOADRACK emissions through VCU	SC VI.1, SC VI.2	R 336.1205(1)(a)
3. VOC	2.3 mg/L of distillate loaded	Continuous	EULOADRACK emissions through VCU	SC VI.1, SC VI.2	R 336.1205(1)(a)
4. VOC	13 mg/L of gasoline loaded	Continuous	EULOADRACK fugitive emissions	SC VI.1, SC VI.2	R 336.1205(1)(a)

**II. MATERIAL LIMITS**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Gasoline/Ethanol	370,000,000 gallons per year	12-month rolling time period as determined at the end of each calendar month.	EULOADRACK	SC VI.1	R 336.1205(1)(a)
2. Distillate	138,000,000 gallons per year	12-month rolling time period as determined at the end of each calendar month.	EULOADRACK	SC VI.1	R 336.1205(1)(a)
3. Gasoline Additive	155,000 gallons per year	12-month rolling time period as determined at the end of each calendar month.	EULOADRACK	SC VI.1	R 336.1205(1)(a)

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall install, maintain and operate in a satisfactory manner, a vapor tight collection line which delivers the organic vapor to a loading rack control device when loading any delivery vessel with an organic compound having a true vapor pressure greater than 1.5 psia, or when loading a delivery vessel which has previously contained an organic compound having a true vapor pressure greater than 1.5 psia. **(R 336.1205(1)(a), R 336.1910)**
2. The permittee shall not load any delivery vessel with gasoline or ethanol unless all provisions of Rule 609 and Rule 627 are met. **(R 336.1205(1)(a), R 336.1609, R 336.1627, R 336.1910)**

3. To minimize loading rack control device downtime, the permittee shall implement and maintain an approved Preventive Maintenance Program (PMP). The PMP shall include the following:
  - a) Daily inspections of the VCU.
  - b) Schedule of regular maintenance as recommended by the manufacturer.
  - c) Log of all VCU outages.

If the PMP fails to address or inadequately addresses an event that meets the characteristics of a malfunction at the time the plan is initially developed, the owner or operator shall revise the PMP within 45 days after such an event occurs. **(R 336.1205(1)(a), R 336.1910)**

#### **IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall not fill any delivery vessel unless the vapor collection system is installed, maintained and operated in a satisfactory manner as follows:
  - a) The vapor-tight collection line shall be connected to the delivery vessel before any organic liquid with a vapor pressure of greater than 1.5 psia is transferred.
  - b) The vapor-tight collection line shall close upon disconnection so as to prevent release of gasoline vapor.
  - c) Hatch and other openings on the delivery vessel shall be closed and vapor-tight to prevent emission of displaced gasoline vapor during transfer operations, except under emergency conditions.
  - d) The liquid transfer line shall be equipped with a device, or a procedure shall be implemented, to prevent liquid drainage from the line when it is disconnected and not in use.

The permittee shall develop written procedures for the operation of all the control measures described above, and such procedures shall be available in an accessible location near the transfer equipment. **(R 336.1205(1)(a), R 336.1609)**

#### **V. TESTING/SAMPLING**

NA

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep records of the EULOADRACK throughput of each specific petroleum product for each calendar month and 12-month rolling time period. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a))**
2. The permittee shall keep the following information on a monthly and 12-month rolling time period basis for EULOADRACK:
  - a) Controlled VOC emission calculations.
  - b) Fugitive VOC emission calculations using an emission factor based on current gasoline distribution facilities loading rack collection system emission factors.
  - c) Miscellaneous VOC emission calculations from pumps, valves, and fittings based on current gasoline distribution facilities emission factors.

All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a))**

3. The permittee shall keep records of the following:
  - a) Compliance with the appropriate leak test for each delivery vessel.
  - b) Part replacements, repairs and maintenance for the loading rack control device as specified in the PMP.
  - c) All VCU malfunctions or failures.

All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a), R 336.1910)**

4. The permittee shall keep records of emissions and operating information. All source emissions data and operating information shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter/Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1.SVVCU	70	30	R 336.1901

**IX. OTHER REQUIREMENTS**

NA

**FLEXIBLE GROUP SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FGIFRTANKS	All storage tanks with internal floating roofs.	EU-TANK28-1, EU-TANK28-2, EU-TANK28-3, EU-TANK28-4, EU-TANK75-5, EU-TANK1-7, and EU-80-10
FGFIXEDROOFTANKS	All storage tanks with fixed roofs.	EU-TANK75-6, EU-TANK8A, and EU-TANK9A
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.	NA

**The following conditions apply to: FGIFRTANKS**

**DESCRIPTION:** All storage tanks with internal floating roofs.

**Emission Units:** EU-TANK28-1, EU-TANK28-2, EU-TANK28-3, EU-TANK28-4, EU-TANK75-5, EU-TANK1-7, and EU-80-10

**POLLUTION CONTROL EQUIPMENT:** Internal floating roof on each tank

**I. EMISSION LIMITS**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period/ Operating Scenario</b>	<b>Equipment</b>	<b>Testing / Monitoring Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	21.8 tpy	12-month rolling time period as determined at the end of each calendar month.	FGIFRTANKS	SC VI.2, SC VI.3	R 336.1205(1)(a), R 336.1225, R 336.1702(a)

**II. MATERIAL LIMITS**

<b>Material</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Testing / Monitoring Method</b>	<b>Underlying Applicable Requirements</b>
1. Gasoline/ Ethanol	370,000,000 gallons per year	12-month rolling time period as determined at the end of each calendar month.	FGIFRTANKS	SC VI.2	R 336.1205(1)(a), R 336.1225, R 336.1702(a)

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall not load any stationary vessel with gasoline/ethanol or store gasoline/ethanol in any stationary vessel unless all provisions of the rules listed below are met, as they apply to FGIFRTANKS.

	<b>Equipment</b>	<b>Rule</b>	<b>Applicable Requirement</b>
1a	EU-TANK28-1	604, 607, 627	R 336.1205(1)(a), R 336.1604, R 336.1607, R 336.1627
1b	EU-TANK28-2	604, 607, 627	R 336.1205(1)(a), R 336.1604, R 336.1607, R 336.1627
1c	EU-TANK28-3	604, 607, 627	R 336.1205(1)(a), R 336.1604, R 336.1607, R 336.1627
1d	EU-TANK28-4	604, 607, 627	R 336.1205(1)(a), R 336.1604, R 336.1607, R 336.1627
1e	EU-TANK75-5	604, 607, 627	R 336.1205(1)(a), R 336.1604, R 336.1607, R 336.1627
1f	EU-TANK1-7	604, 627, 704	R 336.1205(1)(a), R 336.1702(d), R 336.1704
1g	EU-80-10	604, 627, 704	R 336.1205(1)(a), R 336.1225, R 336.1702(d), R 336.1704,

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall equip and maintain the storage tanks with the deck and seal configuration listed in the following table, or a deck and seal configuration that results in the same or lower VOC emissions from the tank.

	<b>Equipment</b>	<b>Type</b>	<b>Deck</b>	<b>Primary Seal</b>	<b>Secondary Seal</b>	<b>Applicable Requirement</b>
1a	EU-TANK28-1	Internal floating roof	Bolted	Mechanical Shoe	None	R 336.1205(1)(a), R 336.1604
1b	EU-TANK28-2	Internal floating roof	Bolted	Mechanical Shoe	Rim-mounted	R 336.1205(1)(a), R 336.1604
1c	EU-TANK28-3	Internal floating roof	Welded	Vapor mounted	None	R 336.1205(1)(a), R 336.1604
1d	EU-TANK28-4	Internal floating roof	Bolted	Mechanical Shoe	None	R 336.1205(1)(a), R 336.1604
1e	EU-TANK75-5	Internal floating roof	Welded	Mechanical Shoe	None	R 336.1205(1)(a), R 336.1604
1f	EU-TANK1-7	Internal floating roof	Welded	Mechanical Shoe	None	R 336.1205(1)(a), R 336.1702(d)
1g	EU-80-10	Internal floating roof	Welded	Mechanical Shoe	Rim-mounted	R 336.1205(1)(a), R 336.1225, R 336.1702(d)

**V. TESTING/SAMPLING**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall perform inspections and monitor operating information for EU-80-10 in accordance with the federal Standards of Performance for New Stationary sources as specified in 40 CFR Part 60 Subparts A and Kb. **(R 336.1205(1)(a), R 336.1225, R 336.1702(d), 40 CFR Part 60 Subparts A and Kb)**
2. The permittee shall keep records of the FGIFRTANKS throughput of each specific petroleum product for each calendar month and 12-month rolling time period. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a))**

3. The permittee shall keep, in a satisfactory manner, monthly and 12-month rolling time period records of VOC emissions calculations for FGIFRTANKS. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1225, R 336.1702(a))**
4. The permittee shall keep records of inspections and operating information for EU-80-10 in accordance with the federal Standards of Performance for New Stationary sources as specified in 40 CFR Part 60 Subparts A and Kb. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1225, R336.1702(d), 40 CFR Part 60 Subparts A and Kb)**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

**The following conditions apply to: FGFIXEDROOFTANKS**

**DESCRIPTION:** All storage tanks with fixed roofs.

**Emission Units:** EU-TANK75-6, EU-TANK8A, and EU-TANK9A

**POLLUTION CONTROL EQUIPMENT:** NA

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period/ Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	1.4 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFIXEDROOFTANKS	SC VI.1, SC VI.2	R 336.1205(1)(a), R 336.1702(a)

**II. MATERIAL LIMITS**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Products with vapor pressures less than 1.5 psia	138,155,000 gallons per year	12-month rolling time period as determined at the end of each calendar month.	FGFIXEDROOFTANKS	SC VI.1	R 336.1205(1)(a), R 336.1702(a)

**III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall equip and maintain FGFIXEDROOFTANKS with conservation vents. **(R 336.1205(1)(a), R 336.1702(a))**

**V. TESTING/SAMPLING**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep records of the FGFIXEDROOFTANKS throughput of each specific petroleum product for each calendar month and 12-month rolling time period. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a))**

2. The permittee shall keep, in a satisfactory manner, monthly and 12-month rolling time period records of VOC emission calculations for FGFIXEDROOFTANKS. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1702(a))**
3. The permittee shall keep records of inspections and operating information for FGFIXEDROOFTANKS. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(1)(a), R 336.1225, R 336.1702(d))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

**The following conditions apply Source-Wide to: FGFACILITY**

**DESCRIPTION:** All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.

**POLLUTION CONTROL EQUIPMENT:** NA

**I. EMISSION LIMITS**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Testing / Monitoring Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	98.7 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFACILITY	SC VI.1	R 336.1205(3)
2. Each HAP	9 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFACILITY	SC VI.1	R 336.1205(3)
3. Aggregate HAPs	22.5 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFACILITY	SC VI.1	R 336.1205(3)

**II. MATERIAL LIMITS**

NA

**III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

**IV. DESIGN/EQUIPMENT PARAMETERS**

NA

**V. TESTING/SAMPLING**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep, in a satisfactory manner, records of monthly and 12-month rolling time period VOC, individual HAP, and total HAP emission rate calculations for FGFACILITY. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **(R 336.1205(3))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

1. The permittee shall comply with all provisions of the National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 63, Subpart BBBBBB, as they apply to FGFACILITY. **(40 CFR Part 63, Subpart BBBBBB)**