


**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

March 8, 2005

**NEW SOURCE REVIEW PERMIT TO INSTALL
409-95B**



ISSUED TO
Robert Bosch Fuel Systems, L.L.C.

LOCATED AT
4300 44th Street, SE
Kentwood, Michigan

IN THE COUNTY OF
Kent

STATE REGISTRATION NUMBER
N5286

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Part 5505(1) of Article II, Chapter I, Part 55 (Air Pollution Control) of P.A. 451 of 1994. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: February 3, 2005	
DATE PERMIT TO INSTALL APPROVED: March 8, 2005	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

NEW SOURCE REVIEW PERMIT TO INSTALL

Alphabetical Listing of Common Abbreviations/Acronyms used in this Permit to Install.

Common Acronyms		Pollutant/Measurement Abbreviations	
AQD	Air Quality Division	Btu	British thermal unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
COM	Continuous Opacity Monitoring	°F	Degrees Fahrenheit
EPA	Environmental Protection Agency	gr	Grains
EU	Emission Unit	Hg	Mercury
GACS	Gallon of Applied Coating Solids	hr	Hour
GC	General Condition	H ₂ S	Hydrogen sulfide
HAP	Hazardous Air Pollutant	hp	Horsepower
HVLP	High Volume Low Pressure *	lb	Pound
ID	Identification	m	Meter
LAER	Lowest Achievable Emission Rate	mm	Millimeter
MACT	Maximum Achievable Control Technology	MM	Million
MAP	Malfuction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NO _x	Oxides of nitrogen
MSDS	Material Safety Data Sheet	PM	Particulate matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM-10	Particulate matter less than 10 microns aerodynamic diameter
NSPS	New Source Performance Standards	pph	Pound per hour
NSR	New Source Review	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO ₂	Sulfur dioxide
SRN	State Registration Number	THC	Total hydrocarbons
TAC	Toxic Air Contaminant	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		VOC	Volatile organic compounds
		yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. [R336.1201(1)]
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. [R336.1201(4)]
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. [R336.1201(6)(b)]
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. [R336.1201(8), Section 5510 of Act 451, PA 1994]
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. [R336.1219]
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. [R336.1901]
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). [R336.1912]
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.

9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R336.1303. [R336.1301]
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this permit to install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R336.1370(2). [R336.1370]
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R336.2001 and R336.2003, under any of the conditions listed in R336.2001. [R336.2001]

SPECIAL CONDITIONS

Emission Unit Identification

Emission Unit ID	Emission Unit Description	Stack Identification
EU-CALIBRATORS	Calibrators and value open pressure machines	
EU-DIPTANKS	Small parts cleaner	
EU-MACHININGOPS	Miscellaneous machining operations	
EU-THERMALDEBURR	Thermal deburring machine	
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.		

Flexible Group Identification

Flexible Group ID	Emission Units Included in Flexible Group	Stack Identification
FGFACILITY	All equipment at the facility including equipment covered by other permits, grand-fathered equipment and exempt equipment.	

The following conditions apply to: EU-CALIBRATORS

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirement
1.1	VOC	EU-CALIBRATORS	24.0 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)

The following conditions apply to: EU-DIPTANKS

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirement
2.1	VOC	EU-DIPTANKS	13.2 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)

The following conditions apply to: EU-MACHININGOPS

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirement
3.1	VOC	EU-MACHININGOPS	20.0 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)

The following conditions apply to: EU-THERMALDEBURR

Visible Emissions limits

4.1 Visible emissions from EU-THERMALDEBURR shall not exceed 5 percent opacity [R 336.1201(3)]

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
4.2	SVTHERMALDEBURR	4.0	40	R 336.1201(3)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: FG-FACILITY

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Compliance Method	Applicable Requirement
5.1a	Individual HAP	FG-FACILITY	9.0 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)
5.1b	Aggregated HAPs	FG-FACILITY	22.50 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)
5.1c	VOC	FG-FACILITY	90.0 Tons	12 month rolling time period	Recordkeeping	R 336.1205(3)

Recordkeeping/Reporting/Notification

- 5.2 The applicant shall keep the following records for FG-FACILITY and shall maintain the records for a period of five years [R 336.1201(3)].
- Total calculated HAP emissions (lbs per month)
 - Individual calculated HAP emissions (lbs per month).
 - VOC content (lbs./gallon minus water as applied and as received) for each coating, reducer, cleanup solvent, calibration fluid, hydraulic oil, and coolant, on a monthly basis.
 - A current listing of the chemical composition of each coating, cleanup solvent, calibration fluid, hydraulic fluid, hydraulic fluid, and coolants used at the facility, including the weight percent of HAPs.
 - Amount of quench oil used on an annual basis.