

SUPPLEMENT TO PERMIT NO. 15-97A

CSM Cremation Services, Inc.  
Canton, Michigan

August 28, 1997

GENERAL CONDITIONS

1. Rule 201(1) - The process or process equipment covered by this permit shall not be reconstructed, relocated, altered, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule.
2. Rule 201(4) - If the installation, reconstruction, relocation, or alteration of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the person to whom this permit was issued, or the designated authorized agent, shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, reconstruction, relocation, or alteration of the equipment allowed by this Permit to Install.
3. Rule 201(6)(a) - If this Permit to Install is issued for a process or process equipment located at a stationary source which is subject to a Renewable Operating Permit pursuant to Rule 210, trial operation is allowed if the equipment performs in accordance with the terms and conditions of this Permit to Install and until the appropriate terms and conditions of this Permit to Install have been incorporated into the Renewable Operating Permit as a modification pursuant to Rule 216 or upon renewal pursuant to Rule 217. Upon incorporation of the appropriate terms and conditions into the Renewable Operating Permit, this Permit to Install shall become void.
4. Rules 201(7)(a) or 216(1)(a)(v)(A) - Except as provided in General Condition No. 3, operation of the process or process equipment is allowed if, not more than 30 days after completion of the installation, construction, reconstruction, relocation, alteration, or modification authorized by this Permit to Install, the person to whom this Permit to Install was issued, or the authorized agent pursuant to Rule 204, notifies the District Supervisor, Air Quality Division, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, alteration, or modification is considered to occur not later than commencement of trial operation of the process or process equipment.
5. Rule 201(7)(b) - Except as provided in General Condition No. 3, not more than 18 months after completion of the installation, construction, reconstruction, relocation, alteration, or modification authorized by this Permit to Install, the person to whom this permit was issued, or the authorized agent pursuant to Rule 204, shall notify the District Supervisor, Air Quality Division, in writing, of the status of compliance of the process or process equipment with the terms and conditions of the Permit to Install. The notification shall include all of the following:
  - A. The results of all testing, monitoring, and recordkeeping performed to determine the actual emissions from the process or process equipment and to demonstrate compliance with the terms and conditions of the Permit to Install.

- B. A schedule of compliance for the process or process equipment as described in Rule 119(a).
  - C. A statement, signed by the person owning or operating the process or process equipment, that, based on information and belief formed after reasonable inquiry, the statements and information in the notification are true, accurate, and complete.
6. Rule 201(8) and Section 5510 of Act 451, P.A. 1994 - The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Departments' rules or the Clean Air Act.
  7. Rule 219 - A new owner or operator of the process or process equipment covered by this Permit to Install shall immediately make a written request to the Department for a change of ownership or operational control. The request shall include all of the information required in Rule 219(1)(a), (b) and (c). If the request for a change in ownership or operational control is approved, the terms and conditions of this Permit to Install shall apply to the person or legal entity which hereafter owns or operates the process or process equipment for which this Permit to Install is issued. The written request shall be sent to the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909.
  8. Rule 901 - Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property.
  9. Rule 912 - The owner or operator of a source, process, or process equipment shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant in excess of standards for more than one hour, or of any air contaminant in excess of standards for more than two hours, as required in this rule, to the District Supervisor, Air Quality Division. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the District Supervisor within 10 days, with the information required in this rule.
  10. Approval of this permit does not exempt the person to whom this permit was issued from complying with any future regulations which may be promulgated under Part 55 of Act 451, P.A. 1994.
  11. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
  12. Operation of this equipment may be subject to other requirements of Part 55 of Act 451, P.A. 1994, and the rules promulgated thereunder.

### SPECIAL CONDITIONS

13. For the purposes of this permit to install, all requirements for notifications or submittal of records to or approvals by the District Supervisor, Air Quality Division should be submitted to the Director of Compliance and Enforcement, Air Quality Management Division, Wayne County Department of Environment unless you are otherwise notified in writing by the Air Quality Division. At no time shall notifications or submittals to or approvals by both agencies be required pursuant to this permit.
14. Rule 331 - The particulate emission from each incinerator shall not exceed 0.2 pound per 1,000 pounds of exhaust gases, corrected to 50% excess air.
15. Visible emissions from each incinerator shall not exceed a 6-minute average of 20% opacity, except as specified in Rule 301(1)(a).
16. Rules 1001, 1003 and 1004 - Verification of particulate emission rates from the incinerators by testing, at owner's expense, in accordance with Department requirements, may be required for operating approval. Verification of emission rates includes the submittal of a complete report of the test results. If a test is required, stack testing procedures and the location of stack testing ports must have prior approval by the District Supervisor, Air Quality Division, and results shall be submitted within 120 days of the written requirement for such verification.
17. Proper operation and adequate maintenance of the incinerators to control emissions is required. A list of recommended operating and maintenance procedures is enclosed.
18. Applicant shall not operate the incinerators unless all provisions of Rule 301 are met.
19. Applicant shall not operate the incinerators unless a minimum temperature of 1600 °F and a minimum retention time of 1.0 seconds in the secondary combustion chamber is maintained. This condition is applicable separately to the operation of each incinerator.
20. Applicant shall not operate the incinerators unless the secondary combustion chamber is preheated for not less than 30 minutes prior to the firing of the primary combustion chamber. This condition is applicable separately to the operation of each incinerator.
21. The exhaust gases from each incinerator shall be discharged unobstructed vertically upwards to the ambient air from separate stacks, each with a maximum diameter of 18 inches at an exit point not less than 18 feet above ground level.
22. Applicant shall not burn any waste in either incinerator other than the following:  
  
Type O -- Trash, a mixture of highly combustible waste such as paper, cardboard cartons, wood boxes, and combustible floor sweepings, from commercial and industrial activities. The mixture may contain up to 10% by weight of plastic bags,

CSM Cremation Services, Inc.

Permit No. 15-97A

Page 4

August 28, 1997

coated paper, laminated paper, treated corrugated cardboard, oily rags and plastic or rubber scraps.

Type 4 -- Human and animal remains, consisting of carcasses, organs and solid organic wastes from hospitals, laboratories, abattoirs, animal pounds, and similar sources.

23. Monthly records of the number of cremations performed in each incinerator and the average temperature in the secondary chamber for each cremation shall be kept on file for a period of at least two years and made available to the Air Quality Division upon request.

#### INCINERATOR OPERATION GUIDELINES

1. Designate a trained operator for your unit and make that person responsible for compliance with the air pollution control requirements.
2. Grates should be cleaned before each day's operation (more often if necessary), and the ashes disposed of properly.
3. Preheat the unit with the burners (not with waste) for at least 15 minutes.
4. Do not overload the incinerator. Stay within the given loading rates, and follow the manufacturer's instructions.
5. Schedule charges to minimize opening the charging door as infrequently as possible. Opening the charging door lets cold air in and quenches the fire causing smoke.
6. Burn only the type of wastes that your incinerator has been approved to burn. Follow the manufacturer's instructions to maximize the efficiency of the unit, and to properly burn the waste(s).
7. Keep the combustion air adjusted according to the manufacturer's instructions.
8. Observe the stack frequently and adjust your operation as necessary to eliminate smoke and flyash.
9. A copy of the manufacturer's manual and this Guideline should be posted near your incinerator.
10. Make quarterly inspections to check and service all of the equipment. If you do not have a qualified person available for proper inspections, a service contract with a reputable manufacturer is advisable.