

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

December 16, 2014

PERMIT TO INSTALL
336-97C

ISSUED TO
Plastatech Engineering, Ltd.

LOCATED AT
725 East Morley Drive
Saginaw, Michigan

IN THE COUNTY OF
Saginaw

STATE REGISTRATION NUMBER
N1749

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: October 16, 2014	
DATE PERMIT TO INSTALL APPROVED: December 16, 2014	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EUCALENDERLN.....	6
Special Conditions for EUEXTRUDERLN.....	8
Flexible Group Summary Table	11
Special Conditions for FGLAMINATORLNS	11
Special Conditions for FGFACILITY	14

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
CO ₂ e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
GHGs	Greenhouse Gases	kW	Kilowatt
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfunction Abatement Plan	NO _x	Oxides of Nitrogen
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter
MSDS	Material Safety Data Sheet	PM10	PM with aerodynamic diameter ≤10 microns
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM with aerodynamic diameter ≤ 2.5 microns
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition	SO ₂	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EULAMINATORLN1	The lamination process thermally bonds two vinyl films to a reinforcing mesh (scrim) to produce a roofing membrane. A plasticizer is used as the laminating adhesive that bonds the two vinyl films to the scrim substrate. Controlled by a Smog-Hog (No. 2).	FGLAMINATORLNS
EULAMINATORLN2	The lamination process thermally bonds two vinyl films to a reinforcing mesh (scrim) to produce a roofing membrane. A plasticizer is used as the laminating adhesive that bonds the two vinyl films to the scrim substrate. Controlled by a Smog-Hog (No. 3).	FGLAMINATORLNS
EUCALENDERLN	The calender process extrudes a measured amount of thermoplastic PVC material between successive pairs of corotating, parallel rolls to form a PVC film 3 to 40 mills in thickness. The process consists of three 90,000 pound storage tanks (two for plasticizer and one for ESO), three 1500 pound totes, three 170,000 pound PVC resin silos, four 2200 pound super sacks, a five story mixing tower, a planetary extruder, a strainer extruder, a 14ft conveyor, calender rolls, and cooling rolls.	NA
EUEXTRUDERLN	A vinyl film extruder process to produce reinforced vinyl film up to 12 feet in width. The extruders will mix the raw materials to make a vinyl fluid, calender the vinyl fluid to make two layers of vinyl film and laminate a reinforcing polyester fiber mesh (scrim) between the film sheets in one process. The dry raw material handling will be controlled by a cyclone and cartridge-type dust collector system.	NA

Changes to the equipment described in this table are subject to the requirements of R336.1201, except as allowed by R336.1278 to R336.1290.

The following conditions apply to: EUCALENDERLN

DESCRIPTION: The calender process extrudes a measured amount of thermoplastic PVC material between successive pairs of corotating, parallel rolls to form a PVC film 3 to 40 mills in thickness. The process consists of three 90,000 pound storage tanks (two for plasticizer and one for ESO), three 1500 pound totes, three 170,000 pound PVC resin silos, four 2200 pound super sacks, a five story mixing tower, a planetary extruder, a strainer extruder, a 14ft conveyor, calender rolls, and cooling rolls.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	16.3 TPY	12-month rolling time period as determined at the end of each calendar month	EUCALENDARLN	SC VI.3	R 336.1205(3), R 336.1702(d)

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall recover and reclaim, recycle, or dispose of waste materials in accordance with all applicable rules and regulations. **(R 336.1702(a))**
2. All waste materials shall be captured and stored in closed containers and shall be disposed of in an acceptable manner in compliance with all applicable rules and regulations. **(R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The VOC content, water content, and density of any material, as applied and as received, may be determined from manufacturer's formulation data. Upon request of the AQD District Supervisor, the VOC content shall be verified using federal Reference Test Method 24. If the Method 24 and the formulation values should differ, the Method 24 results shall be used to determine compliance. **(R 336.1225, R 336.1702(a), R 336.1901)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1225, R 336.1702(a), R 336.1901)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component used in EUCALENDERLN. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a), R 336.1901)**
3. The permittee shall keep the following information on a calendar month basis for EUCALENDERLN:
 - a) Gallons (with water) or pounds of each material used.
 - b) VOC content (with water), in pounds per gallon or pounds per pound, of each material used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.The records shall be kept in a format acceptable to the AQD Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a) & (d), R 336.1901)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-1	42	60	R 336.1225, R 336.1901, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUEXTRUDERLN

DESCRIPTION: A vinyl film extruder process to produce reinforced vinyl film up to 12 feet in width. The extruders will mix the raw materials to make a vinyl fluid, calender the vinyl fluid to make two layers of vinyl film and laminate a reinforcing polyester fiber mesh (scrim) between the film sheets in one process. The dry raw material handling will be controlled by a cyclone and cartridge-type dust collector system.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Cyclone and Cartridge-type dust collector system

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	66.2 TPY	12-month rolling time period as determined at the end of each calendar month	EUEXTRUDERLN	SC VI.3	R 336.1225, R 336.1702(a)
2. PM10	0.04 lb/1000 lb of exhaust air	Test Protocol*	EUEXTRUDERLN	GC 13	R 336.1331

*Test Protocol shall determine the averaging time.

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Plasticizer	16,000,000 lbs/yr	12-month rolling time period as determined at the end of each calendar month	EUEXTRUDERLN	SC VI.3	R 336.1225, R 336.1702(a)
2. Epoxidized Soybean Oil (ESO)	1,000,000 lbs/yr	12-month rolling time period as determined at the end of each calendar month	EUEXTRUDERLN	SC VI.3	R 336.1225, R 336.1702(a)
3. Heat Stabilizer	1,125,000 lbs/yr at 9% VOC by weight	12-month rolling time period as determined at the end of each calendar month	EUEXTRUDERLN	SC VI.3	R 336.1225, R 336.1702(a)

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUEXTRUDERLN for more than 6,000 hours per 12-month rolling time period as determined at the end of each calendar month. (R 336.1205(3), R 336.1225, R 336.1702(a))

2. The permittee shall not operate the raw material air conveying system of EUEXTRUDERLN unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the cyclone and cartridge-type dust collector, has been submitted within 60 days of permit issuance, and is implemented and maintained. If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1225, R 336.1331, R 336.1702(a), R 336.1910, R 336.1911, 40 CFR 52.21(c) and (d))**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate the raw material air conveying system of EUEXTRUDERLN unless the cyclone and cartridge-type dust collector are installed, maintained, and operated in a satisfactory manner. Satisfactory operation includes but is not limited to maintaining the pressure drop across the system as specified by the manufacturer. The proper pressure drop operating range shall be included in the MAP, required by SC III.2. **(R 336.1205, R 336.1225, R 336.1331, R 336.1702, R 336.1910, 40 CFR 52.21(c) and (d))**
2. The permittee shall equip and maintain the cartridge-type dust collector with a device to monitor the pressure drop on a continuous basis. **(R 336.1205, R 336.1225, R 336.1331, R 336.1910, R 336.1702, 40 CFR 52.21(c) and (d))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component used in EUEXTRUDERLN. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a))**
3. The permittee shall keep the following information on a calendar month basis for EUEXTRUDERLN:
 - a) Gallons (with water) of each material used.
 - b) VOC content based on Material Safety Data Sheets, manufacturer's formulation data, or both for each material as used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
 - e) Actual hours of operation per 12-month rolling time period as determined at the end of each calendar month.

The records shall be kept in a format acceptable to the AQD Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1205(3), R 336.1225, R 336.1702(a))**

4. The permittee shall monitor and keep records of the pressure drop across the cartridge-type dust collector system on a weekly basis. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a) & (d), R 336.1910)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVBAGHOUSE	24	20	R 336.1225, R 336.1331, 40 CFR 52.21 (c) & (d)
2. SVEXTRUDER	30	88	R 336.1225, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGLAMINATORLNS	EULAMINATORLN1 and EULAMINATORLN2 including Smog-Hog Air Pollution Control Systems (Nos. 2 and 3) for each line to control particulate emissions.	EULAMINATORLN1, EULAMINATORLN2
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.	

The following conditions apply to: FGLAMINATORLNS

DESCRIPTION: Two lamination lines for producing a roofing membrane. The lamination process thermally bonds two vinyl films to a reinforcing mesh (scrim) to produce the roofing membrane. A plasticizer is used as the laminating adhesive that bonds the two vinyl films to the scrim substrate. Each line is controlled by a Smog-Hog (No. 2 for line 1 and No. 3 for Line 2).

Emission Units: EULAMINATORLN1, EULAMINATORLN2

POLLUTION CONTROL EQUIPMENT: Smog Hogs

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOCs	3.8 TPY	12-month rolling time period as determined at the end of each calendar month	FGLAMINATORLNS	SC VI.4	R 336.1205(3), R 336.1702(d)

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOCs	3.8 lb/gal (minus water as applied)	Instantaneous	FGLAMINATORLNS	SC V.1, SC VI.3, SC VI.4	R 336.1702(a)

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall recover and reclaim, recycle, or dispose of waste materials in accordance with all applicable rules and regulations. **(R 336.1702(a))**

2. All waste materials shall be captured and stored in closed containers and shall be disposed of in an acceptable manner in compliance with all applicable rules and regulations. **(R 336.1702(a))**
3. The permittee shall not operate each emission unit contained in FGLAMINATORLNS for more than 7,000 hours per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205(3), R 336.1225, R 336.1702(a), R 336.1901)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate FGLAMINATORSLNS unless the "Smog-Hog Air Pollution Control System" (Smog-Hog) for each line is installed, maintained and operated in a satisfactory manner. Satisfactory operation of each Smog-Hog system includes the operation of a properly designed and operated ventilation system, and a chiller section that maintains the air temperature to less than 130 °F. **(R 336.1205(3), R 336.225, R 336.702(d), R 336.1901, R 336.1910)**
2. The permittee shall equip and maintain the FGLAMINATORLNS with the roller or equivalent technology with comparable transfer efficiency. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The VOC content, water content, and density of any material, as applied and as received, may be determined from manufacturer's formulation data. Upon request of the AQD District Supervisor, the VOC content shall be verified using federal Reference Test Method 24. If the Method 24 and the formulation values should differ, the Method 24 results shall be used to determine compliance. **(R 336.1205(3), R 336.1225, R 336.1702(a), R 336.1901)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1225, R 336.1702(a) & (d), R 336.1901)**
2. The permittee shall monitor, in a satisfactory manner, the temperature in each Smog-Hog on a continuous basis in a manner and with instrumentation acceptable to the Air Quality Division. **(R 336.1205(3), R 336.1225, R 336.1702(d), R 336.1901)**
3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a), R 336.1901)**
4. The permittee shall keep the following information on a calendar month basis for each emission unit of the FGLAMINATORLNS:
 - a) Gallons (with water) of each material used.
 - b) VOC content (minus water and with water) of each material as applied.
 - c) VOC content of the materials as applied on an instantaneous basis.
 - d) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - e) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
 - f) Actual hours of operation per 12-month rolling time period as determined at the end of each calendar month.

The records shall be kept in a format acceptable to the AQD Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1225, R 336.1702(a) & (d), R 336.1901)**

5. The permittee shall keep, in a satisfactory manner, continuous records of the temperature in each Smog-Hog. All records shall be kept on file and made available to the Department upon request. **(R 336.1205(3), R 336.1224, R 336.1225, R 336.1702(a), R 336.1901)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-SMOGHOGS-02	30	43	R 336.1225, R 336.1901, 40 CFR 52.21(c) & (d)
2. SV-SMOGHOGS-03	30	43	R 336.1225, R 336.1901, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply Source-Wide to: FGFACILITY

POLLUTION CONTROL EQUIPMENT: Smog Hogs

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Each Individual HAP	Less than 9.0 TPY	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 TPY	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The HAP content of any vinyl material, coating, printing material, solvents, etc. (material) as received and as applied, shall be determined using manufacturer's formulation data. Upon request of the AQD District Supervisor, the manufacturer's HAP formulation data shall be verified using EPA Test Method 311. **(R 336.1205(3))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1205(3))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1205(3))**

3. The permittee shall keep the following information on a calendar month basis for FGFACILITY:
- a) Gallons or pounds of each material used.
 - b) Where applicable, gallons or pounds of each material reclaimed.
 - c) HAP content, in pounds per gallon or pounds per pound, of each material used.
 - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
 - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month.
- The records shall be kept in a format acceptable to the AQD Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1205(3))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).