

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

June 5, 2017

PERMIT TO INSTALL
207-98A

ISSUED TO
Pioneer Foundry Company

LOCATED AT
606 Water Street
Jackson, Michigan

IN THE COUNTY OF
Jackson

STATE REGISTRATION NUMBER
B1661

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

| | |
|--|------------|
| DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: March 1, 2017 | |
| DATE PERMIT TO INSTALL APPROVED: June 5, 2017 | SIGNATURE: |
| DATE PERMIT VOIDED: | SIGNATURE: |
| DATE PERMIT REVOKED: | SIGNATURE: |

PERMIT TO INSTALL

Table of Contents

| Section | Page |
|---|-------------|
| Alphabetical Listing of Common Abbreviations / Acronyms | 2 |
| General Conditions | 3 |
| Special Conditions | 5 |
| Emission Unit Summary Table..... | 5 |
| Special Conditions for EUFURNACE..... | 6 |
| Flexible Group Summary Table | 8 |
| Special Conditions for FGMACTZZZZZ..... | 9 |

Common Abbreviations / Acronyms

| Common Acronyms | | Pollutant / Measurement Abbreviations | |
|---------------------------|--|--|---|
| AQD | Air Quality Division | acfm | Actual cubic feet per minute |
| BACT | Best Available Control Technology | BTU | British Thermal Unit |
| CAA | Clean Air Act | °C | Degrees Celsius |
| CAM | Compliance Assurance Monitoring | CO | Carbon Monoxide |
| CEM | Continuous Emission Monitoring | CO _{2e} | Carbon Dioxide Equivalent |
| CFR | Code of Federal Regulations | dscf | Dry standard cubic foot |
| COM | Continuous Opacity Monitoring | dscm | Dry standard cubic meter |
| Department/ department | Michigan Department of Environmental Quality | °F | Degrees Fahrenheit |
| EU | Emission Unit | gr | Grains |
| FG | Flexible Group | HAP | Hazardous Air Pollutant |
| GACS | Gallons of Applied Coating Solids | Hg | Mercury |
| GC | General Condition | hr | Hour |
| GHGs | Greenhouse Gases | HP | Horsepower |
| HVLP | High Volume Low Pressure* | H ₂ S | Hydrogen Sulfide |
| ID | Identification | kW | Kilowatt |
| IRSL | Initial Risk Screening Level | lb | Pound |
| ITSL | Initial Threshold Screening Level | m | Meter |
| LAER | Lowest Achievable Emission Rate | mg | Milligram |
| MACT | Maximum Achievable Control Technology | mm | Millimeter |
| MAERS | Michigan Air Emissions Reporting System | MM | Million |
| MAP | Malfunction Abatement Plan | MW | Megawatts |
| MDEQ | Michigan Department of Environmental Quality | NMOC | Non-methane Organic Compounds |
| MSDS | Material Safety Data Sheet | NO _x | Oxides of Nitrogen |
| NA | Not Applicable | ng | Nanogram |
| NAAQS | National Ambient Air Quality Standards | PM | Particulate Matter |
| NESHAP | National Emission Standard for Hazardous Air Pollutants | PM ₁₀ | Particulate Matter equal to or less than 10 microns in diameter |
| NSPS | New Source Performance Standards | PM _{2.5} | Particulate Matter equal to or less than 2.5 microns in diameter |
| NSR | New Source Review | pph | Pounds per hour |
| PS | Performance Specification | ppm | Parts per million |
| PSD | Prevention of Significant Deterioration | ppmv | Parts per million by volume |
| PTE | Permanent Total Enclosure | ppmw | Parts per million by weight |
| PTI | Permit to Install | psia | Pounds per square inch absolute |
| RACT | Reasonable Available Control Technology | psig | Pounds per square inch gauge |
| ROP | Renewable Operating Permit | scf | Standard cubic feet |
| SC | Special Condition | sec | Seconds |
| SCR | Selective Catalytic Reduction | SO ₂ | Sulfur Dioxide |
| SNCR | Selective Non-Catalytic Reduction | TAC | Toxic Air Contaminant |
| SRN | State Registration Number | Temp | Temperature |
| TEQ | Toxicity Equivalence Quotient | THC | Total Hydrocarbons |
| USEPA/EPA | United States Environmental Protection Agency | tpy | Tons per year |
| VE | Visible Emissions | µg | Microgram |
| | | µm | Micrometer or Micron |
| | | VOC | Volatile Organic Compounds |
| | | yr | Year |

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| Emission Unit ID | Emission Unit Description (Process Equipment & Control Devices) | Flexible Group ID |
|--|---|--------------------------|
| EUFURNACE | Two (2) electric induction furnaces capable of melting 3,500 lbs of gray iron per hour, operated by a single 1,250 kW power source. This includes charging, inoculation, pouring, and cooling activities. | FGMACTZZZZZ |
| Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290. | | |

The following conditions apply to: EUFURNACE

DESCRIPTION: Two (2) electric induction furnaces capable of melting 3,500 lbs of gray iron per hour, operated by a single 1,250 kW power source. This includes charging, inoculation, pouring, and cooling activities.

Flexible Group ID: FGMACTZZZZZ

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

| Pollutant | Limit | Time Period / Operating Scenario | Equipment | Testing / Monitoring Method | Underlying Applicable Requirements |
|-----------|---------------------------|----------------------------------|-----------|-----------------------------|------------------------------------|
| 1. PM | 0.10 lb /1,000 lbs of gas | Test Protocol* | EUFURNACE | SC V.1 | R 336.1331 |

* Test Protocol shall specify averaging time.

II. MATERIAL LIMITS

| Material | Limit | Time Period / Operating Scenario | Equipment | Testing / Monitoring Method | Underlying Applicable Requirements |
|--------------|------------|--|-----------|-----------------------------|--|
| 1. Gray Iron | 4,900 tons | 12-month rolling time period as determined at the end of each calendar month | EUFURNACE | SC VI.2 | R 336.1205(1)(a) and (3), 40 CFR 52.21(c) and (d) |

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Upon request from the AQD District Supervisor, the permittee may be required to verify the PM emission rate from EUFURNACE by testing at owner's expense, in accordance with Department requirements. No less than 60 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing. Verification of emission rates includes the submittal of a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1331, R 336.2001, R 336.2003, R 336.2004)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor and make them available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1205(1)(a) and (3))**
2. The permittee shall keep records of the EUFURNACE throughput for each calendar month and 12-month rolling time period. The permittee shall keep all records on file for a period of at least five years and make them available to the Department upon request. **(R 336.1205(1)(a) and (3), 40 CFR 52.21(c) and (d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| Flexible Group ID | Flexible Group Description | Associated Emission Unit IDs |
|--------------------------|--|-------------------------------------|
| FGMACTZZZZZ | The affected source is an existing iron and steel foundry, that is (or is part of) an area source of hazardous air pollutant (HAP) emissions. The affected source is an existing small foundry as defined by 40 CFR Part 63 Subpart ZZZZZ. | EUFURNACE |

The following conditions apply to: FGMACTZZZZZ

DESCRIPTION: The affected source is an existing iron and steel foundry, that is (or is part of) an area source of hazardous air pollutant (HAP) emissions. The affected source is an existing small foundry as defined by 40 CFR Part 63 Subpart ZZZZZ.

Emission Units: EUFURNACE

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

1. If applicable, the permittee shall not utilize a binder chemical formulation that uses methanol as a specific ingredient of the catalyst formulation for a furfuryl alcohol warm box mold or core making line. This requirement does not apply to the resin portion of the binder system. **(40 CFR 63.10886)**

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall implement and maintain an approved plan to address the pollution prevention management practices for metallic scrap and mercury switches by the applicable compliance date specified in 40 CFR 63.10881. The plan shall include the following:
 - a) Metallic scrap management program. **(40 CFR 63.10885(a))**
 - b) Mercury requirements. **(40 CFR 63.10885(b))**

The permittee shall revise the plan within 30 days after a change occurs. **(40 CFR 63.10885)**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall maintain files of all information as required by §63.10(b)(1), (including all reports and notifications) for at least 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. At a minimum, the most recent 2 years of data shall be retained on site. The remaining 3 years of data may be retained off site. **(40 CFR 63.10890(d))**
2. The permittee shall maintain records of the information specified in paragraphs (e)(1) through (7) of 40 CFR 63.10890 according to the requirements in §63.10(b)(1). **(40 CFR 63.10890(e))**

VII. REPORTING

1. The permittee shall submit semiannual compliance reports to the AQD District Supervisor according to the requirements in §63.10(e). The report must clearly identify any deviation from the pollution prevention management practices in §63.10885 or §63.10886 and the corrective action taken. **(40 CFR 63.10890 (f))**

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

1. The permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants, as specified in 40 CFR Part 63, Subpart A and Subpart ZZZZZ for Iron and Steel Foundries by the initial compliance date. **(40 CFR Part 63 Subparts A and ZZZZZ)**