

SUPPLEMENT to PERMIT No. 153-00
Electro-Plating Service, Inc.
Madison Heights, Michigan
October 26, 2000

GENERAL CONDITIONS

1. Rule 201(1) - The process or process equipment covered by this permit shall not be reconstructed, relocated, altered, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule.
2. Rule 201(4) - If the installation, reconstruction, relocation, or alteration of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the person to whom this permit was issued, or the designated authorized agent, shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, reconstruction, relocation, or alteration of the equipment allowed by this Permit to Install.
3. Rule 201(6)(a) - If this Permit to Install is issued for a process or process equipment located at a stationary source that is subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, trial operation is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install and until the appropriate terms and conditions of this Permit to Install have been incorporated into the Renewable Operating Permit. Upon incorporation of the appropriate terms and conditions into the Renewable Operating Permit, this Permit to Install shall become void.
4. Rules 201(6)(b) - If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install.
5. Rule 201(8) and Section 5510 of Act 451, P.A. 1994 - The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act.
6. Rule 219 - The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b) and (c) of R 336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality.

7. Rule 901 - Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property.
8. Rule 912 - The owner or operator of a source, process, or process equipment shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant in excess of standards for more than one hour, or of any air contaminant in excess of standards for more than two hours, as required in this rule, to the District Supervisor, Air Quality Division. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the District Supervisor within 10 days, with the information required in this rule.
9. Approval of this permit does not exempt the person to whom this permit was issued from complying with any future applicable requirements which may be promulgated under Part 55 of Act 451, P.A. 1994 of the Clean Air Act.
10. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
11. Operation of this equipment may be subject to other requirements of Part 55 of Act 451, P.A. 1994, and the rules promulgated thereunder.
12. Rule 301 - Except as provided in subrules (2), and (3), or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, a person shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303.
 - a) A 6-minute average of 20% opacity, except for one 6-minute average per hour of not more than 27% opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this permit to install.
13. Rule 370 - Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2).

14. Rule 285 - Except as allowed by Rule 285 (a), (b), and (c), applicant shall not substitute any fuels, coatings, nor raw materials for those described in the application and allowed by this permit, nor make changes to the process or process equipment described in the application, without prior notification to and approval by the Air Quality Division.
15. The Department may require the applicant to conduct acceptable performance tests, at the applicant's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001.

SPECIAL CONDITIONS
October 26, 2000
(11 Special Conditions)

1. The total chromium emission rate from the emission unit consisting of two (2) rack hard chrome plating tanks controlled by a wet scrubber, hereinafter "EUPLATERS", shall not exceed 0.0004 pounds per hour, nor 0.0007 tons per 12 month rolling time period as determined at the end of each calendar month. [R336.1225]
2. The total chromium emission from the EUPLATERS shall not exceed 0.015 milligrams per cubic meter, corrected to 70 degrees Fahrenheit and 29.92 inches Hg. [40CFR63.342, R336.1225]
3. Verification and quantification of chromium emission rates from the EUPLATERS by testing, at owner's expense, in accordance with Department requirements, will be required for continued operation. Verification of emission rates includes the submittal of a complete report of the test results. No less than 60 days prior to testing, a complete stack testing plan must be submitted to the Air Quality Division. The plan must be approved by the Air Quality Division prior to testing. [R336.1205(3), R336.1225, R336.2001, R336.2003, R336.2004]
4. Applicant shall not operate the EUPLATERS unless the wet scrubber is installed and operating properly as described in the preventative maintenance and malfunction abatement plan required by special condition No. 5. [R336.1225, R336.1910, 40CFR63.342]
5. The applicant shall submit an approvable preventative maintenance and malfunction abatement plan to the District Supervisor within 60 days after installation of the wet scrubber. [R336.1911]
6. Applicant shall equip and maintain the wet scrubber with a pressure drop indicator. [R336.1910, R336.1225]
7. The exhaust gases from the process shall be discharged unobstructed vertically upwards to the ambient air from a stack with a maximum diameter of 24 inches at an exit point not less than 39 feet above ground level. [R336.1225]
8. Applicant shall use fresh water for any make-up water to the recirculation tank and shall supply this water to the scrubber. [R336.1225, R336.1910]
9. The applicant shall not operate the EUPLATERS for more than 3600 hours per 12 month rolling time period as determined at the end of each calendar month. A written log of the hours of operation shall be kept on file for a period of at least five years and made available to the Department upon request. [R336.1225]

10. At least once a month, the applicant shall visually inspect the controls to ensure proper drainage, no chromic acid build-up on the packed bed scrubber, and that structural integrity is sound. [R336.1225, R336.1910 and 40 CFR Part 63, (N)]

11. Monitoring and recording of emissions, operating and maintenance information is required to comply with the National Emission Standard for Hazardous Air Pollutants as specified in 40 CFR Part 63, Subpart A and N. All source emissions, operating, and maintenance data shall be kept on file for a period of at least five years and made available to the Department upon request.