

## NEW SOURCE REVIEW PERMIT TO INSTALL

### Table of Contents

| <b>Section</b>  | <b>Page</b> |
|---|-------------|
| Alphabetical Listing of Common Abbreviations / Acronyms ..... | 2           |
| General Conditions .....                                      | 3           |
| Emission Unit Identification.....                             | 5           |
| Emission Unit Special Conditions.....                         | 5           |
| Appendices.....   | 6           |

**Common Abbreviations / Acronyms Used in this Permit to Install**

| Common Acronyms |   | Pollutant/Measurement Abbreviations |  |
|-----------------|---|-------------------------------------|--|
| AQD             | Air Quality Division                                    | BTU                                 | British Thermal Unit                             |
| BACT            | Best Available Control Technology                       | °C                                  | Degrees Celsius                                  |
| CAA             | Clean Air Act   | CO                                  | Carbon Monoxide                                  |
| CEM             | Continuous Emission Monitoring                          | dscf                                | Dry standard cubic foot                          |
| CFR             | Code of Federal Regulations                             | dscm                                | Dry standard cubic meter                         |
| COM             | Continuous Opacity Monitoring                           | °F                                  | Degrees Fahrenheit                               |
| EPA             | Environmental Protection Agency                         | gr                                  | Grains   |
| EU              | Emission Unit   | Hg                                  | Mercury  |
| FG              | Flexible Group  | hr                                  | Hour   |
| GACS            | Gallon of Applied Coating Solids                        | H <sub>2</sub> S                    | Hydrogen Sulfide                                 |
| GC              | General Condition                                       | HP                                  | Horsepower                                       |
| HAP             | Hazardous Air Pollutant                                 | lb                                  | Pound  |
| HVLP            | High Volume Low Pressure *                              | m                                   | Meter  |
| ID              | Identification  | mg                                  | Milligram  |
| LAER            | Lowest Achievable Emission Rate                         | mm                                  | Millimeter                                       |
| MACT            | Maximum Achievable Control Technology                   | MM                                  | Million  |
| MAERS           | Michigan Air Emissions Reporting System                 | MW                                  | Megawatts  |
| MAP             | Malfunction Abatement Plan                              | NO <sub>x</sub>                     | Oxides of Nitrogen                               |
| MDEQ            | Michigan Department of Environmental Quality            | PM                                  | Particulate Matter                               |
| MSDS            | Material Safety Data Sheet                              | PM-10                               | Particulate Matter less than 10 microns diameter |
| NESHAP          | National Emission Standard for Hazardous Air Pollutants | pph                                 | Pound per hour                                   |
| NSPS            | New Source Performance Standards                        | ppm                                 | Parts per million                                |
| NSR             | New Source Review                                       | ppmv                                | Parts per million by volume                      |
| PS              | Performance Specification                               | ppmw                                | Parts per million by weight                      |
| PSD             | Prevention of Significant Deterioration                 | psia                                | Pounds per square inch absolute                  |
| PTE             | Permanent Total Enclosure                               | psig                                | Pounds per square inch gauge                     |
| PTI             | Permit to Install                                       | scf                                 | Standard cubic feet                              |
| RACT            | Reasonable Available Control Technology                 | sec                                 | Seconds  |
| SC              | Special Condition                                       | SO <sub>2</sub>                     | Sulfur Dioxide                                   |
| SCR             | Selective Catalytic Reduction                           | THC                                 | Total Hydrocarbons                               |
| SRN             | State Registration Number                               | tpy                                 | Tons per year                                    |
| TAC             | Toxic Air Contaminant                                   | µg                                  | Microgram  |
| VE              | Visible Emissions                                       | VOC                                 | Volatile Organic Compounds                       |
|                 |   | yr                                  | Year   |

\* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **[R336.1201(1)]**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, PO Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **[R336.1201(4)]**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **[R336.1201(6)(b)]**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **[R336.1201(8), Section 5510 of Act 451, PA 1994]**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **[R336.1219]**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **[R336.1901]**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **[R336.1912]**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.

9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA Act 451, as amended and the rules promulgated thereunder.
11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R336.1303. **[R336.1301]**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this permit to install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R336.1370(2). **[R336.1370]**
13. Except as allowed by Rule 285 (a), (b), and (c), the permittee shall not substitute any fuels, coatings, nor raw materials for those described in the application and allowed by this permit, nor make changes to the process or process equipment described in the application, without prior notification to and approval by the Air Quality Division. **[R336.1201(1)]**
14. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R336.2001 and R336.2003, under any of the conditions listed in R336.2001. **[R336.2001]**

**SPECIAL CONDITIONS**

**Emission Unit Identification**

| <b>Emission Unit ID</b>   | <b>Emission Unit Description</b> | <b>Stack Identification</b> |
|---|----------------------------------|-----------------------------|
| EUSOIL  | Soil vapor extraction wells      | SVSOIL                      |
| Changes to the equipment described in this table are subject to the requirements of R336.1201, except as allowed by R336.1278 to R336.1290. |                                  |                             |

**The following conditions apply to: EUSOIL**

**Emission Limits**

|     | <b>Pollutant</b> | <b>Equipment</b> | <b>Limit</b> | <b>Time Period</b>  | <b>Testing/<br/>Monitoring<br/>Method</b> | <b>Applicable<br/>Requirements</b> |
|-----|------------------|------------------|--------------|---|---|------------------------------------|
| 1.1 | VOC              | EUSOIL           | 2.7 tpy      | 12-month rolling time period as determined at the end of each calendar month. | SC 1.4                                    | R336.1702(a)<br>R336.1225          |

**Monitoring**

1.2 The permittee shall monitor, in a satisfactory manner, the flow rate, and the total VOC concentration of influent stream(s) to EUSOIL. This shall be done on a weekly basis until four valid samples, which pass all quality assurance and quality control requirements have been obtained. Thereafter, influent stream(s) to EUSOIL shall be monitored for these parameters on a monthly basis. Any request for a change in the sampling frequency must be submitted to the AQD District Supervisor for review and approval. **[R336.1225, R336.1702(a)]**

**Recordkeeping/Reporting/Notification**

1.3 The permittee shall record the flow rate, and total VOC concentration of the influent stream(s) to EUSOIL. This shall be done on a weekly basis until four valid samples have been obtained. Thereafter, these parameters shall be recorded on a monthly basis. All data, including calculation of VOC emission rates, shall be submitted to the AQD District Supervisor using Appendix A, or an approved equivalent method, within 30 days following collection of the initial data, and thereafter within 30 days following the end of the quarter in which the data were collected. Any request for a change in the reporting frequency must be submitted to the AQD District Supervisor for review and approval. **[R336.1225, R336.1702(a)]**

1.4 The permittee shall keep, in a satisfactory manner, monthly and 12-month rolling time period calculations of VOC emission rates for EUSOIL. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1225, R336.1702(a)]**

**Stack/Vent Restrictions**

|   | <b>Stack &amp; Vent ID</b> | <b>Maximum Diameter<br/>(inches)</b> | <b>Minimum Height Above<br/>Ground Level (feet)</b> | <b>Applicable<br/>Requirements</b> |
|---|----------------------------|--------------------------------------|---|------------------------------------|
| 1.12a   | SVSOIL                     | 1.5                                  | 30  | R336.1225,<br>R336.1901            |
| The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air. |                            |                                      |   |                                    |

