

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

July 31, 2013

PERMIT TO INSTALL
34-03A

ISSUED TO
Woodworth, Inc.

LOCATED AT
20251 Sherwood
Detroit, Michigan

IN THE COUNTY OF
Wayne

STATE REGISTRATION NUMBER
N6693

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

June 25, 2013

DATE PERMIT TO INSTALL APPROVED:

July 31, 2013

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EUDEGREASER1	5

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
CO ₂ e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
GHGs	Greenhouse Gases	kW	Kilowatt
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfunction Abatement Plan	NO _x	Oxides of Nitrogen
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter
MSDS	Material Safety Data Sheet	PM10	PM with aerodynamic diameter ≤10 microns
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM with aerodynamic diameter ≤ 2.5 microns
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition	SO ₂	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUDEGREASER1	Open top batch vapor degreaser, model BACT-120A equipped with a Rite-Temp water chiller which provides the cooling source for the freeboard chilling coils. The solvent air interface is 47.25 square feet. The degreaser will utilize the solvent n-propyl bromide for degreasing.	NA
Changes to the equipment described in this table are subject to the requirements of R336.1201, except as allowed by R336.1278 to R336.1290.		

The following conditions apply to: EUDEGREASER1

DESCRIPTION: Open top batch vapor degreaser, model BACT-120A equipped with a Rite-Temp water chiller which provides the cooling source for the freeboard chilling coils. The solvent air interface is 47.25 square feet. The degreaser will utilize the solvent n-propyl bromide for degreasing.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Cover and refrigerated freeboard device

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	15.0 TPY	12-month rolling time period as determined at the end of each calendar month	EUDEGREASER1	SC VI.4	R 336.1702(a)

II. MATERIAL LIMITS

1. The permittee shall not use more than 2725 gallons of vapor degreaser solvents, hereinafter "solvent", per year based on a 12-month rolling period as determined at the end of each calendar month. The permittee shall determine the amount of solvent used on a "net usage" basis. "Net usage" is defined as the amount of solvent added to EUDEGREASER1 to bring the solvent levels up to starting levels less any amount of solvent removed as waste. **(R 336.1205(1)(a), R 336.1225, R 336.1702(a))**

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall recover and reclaim, recycle, or dispose of, in accordance with all applicable state rules and federal regulations, the solvents used for EUDEGREASER1. **(R 336.1225, R 336.1702(a))**
2. The permittee shall capture all waste solvents and shall store them in closed containers. The permittee shall dispose of all waste solvents in a manner such that not more than 20% by weight is allowed to evaporate into the atmosphere. **(R 336.1225, R 336.1702(a), R 336.1708(3)(i))**
3. The permittee shall develop written procedures in accordance with SC IV.1 for the operation of EUDEGREASER1, and such procedures shall be posted in an accessible, conspicuous location near the vapor degreaser. **(R 336.1708(4))**
4. The permittee shall not use any of the listed halogenated solvents in EUDEGREASER1, pursuant to the National Emission Standards for Hazardous Air Pollutants as specified in 40 CFR Part 63, Subparts T. **(R 336.1205(3), R 336.1225)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate EUDEGREASER1 unless the degreaser is equipped with at least one of the following:
 - a. The freeboard height to the width of the degreaser is equal to or greater than 0.75. And if the degreaser opening is more than 10 square feet, the degreaser shall be designed with a powered or mechanically assisted cover.
 - b. The degreaser is equipped with a refrigerated freeboard device. **(R 336.1708(2)(a) & (b))**
2. The permittee shall not operate EUDEGREASER1 unless all of the following conditions are met:
 - a. A cover shall be installed that is designed to be opened and closed easily without disturbing the vapor zone. The cover shall be closed at all times, except when processing workloads through the degreaser.
 - b. A procedure shall be developed to minimize solvent carryout by doing all of the following:
 - i. Racking parts to allow complete drainage.
 - ii. Moving parts in and out of the degreaser at a vertical speed of less than 11 feet per minute when a powered hoist is used to raise or lower the parts.
 - iii. Holding parts in the vapor zone not less than 30 seconds or until condensation ceases.
 - iv. Tipping or tumbling parts in a manner such that no pools of organic solvent remain on the cleaned parts before removal.
 - v. Allowing parts to dry within the degreaser for not less than 15 seconds or until visually dry.
 - c. The following control devices shall be installed:
 - i. A condenser flow switch and thermostat that shut off the sump heat if the condenser coolant is either not circulating or is too warm.
 - ii. If equipped with spray, a spray safety switch that shuts off the spray pump if the vapor level drops excessively.
 - iii. A vapor level control device that shuts off the sump heat if the solvent vapor level rises above the normal design level.
 - d. The total workload shall not occupy more than 1/2 of the degreaser's open top area.
 - e. Solvent shall not be sprayed above the vapor level.
 - f. Solvent leaks shall be repaired immediately.
 - g. The degreaser shall be operated in such a manner that no water is visibly detectable in solvent exiting the water separator. **(R 336.1708(3))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each vapor degreaser solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a monthly basis for the use of vapor degreaser solvents associated with EUDEGREASER1:
 - a. Gallons of each solvent used and removed as waste.
 - b. Solvent usage calculations determining the monthly "net usage" rate in gallons per calendar month.
 - c. Solvent usage calculations determining the annual "net usage" rate in gallons per 12-month rolling time period as determined at the end of each calendar month.The permittee shall keep the records on file in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1205(1)(a), R 336.1225, R 336.1702)**
4. The permittee shall keep, in a satisfactory manner, monthly and 12-month rolling time period VOC emission calculation records for EUDEGREASER, as required by SC I.1. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1205(1)(a), R 336.1225, R 336.1702(a))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVDEGREASER1	18	45	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).