

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

October 12, 2021

**PERMIT TO INSTALL**  
196-04H

**ISSUED TO**  
PPG Industries, Inc.

**LOCATED AT**  
961 Division Street  
Adrian, Michigan 49221

**IN THE COUNTY OF**  
Lenawee

**STATE REGISTRATION NUMBER**  
B8801

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>October 7, 2021</b>	
DATE PERMIT TO INSTALL APPROVED: <b>October 12, 2021</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

## PERMIT TO INSTALL

### Table of Contents

COMMON ACRONYMS .....	2
POLLUTANT / MEASUREMENT ABBREVIATIONS .....	3
GENERAL CONDITIONS .....	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE .....	6
FLEXIBLE GROUP SPECIAL CONDITIONS.....	8
FLEXIBLE GROUP SUMMARY TABLE .....	8
FGMIXERS.....	9
FGBLENDTANKS.....	13
FGFACILITY CONDITIONS.....	15

## COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

## EMISSION UNIT SPECIAL CONDITIONS

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Flexible Group ID
EU-DC1	This is a grouping of mixers which vent to the atmosphere through Dust Collector 1 (SV-DC1). These mixers are identified in the MAERS as EUMixer13, EUMixer89, and EUMixer90. The mixers are used to manufacture adhesives and sealants for the automotive industry.	FGMIXERS
EU-DC2	This is a grouping of mixers which vent to the atmosphere through Dust Collector 2 (SV-DC2). These mixers are identified in the MAERS as EUMixer85, EUMixer87, EUMixer88. The mixers are used to manufacture adhesives and sealants for the automotive industry.	FGMIXERS
EU-DC4	This is a grouping of mixers which vent to the atmosphere through Dust Collector 4 (SV-DC4). These mixers are identified in the MAERS as EUMixer01, EUMixer03, EUMixer04, EUMixer17, EUMixer37, EUMixer94, EUMixer96, and EUMixer97. The mixers are used to manufacture adhesives and sealants for the automotive industry. This grouping also includes the pre-assembly area of the facility where raw materials are broken down into smaller packaging sizes for use in the manufacturing areas (weigh station). This area has ventilation for capturing fugitive dust from the opening of bags containing solids.	FGMIXERS
EU-DC5	This is a grouping of mixers which vent to the atmosphere through Dust Collector 5 (SV-DC5). These mixers are identified in the MAERS as EUMixer118, EUMixer119, EUMixer301, and EUMixer302. The mixers are used to manufacture adhesives and sealants for the automotive industry.	FGMIXERS
EU-DC8	This is a grouping of mixers which vent to the atmosphere through Dust Collector 8 (SV-DC8). These mixers are identified in the MAERS as EUMixer29, EUMixer30, EUMixer93, EUMixer14, EUMixer250, EUMixer201, EUMixer202, and EUMixer203. The mixers are used to manufacture adhesives and sealants for the automotive industry.	FGMIXERS
EU-DC10	This is a grouping of mixers which vent to the atmosphere through a Dust Collector 10 (SV-DC10). These mixers are identified in the MAERS as EUMixer112, EUMixer115, EUMixer116 and EUMixer117. The mixers are used to manufacture adhesives and sealants for the automotive industry.	FGMIXERS
EU-DC11	Storage and day bins for PVC materials, consisting of silos 1-4 and day bins 1-4. Day bins 1-4 serve EUMixer201, EUMixer202, and EUMixer203 in EU-DC8. Emissions due to material transfers to and from the silos and to the day bins vent to the atmosphere through SV-DC11.	FGMIXERS
EU-DC12	Storage and day bin for glass microspheres, consisting of silo 5 and day bin 5. Day bin 5 serves EUMixer201, EUMixer202, and EUMixer203 in EU-DC8. Emissions due to material transfers to and from the silo and to the day bin vent to the atmosphere through SV-DC12.	FGMIXERS
EU-DC13	Storage and day bins for calcium carbonate materials, consisting of silos 6-8, and day bins 6-8. Day bins 6-8 serve EUMixer201, EUMixer202, and EUMixer203 in EU-DC8. Emissions due to material transfers to and from the silos and to the day bins vent to the atmosphere through SV-DC13.	FGMIXERS
EU-CleanUp	Mixers are cleaned by solvent based cleaners.	FGMIXERS

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Flexible Group ID</b>
EU-BT1	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT2	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT3	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT4	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT5	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT6	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS
EU-BT7	One 7,250-gallon blending tank for the final blending of intermediate liquid products. This EU is fully enclosed except during loading and unloading of materials.	FGBLENDTANKS

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

## FLEXIBLE GROUP SPECIAL CONDITIONS

### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FGMIXERS	This flexible group consists of all the mixing vessels at the facility for producing the various adhesives and sealants for the automotive industry.	EU-DC1, EU-DC2, EU-DC4, EU-DC5, EU-DC8, EU-DC10, EU-DC11, EU-DC12, EU-DC13, and EU-CleanUp
FGBLENDTANKS	Seven 7,250-gallon blending tanks	EU-BT1, EU-BT2, EU-BT3, EU-BT4, EU-BT5, EU-BT6, EU-BT7

**FGMIXERS  
 FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

This flexible group consists of all the mixing vessels at the facility for producing the various adhesives and sealants for the automotive industry.

**Emission Unit:** EU-DC1, EU-DC2, EU-DC4, EU-DC5, EU-DC8, EU-DC10, EU-DC11, EU-DC12, EU-DC13, and EU-CleanUp

**POLLUTION CONTROL EQUIPMENT**

Dust collectors

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	23.31 TPY	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC II.1, SC II.3, SC II.4, SC VI.4, SC VI.5	R 336.1702(a)
2. PVC Powder	2.25 TPY	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC II.2, SC II.3, SC II.4, SC VI.4, SC VI.5	R 336.1224, R 336.1225
3. PM	0.10 pounds per 1,000 pounds of exhaust gases, calculated on a dry gas basis	Hourly	EU-DC1, EU-DC2, EU-DC4, EU-DC5, EU-DC8, and EU-DC10 *	SC VI.2, SC VI.3	R 336.1331
4. PM	0.012 pounds per 1,000 pounds of exhaust gases, calculated on a dry gas basis	Hourly	EU-DC11	SC VI.2, SC VI.3	R 336.1225, R 336.1331
5. PM	0.003 pounds per 1,000 pounds of exhaust gases, calculated on a dry gas basis	Hourly	EU-DC12	SC VI.2, SC VI.3	R 336.1225, R 336.1331
6. PM	0.009 pounds per 1,000 pounds of exhaust gases, calculated on a dry gas basis	Hourly	EU-DC13	SC VI.2, SC VI.3	R 336.1225, R 336.1331

\* The emission limit applies separately to the emissions from each emission unit.

**II. MATERIAL LIMIT(S)**

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. Solids processed	145,000 tons per year	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC VI.5	R 336.1224, R 336.1225, R 336.1702
2. Polyvinyl chloride (PVC) powder processed	4,500 tons per year <sup>1</sup>	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC VI.5	R 336.1224, R 336.1225
3. VOC processed, including cleanup solvents	6,000,000 gallons per year	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC VI.5	R 336.1224, R 336.1225, R 336.1702
4. Adhesives and sealants produced	50,000,000 gallons per year	12-month rolling time period as determined at the end of each calendar month	FGMIXERS	SC VI.5	R 336.1224, R 336.1225, R 336.1702

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. All waste from the mixing process shall be captured and stored in closed containers and shall be disposed of in an acceptable manner in compliance with all applicable rules and regulations. **(R 336.1224, R 336.1702(a))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate FGMIXERS unless the associated dust collectors for EU-DC1, EU-DC2, EU-DC4, EU-DC5, EU-DC8, EU-DC10, EU-DC11, EU-DC12, and EU-DC13 are installed, maintained, and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1331, R 336.1910)**
2. The permittee shall not operate FGMIXERS unless a gauge, which measures the pressure drop across each associated dust collector in EU-DC1, EU-DC2, EU-DC4, EU-DC5, EU-DC8, EU-DC10, EU-DC11, EU-DC12, and EU-DC13 is installed, maintained, and operated in a satisfactory manner. **(R 336.1224, R 336.1225, R 336.1301, R 336.1331, R 336.1910)**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1224, R 336.1225, R 336.1702)**
2. The permittee shall monitor, in a satisfactory manner, the pressure drop across each dust collector in FGMIXERS on a continuous basis. **(R 336.1910)**
3. The permittee shall keep, in a satisfactory manner, weekly pressure drop readings for each dust collector in FGMIXERS. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1910)**

4. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each mixing component, including the weight percent of each component. The data may consist of Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**
5. The permittee shall keep the following information on a monthly basis for FGMIXERS:
  - a) Gallons and/or pounds of each mixing material as well as cleanup solvents used and product produced.
  - b) VOC content of each product mixed/made in each emission unit of FGMIXERS.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
  - e) Tons of PVC processed through FGMIXERS per 12-month rolling time period as determined at the end of each calendar month.
  - f) Throughput records for addition of VOCs, solids and/or powders, determining the monthly throughput rates for each emission unit in FGMIXERS.

The records shall be kept using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-DC1	13.5	42.0	R 336.1225, 40 CFR 52.21(c)&(d)
2. SV-DC2	28.0	42.0	R 336.1225, 40 CFR 52.21(c)&(d)
3. SV-DC4	26.0	42.0	R 336.1225, 40 CFR 52.21(c)&(d)
4. SV-DC5	26.0	42.0	R 336.1225, 40 CFR 52.21(c)&(d)
5. SV-DC8	26.0	42.0	R 336.1225, 40 CFR 52.21(c)&(d)
6. SV-DC10*	10	NA	R 336.1225, 40 CFR 52.21(c)&(d)
7. SV-DC11**	6	16	R 336.1225, 40 CFR 52.21(c)&(d)
8. SV-DC12**	6	16	R 336.1225, 40 CFR 52.21(c)&(d)
9. SV-DC13**	6	16	R 336.1225, 40 CFR 52.21(c)&(d)
* SV-DC10 shall vent only to the general in-plant environment.			
** This vent may exhaust horizontally.			

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**FGBLENDTANKS  
 FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

Seven 7,250-gallon blending tanks

**Emission Unit:** EU-BT1, EU-BT2, EU-BT3, EU-BT4, EU-BT5, EU-BT6, EU-BT7

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	0.41 tpy	12-month rolling time period as determined at the end of each calendar month	FGBLENDTANKS	SC VI.2, SC VI.3	R 336.1702(a)

**II. MATERIAL LIMIT(S)**

<b>Material</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. Intermediate Products Processed*	1,819,629 gallons per year	12-month rolling time period as determined at the end of each calendar month	FGBLENDTANKS	SC VI.2, SC VI.3	R 336.1702(a)

\*Intermediate products are defined as materials produced in other processes at the facility and transferred into FGBLENDTANKS. Diluents are not considered to be intermediate products.

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate any EU in FGBLENDTANKS unless it is fully enclosed except when loading or unloading intermediate product or diluent. **(R 336.1225, R 336.1702)**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1225, R 336.1702)**

2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each mixing component, including the weight percent of each component. The data may consist of Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a monthly basis for FGBLENDTANKS:
  - a) Gallons and type of each intermediate product loaded into blend tanks.
  - b) Gallons of total intermediate products loaded into blend tanks per 12-month rolling time period as determined at the end of each calendar month.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(a))**

## **VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of FGBLENDTANKS. **(R 336.1201(7)(a))**

## **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

NA

## **IX. OTHER REQUIREMENT(S)**

NA

### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

## FGFACILITY CONDITIONS

### DESCRIPTION

The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment, and exempt equipment.

### POLLUTION CONTROL EQUIPMENT

Dust collectors

#### I. EMISSION LIMIT(S)

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. Each Individual HAP	Less than 9 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFACILITY	SC VI.2	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 tpy	12-month rolling time period as determined at the end of each calendar month.	FGFACILITY	SC VI.2	R 336.1205(3)

#### II. MATERIAL LIMIT(S)

NA

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All required calculations shall be completed in a format acceptable to the AQD District Supervisor and made available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1205(3))**

2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
  - a) Gallons or pounds of each HAP containing material used.
  - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
  - c) HAP content, in pounds per gallon or pounds per pound, of each product mixed in each emission unit of FGMIXERS and/or used in FGFACILITY.
  - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month using mass balance or an alternate method acceptable to the AQD District Supervisor.
  - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month using mass balance or an alternate method acceptable to the AQD District Supervisor.

The records shall be kept using mass balance or an alternate method and format acceptable to the AQD District Supervisor. All records shall be kept on file and made available to the Department upon request.  
**(R 336.1205(3))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

NA

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).