

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY
AIR QUALITY DIVISION**

JANUARY 6, 2021

PERMIT TO INSTALL
228-041

ISSUED TO
SUMMIT POLYMERS, INC.

LOCATED AT
115 SOUTH LEJA DRIVE
VICKSBURG, MICHIGAN 49097

IN THE COUNTY OF
KALAMAZOO

STATE REGISTRATION NUMBER
N5044

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: December 17, 2020	
DATE PERMIT TO INSTALL APPROVED: January 6, 2021	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE	6
EUSystem1	7
EUSystem2.....	10
EUBTHLINE05.....	14
FGFACILITY CONDITIONS.....	17

COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IR	Infrared
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

**For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.*

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO ₂ e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H ₂ S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO _x	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO ₂	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EUSystem1	Air-dried plastic automotive interior parts spray booths and associated IR cure ovens. Booths are equipped with dry filters to control particulate overspray.	07-30-2010 / 08-02-2010 / 04-18-2014	NA
EUSystem2	Air-dried plastic automotive interior parts spray coating line consisting of a CO ₂ cleaner, one flame treat booth, one top coat spray booth, one flash zone, one clear coat spray booth, and one IR cure oven. Booths are equipped with dry filters to control particulate overspray.	07-30-2010 / 10-04-2010 / 03-01-2019	NA
EUBTHLINE05	Air-dried plastic automotive interior parts coating line consisting of a CO ₂ cleaner, spray booth #5, and one IR cure oven. The booth is equipped with dry filters to control particulate overspray.	04-01-1995 / 04-18-2014 / PTI Issuance Date	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EUSystem1
 EMISSION UNIT CONDITIONS**

DESCRIPTION

Air-dried plastic automotive interior parts spray booths and associated IR cure ovens.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

Spray booths are equipped with dry filters to control particulate overspray.

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs, Acetone (CAS No. 67-64-1), and t-butyl acetate (CAS No. 123-86-4) combined	60.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUSystem1	SC VI.4	R 336.1224, R 336.1702(d)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs	5.0 lb/gal (minus water) ^a , as applied	Daily volume-weighted average	EUSystem1	SC VI.4	R 336.1702(d)

^a The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste coatings, reducers, thinners, additives, catalysts, purge solvents, and cleanup solvents (materials) and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**
3. The permittee shall handle all VOC and/or HAP containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1702(a))**
4. The permittee shall not operate the bake oven portion of EUSystem1 at a temperature in excess of 194°F. **(R 336.1702(d))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not operate any spray booth portion of EUSystem1 unless its respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1331, R 336.1910)**
2. The permittee shall equip and maintain each spray booth portion of EUSystem1 with HVLP applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating, as applied and as received, using federal Reference Test Method 24. The permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702, R 336.2001, R 336.2003, R 336.2004)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1224, R 336.1225, R 336.1702)**
2. The permittee shall install, calibrate, maintain, and operate in a satisfactory manner a device to monitor and record the bake oven temperature on the bake oven portion of EUSystem1 on a continuous basis. Temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. **(R 336.1702(d))**
3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, thinner, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**
4. The permittee shall keep the following information on a calendar day basis for EUSystem1:
 - a) Gallons (with water) of each coating, reducer, thinner, additive, catalyst, clean-up solvents material used and reclaimed.
 - b) VOC content (minus water and with water), of each material as applied.
 - c) VOC emission calculations determining the volume-weighted average VOC content of the coatings as applied on a calendar day basis.
 - d) Acetone content and t-butyl acetate content of each material as applied.
 - e) VOC, acetone and t-butyl acetate separate and combined mass emission calculations determining the monthly emission rate in tons per calendar month.
 - f) VOC, acetone and t-butyl acetate separate and combined mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702)**

5. As required by SC VI.2, the permittee shall keep, in a satisfactory manner, records of the operating temperature for the bake oven portion of EUSystem1. All records shall be kept on file and made available to the Department upon request. **(R 336.1702(d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-System1-01 (SV0001; System 1: Booth 1)	24.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)
2. SV-System1-02 (SV0007; System 1: Booth 2)	24.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENT(S)

NA

**EUSystem2
EMISSION UNIT CONDITIONS**

DESCRIPTION

Air-dried plastic automotive interior parts spray coating line consisting of a CO₂ cleaner, one flame treat booth, one top coat spray booth, one flash zone, one clear coat spray booth, and one IR cure oven.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

Spray booths are equipped with dry filters to control particulate overspray.

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs	78.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUSystem2	SC VI.4	R 336.1702(a)
2. VOCs, Acetone (CAS No. 67-64-1) and tert-butyl acetate (TBA, CAS No. 540-88-5), combined	114.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUSystem2	SC VI.4	R 336.1224, R 336.1702(a)
3. VOCs, Acetone (CAS No. 67-64-1) and tert-butyl acetate (TBA, CAS No. 540-88-5), combined	58.0 tpy	12-month rolling time period as determined at the end of each calendar month	Any Single Booth portions (two total) of EUSystem2	SC VI.4	R 336.1224, R 336.1702(a)
4. glycol ether db (CAS No. 112-34-5)	1.7 tpy ¹	12-month rolling time period as determined at the end of each calendar month	EUSystem2	SC VI.5	R 336.1225(1)
5. 2-(2-butoxyethoxy) ethyl acetate (CAS No. 124-17-4)	1.7 tpy ¹	12-month rolling time period as determined at the end of each calendar month	EUSystem2	SC VI.5	R 336.1225(1)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs	5.0 lb/gal (minus water) ^a , as applied	Daily volume-weighted average	EUSystem2	SC VI.6	R 336.1702(d)

^a The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste coatings, reducers, thinners, additives, catalysts, purge solvents, and cleanup solvents (materials) and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**
3. The permittee shall handle all VOC and/or HAP containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
4. The permittee shall not operate the bake oven portion of EUSystem2 at a temperature in excess of 194°F. **(R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not operate any spray booth portion of EUSystem2 unless its respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1331, R 336.1910)**
2. The permittee shall equip and maintain each spray booth portion of EUSystem2 with HVLP applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating, as applied and as received, using federal Reference Test Method 24. The permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702, R 336.2001, R 336.2003, R 336.2004)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1224, R 336.1225, R 336.1702)**
2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor and record the bake oven temperature on the bake oven portion of EUSystem2 on a continuous basis. Temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. **(R 336.1702(d))**
3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, thinner, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**

4. The permittee shall keep the following information, each separately, for any single booth portions (two total) of EUSystem2, and total combined for EUSystem2:
- Gallons (with water) of each VOC, acetone (CAS No. 67-64-1), and TBA (CAS No. 540-88-5) containing material used and, if applicable, reclaimed on a monthly basis.
 - VOC (with water), acetone, and TBA contents of each material as applied on a monthly basis.
 - VOC, acetone, and TBA mass emission calculations determining the monthly emission rate in tons per calendar month, each separately and combined.
 - VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.
 - Combined VOC, acetone, and TBA mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1702)**

5. The permittee shall keep the following information on a monthly basis for EUSystem2:
- Gallons (with water) of each glycol ether DB (CAS No. 112-34-5) and 2-(2-butoxyethoxy) ethyl acetate (CAS No. 124-17-4) (TACs) containing material used and, if applicable, reclaimed.
 - Each TAC content (with water) in pounds per gallon of each material used.
 - Each TAC mass emission calculations determining the monthly emission rate in tons per calendar month, (each separately).
 - Each TAC's mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month (each separately).

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1225(1))**

6. The permittee shall keep the following information for EUSystem2:
- Gallons (minus water) of each VOC containing material used and, if applicable, reclaimed on a daily basis.
 - VOC (minus water) content of each material as applied on a daily basis.
 - VOC emission calculations determining the volume-weighted average VOC content of the coatings in pounds per gallon, minus water, as applied on a daily basis.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(d))**

7. As required by SC VI.2, the permittee shall keep, in a satisfactory manner, records of the operating temperature for the bake oven portion of EUSystem2. All records shall be kept on file and made available to the Department upon request. **(R 336.1702(d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-System2-01 (System 2: Flame Treat Booth)	42.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)
2. SV-System2-02 (System 2: Topcoat Spray Booth)	42.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)
3. SV-System2-03 (System 2: Flash Zone)	24.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)
4. SV-System2-04 (System 2: Clearcoat Spray Booth)	42.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)
5. SV-System2-05 (System 2: IR Oven)	24.0	48.0	R 336.1225, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**EUBTHLINE05
EMISSION UNIT CONDITIONS**

DESCRIPTION

Air-dried plastic automotive interior parts coating line consisting of a CO₂ cleaner, spray booth #5, and one IR cure oven. The booth is equipped with dry filters to control particulate overspray.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

Spray booths are equipped with dry filters to control particulate overspray.

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs and acetone (CAS No. 67-64-1) combined	30.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUBTHLINE05	SC VI.4	R 336.1224, R 336.1702(d)
2. glycol ether db (CAS No. 112-34-5)	4.4 tpy ¹	12-month rolling time period as determined at the end of each calendar month	EUBTHLINE05	SC VI.5	R 336.1225(1)
3. 2-(2-butoxyethoxy) ethyl acetate (CAS No. 124-17-4)	5.0 tpy ¹	12-month rolling time period as determined at the end of each calendar month	EUBTHLINE05	SC VI.5	R 336.1225(1)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOCs	5.0 lb/gal (minus water) ^a , as applied	Daily volume-weighted average	EUBTHLINE05	SC VI.4	R 336.1702(d)

^a The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste coatings, reducers, thinners, additives, catalysts, purge solvents, and cleanup solvents (materials) and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**
3. The permittee shall handle all VOC and/or HAP containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1702(a))**
4. The permittee shall not operate the bake oven portion of EUBTHLINE05 at a temperature in excess of 194°F. **(R 336.1702(d))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not operate any spray booth portion of EUBTHLINE05 unless its respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1331, R 336.1910)**
2. The permittee shall equip and maintain each spray booth portion of EUBTHLINE05 with HVLP applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating, as received and as applied, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702, R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1224, R 336.1225, R 336.1702)**
2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor and record the bake oven temperature on the bake oven portion of EUBTHLINE05 on a continuous basis. Temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. **(R 336.1702(d))**
3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, thinner, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**
4. The permittee shall keep the following information on a calendar day basis for EUBTHLINE05:
 - a) Gallons (with water) of each coating, reducer, thinner, additive, catalyst, clean-up solvents material used and reclaimed.
 - b) VOC content (minus water and with water) and acetone content of each material as applied.
 - c) VOC emission calculations determining the volume-weighted average VOC content of the coatings as applied on a calendar day basis.
 - d) VOC and acetone combined mass emission calculations determining the monthly emission rate in tons per calendar month.
 - e) VOC and acetone combined mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1702)**

5. The permittee shall keep the following information on a monthly basis for EUBTHLINE05:
 - a) Gallons (with water) of each glycol ether DB (CAS No. 112-34-5) and 2-(2-butoxyethoxy) ethyl acetate (CAS No. 124-17-4) (TACs) containing material used and, if applicable, reclaimed.
 - b) Each TAC content (with water) in pounds per gallon of each material used.

- c) Each TAC mass emission calculations determining the monthly emission rate in tons per calendar month, (each separately).
- d) Each TAC's mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month (each separately).

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1225(1))**

- 6. As required by SC VI.2, the permittee shall keep, in a satisfactory manner, records of the operating temperature for the bake oven portion of EUBTHLINE05. All records shall be kept on file and made available to the Department upon request. **(R 336.1702(d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-BTHLINE05-01 (SV00024; Line 5: Booth 1)	42	43.5	R 336.1225, 40 CFR 52.21 (c) & (d)
2. SV-BTHLINE05-02 (New Stack; Line 5: Booth 2)	42	43.5	R 336.1225, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENT(S)

- 1. Within 30-days after the completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or authorized agent per Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EUBTHLINE05. **(R 336.1201(7)(a))**

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FGFACILITY CONDITIONS

DESCRIPTION: The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment, and exempt equipment.

POLLUTION CONTROL EQUIPMENT

Dry filters in each spray booth.

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. Each Individual HAP	Less than 9.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)
3. VOCs	80.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(3)
4. ethyl benzene (CAS No. 100-41-4)	4.1 tpy ¹	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.5	R 336.1225(2)

II. MATERIAL LIMIT(S)

Material	Maximum VOC Content, With Water As Applied, in pounds per gallon	Annual Usage Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Group 1 Coatings	0.0 – 2.0	32,000 gallons (with water) per year	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(1)(a)
2. Group 2 Coatings	2.01 – 3.0	3,000 gallons (with water) per year	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(1)(a)
3. Group 3 Coatings	3.01 – 4.0	3,925 gallons (with water) per year	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(1)(a)
4. Group 4 Coatings	4.01 – 5.0	14,125 gallons (with water) per year	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(1)(a)

Material	Maximum VOC Content, With Water As Applied, in pounds per gallon	Annual Usage Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
5. Group 5 Coatings	5.01 – 6.0	110 gallons (with water) per year	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.4	R 336.1205(1)(a)

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer’s formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer’s HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**
2. The permittee shall determine the VOC content, water content, and density of any coating, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer’s formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205(3))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer’s formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**
3. The permittee shall keep the following information on a monthly basis for FGFACILITY:
 - a) Gallons or pounds of each HAP containing material used.
 - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
 - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
 - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

4. The permittee shall keep the following information on a monthly basis for FGFACILITY:
- a) Gallons or pounds of each VOC containing material used and, if applicable, reclaimed.
 - b) VOC content, in pounds per gallon or pounds per pound, of each VOC containing material used.
 - c) Gallons, with water, of each of the following coatings groups used per 12-month rolling time period as determined at the end of each calendar month, each separately:
 - i) Group 1 Coatings
 - ii) Group 2 Coatings
 - iii) Group 3 Coatings
 - iv) Group 4 Coatings
 - v) Group 5 coatings
 - d) VOC emission calculations determining the monthly emission rate in tons per calendar month.
 - e) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(1)(a), R 336.1205(3))**

5. The permittee shall keep the following information on a monthly basis for FGFACILITY:
- a) Gallons (with water) of each ethylbenzene (CAS No. 100-41-4) containing material used and, if applicable, reclaimed.
 - b) Ethylbenzene (CAS No. 100-41-4) content (with water) in pounds per gallon of each material used.
 - c) Ethylbenzene (CAS No. 100-41-4) mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) Ethylbenzene (CAS No. 100-41-4) mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1225(2))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).