

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

January 10, 2005

**NEW SOURCE REVIEW PERMIT TO INSTALL
No. 293-04**



ISSUED TO
Quincy Street, Incorporated

LOCATED AT
13350 Quincy Street
Holland, Michigan 49424

IN THE COUNTY OF
OTTAWA

STATE REGISTRATION NUMBER
N5226

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Part 5505(1) of Article II, Chapter I, Part 55 (Air Pollution Control) of P.A. 451 of 1994. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: 12/14/2004	
DATE PERMIT TO INSTALL APPROVED: 1/10/2005	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms.....	2
General Conditions.....	3
Emission Unit Identification	5
Flexible Group Identification	6
Emission Unit Special Conditions.....	7
Flexible Group Special Conditions	13

Common Abbreviations / Acronyms

Common Acronyms		Pollutant/Measurement Abbreviations	
AQD	Air Quality Division	Btu	British Thermal Unit
ANSI	American National Standards Institute	°C	Degrees Celsius
BACT	Best Available Control Technology	CO	Carbon Monoxide
CAA	Clean Air Act	dscf	Dry standard cubic foot
CEM	Continuous Emission Monitoring	dscm	Dry standard cubic meter
CFR	Code of Federal Regulations	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	NO _x	Oxides of Nitrogen
MAP	Malfunction Abatement Plan	PM	Particulate Matter
MDEQ	Michigan Department of Environmental Quality	PM-10	Particulate Matter less than 10 microns diameter
MIOSHA	Michigan Occupational Safety & Health Administration	pph	Pound per hour
MSDS	Material Safety Data Sheet	ppm	Parts per million
NESHAP	National Emission Standard for Hazardous Air Pollutants	ppmv	Parts per million by volume
NSPS	New Source Performance Standards	ppmw	Parts per million by weight
NSR	New Source Review	psia	Pounds per square inch absolute
PS	Performance Specification	psig	Pounds per square inch gauge
PSD	Prevention of Significant Deterioration	scf	Standard cubic feet
PTE	Permanent Total Enclosure	sec	Seconds
PTI	Permit to Install	SO ₂	Sulfur Dioxide
RACT	Reasonable Available Control Technology	THC	Total Hydrocarbons
ROP	Renewable Operating Permit	tpy	Tons per year
SC	Special Condition Number	µg	Microgram
SCR	Selective Catalytic Reduction	VOC	Volatile Organic Compounds
SRN	State Registration Number	yr	Year
TAC	Toxic Air Contaminant		
VE	Visible Emissions		

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **[R336.1201(1)]**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **[R336.1201(4)]**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **[R336.1201(6)(b)]**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **[R336.1201(8), Section 5510 of Act 451, PA 1994]**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R336.1219. The written request shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **[R336.1219]**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **[R336.1901]**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **[R336.1912]**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.

9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R336.1303. **[R336.1301]**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this permit to install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R336.1370(2). **[R336.1370]**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R336.2001 and R336.2003, under any of the conditions listed in R336.2001. **[R336.2001]**

SPECIAL CONDITIONS

Emission Unit Identification

Emission Unit ID	Emission Unit Description	Stack Identification
EUGERMOSOVEN1	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN1
EUGERMOSOVEN2	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN2
EUGERMOSOVEN3	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN3
EUGERMOSOVEN4	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN4
EUGERMOSOVEN5	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN5
EUGERMOSOVEN6	One Germos brand smoke house. Air drying of the meat occurs first. Vapor smoke is then introduced into the oven for product curing. A final cooking cycle follows the curing process.	SVGERMOSOVEN6
EUCHAMBER1	One wood smoke generator which supplies two ovens. Super heated steam from the boiler is passed through wood chips to form vapor smoke which is then directed to the ovens.	
EUCHAMBER2	One wood smoke generator which supplies two ovens. Super heated steam from the boiler is passed through wood chips to form vapor smoke which is then directed to the ovens.	
EUCHAMBER3	One wood smoke generator which supplies two ovens. Super heated steam from the boiler is passed through wood chips to form vapor smoke which is then directed to the ovens.	
EUSTEAMGEN	One twelve (12) MM BTU/hour natural gas fired boiler. Steam is used to heat the smokehouse as well as the smoking process.	SVSTEAMGEN
Changes to the equipment described in this table are subject to the requirements of R336.1201, except as allowed by R336.1278 to R336.1290.		

Flexible Group Identification

Flexible Group ID	Emission Units Included in Flexible Group	Stack Identification
FGSMOKE	EUGERMOSOVEN1, EUGERMOSOVEN2, EUGERMOSOVEN3, EUGERMOSOVEN4, EUGERMOSOVEN5, EUGERMOSOVEN6, EUCHAMBER1, EUCHAMBER2, EUCHAMBER3, EUSTEAMGEN	SVSTEAMGEN, SVGERMOSOVEN1 SVGERMOSOVEN2 SVGERMOSOVEN3 SVGERMOSOVEN4 SVGERMOSOVEN5 SVGERMOSOVEN6

The following conditions apply to: EUGERMOSOVEN1

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
1.1	PM	EUGERMOSOVEN1	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

1.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN1. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
1.3	SVGERMOSOVEN1	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUGERMOSOVEN2

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
2.1	PM	EUGERMOSOVEN2	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

2.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN2. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
2.3	SVGERMOSOVEN2	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUGERMOSOVEN3

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
3.1	PM	EUGERMOSOVEN3	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

3.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN3. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
3.3	SVGERMOSOVEN3	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUGERMOSOVEN4

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
4.1	PM	EUGERMOSOVEN4	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

4.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN4. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
4.3	SVGERMOSOVEN4	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUGERMOSOVEN5

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
5.1a	PM	EUGERMOSOVEN5	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

5.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN5. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
5.3	SVGERMOSOVEN5	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUGERMOSOVEN6

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirement
6.1a	PM	EUGERMOSOVEN6	0.10 lbs PM per 1000 lbs exhaust gas (on a dry gas basis)	General Condition No. 13	General Condition No. 13	R336.1331

Recordkeeping/Reporting/Notification

6.2 The permittee shall keep, in a satisfactory manner, daily records of the batches processed in EUGERMOSOVEN6. All records shall be kept on file for a period of at least five years and made available to the Department upon request. **[R336.1331, 40 CFR 52.21(c) and (d)]**

Stack/Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
6.3	SVGERMOSOVEN6	12	30	R336.1901, 40 CFR 52.21 (c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				

The following conditions apply to: EUSTEAMGEN

Monitoring

7.1 Monitoring and recording of boiler operating information is required to comply with the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and Dc. [**40 CFR Part 60 Subparts A & Dc**]

Stack/Vent Restrictions

Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
7.2 SVSTEAMGEN	19	28	R336.1901, 40 CFR Part 60 Subparts A & Dc
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.			