

**MICHIGAN DEPARTMENT OF NATURAL RESOURCES AND ENVIRONMENT  
AIR QUALITY DIVISION**

February 9, 2010

**PERMIT TO INSTALL**  
85-04B

**ISSUED TO**  
LocPac, Inc.

**LOCATED AT**  
13505 Haggerty Road  
Plymouth, Michigan

**IN THE COUNTY OF**  
Wayne

**STATE REGISTRATION NUMBER**  
N7067

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Natural Resources and Environment. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

**February 1, 2010**

DATE PERMIT TO INSTALL APPROVED:

**February 9, 2010**

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

**PERMIT TO INSTALL**

**Table of Contents**

| <b>Section</b>  | <b>Page</b> |
|---|-------------|
| Alphabetical Listing of Common Abbreviations / Acronyms ..... | 2           |
| General Conditions .....                                      | 3           |
| Special Conditions .....                                      | 5           |
| Emission Unit Summary Table.....                              | 5           |
| Special Conditions for EU-Coating Line 1.....                 | 6           |
| Special Conditions for EU-Coating Line 2.....                 | 9           |
| Flexible Group Summary Table .....                            | 12          |
| Special Conditions for FG-COATING-LINES.....                  | 13          |
| Special Conditions for FGFACILITY .....                       | 16          |

**Common Abbreviations / Acronyms**

| <b>Common Acronyms</b> |   | <b>Pollutant/Measurement Abbreviations</b> |                                   |
|------------------------|---|--|-----------------------------------|
| AQD                    | Air Quality Division                                    | BTU  | British Thermal Unit              |
| BACT                   | Best Available Control Technology                       | °C   | Degrees Celsius                   |
| CAA                    | Clean Air Act   | CO   | Carbon Monoxide                   |
| CEM                    | Continuous Emission Monitoring                          | dscf                                       | Dry standard cubic foot           |
| CFR                    | Code of Federal Regulations                             | dscm                                       | Dry standard cubic meter          |
| COM                    | Continuous Opacity Monitoring                           | °F   | Degrees Fahrenheit                |
| EPA                    | Environmental Protection Agency                         | gr   | Grains                            |
| EU                     | Emission Unit   | Hg   | Mercury                           |
| FG                     | Flexible Group  | hr   | Hour                              |
| GACS                   | Gallon of Applied Coating Solids                        | H <sub>2</sub> S                           | Hydrogen Sulfide                  |
| GC                     | General Condition                                       | hp   | Horsepower                        |
| HAP                    | Hazardous Air Pollutant                                 | lb   | Pound                             |
| HVLP                   | High Volume Low Pressure *                              | m  | Meter                             |
| ID                     | Identification  | mg   | Milligram                         |
| LAER                   | Lowest Achievable Emission Rate                         | mm   | Millimeter                        |
| MACT                   | Maximum Achievable Control Technology                   | MM   | Million                           |
| MAERS                  | Michigan Air Emissions Reporting System                 | MW   | Megawatts                         |
| MAP                    | Malfunction Abatement Plan                              | ng   | Nanogram                          |
| MDEQ                   | Michigan Department of Environmental Quality            | NO <sub>x</sub>                            | Oxides of Nitrogen                |
| MSDS                   | Material Safety Data Sheet                              | PM   | Particulate Matter                |
| NESHAP                 | National Emission Standard for Hazardous Air Pollutants | PM10                                       | PM less than 10 microns diameter  |
| NSPS                   | New Source Performance Standards                        | PM2.5                                      | PM less than 2.5 microns diameter |
| NSR                    | New Source Review                                       | pph  | Pound per hour                    |
| PS                     | Performance Specification                               | ppm  | Parts per million                 |
| PSD                    | Prevention of Significant Deterioration                 | ppmv                                       | Parts per million by volume       |
| PTE                    | Permanent Total Enclosure                               | ppmw                                       | Parts per million by weight       |
| PTI                    | Permit to Install                                       | psia                                       | Pounds per square inch absolute   |
| RACT                   | Reasonably Available Control Technology                 | psig                                       | Pounds per square inch gauge      |
| ROP                    | Renewable Operating Permit                              | scf  | Standard cubic feet               |
| SC                     | Special Condition                                       | sec  | Seconds                           |
| SCR                    | Selective Catalytic Reduction                           | SO <sub>2</sub>                            | Sulfur Dioxide                    |
| SRN                    | State Registration Number                               | THC  | Total Hydrocarbons                |
| TAC                    | Toxic Air Contaminant                                   | tpy  | Tons per year                     |
| TEQ                    | Toxicity Equivalence Quotient                           | µg   | Microgram                         |
| VE                     | Visible Emissions                                       | VOC  | Volatile Organic Compounds        |
|                        |   | yr   | Year                              |

\* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

### GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Natural Resources and Environment **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

### SPECIAL CONDITIONS

#### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| <b>Emission Unit ID</b>  | <b>Emission Unit Description<br/>(Process Equipment &amp; Control Devices)</b>  | <b>Flexible Group ID</b>        |
|--|---|---------------------------------|
| EU-Coating Line 1  | A miscellaneous metal parts coating line consisting of two primer booths, a primer oven, a topcoat booth, and a topcoat oven. | FG-COATING LINES,<br>FGFACILITY |
| EU-Coating Line 2  | A miscellaneous metal parts coating line consisting of two primer booths, a primer oven, a topcoat booth, and a topcoat oven. | FG-COATING LINES,<br>FGFACILITY |
| Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290. |   |                                 |

**The following conditions apply to: EU-Coating Line 1**

**DESCRIPTION:**

A miscellaneous metal parts coating line consisting of two primer booths, a primer oven, a topcoat booth, and a topcoat oven.

**Flexible Group ID:** FG-COATING LINES and FGFACILITY

**POLLUTION CONTROL EQUIPMENT:**

Dry filters within the paint spray booths.

**I. EMISSION LIMITS**

| <b>Pollutant</b>   | <b>Limit</b>                         | <b>Time Period / Operating Scenario</b>                                      | <b>Equipment</b>  | <b>Testing / Monitoring Method</b> | <b>Underlying Applicable Requirements</b> |
|--|--------------------------------------|--|-------------------|------------------------------------|---|
| 1. VOCs  | 30.0 tpy                             | 12-month rolling time period as determined at the end of each calendar month | EU-Coating Line 1 | SC VI.3, SC VI.4                   | R 336.1702(d)                             |
| 2. VOCs  | 3.5 lb/gal (minus water)* as applied | Daily volume-weighted average.   | EU-Coating Line 1 | SC VI.3                            | R 336.1702(d)                             |
| * The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. <b>(R 336.1602(4))</b> |                                      |  |                   |                                    |   |

**II. MATERIAL LIMITS**

NA

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall capture all waste coatings, reducers, additives, catalysts, purge solvents, and cleanup solvents and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a), R 336.1901)**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall not operate any paint booth portion of EU-Coating Line 1 unless all respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1901, R 336.1910)**
2. The permittee shall equip and maintain each paint booth portion of EU-Coating Line 1 with high volume low pressure (HVLP) applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1225, R 336.1702, R 336.1901, R 336.2001, R 336.2003, R 336.2004)**

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1702, R 336.1901)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702, R 336.1901)**
3. The permittee shall keep the following information for EU-Coating Line 1:
  - a) Gallons (with water) of each coating, reducer, additive, and catalyst used, on a daily basis
  - b) VOC content (with water) of each coating, reducer, additive, and catalyst as applied, on a daily basis
  - c) VOC emission calculations determining the volume-weighted average VOC content (minus water) of each coating as applied on a calendar day average basis.
  - d) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - e) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702(d), R 336.1901)**

4. The permittee shall keep the following information on a monthly basis for the use of purge and clean-up solvents associated with EU-Coating Line 1:
  - a) Gallons of each solvent used and reclaimed.
  - b) VOC content, in pounds per gallon, of each solvent used.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records on file in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1225, R 336.1702, R 336.1901)**

#### **VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

| <b>Stack &amp; Vent ID</b> | <b>Maximum Exhaust Dimensions (inches)</b> | <b>Minimum Height Above Ground (feet)</b> | <b>Underlying Applicable Requirements</b>   |
|----------------------------|--|---|---|
| 1. SVBLUSHWASH             | 34.0                                       | 51.0                                      | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 2. SVPRIME                 | 34.0                                       | 51.0                                      | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 3. SVPRIMEOVEN             | 12.0                                       | 30.0                                      | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 4. SVTOPCOAT               | 34.0                                       | 51.0                                      | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 5. SVTOPOVEN               | 12.0                                       | 30.0                                      | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |

**IX. OTHER REQUIREMENTS**

NA

**The following conditions apply to: EU-Coating Line 2**

**DESCRIPTION:**

A miscellaneous metal parts coating line consisting of two primer booths, a primer oven, a topcoat booth, and a topcoat oven.

**Flexible Group ID:** FG-COATING LINES and FGFACILITY

**POLLUTION CONTROL EQUIPMENT:**

Dry filters within the paint spray booths.

**I. EMISSION LIMITS**

| <b>Pollutant</b> | <b>Limit</b>                         | <b>Time Period / Operating Scenario</b>                                      | <b>Equipment</b>  | <b>Testing / Monitoring Method</b> | <b>Underlying Applicable Requirements</b> |
|------------------|--------------------------------------|--|-------------------|------------------------------------|---|
| 1. VOCs          | 30.0 tpy                             | 12-month rolling time period as determined at the end of each calendar month | EU-Coating Line 2 | SC VI.3, SC VI.4                   | R 336.1702(d)                             |
| 2. VOCs          | 3.5 lb/gal (minus water)* as applied | Daily volume-weighted average.   | EU-Coating Line 2 | SC VI.3                            | R 336.1702(d)                             |

\* The phrase "minus water" shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

**II. MATERIAL LIMITS**

NA

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall capture all waste coatings, reducers, additives, catalysts, purge solvents, and cleanup solvents and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a), R 336.1901)**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall not operate any paint booth portion of EU-Coating Line 2 unless all respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1901, R 336.1910)**
2. The permittee shall equip and maintain each paint booth portion of EU-Coating Line 2 with high volume low pressure (HVLP) applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1225, R 336.1702, R 336.1901, R 336.2001, R 336.2003, R 336.2004)**

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1702, R 336.1901)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702, R 336.1901)**
3. The permittee shall keep the following information for EU-Coating Line 2:
  - a) Gallons (with water) of each coating, reducer, additive, and catalyst used, on a daily basis
  - b) VOC content (with water) of each coating, reducer, additive, and catalyst as applied, on a daily basis
  - c) VOC emission calculations determining the volume-weighted average VOC content (minus water) of each coating as applied on a calendar day average basis.
  - d) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - e) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702(d), R 336.1901)**

4. The permittee shall keep the following information on a monthly basis for the use of purge and clean-up solvents associated with EU-Coating Line 2:
  - a) Gallons of each solvent used and reclaimed.
  - b) VOC content, in pounds per gallon, of each solvent used.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records on file in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1225, R 336.1702, R 336.1901)**

#### **VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

| Stack & Vent ID | Maximum Exhaust Dimensions (inches) | Minimum Height Above Ground (feet) | Underlying Applicable Requirements  |
|-----------------|-------------------------------------|------------------------------------|---|
| 1. SVBLUSHWASH2 | 30.0                                | 51.0                               | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 2. SVPRIME2     | 30.0                                | 51.0                               | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 3. SVPRIMEOVEN2 | 12.0                                | 30.0                               | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 4. SVTOPCOAT2   | 30.0                                | 51.0                               | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |
| 5. SVTOPOOVEN2  | 12.0                                | 30.0                               | R 336.1225,<br>R 336.1901,<br>R 336.2803,<br>R 336.2804,<br>40 CFR 52.21(c) & (d) |

**IX. OTHER REQUIREMENTS**

NA

### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| <b>Flexible Group ID</b> | <b>Flexible Group Description</b>   | <b>Associated Emission Unit IDs</b>    |
|--------------------------|---|--|
| FG-COATING LINES         | Two miscellaneous metal parts coating lines. Each line consists of two primer booths, a primer oven, a topcoat booth, and a topcoat oven. | EU-Coating Line 1<br>EU-Coating Line 2 |
| FGFACILITY               | All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.            | N/A                                    |

**The following conditions apply to: FG-COATING LINES**

**DESCRIPTION:**

Two miscellaneous metal parts coating lines. Each line consists of two primer booths, a primer oven, a topcoat booth, and a topcoat oven.

**Emission Units:** EU-Coating Line 1 and EU-Coating Line 2

**POLLUTION CONTROL EQUIPMENT:** Dry filters within the paint spray booths.

**I. EMISSION LIMITS**

| <b>Pollutant</b>                  | <b>Limit</b> | <b>Time Period/<br/>Operating<br/>Scenario</b>   | <b>Equipment</b> | <b>Testing /<br/>Monitoring<br/>Method</b> | <b>Underlying<br/>Applicable<br/>Requirements</b>    |
|-----------------------------------|--------------|--|------------------|--|--|
| 1. Naphthalene<br>(CAS # 91-20-3) | 876 Pounds*  | 12-month rolling<br>time period as<br>determined at the<br>end of each<br>calendar month | FG-COATING LINES | SC VI.3,<br>SC VI.4                        | R 336.1225 <sup>1</sup> ,<br>R 336.1901 <sup>1</sup> |

\* The naphthalene limit shall be in effect through the end of the month in which the permittee gives the AQD District Supervisor written notification that the use of naphthalene-containing coatings will be discontinued.

**II. MATERIAL LIMITS**

1. The permittee may use a maximum of 55 gallons total of coatings, on a 12-month rolling basis, on FG-COATING LINES, that will be excluded from the calculation of the daily volume-weighted average specified for EU-CoatingLine1 SC I.2 and EU-CoatingLine2 SC I.2. The mass emissions of VOCs from these coatings shall be counted toward the 30 ton per year limit specified for EU-CoatingLine1 and EU-CoatingLine2. **(R 336.1702(d))**

**III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

**IV. DESIGN/EQUIPMENT PARAMETERS**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Until the permittee gives the AQD District Supervisor written notification that the use of naphthalene-containing coatings has been discontinued, the permittee shall determine the Naphthalene (CAS # 91-20-3) content of any coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, as applied and as received, from manufacturer's formulation data. Upon written notice from the AQD District Supervisor, the permittee shall determine the Naphthalene (CAS # 91-20-3) content using an approved test method. **(R 336.1225, R 336.1901, R 336.2001, R 336.2003, R 336.2004)**

## **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Until the permittee gives the AQD District Supervisor written notification that the use of naphthalene-containing coatings has been discontinued, the permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225, R 336.1901)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating, reducer, additive, catalyst, purge solvent, and cleanup solvent, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1901)**
3. Until the permittee gives the AQD District Supervisor written notice that the use of naphthalene-containing coatings has been discontinued, the permittee shall keep the following information on a monthly basis for FG-Coating Lines:
  - a) Gallons of each coating, reducer, additive, and catalyst used.
  - b) The Naphthalene (CAS # 91-20-3) content of each coating, reducer, additive, and catalyst as applied.
  - c) Naphthalene (CAS # 91-20-3) mass emission calculations determining the monthly emission rate in pounds per calendar month.
  - d) Naphthalene (CAS # 91-20-3) mass emission calculations determining the annual emission rate in pounds per 12-month rolling time period as determined at the end of each calendar month.The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1901)**
4. Until the permittee gives the AQD District Supervisor written notice that the use of naphthalene-containing coatings has been discontinued, the permittee shall keep the following information on a monthly basis for the use of purge and clean-up solvents associated with FG-Coating Lines:
  - a) Gallons of each solvent used and reclaimed.
  - b) The Naphthalene (CAS # 91-20-3) content, in pounds per gallon, of each solvent used.
  - c) Naphthalene (CAS # 91-20-3) mass emission calculations determining the monthly emission rate in pounds per calendar month.
  - d) Naphthalene (CAS # 91-20-3) mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.The permittee shall keep the records on file in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1225, R 336.1901)**
5. The permittee shall record, on a daily basis, the number of gallons of coatings used in FG-COATINGLINES that are excluded from the calculation of the daily volume-weighted average specified for EU-CoatingLine1 SC I.2 and EU-CoatingLine2 SC I.2, on a 12-month rolling basis. Records shall be kept in a format acceptable to the AQD District Supervisor and made available to the Department upon request. **(R 336.1702(d))**

## **VII. REPORTING**

NA

## **VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**The following conditions apply Source-Wide to: FGFACILITY**

**POLLUTION CONTROL EQUIPMENT:**

**I. EMISSION LIMITS**

| <b>Pollutant</b>       | <b>Limit</b>       | <b>Time Period /<br/>Operating Scenario</b>                                  | <b>Equipment</b> | <b>Testing /<br/>Monitoring<br/>Method</b> | <b>Underlying<br/>Applicable<br/>Requirements</b> |
|------------------------|--------------------|--|------------------|--|---|
| 1. Each Individual HAP | Less than 9.0 tpy  | 12-month rolling time period as determined at the end of each calendar month | FGFACILITY       | SC VI.2                                    | R 336.1205(3)                                     |
| 2. Aggregate HAPs      | Less than 22.5 tpy | 12-month rolling time period as determined at the end of each calendar month | FGFACILITY       | SC VI.2                                    | R 336.1205(3)                                     |
| 3. VOCs                | Less than 89.9 tpy | 365-day rolling time period as determined at the end of each calendar day    | FGFACILITY       | SC VI.3                                    | R 336.1205(3)                                     |

**II. MATERIAL LIMITS**

NA

**III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

**IV. DESIGN/EQUIPMENT PARAMETERS**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**
2. The permittee shall determine the VOC content, water content, and density of any material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205(3))**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
  - a) Gallons or pounds of each HAP containing material used.
  - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
  - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
  - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
  - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month. For the first month following permit issuance, the calculations shall include the summation of emissions from the 11-month period immediately preceding the issuance date. For each month thereafter, calculations shall include the summation of emissions for the appropriate number of months prior to permit issuance plus the months following permit issuance for a total of 12 consecutive months.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

3. The permittee shall keep the following information on a daily basis for FGFACILITY:
  - a) Gallons or pounds of each VOC containing material used.
  - b) Where applicable, gallons or pounds of each VOC containing material reclaimed.
  - c) VOC content, in pounds per gallon or pounds per pound, of each VOC containing material used.
  - d) VOC emission calculations determining the annual emission rate in tons per 365-day rolling time period as determined at the end of each calendar day

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

**Footnotes:**

<sup>1</sup>This condition is state only enforceable and was established pursuant to Rule 201(1)(b).