

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

October 20, 2016

**PERMIT TO INSTALL
302-05D**

**ISSUED TO
MPLX Terminals LLC**

**LOCATED AT
6300 West Grand River
Lansing, Michigan**

**IN THE COUNTY OF
Clinton**

**STATE REGISTRATION NUMBER
B5215**

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

October 4, 2016

DATE PERMIT TO INSTALL APPROVED:

October 20, 2016

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EURACK	6
Special Conditions for EUORTANK	8
Special Conditions for EUTANK8-11	10
Special Conditions for EUSUMP	11
Flexible Group Summary Table	12
Special Conditions for FGGASOLINETANKS.....	13
Special Conditions for FGNSPSTANKS	14
Special Conditions for FGDISTALATETANKS	15
Special Conditions for FGTRANSMIXTANKS	16
Special Conditions for FGFACILITY	18

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO ₂ e	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H ₂ S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO _x	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM10	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO ₂	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EURACK	Tanker truck loading rack	FGFACILITY
EUORTANK	Fixed roof storage tank for overpressure relief	FGFACILITY
EUTANK8-11	Fixed roof storage tank	FGGASOLINETANKS, FGFACILITY
EUSUMP	935 gallon in-ground sump (steel)	FGFACILITY
EUTANK25-1	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK25-2	Fixed roof storage tank	FGDISTILLATETANKS, FGFACILITY
EUTANK25-3	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK25-4	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK5-5	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK25-6	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK25-7	Fixed roof storage tank	FGDISTILLATETANKS, FGFACILITY
EUTANK25-8	Internal floating roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANK15-9	Fixed roof storage tank	FGDISTILLATETANKS, FGFACILITY
EUTANK1-12	Fixed roof storage tank	FGTRANSMIXTANKS, FGFACILITY
EUTANK1-13	Fixed roof storage tank	FGTRANSMIXTANKS, FGFACILITY
EUTANKAA-1-14	Fixed roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANKAA-1-16	Fixed roof storage tank	FGGASOLINETANKS, FGFACILITY
EUTANKAA-1-18	Horizontal storage tank	FGDISTILLATETANKS, FGFACILITY
EUTANKAA-1-19	Horizontal storage tank	FGDISTILLATETANKS, FGFACILITY
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.		

The following conditions apply to: EURACK

DESCRIPTION: Tanker truck loading rack

Flexible Group ID: FGFACILITY

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	31mg/L	Test protocol*	EURACK	GC 13	R 336.1205(3)
* Test protocol shall determine averaging time					

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Gasoline, gasoline additives, and ethanol	400,000,000 gallons	12-month rolling time period as determined at the end of each calendar month	EURACK	VI.1.a. in FGFACILITY section	R 336.1205
2. Distillate fuel and distillate additives	100,250,000 gallons	12-month rolling time period as determined at the end of each calendar month	EURACK	VI.1.a. in FGFACILITY section	R 336.1205

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not use EURACK to load tanker trucks with organic compounds having a true vapor pressure of more than 1.5 psia unless the vapor control system is installed, maintained, and operated in a satisfactory manner. (R 336.1609)
2. The permittee shall not use EURACK to load tanker trucks with organic compounds having a true vapor pressure of more than 1.5 psia unless all provisions of Rules 609 & 627 and NSPS Subparts A & XX are met. (R 336.1609, R 336.1627, 40 CFR Part 60 Subpart XX)

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall maintain a log of all vapor control system outages, however no organic compounds having true vapor pressure of more than 1.5 psia shall be loaded out during outages. The log shall be kept on file for a period of at least five years and made available to the Air Quality Division upon request. **(R 336.1609)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVVRU	10 ¹	20 ¹	R 336.1225(3(a))

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUORTANK

DESCRIPTION: Fixed roof storage tank for overpressure relief

Flexible Group ID: FGFACILITY

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Petroleum product	100,000 gallons	12-month rolling time period as determined at the end of each calendar month	EUORTANK	VI.1.b. in FGFACILITY section	R 336.1205

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not store any organic compound in EUORTANK having a true vapor pressure of more than 1.5 psia unless the requirements of Rule 604 are met. **(R 336.1604)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate EUORTANK unless the respective conservation vent/thief hatch is installed and operating properly. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. EUORTANK	10 ¹	32 ¹	R 336.1225

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUTANK8-11

DESCRIPTION: Fixed roof storage tank

Flexible Group ID: FGGASOLINETANKS, FGFACILITY

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not store any organic compound in EUTANK8-11 having a true vapor pressure of more than 1.5 psia unless the requirements of Rule 604 are met. **(R 336.1604)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate EUTANK8-11 unless the respective conservation vent/thief hatch is installed and operating properly. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

The following conditions apply to: EUSUMP

DESCRIPTION: 935 gallon in ground sump (steel)

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall operate EUSUMP in a manner which minimizes the introduction of air contaminants to the air. This includes keeping the hatch on EUSUMP closed at all times that the hatch is not in use. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

NA

IX. OTHER REQUIREMENTS

NA

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGGASOLINETANKS	Tanks storing gasoline	EUTANK25-1, EUTANK25-3, EUTANK25-4, EUTANK5-5, EUTANK25-6, EUTANK25-8, EUTANKAA-1-14, EUTANKAA-1-16, EUTANK8-11
FGNSPSTANKS	Tanks subject to 40 CFR part 60 Subpart Kb	EUTANK25-1, EUTANK25-3, EUTANK25-4, EUTANK5-5, EUTANK25-6
FGDISTILLATETANKS	Tanks storing distillate	EUTANK25-2, EUTANK25-7, EUTANK15-9, EUTANKAA-1-18, EUTANKAA-1-19
FGTRANSMIXTANKS	Tanks storing transmix	EUTANK1-12, EUTANK1-13
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grandfathered equipment and exempt equipment.	NA

The following conditions apply to: FGGASOLINETANKS

DESCRIPTION: Tanks storing gasoline.

Emission Units: EUTANK25-1, EUTANK25-3, EUTANK25-4, EUTANK5-5, EUTANK25-6, EUTANK25-8, EUTANKAA-1-14, EUTANKAA-1-16, EUTANK8-11

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate FGGASOLINETANKS unless the internal floating roof controls are installed and operating properly and all provisions of Rule 604 are met. **(R 336.1604)**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

The following conditions apply to: FGNSPSTANKS

DESCRIPTION: Tanks subject to 40 CFR part 60 Subpart Kb.

Emission Units: EUTANK25-1, EUTANK25-3, EUTANK25-4, EUTANK5-5, EUTANK25-6

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep records of emissions and operating information to comply with the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and Kb. The permittee shall keep all source emissions data and operating information on file at the facility for a period of at least five years and make them available to the Department upon request. **(40 CFR Part 60 Subparts A & Kb, R 336.1205, R 336.1702)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

The following conditions apply to: FGDISTILLATETANKS

DESCRIPTION: Tanks storing distillate.

Emission Units: EUTANK25-2, EUTANK25-7, EUTANK15-9, EUTANKAA-1-18, EUTANKAA-1-19.

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate FGDISTILLATETANKS unless the respective conservation vent/thief hatch is installed and operating properly. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

The following conditions apply to: FGTRANSMIXTANKS

DESCRIPTION: Tanks storing transmix

Emission Units: EUTANK1-12, EUTANK1-13

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

NA

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate FGTRANSMIXTANKS unless the respective conservation vent/thief hatch is installed and operating properly. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVTANK1-12	10 ¹	40 ¹	R 336.1225
2. SVTANK1-13	10 ¹	40 ¹	R 336.1225

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply Source-Wide to: FGFACILITY

DESCRIPTION: All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	90 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	VI.1	R 336.1205(3)
2. Individual HAP	9 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	VI.1	R 336.1205(3)
3. Total HAPs	22.5 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	VI.1	R 336.1205(3)

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep records of the following for each calendar month and 12-month rolling time period:
 - a) Tank specific and petroleum product specific throughput for all tanks except EUORTANK.
 - b) Throughput for EUORTANK.

For emission calculation purposes, the permittee shall use worst case gasoline as the throughput product for EUORTANK, unless product specific data is available. The permittee shall keep all records on file at the facility for a period of at least five years and make them available to the Department upon request. **(R 336.1205(3))**

VII. REPORTING

1. The permittee shall notify the Department if a change in land use occurs for property classified as industrial or as a public roadway, where this classification was relied upon to demonstrate compliance with Rule 225(1). The permittee shall submit the notification to the AQD District Supervisor, within 30 days of the actual land use change. Within 60 days of the land use change, the permittee shall submit to the AQD District Supervisor a plan for complying with the requirements of Rule 225(1). The plan shall require compliance with Rule 225(1) no later than one year after the due date of the plan submittal.¹
(R 336.1225(4))

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).