

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY  
AIR QUALITY DIVISION**

July 13, 2016

**PERMIT TO INSTALL**  
249-06B

**ISSUED TO**  
Valassis Manufacturing Company, Anderson Printing Division

**LOCATED AT**  
35955 Schoolcraft Road  
Livonia, Michigan

**IN THE COUNTY OF**  
Wayne

**STATE REGISTRATION NUMBER**  
A4493

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

**June 28, 2016**

DATE PERMIT TO INSTALL APPROVED:

**July 13, 2016**

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

## PERMIT TO INSTALL

### Table of Contents

<b>Section</b>	<b>Page</b>
Alphabetical Listing of Common Abbreviations / Acronyms .....	2
General Conditions .....	3
Special Conditions .....	5
Emission Unit Summary Table.....	5
Special Conditions for EU-GOSS-04 .....	6
Flexible Group Summary Table .....	10
Flexible Group Conditions for FG-OFFSETLITHO .....	11
Special Conditions for FGFACILITY .....	15
Appendix A: Weight Percent of VOC in Fountain Solution .....	17

**Common Abbreviations / Acronyms**

<b>Common Acronyms</b>		<b>Pollutant / Measurement Abbreviations</b>	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO <sub>2</sub> e	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H <sub>2</sub> S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO <sub>x</sub>	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM10	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO <sub>2</sub>	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
  - a. A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b. A visible emission limit specified by an applicable federal new source performance standard.
  - c. A visible emission limit specified as a condition of this Permit to Install.
  
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
  
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

**SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Process Equipment &amp; Control Devices)</b>	<b>Installation Date/ Modification Date</b>	<b>Flexible Group ID</b>
EU-HEIDELBERG-01	Heidelberg No. 1: Heidelberg Harris M600 (formerly known as Press #12) Offset Litho, Heatset, Web fed, Automatic Wash Web Width: 38", 6 Color Control Equipment: Regenerative Thermal Oxidizer (RTO)	04-01-1998 / 11-20-2006	FG-OFFSETLITHO, FG-FACILITY
EU-HEIDELBERG-02	Heidelberg No. 2: Heidelberg Harris M600 (formerly known as Press #15) Offset Litho, Heatset, Web fed, Automatic Wash Web Width: 38", 6 Color Control Equipment: RTO	09-01-1994 / 11-20-2006	FG-OFFSETLITHO, FG-FACILITY
EU-HEIDELBERG-03	Heidelberg No. 3: Heidelberg Harris N9000D (formerly known as Press #17) Offset Litho, Heatset, Web fed, Automatic Wash Web Width: 75", 4 Color Control Equipment: RTO	03-01-1989 / 11-20-2006	FG-OFFSETLITHO, FG-FACILITY
EU-GOSS-02	Goss No. 2: Goss Sunday 2000 (known as Press #16) Offset Litho, Heatset, Web fed, Automatic Wash Web Width: 57", 4 Color Control Equipment: RTO	02-01-2007	FG-OFFSETLITHO, FG-FACILITY
EU-GOSS-03	Goss No. 3: Goss Sunday 2000/24 (known as Press #13) Offset Litho, Heatset, Web fed, 5 Units, Automatic Wash Web Width: 57", 4 Color Control Equipment: RTO	4/1/2005	FG-OFFSETLITHO, FG-FACILITY
EU-GOSS-04	Goss No. 4: Goss Sunday 2000/24 (Known as Press #11) Offset Litho, Heatset, Web fed, Automatic Wash Web Width: 57", 4 Color Control Equipment: RTO	TBD	FG-FACILITY

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.

**The following conditions apply to: EU-GOSS-04**

**DESCRIPTION:** Goss No. 4: Goss Sunday 2000/24 (Known as Press #11), Offset Litho, Heatset, Web fed, Automatic Wash, Web Width: 57", 4 Color, Control Equipment: RTO

**Flexible Group ID:** FGFACILITY

**POLLUTION CONTROL EQUIPMENT:** RTO

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOCs	6.0 tpy	12-month rolling time period as determined at the end of each calendar month	EU-GOSS-04	SC V.1, SC VI.2, SC VI.3	R 336.1205(1)(a)(ii)(A), R 336.1702(a)

**II. MATERIAL LIMITS**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC content of the fountain solution	5.0% by weight, as applied and no alcohol*	Instantaneous	EU-GOSS-04	SC VI.1, SC VI.2, SC VI.4	R 336.1702(a)
* No alcohol includes isopropyl alcohol (CAS No. 67-63-0), propyl alcohol (CAS No. 71-23-8), and ethanol (CAS No. 64-17-5).					

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall capture all VOC-containing inks, fountain solutions, coatings, cleaning solvents such as blanket and roller washes, used shop towels, etc., and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
3. All printing press-related cleaning solvents shall have VOC composite partial vapor pressures that do not exceed 10 mmHg @ 20°C (68°F). **(R 336.1702(a))**

4. The permittee shall not operate EU-GOSS-04 unless a malfunction abatement plan (MAP), as described in Rule 911(2) for the RTO, has been submitted, implemented, and maintained. The MAP shall, at a minimum, specify the following:
  - a. A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b. An identification of the sources and air cleaning operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c. A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.
  - d. A description of the procedures to capture, handle, and dispose of all materials to minimize the generation of fugitive emissions per SC III.1 and III.2.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1205, R 336.1225, R 336.1702(a), R 336.1910, R 336.1911)**

#### **IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall not operate EU-GOSS-04 unless the dryer is installed, maintained, and operated in a satisfactory manner. Satisfactory operation requires that each dryer is operating at a pressure lower than all adjacent areas so that air flows into each dryer through all natural draft openings at all times. **(R 336.1205, R 336.1225, R 336.1702(a), R 336.1910)**
2. The permittee shall not operate EU-GOSS-04 unless the RTO is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of the RTO includes a minimum VOC destruction efficiency of 98 percent (by weight), a minimum retention time of 0.5 seconds, a minimum combustion temperature of 1400°F, and in accordance with the MAP required in SC III.4. **(R 336.1205, R 336.1702(a), R 336.1910)**
3. The permittee shall install, calibrate, maintain, and operate a temperature monitoring device in the combustion chamber of the RTO in a satisfactory manner. The monitoring device shall monitor and record the temperature on a continuous basis during the operation of EU-GOSS-04. **(R 336.1205, R 336.1702(a))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify the VOC content of any ink, coating, *etc.* (material), as received and as applied, using federal Reference Test Method 24 or 24A pursuant to Rule 1040(5). Upon prior written approval by the AQD District Supervisor, VOC content may be determined from manufacturer's formulation data. If the Method 24 or 24A results and the formulation values should differ, the Method 24 or 24A results shall be used to determine compliance. **(R 336.1702(a), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**
2. The permittee may be required to verify the destruction efficiency of the RTO for EU-GOSS-04 by testing at the owner's expense and in accordance with Department requirements. No less than 60 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. Verification of the destruction efficiency includes the submittal of a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1205, R 336.1702(a), R 336.2001, R 336.2003, R 336.2004)**

## **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702(a))**
2. During operation of EU-GOSS-04, the permittee shall monitor and record, in a satisfactory manner, the temperature in the combustion chamber of the RTO on a continuous basis in a manner and with instrumentation acceptable to the Air Quality Division. Temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1225, R 336.1702(a))**
3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
4. The permittee shall keep the following information on a monthly basis for EU-GOSS-04:
  - a. The type and amount (in pounds or gallons (with water)) of each VOC-containing material used and, if applicable, reclaimed.
  - b. VOC content of each material, as received and as applied (in percent by weight or pounds per gallon).
  - c. VOC mass emission calculations determining the monthly emission rate in tons per calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used or an alternate factor approved by the AQD District Supervisor)
  - d. VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used or an alternate factor approved by the AQD District Supervisor)

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(a))**

5. The permittee shall calculate the VOC content of the fountain solution using the method detailed in Appendix A or an alternate method approved by the AQD District Supervisor. Calculations shall include both dampening aid and wetting agent, as used, in percent by weight. The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1702(a))**
6. The permittee shall keep records of the air pressure within the dryer associated with EU-GOSS-04 and the direction of the airflow. The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1225, R 336.1702(a))**

**VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU-GOSS-04. **(R 336.1201(7)(a))**

**VIII. STACK/VENT RESTRICTIONS**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter/ Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-RTO	55	50	R 336.1225, 40 CFR 52.21(c) & (d)

**IX. OTHER REQUIREMENTS**

1. After the completion of removal and addition of presses, the permittee shall label the each emission unit (e.g. EU-Heidelberg-01, EU-Heidelberg-02, EU-Heidelberg-03, ...) according to a method acceptable to the AQD District Supervisor. Within seven days of completing the labeling, the permittee shall notify the AQD District Supervisor, in writing, as to the date the labeling was completed. **(R 336.1201)**

### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FG-OFFSETLITHO	Heatset, Web Fed, Offset Lithographic Printing Presses.	EU-HEIDELBERG-01, EU-HEIDELBERG-02, EU-HEIDELBERG-03, EU-GOSS-02, EU-GOSS-03
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.	NA

**The following Flexible Group conditions apply to: FG-OFFSETLITHO**

**DESCRIPTION:** Heatset, Web Fed, Offset Lithographic Printing Presses.

**Emission Units:** EU-Heidelberg-01, EU-Heidelberg-02, EU-Heidelberg-03, EU-Goss-02, and EU-Goss-03

**POLLUTION CONTROL EQUIPMENT:** Regenerative Thermal Oxidizer (RTO)

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC	35.1 tpy	12-month rolling time period as determined at the end of each calendar month	FG-OFFSETLITHO	SC VI.1, SC VI.2, SC VI.3	R 336.1205, R 336.1702(a)

**II. MATERIAL LIMITS**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC content of the fountain solution	5.0% by weight, as applied and no alcohol*	Instantaneous	FG-OFFSETLITHO	SC VI.1, SC VI.2, SC VI.4	R 336.1702(a)
* No alcohol includes isopropyl alcohol (CAS No. 67-63-0), propyl alcohol (CAS No. 71-23-8), and ethanol (CAS No. 64-17-5).					

**III. PROCESS/OPERATIONAL RESTRICTIONS**

- All VOC containing inks, fountain solution, coatings, cleaning solvents such as blanket and roller washes, used shop towels, etc. (materials) shall be stored in closed containers and disposed of in an acceptable manner, in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
- The permittee shall handle all VOC and/or HAP containing materials, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
- All printing press-related cleaning solvents shall have VOC composite partial vapor pressures that do not exceed 10 mmHg @ 20°C (68°F). **(R 336.1702(a))**

4. The permittee shall not operate FG-OFFSETLITHO unless a malfunction abatement plan (MAP) as described in Rule 911(2) for the regenerative thermal oxidizer (RTO), has been submitted within 90 days of permit issuance, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a. A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b. An identification of the sources and air cleaning operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c. A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.
  - d. A description of the procedures to capture, handle, and dispose of all materials to minimize the generation of fugitive emissions per SC III.1 and III.2.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1205, R 336.1225, R 336.1702(a), R 336.1910, R 336.1911)**

#### **IV. DESIGN/EQUIPMENT PARAMETERS**

1. The permittee shall not operate FG-OFFSETLITHO unless all dryers are installed, maintained and operated in a satisfactory manner. Satisfactory operation requires that the each dryer is operating at a pressure lower than all adjacent areas so that air flows into the each dryer through all natural draft openings at all times. **(R 336.1205, R 336.1225, R 336.1702(a), R 336.1910)**
2. The permittee shall not operate FG-OFFSETLITHO unless the RTO is installed, maintained and operated in a satisfactory manner. Satisfactory operation of the RTO includes a minimum VOC destruction efficiency of 98 percent (by weight), a minimum retention time of 0.5 seconds, a minimum combustion temperature of 1400°F, and in accordance with the MAP required in SC III.4. **(R 336.1205, R 336.1702(a), R 336.1910)**
3. The permittee shall install, calibrate, maintain and operate a temperature monitoring device in the combustion chamber of the RTO in a satisfactory manner. The monitoring device shall monitor and record the temperature on a continuous basis during the operation of FG-OFFSETLITHO. **(R 336.1205, R 336.1702(a))**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify the VOC content of any ink, coating, *etc.* (material), as received and as applied, using federal Reference Test Method 24 or 24A pursuant to Rule 1040(5). Upon prior written approval by the AQD District Supervisor, VOC content may be determined from manufacturer's formulation data. If the Method 24 or 24A and the formulation values should differ, the Method 24 or 24A results shall be used to determine compliance. **(R 336.1702(a), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**
2. Within 180 days of trial operation for EU-Goss-03, the permittee shall verify, by testing at the owner's expense and in accordance with Department requirements, the destruction efficiency of the RTO for the FG-OFFSETLITHO. No less than 60 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. Verification of the destruction efficiency includes the submittal of a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1205, R 336.1702(a), R 336.2001, R 336.2003, R 336.2004)**

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15<sup>th</sup> day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a calendar month basis for FG-OFFSETLITHO:
  - a. The type of each VOC containing material used and reclaimed (ink, coating, fountain solution, blanket wash, roller wash, press wash, *etc.*)
  - b. The VOC content of each material as received and as applied (in percent by weight or pounds per gallon)
  - c. VOC mass emission calculations determining the monthly emission rate in tons per calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used or an alternate factor approved by the AQD District Supervisor)
  - d. VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used or an alternate factor approved by the AQD District Supervisor)

The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1702(a))**

4. The permittee shall calculate the VOC content of the fountain solution using the method detailed in Appendix A or an alternate method approved by the AQD District Supervisor. Calculations shall include both dampening aid and wetting agent, as used, in percent by weight. The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1702(a))**
5. The permittee shall keep records of the air pressure within each dryer associated with appropriate press and the direction of the airflow. The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1225, R 336.1702(a))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted in the table below:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter/ Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-RTO	55	50	R 336.1225, 40 CFR 52.21 (c) & (d)

**IX. OTHER REQUIREMENTS**

1. After the completion of removal and addition of presses, the permittee shall label the each emission unit (e.g. EU-Heidelberg-01, EU-Heidelberg-02, EU-Heidelberg-03, ...) according to a method acceptable to the AQD District Supervisor. Within seven days of completing the labeling, the permittee shall notify the AQD District Supervisor, in writing, as to the date the labeling was completed. **(R 336.1201)**

**The following conditions apply Source-Wide to: FGFACILITY**

**POLLUTION CONTROL EQUIPMENT:** RTO

**I. EMISSION LIMITS**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period/ Operating Scenario</b>	<b>Equipment</b>	<b>Testing/ Monitoring Method</b>	<b>Underlying Applicable Requirements</b>
1. Each Individual HAP	Less than 9.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1205(3)

**II. MATERIAL LIMITS**

NA

**III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

**IV. DESIGN/EQUIPMENT PARAMETERS**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as applied and as received, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
  - a) Gallons or pounds of each HAP containing material used.
  - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
  - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
  - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
  - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month. For the first month following permit issuance, the calculations shall include the summation of emissions from the 11-month period immediately preceding the issuance date. For each month thereafter, calculations shall include the summation of emissions for the appropriate number of months prior to permit issuance plus the months following permit issuance for a total of 12 consecutive months.

The permittee shall keep records using mass balance or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

