


**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

August 28, 2008

PERMIT TO INSTALL

No. 41-06A



ISSUED TO

Durcon, Inc.

LOCATED AT

8464 Ronda Drive
Canton, Michigan 48187

IN THE COUNTY OF

Wayne

STATE REGISTRATION NUMBER

N0516

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: 8/28/2008	
DATE PERMIT TO INSTALL APPROVED: 8/28/2008	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Emission Unit Identification	5
Flexible Group Identification	6
Flexible Group Special Conditions	7

Common Abbreviations / Acronyms

Common Acronyms		Pollutant/Measurement Abbreviations	
AQD	Air Quality Division	Btu	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
COM	Continuous Opacity Monitoring	°F	Degrees Fahrenheit
EPA	Environmental Protection Agency	gr	Grains
EU	Emission Unit	Hg	Mercury
FG	Flexible Group	hr	Hour
GACS	Gallon of Applied Coating Solids	H ₂ S	Hydrogen Sulfide
GC	General Condition	hp	Horsepower
HAP	Hazardous Air Pollutant	lb	Pound
HVLP	High Volume Low Pressure *	m	Meter
ID	Identification	mg	Milligram
LAER	Lowest Achievable Emission Rate	mm	Millimeter
MACT	Maximum Achievable Control Technology	MM	Million
MAERS	Michigan Air Emissions Reporting System	MW	Megawatts
MAP	Malfunction Abatement Plan	ng	Nanogram
MDEQ	Michigan Department of Environmental Quality	NO _x	Oxides of Nitrogen
MSDS	Material Safety Data Sheet	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM-10	Particulate Matter less than 10 microns diameter
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition Number	SO ₂	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The AQD District Supervisor shall be notified, in writing, of a change in ownership or operational control of the stationary source or emission unit(s) authorized by this Permit to Install pursuant to R 336.1219. The notification shall include all of the information required by R 336.1219(1)(a) and (b). In addition, a new owner or operator must submit a written statement pursuant to R 336.1219(1)(c), agreeing to and accepting the terms and conditions of this Permit to Install, and shall notify the AQD District Supervisor of any change in the contact person for this Permit to Install. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**

8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law nor does it affect any liability for past violations under the Natural Resources and Environmental Protection Act, 1994 PA 451.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this permit to install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

Emission Unit Identification

Emission Unit ID	Emission Unit Description	Stack Identification
EU-MIXING	Seven closed mixing tanks that combine silica, resins, and pigments at high temperatures and controlled by a baghouse, two silica silos each controlled by a baghouse, and a number of area exhausts that go to vertical stacks.	SV-MixingTanks(#14) SV-SilicaSilo(#15) SV-SilicaSilo(#18)
EU-BLENDING	Blending stage that combines the resin mixture from the mixing tanks with phthalic anhydride and a catalyst. Ventilation goes to vertical stacks.	NA
EU-SLABCASTING	Seven (7) mold casting areas with associated cure ovens, and curing/cooling areas. Multiple area exhausts vent to vertical stacks for the slabcasting operation.	NA
EU-SINKCASTING	Three (3) sink casting stations with molding, associated cure ovens, and curing/cooling areas. Fabric filters on the three (3) sink casting stations vent to vertical stacks.	SV-SinkStation#1(#34) SV-SinkStation#2(#33) SV-SinkStation#3(#32)
EU-CUTSANDMILL	Cutting, sanding and milling of molded parts to meet customer specifications. Process is controlled by baghouse(s).	SV-Stack#1 SV-Stack#2 SV-Stack#3 SV-Stack#4 SV-Stack#5 SV-Stack#6 SV-Stack#16
EU-MILLROUTE	Routing and milling of cured molded parts. Process is controlled by baghouse(s).	SV-Stack#7 SV-Stack#8 SV-Stack#9
EU-SAWING	Wet and dry sawing of cured molded parts. Process is controlled by baghouse(s).	SV-Stack#10 SV-Stack#11 SV-Stack#12 SV-Stack#13

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.

Flexible Group Identification

Flexible Group ID	Emission Units Included in Flexible Group	Stack Identification
FG-CASTING	EU-MIXING, EU-BLENDING, EU-SLABCASTING, EU-SINKCASTING, EU-CUTSANDMILL, EU-MILLROUTE, EU-SAWING	SV-MixingTanks(#14) SV-SilicaSilo(#15) SV-SilicaSilo(#18) SV-SinkStation#1(#34) SV-SinkStation#2(#33) SV-SinkStation#3(#32) SV-Stack#1, SV-Stack#2 SV-Stack#3, SV-Stack#4 SV-Stack#5, SV-Stack#6 SV-Stack#16, SV-Stack#7 SV-Stack#8, SV-Stack#9 SV-Stack#10, SV-Stack#11 SV-Stack#12, SV-Stack#13

The following conditions apply to: FG-CASTING

Emission Limits

	Pollutant	Equipment	Limit	Time Period	Testing/ Monitoring Method	Applicable Requirements
1.1a	PM	Baghouses and fabric filters associated with FG-CASTING	0.01 lbs per 1000 lbs of exhaust gases*	Test Protocol	General Condition No. 13	R 336.1205 R 336.1331
* Calculated on a dry gas basis.						

Process / Operational Limits

1.2 The permittee shall not operate any portion of FG-CASTING unless a malfunction abatement plan (MAP) as described in Rule 911(2) is implemented and maintained. If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1331, R 336.1910, R 336.1911)**

Equipment

1.3 The permittee shall not operate FG-CASTING unless the baghouses and fabric filters associated with the process are installed, maintained, and operated in a satisfactory manner. **(R 336.1331, R 336.1901, R 336.1910, R 336.2803, R 336.2804, 40 CFR 52.21(c) and (d))**

Recordkeeping /Reporting /Notification

1.4 The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor and make them available by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any recordkeeping, reporting or notification special condition. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901)**

1.5 The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material (resin, pigment, filler, catalyst, mold release, cleanup solvent, etc.), including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file at the facility for a period of at least five years and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901)**

1.6 The permittee shall keep, in a satisfactory manner, monthly and previous 12-month rolling time period records of the amount of materials (resin, pigment, filler, catalyst, mold release, cleanup solvent, etc.) used in FG-CASTING. All records shall be kept on file at the facility for a period of at least five years and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901)**

Stack / Vent Restrictions

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
1.7a	SV-MixingTanks(#14)— baghouse	10	13	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7b	SV-SilicaSilo(#15)	10	46	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7c	SV-SilicaSilo(#18)	10	46	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7d	SV-SinkStation#1(#34)	20	34.67	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7e	SV-SinkStation#2(#33)	20	34.67	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7f	SV-SinkStation#3(#32)	20	34.67	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7g	SV-Stack#1	72 sq. in.	12.25	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7h	SV-Stack#2	72 sq. in.	13.41	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7i	SV-Stack#3	72 sq. in.	12.25	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
1.7j	SV-Stack#4	72 sq. in.	11.75	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7k	SV-Stack#5	109.4 sq. in.	10.5	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7l	SV-Stack#6	72 sq. in.	12.41	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7m	SV-Stack#7	118.1 sq. in.	13.83	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7n	SV-Stack#8	237.6 sq. in.	19.6	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7o	SV-Stack#9	72 sq. in.	12.41	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7p	SV-Stack#10	237.6 sq. in.	19.58	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7q	SV-Stack#11	237.6 sq. in.	19.58	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7r	SV-Stack#12	63.36 sq. in.	11.41	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
1.7s	SV-Stack#13	237.6 sq. in.	19.58	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)

	Stack & Vent ID	Maximum Diameter (inches)	Minimum Height Above Ground Level (feet)	Applicable Requirement
1.7t	SV-Stack#16	195.8 sq. in.	10.17	R 336.1225, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d)
The exhaust gases shall be discharged unobstructed vertically upwards to the ambient air.				