

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY
AIR QUALITY DIVISION**

March 31, 2023

PERMIT TO INSTALL
158-11D

ISSUED TO
TRMI, Inc.

LOCATED AT
100 Hill Brady Road
Battle Creek, Michigan 49037

IN THE COUNTY OF
Calhoun

STATE REGISTRATION NUMBER
N2354

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: January 6, 2023	
DATE PERMIT TO INSTALL APPROVED: March 31, 2023	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE	6
EUIPA.....	8
FLEXIBLE GROUP SPECIAL CONDITIONS.....	10
FLEXIBLE GROUP SUMMARY TABLE	10
FGSOLDER	11
FGTOLUENE	14
FGELEPCOAT.....	16
FGPAINTLINES.....	18
FGRULE632	21
FGFACILITY CONDITIONS.....	23

COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO ₂ e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H ₂ S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO _x	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO ₂	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EUSOL1	Soldering ventilation	04-01-2006 / 07-07-2020	FGSOLDER
EUSOL2	Soldering ventilation 2	01-01-2009 / 07-07-2020	FGSOLDER
EUSOL3	Soldering ventilation 3	07-01-2010 / 07-07-2020	FGSOLDER
EUSOL4	Soldering ventilation 4	12-01-2018 / 07-07-2020	FGSOLDER
EURFSOL1	Alpha telecore 63Sn/37Pb soldering station – reflow	01-01-2007 / 07-07-2020	FGSOLDER
EURFSOL2	Soldering station - reflow	01-01-2007 / 07-07-2020	FGSOLDER
EURFSOL3	Soldering station - reflow	01-01-2008 / 07-07-2020	FGSOLDER
EURFSOL4	Soldering station - reflow	01-01-2010 / 07-07-2020	FGSOLDER
EURFSOL5	Soldering station - reflow	01-01-2016 / 07-07-2020	FGSOLDER
EURFSOL6	Soldering station - reflow	11-01-2016 / 07-07-2020	FGSOLDER
EURFSOL7	Soldering station - reflow	01-01-2017 / 07-07-2020	FGSOLDER
EUTOLTK	Toluene dip tank	12-01-2018 / 07-07-2020	FGTOLUENE
EUTOLSQZBOTTLES	Toluene squeeze bottles	01-01-2000 / 07-07-2020	FGTOLUENE
EUTOLELEPCOAT	Toluene solvent in elepcoat	01-01-2000 / 07-07-2020	FGTOLUENE
EUIPA	Use of IPA squeeze bottles at various locations throughout the facility	01-01-2000 / 07-07-2020	NA
EUELEPCOAT1	Elepcoat 1	03-31-2023	FGELEPCOAT
EUELEPCOAT2	Elepcoat 2	03-01-2000 / 03-31-2023	FGELEPCOAT
EUELEPCOAT3	Elepcoat 3	03-01-2000 / 03-31-2023	FGELEPCOAT
EUELEPCOAT4	Elepcoat 4	04-01-2002 / 03-31-2023	FGELEPCOAT
EUELEPCOAT5	Elepcoat 5	04-01-2002 / 03-31-2023	FGELEPCOAT
EUELEPCOAT6	Elepcoat 6	04-01-2002 / 03-31-2023	FGELEPCOAT
EUELEPCOAT7	Elepcoat 7	04-01-2002 / 03-31-2023	FGELEPCOAT

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EUELEPCOAT8	Elepcoat 8	07-01-2004 / 03-31-2023	FGELEPCOAT
EUELEPCOAT9	Elepcoat 9	07-01-2004 / 03-31-2023	FGELEPCOAT
EUELEPCOAT10	Elepcoat 10	07-01-2004 / 03-31-2023	FGELEPCOAT
EUELEPCOAT11	Elepcoat 11	07-01-2004 / 03-31-2023	FGELEPCOAT
EUELEPCOAT12	Elepcoat 12	07-01-2004 / 03-31-2023	FGELEPCOAT
EUELEPCOAT13	Elepcoat 13	06-01-2005 / 03-31-2023	FGELEPCOAT
EUELEPCOAT14	Elepcoat 14	07-01-2015 / 03-31-2023	FGELEPCOAT
EUELEPCOAT15	Elepcoat 15	10-01-2015 / 03-31-2023	FGELEPCOAT
EUELEPCOAT16	Elepcoat 16	10-01-2015 / 03-31-2023	FGELEPCOAT
EUELEPCOAT17	Elepcoat 17	10-01-2015 / 03-31-2023	FGELEPCOAT
EUPAINTLINE1	A paint line used to coat interior plastic automotive parts. The emission unit consists of a booth, cure area and mixing area and include emissions from purge and cleanup. A robot operates only one of the two HVLP spray guns at any given time. The particulate emissions are controlled by use of a water curtain.	11-28-2011	FGPAINTLINES, FGRULE632
EUPAINTLINE2	A paint line used to coat interior plastic automotive parts. The emission unit consists of a booth, cure area and mixing area and include emissions from purge and cleanup. A robot operates only one of the two HVLP spray guns at any given time. The particulate emissions are controlled by use of a water curtain.	07-19-2013	FGPAINTLINES, FGRULE632

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EUIPA
EMISSION UNIT CONDITIONS**

DESCRIPTION

Use of IPA squeeze bottles at various locations throughout the facility

Flexible Group: NA

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	26.4 tpy	12-month rolling time period as determined at the end of each calendar month	EUIPA	SC VI.2 SC VI.3	R 336.1702(a)

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste IPA materials and shall store them in closed containers. The permittee shall dispose of all waste IPA materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing IPA materials, in a manner to minimize the generation of fugitive emissions. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any IPA material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205, R 336.1225, R 336.1702)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**

2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each IPA material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702).**
3. The permittee shall keep the following information on a calendar month basis for EUIPA:
 - a) Gallons (with water) of each IPA material used and reclaimed.
 - b) VOC content (minus water and with water) of each IPA material as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1702(a))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

1. The exhaust gases from EUIPA shall be released only into the general in-plant environment. **(R 336.1225, 40 CFR 52.21(c) & (d))**

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

- ¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SPECIAL CONDITIONS

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGSOLDER	11 soldering stations	EUSOL1, EUSOL2, EUSOL3, EUSOL4, EURFSOL1, EURFSOL2, EURFSOL3, EURFSOL4, EURFSOL5, EURFSOL6, EURFSOL7
FGTOLUENE	Toluene dip tank, toluene squeeze bottles, and toluene in elepcoat	EUTOLTK, EUTOLSQZBOTTLES, EUTOLELEPCOAT
FGELEPCOAT	17 Elepcoat units	EUELEPCOAT1, EUELEPCOAT2, EUELEPCOAT3, EUELEPCOAT4, EUELEPCOAT5, EUELEPCOAT6, EUELEPCOAT7, EUELEPCOAT8, EUELEPCOAT9, EUELEPCOAT10, EUELEPCOAT11, EUELEPCOAT12, EUELEPCOAT13, EUELEPCOAT14, EUELEPCOAT15, EUELEPCOAT16, EUELEPCOAT17
FGPAINTLINES	Two Paint lines used for coating interior plastic automotive parts and mixing area and include emissions from purge and cleanup	EUPAINTLINE1, EUPAINTLINE2
FGRULE632	All plastic parts coating lines within the stationary source including equipment covered by other permits, grandfathered equipment, and exempt equipment pursuant to Rule 632(15)(a).	EUPAINTLINE1, EUPAINTLINE2

**FGSOLDER
EMISSION UNIT CONDITIONS**

DESCRIPTION

11 soldering stations.

Emission Units: EUSOL1, EUSOL2, EUSOL3, EUSOL4, EURFSOL1, EURFSOL2, EURFSOL3, EURFSOL4, EURFSOL5, EURFSOL6, EURFSOL7

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	12.1 tpy	12-month rolling time period as determined at the end of each calendar month	FGSOLDER	SC VI.2 SC VI.3	R 336.1702(a)
2. di(ethylene glycol) hexyl ether (CAS No. 112-59-4) ¹	0.82 tpy	12-month rolling time period as determined at the end of each calendar month	FGSOLDER	SC VI.2 SC VI.4	R 336.1225(1)
3. terpineol (CAS No. 8000-41-7) ¹	0.07 tpy	12-month rolling time period as determined at the end of each calendar month	FGSOLDER	SC VI.2 SC VI.4	R 336.1225(1)
4. maleic acid, dibutyl ester (CAS No. 105-76-0) ¹	0.07 tpy	12-month rolling time period as determined at the end of each calendar month	FGSOLDER	SC VI.2 SC VI.4	R 336.1225(1)
5. thixotropic agent (CAS No. 8001-78-3) ¹	6.4 lb/month	12-month rolling time period as determined at the end of each calendar month	FGSOLDER	SC VI.2 SC VI.4	R 336.1225(1)

II. MATERIAL LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC content of solder enhancing material	6.9 lb/gal (minus water) ^a as applied	Instantaneous	Each emission unit of FGSOLDER	SC V.1	R 336.1702(a)

^a The phrase "minus water" shall also include compounds which are used as organic solvents, and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste solder and solder enhancing materials and shall store them in closed containers. The permittee shall dispose of all waste solder enhancing materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing waste solder and solder enhancing materials, in a manner to minimize the generation of fugitive emissions. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any solder enhancing material, as applied, and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205, R 336.1225, R 336.1702)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each solder enhancing material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a calendar month basis for FGSOLDER:
 - a) Gallons or pounds (with water) of each solder enhancing material used and reclaimed.
 - b) VOC content (minus water and with water) of each solder enhancing material as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1225(1), R 336.1702(a))**

4. The permittee shall keep the following information on a calendar month basis for FGSOLDER:
 - a) Gallons (with water) of each di(ethylene glycol) hexyl ether (CAS No. 112-59-4), terpineol (CAS No. 8000-41-7); maleic acid, dibutyl ester (CAS No. 105-76-0), and thixotropic agent (CAS No. 8001-78-3) (identified as "TAC_{Annual}") containing material used.
 - b) Where applicable, gallons (with water) of each TAC_{Annual} containing material reclaimed.
 - c) Each TAC_{Annual} content (with water) in pounds per gallon of each material used.
 - d) Each TAC_{Annual} mass emission calculations determining the monthly emission rate in pounds/tons per calendar month.
 - e) Each TAC_{Annual} mass emission calculations determining the annual emission rate in pounds/tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1225(1))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVSOL (Solder Station 1)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
2. SVSOL2 (Solder Station 2)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
3. SVSOL3 (Solder Station 3)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
4. SVSOL6 (Solder Station 4)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
5. SVNXT1 (Reflow Stack NXT1 Alpha Telecore 63Sn/37Pb)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
6. SVNXT2 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
7. SVNXT3&4 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
8. SVNXT3&6 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
9. SVNXT5 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
10. SVNXT7 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)
11. SVNXT3 (Soldering Station – Reflow)	12	26	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FGTOLUENE EMISSION UNIT CONDITIONS

DESCRIPTION

Toluene dip tank, toluene squeeze bottles, and toluene in elepcoat.

Emission Units: EUTOLTK, EUTOLSQZBOTTLES, EUTOLELEPCOAT

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	6.6 tpy	12-month rolling time period as determined at the end of each calendar month	FGTOLUENE	SC VI.2 SC VI.3	R 336.1702(a)

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste toluene and toluene containing materials and shall store them in closed containers. The permittee shall dispose of all waste stencil materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing toluene and toluene containing materials, including coatings, reducers, solvents, and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any toluene material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205, R 336.1225, R 336.1702)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each toluene material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702).**
3. The permittee shall keep the following information on a calendar month basis for FGTOLUENE:
 - a) Gallons (with water) of each toluene material used and reclaimed.
 - b) VOC content (minus water and with water) of each toluene material as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1702(a))**

VII. REPORTING

1. Within 30 days after completion of the installation, construction, reconstruction, relocation or modification of each emission unit of EUTOLTK portion of FGTOLUENE authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than the commencement of trial operation of EUTOLTK portion of FGTOLUENE. **(R 336.1201(7)(a)).**

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVTOLTK (Toluene Dip Tank Stack)	18	29	R 336.1225, 40 CFR 52.21(c) & (d)

2. The exhaust gases from toluene squeeze bottles operations and toluene solvent in elepcoat operation of FGTOLUENE shall be released only into the general in-plant environment. **(R 336.1225, 40 CFR 52.21(c) & (d))**

IX. OTHER REQUIREMENT(S)

NA

**FGELEPCOAT
 EMISSION UNIT CONDITIONS**

DESCRIPTION

17 Elepcoat units.

Emission Units: NA

EUELEPCOAT1, EUELEPCOAT2, EUELEPCOAT3, EUELEPCOAT4, EUELEPCOAT5, EUELEPCOAT6, EUELEPCOAT7, EUELEPCOAT8, EUELEPCOAT9, EUELEPCOAT10, EUELEPCOAT11, EUELEPCOAT12, EUELEPCOAT13, EUELEPCOAT14, EUELEPCOAT15, EUELEPCOAT16, EUELEPCOAT17

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	6.8 tpy	12-month rolling time period as determined at the end of each calendar month	FGELPCOAT	SC VI.2 SC VI.3	R 336.1702(a)

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste elepcoat materials and shall store them in closed containers. The permittee shall dispose of all waste elepcoat materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing elepcoat materials, including coatings, reducers, solvents, and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any elepcoat material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer’s formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205, R 336.1225, R 336.1702)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each elepcoat material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702).**
3. The permittee shall keep the following information on a calendar month basis for FGELEPCOAT:
 - a) Gallons (with water) of each elepcoat material including clean-up solvents used and reclaimed.
 - b) VOC content (minus water and with water) of each elepcoat material as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1702(a))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

1. The exhaust gases from FGELEPCOAT shall be released only into the general in-plant environment. **(R 336.1225, 40 CFR 52.21(c) & (d))**

IX. OTHER REQUIREMENT(S)

NA

FGPAINTLINES FLEXIBLE GROUP CONDITIONS

DESCRIPTION

Two Paint lines used for coating plastic automotive parts and include emissions from purge and cleanup.

Emission Unit: EUPAINTLINE1, EUPAINTLINE2.

POLLUTION CONTROL EQUIPMENT

Water curtain to control particulate emissions

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC (coating only)	17.18 tpy	12-month rolling time period as determined at the end of each calendar month	FGPAINTLINES	SC VI.2	R 336.1702(d)
2. VOC (purge and cleanup)	7.02 tpy	12-month rolling time period as determined at the end of each calendar month	FGPAINTLINES	SC VI.3	R 336.1702(d)

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste coatings, thinners, thickeners, and purge materials and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1702(a))**
2. The permittee shall handle all VOC/HAP containing materials, including coatings, reducers, solvents, and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1205(3), R 336.1224, R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not operate FGPAINTLINES unless the water curtain is installed, maintained, and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1910)**
2. The permittee shall equip and maintain FGPAINTLINES with HVLP applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content and density of any coating and purge solvent, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702, R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1702(d))**
2. The permittee shall keep the following information for coatings on a monthly basis for FGPAINTLINES:
 - a) Gallons (with water) of each coating used.
 - b) VOC content (with water) of each coating as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(d))**

3. The permittee shall keep the following information on a monthly basis for the use of purge and clean-up solvents associated with FGPAINTLINES:
 - a) Gallons of each solvent used, reclaimed, or manifested and shipped off-site for disposal.
 - b) VOC content, in pounds per gallon, of each solvent used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-PAINTLINE1 (for EUPAINTLINE1)	24	37	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-PAINTLINE2 (for EUPAINTLINE2)	24	37	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENT(S)

NA

**FGRULE632
 FLEXIBLE GROUP CONDITIONS**

DESCRIPTION

All plastic parts coating lines within the stationary source including equipment covered by other permits, grandfathered equipment, and exempt equipment pursuant to Rule 632(15)(a).

Emission Units: EUPAINTLINE1, EUPAINTLINE2

POLLUTION CONTROL EQUIPMENT

Exhaust filters to control particulate matter

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC*	Less than 30.0 tpy	12-month rolling time period as determined at the end of each calendar month	All plastic parts coating lines within the stationary source including equipment covered by other permits, grandfathered equipment, and exempt equipment pursuant to Rule 632(15)(a).	SC VI.2, SC VI.3 SC VI.4	R 336.1702(d)
* Excludes purging and project cleanup					

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content, and density of any coating used to coat plastic parts, as applied, and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702(d))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1702(d))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each coating and reducer including the weight percent of each component. The data may consist of Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(d))**
4. The permittee shall keep the following information on a calendar month basis for all plastic parts coating lines operating per the requirements of R 336.1632(15)(a) in FGRULE632:
 - a) Type of parts painted (plastic only).
 - b) Gallons or pounds of each VOC containing coating used.
 - c) VOC content, in pounds per gallon or pounds per pound, of each VOC containing coating used.
 - d) VOC emission calculations determining the monthly emission rate in tons per calendar month.
 - e) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month from the coating of plastic parts.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FGFACILITY CONDITIONS

DESCRIPTION

The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment, and exempt equipment.

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. Each Individual HAP	Less than 9.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)
3. VOC	Less than 90.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC II.1 SC VI.2 SC VI.4	R 336.1205(1)(a), R 336.1205(3)

II. MATERIAL LIMIT(S)

- The permittee shall not use VOC containing material (material) in excess of the limits specified in the following table based upon 12-month rolling time period as determined at the end of each calendar month: **(R 336.1205(1)(a))**

Material Usage Group	Maximum VOC Content (in pounds per gallon)	Material Usage Limit (Gallons per 12-month rolling time period)	VOC Emissions in tpy
EUIPA	6.6	8,000	26.4
FGSOLDER	6.9	3,500	12.1
FGTOLUENE	7.3	1,800	6.6
FGELEPCOAT	6.8	2,000	6.8
FGPAINTLINES coatings, as-applied	6.0	5,693	17.1
FGPAINTLINES purge solvents	6.7	1,200	4.0
Total			73.0

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**
2. The permittee shall determine the VOC content, water content, and density of any coating, as applied, and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205(3))**.

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall keep usage records to show compliance with the SC I.1, in a format acceptable to the AQD District Supervisor, indicating the types and amounts (in gallons) of materials used on a calendar month and 12-month rolling time period as determined at the end of each calendar month basis. The records must indicate the name of material, usage, and its VOC content. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1205(1)(a))**
3. The permittee shall keep the following information on a calendar month basis for FGFACILITY:
 - a) Gallons or pounds of each HAP containing material used.
 - b) Where applicable, gallons or pounds of each HAP containing material reclaimed or manifested and shipped off-site for disposal.
 - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
 - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
 - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

4. The permittee shall keep the following information on a calendar month basis for FGFACILITY:
 - a) Gallons or pounds of each VOC containing material used.
 - b) Where applicable, gallons or pounds of each VOC containing material reclaimed or manifested and shipped off-site for disposal.
 - c) VOC content, in pounds per gallon or pounds per pound, of each VOC containing material used.
 - d) VOC emission calculations determining the monthly emission rate in tons per calendar month.
 - e) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).