

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

July 13, 2012

PERMIT TO INSTALL
74-12

ISSUED TO
Sargent Sand Co.

LOCATED AT
7690 M-116
Ludington, Michigan

IN THE COUNTY OF
Mason

STATE REGISTRATION NUMBER
P0352

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

May 21, 2012

DATE PERMIT TO INSTALL APPROVED:

July 13, 2012

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EUSANDDRYER	6
Special Conditions for EUSANDPROCESS	9
Flexible Group Summary Table	11
Special Conditions for FGOUTSIDEOPS	11
Appendix A.....	13

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
CO ₂ e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
GHGs	Greenhouse Gases	kW	Kilowatt
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfuction Abatement Plan	NO _x	Oxides of Nitrogen
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter
MSDS	Material Safety Data Sheet	PM10	PM less than 10 microns diameter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM less than 2.5 microns diameter
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition	SO ₂	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUSANDDRYER	A 36 MMBtu/hr natural gas fired fluidized bed sand dryer rated at 200 tons of sand per hour and controlled by a baghouse dust collector.	
EUSANDPROCESS	<p>Dry sand handling process consisting of equipment used for screening, classifying, storing, and loading of finished sand. The dry sand handling process is completely enclosed within a building with dry dust control.</p> <p>Sand processing equipment consisting of hoppers, conveyors, elevators, screens, bins, storage silos, etc, used for material handling, sorting/blending of the sand into various product types, truck loading and bagging operations. Process equipment will minimize emissions by lowering drop heights, conveyor covers, enclosures, and/or be operated within a building.</p>	
EUTRUCKTRAFFIC	Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area.	FGOUTSIDEOPS
EUOFFSPECSTORAGE	Waste sand stored in a three-sided bunker.	FGOUTSIDEOPS
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.		

The following conditions apply to: EUSANDDRYER

DESCRIPTION: A 36 MMBtu/hr natural gas fired fluidized bed sand dryer rated at 200 tons of sand per hour

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Baghouse dust collector

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. PM	0.025 gr/dscf	Test Protocol*	EUSANDDRYER	SC V.1	R 336.1331(1)(c), 40 CFR 60.732
2. PM10	1.1 pph	Test Protocol*	EUSANDDRYER	GC 13	R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d)
3. PM2.5	1.1 pph	Test Protocol*	EUSANDDRYER	GC 13	R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d)

*Test Protocol shall specify averaging time

4. Visible emissions from EUSANDDRYER shall not exceed a six-minute average of 10 percent opacity. (R 336.1301, R 336.1331, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d), 40 CFR 60.732)

II. MATERIAL LIMITS

- The permittee shall not process more than 200 tons of sand product per hour through EUSANDDRYER based on a daily average, which shall be determined by dividing the daily sand production by the daily operating hours. (R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))
- The permittee shall burn only natural gas in EUSANDDRYER. (R 336.1205, R 336.1225, R 336.1702, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))

III. PROCESS/OPERATIONAL RESTRICTIONS

- The permittee shall not operate EUSANDDRYER unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the EUSANDDRYER baghouse dust collector, has been submitted prior to commencement of operation, and is implemented and maintained. If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. (R 336.1331, R 336.1910, R 336.1911, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any portion of EUSANDDRYER unless the baghouse dust collector is installed, maintained and operated in a satisfactory manner. **(R 336.1205, R 336.1331, R 336.1910, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))**
2. The permittee shall install and maintain a belt scale on the dryer belt feeder portion of EUSANDDRYER which continuously shows the hourly throughput rate for the feeder. **(R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Within 60 days after achieving the maximum production rate, but not later than 180 days after commencement of initial startup, the permittee shall verify PM emission rates from stack emissions from EUSANDDRYER, as required by federal Standards of Performance for New Stationary Sources, by testing at owner's expense, in accordance with 40 CFR Part 60 Subparts A and UUU. The permittee shall notify the AQD District Supervisor in writing within 15 days of the date of commencement of trial operation in accordance with 40 CFR 60.7(a)(3). Stack testing procedures and the location of stack testing ports shall be in accordance with the applicable federal Reference Methods, 40 CFR Part 60 Appendix A. No less than 60 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing. Verification of emission rates includes the submittal of a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(40 CFR Part 60 Subparts A & UUU)**
2. Within 60 days after achieving the maximum production rate, but not later than 180 days after commencement of initial startup, the permittee shall evaluate visible emissions from EUSANDDRYER, as required by federal Standards of Performance for New Stationary Sources, at owner's expense, in accordance 40 CFR Part 60 Subparts A and UUU. Visible emission observation procedures must have prior approval by the AQD Technical Programs Unit and District Office. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD Technical Programs Unit and District Office within 60 days following the last date of the evaluation. **(R 336.1301, 40 CFR Part 60 Subparts A & UUU)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))**
2. The permittee shall keep average daily (from the dryer belt feeder scale) records of the amount of sand processed through EUSANDDRYER. The permittee shall keep records of the amount of material processed on file and make them available to the Department upon request. **(R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))**
3. The permittee shall verify the presence of visible emissions by taking three six-minute visible emission readings from EUSANDDRYER a minimum of once per calendar day. A certified reader shall take each visible emission reading during routine operating conditions. The certified reader shall determine the opacity using Federal Reference Test Method 9 (40 CFR Part 60, Appendix A). If the results of the Federal Reference Test Method 9 visible emission observation indicate a violation of the opacity standard specified in SC I.4, the permittee shall immediately initiate corrective actions. **(R 336.1301, R 336.1303, 40 CFR 60.734(b))**
4. The permittee shall keep, in a satisfactory manner, records of all visible emission readings from EUSANDDRYER. At a minimum, records shall include the date, time, name of observer/reader, whether

the reader is certified, and status of visible emissions. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1301, R 336.1303, 40 CFR 60.734(b))**

VII. REPORTING

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EUSANDDRYER. **(R 336.1201(7)(a))**
2. The permittee shall provide written notification of construction and operation to comply with the federal Standards of Performance for New Stationary Sources, 40 CFR 60.7. The permittee shall submit this notification to the AQD District Supervisor within the time frames specified in 40 CFR 60.7. **(40 CFR 60.7)**
3. The permittee shall submit all required semiannual exceedance reports to the AQD District Supervisor in an acceptable format within 30 days following the end of the timeframe in which the data were collected. **(40 CFR Part 60 Subparts A & UUU, 40 CFR 60.735(c))**

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stack listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVSANDDRYER	56	40	R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENTS

1. The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and UUU, as they apply to EUSANDDRYER. **(40 CFR Part 60 Subparts A & UUU)**

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUSANDPROCESS

DESCRIPTION: Dry sand handling process consisting of equipment used for screening, classifying, storing, and loading of finished sand.

Flexible Group ID:

POLLUTION CONTROL EQUIPMENT: The dry sand handling process is completely enclosed within a building with dry dust control.

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. PM	0.004 lbs per 1,000 lbs exhaust gases	Test Protocol*	EUSANDPROCESS	GC 13	R 336.1331(1)(c)
2. PM10	0.94 pph	Test Protocol*	EUSANDPROCESS	GC 13	R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c)&(d)
3. PM2.5	0.94 pph	Test Protocol*	EUSANDPROCESS	GC 13	R 336.1205, R 336.2803, R 336.2804, 40 CFR 52.21 (c)&(d)

*Test Protocol shall specify averaging time

4. Visible emissions from EUSANDPROCESS shall not exceed a six-minute average of 10 percent opacity. (R 336.1301, R 336.1331, R 336.1901, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any portion of EUSANDPROCESS unless the dry dust control is installed, maintained and operated in a satisfactory manner. (R 336.1901, R 336.1910, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d))**
2. The permittee shall perform and record the results of a six-minute non-certified visible emission observation from EUSANDPROCESS a minimum of once per calendar day. The visible emission check shall verify the presence of visible emissions and need not follow the procedures specified in Federal Reference Test Method 9. Each visible emission observation shall be taken during routine operating conditions. If visible emissions are observed, the permittee shall immediately implement the following procedures. **(R 336.1301, R 336.1303, R 336.1910, R 336.2803, R 336.2804, 40 CFR 52.21 Subparts (c) & (d))**
 - a) If visible emissions have been observed during the six-minute non-certified visible emission check, the permittee shall perform and record the results of a 15 minute Federal Reference Test Method 9 visible emission observation.
 - b) If the results of the Federal Reference Test Method 9 visible emission observation indicate a violation of the opacity standard, the permittee shall immediately initiate corrective actions and document the corrective actions taken.
3. The permittee shall keep, in a satisfactory manner, records of all visible emission observations from EUSANDPROCESS. At a minimum, records shall include the date, time, name of observer/reader, whether the reader is certified, and status of visible emissions. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1301, R 336.1303, R 336.2803, R 336.2804, 40 CFR 52.21 Subparts (c) & (d))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stack listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVSANDPROCESS	46	40	R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d)

IX. OTHER REQUIREMENTS

1. Prior to start-up, the permittee shall provide a final list of and label all EUSANDPROCESS equipment using the company-provided ID Numbers, according to a method acceptable to the AQD District Supervisor. Labels shall be in a conspicuous location on the equipment. Within seven days of completing the labeling, the permittee shall notify the AQD District Supervisor, in writing, as to the date the labeling was completed. **(R 336.1201)**

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGOUTSIDEOPS	Outside material handling operations: Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area. Waste sand stored in a three-sided bunker.	EUTRUCKTRAFFIC, EUOFFSPECSTORAGE

The following conditions apply to: FGOUTSIDEOPS

DESCRIPTION: Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area. Waste sand stored in a three-sided bunker.

Emission Units: EUTRUCKTRAFFIC, EUOFFSPECSTORAGE

POLLUTION CONTROL EQUIPMENT: Fugitive Dust Control Plan

I. EMISSION LIMITS

1. Visible emissions from all wheel loaders and all truck traffic, operated in conjunction with EUTRUCKTRAFFIC, shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))**
2. Visible emissions from the material storage pile maintained under EUOFFSPECSTORAGE, shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21(c) & (d))**

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate FGOUTSIDEOPS unless the fugitive dust control plan for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix A (or a revised fugitive dust control plan as approved by the AQD District Supervisor) has been implemented and is maintained. **(R 336.1371, R 336.1372, Act 451 324.5524)**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

APPENDIX A Fugitive Dust Control Plan

I. Site Roadways / Plant Yard

- A. The dust on the site roadways and the plant yard shall be controlled by applications of water, calcium chloride or other acceptable and approved fugitive dust control compounds. Applications of dust suppressants shall be done as often as necessary to meet all applicable emission limits. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.
- B. All paved roadways and the plant yards shall be swept as needed between applications.
- C. Any material spillage on roads shall be cleaned up immediately.

II. Plant

The drop distance at each transfer point shall be reduced to the minimum the equipment can achieve.

III. Storage Piles

- A. Stockpiling of all sand shall be performed to minimize drop distance and control potential dust problems.
- B. Stockpiles shall be watered on an as needed basis in order to meet the opacity limit of 5 percent. Equipment to apply water or dust suppressant shall be available at the site or on call for use at the site within a given operating day. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.

IV. Truck Traffic

On-site vehicles shall be loaded to prevent their contents from dropping, leaking, blowing or otherwise escaping. This shall be accomplished by loading so that no part of the load shall come in contact within 6 inches of the top of any side board, side panel or tailgate. Otherwise, the truck shall be tarped.

V. AQD/MDEQ Inspection

The provisions and procedures of this plan are subject to adjustment by written notification from the AQD if, following an inspection, the AQD finds the fugitive dust requirements and/or permitted emission limits are not being met.