

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

December 18, 2014

**PERMIT TO INSTALL
156-14**

ISSUED TO
Wilkie Brothers Conveyors Inc.

LOCATED AT
1765 Michigan Avenue
Marysville, Michigan

IN THE COUNTY OF
Saint Clair

STATE REGISTRATION NUMBER
N3337

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: November 18, 2014	
DATE PERMIT TO INSTALL APPROVED: December 18, 2014	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EU-BURNOFF4710	6
Flexible Group Summary Table	8
Special Conditions for FG-BURNOFF	9

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
CO ₂ e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H ₂ S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
GHGs	Greenhouse Gases	kW	Kilowatt
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfunction Abatement Plan	NO _x	Oxides of Nitrogen
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter
MSDS	Material Safety Data Sheet	PM10	PM with aerodynamic diameter ≤10 microns
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM with aerodynamic diameter ≤ 2.5 microns
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition	SO ₂	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Installation Date / Modification Date	Flexible Group ID
EU-BURNOFF4710	A batch type natural gas-fired burn-off oven (Blu-surf Model 6610) with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.	04-07-1992	N/A
EU-BURNOFF4730	A batch type natural gas-fired burn-off oven (Blu-surf Model 6606) with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.	03-18-1994	FG-BURNOFF
EU-BURNOFF4740	A batch type natural gas-fired burn-off oven (Pollution Control Products Model 150-943) with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.	02-15-1998	FG-BURNOFF
EU-BURNOFF4750	A batch type natural gas-fired burn-off oven (Pollution Control Products Model 150-1892) with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.	02-15-1998	FG-BURNOFF
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.			

The following conditions apply to: EU-BURNOFF4710

DESCRIPTION: A batch type natural gas-fired burn-off oven (Blu-surf Model 6610) with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.

Flexible Group ID: N/A

POLLUTION CONTROL EQUIPMENT: Secondary Combustion Chamber (Afterburner)

I. EMISSION LIMITS

N/A

II. MATERIAL LIMITS

1. The permittee shall not substitute any material or fuel which would result in an appreciable change in the quality or any appreciable increase in the quantity of the emission of an air contaminant without prior notification to and approval by the AQD. **(R 336.1224, R 336.1225, R 336.1301)**

III. PROCESS/OPERATIONAL RESTRICTIONS

N/A

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate EU-BURNOFF4710 unless a secondary chamber or afterburner is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of the secondary chamber or afterburner includes maintaining a minimum temperature of 1400°F. **(R 336.1224, R 336.1225, R 336.1301, R 336.1910)**
2. The permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to monitor the temperature in the burn-off oven secondary chamber or afterburner. **(R 336.1224, R 336.1225, R 336.1301, R 336.1910)**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

N/A

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required records in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1224, R 336.1225, R 336.1301)**
2. The permittee shall keep, in a satisfactory manner for each period of operation, temperature data records for the secondary chamber or afterburner in EU-BURNOFF4710. All records shall be kept on file and made available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1301)**

3. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material (cured coating, oil or grease) processed in EU-BURNOFF4710, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1224, R 336.1225)**

VII. REPORTING

N/A

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-BURNOFF4710	12	35	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENTS

N/A

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FG-BURNOFF	Three batch type natural gas-fired burn-off ovens, each with a secondary chamber used to remove grease from chains by thermal decomposition in a primary chamber.	EU-BURNOFF4730 EU-BURNOFF4740 EU-BURNOFF4750

The following conditions apply to: FG-BURNOFF

DESCRIPTION: Three batch type natural gas-fired burn-off ovens used to remove grease from chains by thermal decomposition in a primary chamber.

Emission Units: EU-BURNOFF4730, EU-BURNOFF4740, EU-BURNOFF4750

POLLUTION CONTROL EQUIPMENT: Each equipped with a Secondary Combustion Chamber (Afterburner)

I. EMISSION LIMITS

1. There shall be no visible emissions from FG-BURNOFF. (R 336.1225, R 336.1910)

II. MATERIAL LIMITS

1. The permittee shall burn only natural gas in FG-BURNOFF. (R 336.1205(1)(a))
2. The permittee shall not process any material in FG-BURNOFF other than cured paints, oil or grease on metal parts, chains, racks and/or hangers. (R 336.1224, R 336.1225)

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not use FG-BURNOFF for the thermal destruction or removal of rubber, plastics, uncured paints, or any other materials containing sulfur or halogens (chlorine, fluorine, bromine, etc.) such as plastisol, polyvinyl chloride (PVC), or Teflon. (R 336.1224, R 336.1225)
2. The permittee shall not load any transformer cores, which may be contaminated with PCB-containing dielectric fluid, wire or parts coated with lead or rubber, or any waste materials such as paint sludge or waste powder coatings into FG-BURNOFF. (R 336.1224, R 336.1225)

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any oven in FG-BURNOFF unless that oven has a secondary chamber or afterburner is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of the secondary chamber or afterburner includes maintaining a minimum temperature of 1400°F and a minimum retention time of 0.5 seconds. (R 336.1224, R 336.1225, R 336.1301, R 336.1910)
2. The permittee shall not operate any oven in FG-BURNOFF unless that oven has an automatic temperature control system for the primary chamber and secondary chamber or afterburner is installed, maintained, and operated in a satisfactory manner. (R 336.1224, R 336.1225, R 336.1301, R 336.1910)
3. The permittee shall not operate any oven in FG-BURNOFF unless that oven has an interlock system that shuts down the primary chamber burner when the secondary chamber or afterburner is not operating properly, is installed, maintained and operated in a satisfactory manner. (R 336.1224, R 336.1225, R 336.1301, R 336.1910)
4. For each oven in FG-BURNOFF, the permittee shall install, calibrate, maintain and operate in a satisfactory manner a device to continuously monitor the temperature in the burn-off oven secondary chamber or afterburner and record the temperature at least once every 15 minutes. (R 336.1224, R 336.1225, R 336.1301, R 336.1910)

V. TESTING/SAMPLING

N/A

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required records in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1224, R 336.1225, R 336.1301)**
2. The permittee shall continuously monitor the temperature in the burn-off oven secondary chamber or afterburner and record the temperature at least once every 15 minutes during operation of each oven in FG-BURNOFF. **(R 336.1224, R 336.1225, R 336.1301, R 336.1910)**
3. The permittee shall calibrate the thermocouples associated with the primary and secondary chambers at least once per year for each oven in FG-BURNOFF. **(R 336.1201(3), R 336.1224, R 336.1225)**
4. The permittee shall keep, in a satisfactory manner, temperature data records of the secondary chamber or afterburner for each oven in FG-BURNOFF. All records shall be kept on file and made available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1301, R 336.1910)**
5. The permittee shall keep, in a satisfactory manner, records of the date, duration, and description of any malfunction of the control equipment, any maintenance performed and any testing results for FG-BURNOFF. All records shall be kept on file and made available to the Department upon request. **(R 336.1910, R 336.1912)**
6. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material (cured coating, oil or grease) processed in FG-BURNOFF, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both. All records shall be kept on file and made available to the Department upon request. **(R 336.1224, R 336.1225)**
7. The permittee shall maintain current information from the manufacturer that FG-BURNOFF is equipped with a secondary chamber or afterburner, an automatic temperature control system for the primary chamber and secondary chamber or afterburner, and an interlock system that shuts down the primary chamber burner when the secondary chamber or afterburner is not operating properly. All records shall be kept on file and made available to the Department upon request. **(R 336.1224, R 336.1225)**

VII. REPORTING

N/A

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-BURNOFF4730	8	37	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-BURNOFF4740	8	30	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-BURNOFF4750	8	30	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENTS

N/A

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).