

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY  
AIR QUALITY DIVISION**

March 9, 2015

**PERMIT TO INSTALL**  
201-14

**ISSUED TO**  
Padnos Manufacturing Inc.

**LOCATED AT**  
3495 Viaduct Southwest  
Grandville, Michigan

**IN THE COUNTY OF**  
Kent

**STATE REGISTRATION NUMBER**  
P0569

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>January 12, 2015</b>	
DATE PERMIT TO INSTALL APPROVED: <b>March 9, 2015</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

## PERMIT TO INSTALL

### Table of Contents

<b>Section</b>	<b>Page</b>
Alphabetical Listing of Common Abbreviations / Acronyms .....	2
General Conditions .....	3
Special Conditions .....	5
Emission Unit Summary Table.....	5
Special Conditions for EU-WIRECHOP .....	6
Appendix A: Control of Fugitive Emissions Plant Roadways.....	8

### Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	BTU	British Thermal Unit
BACT	Best Available Control Technology	°C	Degrees Celsius
CAA	Clean Air Act	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	dscf	Dry standard cubic foot
CFR	Code of Federal Regulations	dscm	Dry standard cubic meter
CO <sub>2</sub> e	Carbon Dioxide Equivalent	°F	Degrees Fahrenheit
COM	Continuous Opacity Monitoring	gr	Grains
EPA	Environmental Protection Agency	Hg	Mercury
EU	Emission Unit	hr	Hour
FG	Flexible Group	H <sub>2</sub> S	Hydrogen Sulfide
GACS	Gallon of Applied Coating Solids	hp	Horsepower
GC	General Condition	lb	Pound
GHGs	Greenhouse Gases	kW	Kilowatt
HAP	Hazardous Air Pollutant	m	Meter
HVLP	High Volume Low Pressure *	mg	Milligram
ID	Identification	mm	Millimeter
LAER	Lowest Achievable Emission Rate	MM	Million
MACT	Maximum Achievable Control Technology	MW	Megawatts
MAERS	Michigan Air Emissions Reporting System	ng	Nanogram
MAP	Malfunction Abatement Plan	NO <sub>x</sub>	Oxides of Nitrogen
MDEQ	Michigan Department of Environmental Quality (Department)	PM	Particulate Matter
MSDS	Material Safety Data Sheet	PM10	PM with aerodynamic diameter ≤10 microns
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM2.5	PM with aerodynamic diameter ≤ 2.5 microns
NSPS	New Source Performance Standards	pph	Pounds per hour
NSR	New Source Review	ppm	Parts per million
PS	Performance Specification	ppmv	Parts per million by volume
PSD	Prevention of Significant Deterioration	ppmw	Parts per million by weight
PTE	Permanent Total Enclosure	psia	Pounds per square inch absolute
PTI	Permit to Install	psig	Pounds per square inch gauge
RACT	Reasonably Available Control Technology	scf	Standard cubic feet
ROP	Renewable Operating Permit	sec	Seconds
SC	Special Condition	SO <sub>2</sub>	Sulfur Dioxide
SCR	Selective Catalytic Reduction	THC	Total Hydrocarbons
SRN	State Registration Number	tpy	Tons per year
TAC	Toxic Air Contaminant	µg	Microgram
TEQ	Toxicity Equivalence Quotient	VOC	Volatile Organic Compound
VE	Visible Emissions	yr	Year

\* For High Volume Low Pressure (HVLP) applicators, the pressure measured at the HVLP gun air cap shall not exceed ten (10) pounds per square inch gauge (psig).

### GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
  
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**
  
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

**SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Process Equipment &amp; Control Devices)</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU-WIRECHOP	Wire Chopping system for reclaiming copper from scrap wire. Emission unit includes a feed hopper, material shredder, screening system, granulators, internally vented cyclones and baghouse, material storage, and associated conveyors.	July 2014	NA
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.			

**The following conditions apply to: EU-WIRECHOP**

**DESCRIPTION:** Wire Chopping system for reclaiming copper from scrap wire. Emission unit includes a feed hopper, material shredder, screening system, granulators, internally vented cyclones and baghouse, material storage, and associated conveyors.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT:** Water suppression system for the feed hopper

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. PM	3.4 tpy*	12-month rolling time period as determined at the end of each calendar month	EU-WIRECHOP	SC VI.1	R 336.1331
2. PM10	1.4 tpy*	12-month rolling time period as determined at the end of each calendar month	EU-WIRECHOP	SC VI.1	40 CFR 52.21 Subparts (c) & (d)

\*Based upon emission factors of 0.04768 lb PM/ton scrap wire and 0.01950 lb PM10/ton scrap wire. These emission factors are based upon process parameters specified in the permit application with an allowable increase of less than 10% based on the potential to emit.

3. Visible emissions from EU-WIRECHOP shall not exceed a six-minute average of 20 percent opacity. **(R 336.1301, R 336.1331, R 336.1901, R 336.2802, 40 CFR 52.21)**

**II. MATERIAL LIMITS**

1. The permittee shall not process more than 131,400 tons of scrap wire in EU-WIRECHOP per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205, R 336.1225, 40 CFR 52.21, 40 CFR 52.21(c) & (d))**

**III. PROCESS/OPERATIONAL RESTRICTIONS**

1. The permittee shall not operate EU-WIRECHOP unless the fugitive emissions from the plant roadways are controlled as specified in Appendix A. **(R 336.1371, R 336.1372, R 336.1901)**
2. No later than 60 days after issuance of this permit, the permittee shall submit to the AQD District Supervisor, for review and approval, a fugitive dust control plan for the material storage and handling operations in EU-WIRECHOP. The permittee shall not operate EU-WIRECHOP after the date of submittal unless the fugitive dust control plan is implemented and maintained. **(R 336.1371, R 336.1372, R 336.1901, Act 451 324.5524)**

**IV. DESIGN/EQUIPMENT PARAMETERS**

1. No later than 45 days after issuance of this permit, the permittee shall not operate EU-WIRECHOP unless a water suppression system for the feed hopper is installed, maintained, and operated in a satisfactory manner, as needed. **(R 336.1205, R 336.1224, R 336.1225, R 336.1331, R 336.1901, R 336.1910, 40 CFR 52.21(c) and (d))**

**V. TESTING/SAMPLING**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall keep, in a satisfactory manner, monthly records of scrap wire processed in EU-WIRECHOP. The permittee shall keep all records on file for a period of at least five years and make them available to the Department upon request. **(R 336.1205(1)(a))**
2. The permittee shall not operate EU-WIRECHOP unless permittee performs a monthly non-certified visual opacity observation during operation. If opacity exceeds 20 percent as specified in SC I.3, the permittee shall take corrective action. The permittee shall keep records of all observations and corrective actions on file for a period of at least five years and make them available to the Department upon request. **(R 336.1371, R 336.1372, R 336.1901, Act 451 324.5524)**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

**Appendix A**  
**Control of Fugitive Emissions Plant Roadways**

**PURPOSE:** Management of fugitive emissions from on-site roadways

- a. No later than 60 days after issuance of this permit, the permittee shall submit to the AQD District Supervisor, for review and approval, a fugitive dust control plan including the control of the fugitive emissions from the plant roadways.
- b. Visible emissions from all cranes, loaders and truck traffic shall not exceed 20 percent opacity for the time period specified in the fugitive dust plan before corrective action is taken.
- c. During operation, the plant roads shall be controlled by the application of water, sweeping, vacuuming, or other acceptable dust control method that minimizes the introduction of the dust to the ambient air to control fugitive dust emissions and track-out dust. Applications of dust suppressants shall be done as often as necessary to meet all applicable emission limits. The dust control method shall be acceptable as determined by the District Supervisor.
- d. Any aggregate spillage on roads shall be removed immediately.
- e. The front-end loader operator shall be directed to avoid overfilling the bucket of the loader and the feed hoppers to prevent spillage, and to minimize the drop height of the material when loading the feed hoppers or transferring material to stockpiles.
- f. Records of dust control activities on travel surfaces and other surfaces where fugitive dust emissions occur shall be kept on file and made available to AQD staff upon request. The records will indicate the date, time, what was observed or the reason for the dust control activity (routine or other), and what action was taken.