

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

August 12, 2015

PERMIT TO INSTALL
207-14A

ISSUED TO
Otto Block Polyurethane Technologies, Inc.

LOCATED AT
2923 Technology Drive
Rochester Hills, Michigan

IN THE COUNTY OF
Oakland

STATE REGISTRATION NUMBER
P0583

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: July 14, 2015	
DATE PERMIT TO INSTALL APPROVED: August 12, 2015	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Flexible Group Summary Table	6
Special Conditions for FGPOLYFOAM	7
Special Conditions for FGFACILITY	11

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO ₂ e	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H ₂ S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO _x	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM10	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO ₂	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a. A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b. A visible emission limit specified by an applicable federal new source performance standard.
 - c. A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUPOLY1	Stationary 1: A reaction injection mold processing cell with manual spray application of mold release agents and paint coatings. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY2	Turntable #1: A reaction injection mold processing cell with manual spray application of mold release agents. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY3	Turntable #2: A reaction injection mold processing cell with manual spray application of mold release agents. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY4	Turntable #3: A reaction injection mold processing cell with manual spray application of mold release agents and paint coatings. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY5	Turntable #4: A reaction injection mold processing cell with manual spray application of mold release agents and paint coatings. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY6	Turntable #5: A reaction injection mold processing cell with manual spray application of mold release agents. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY7	Turntable #6: A reaction injection mold processing cell with manual spray application of mold release agents and paint coatings. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY8	Stationary 2: A reaction injection mold processing cell with manual spray application of mold release agents and paint coatings. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY9	Stationary 3: A reaction injection mold processing cell with manual spray application of mold release agents. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
EUPOLY10	Stationary Prototype: A reaction injection mold processing cell with manual spray application of mold release agents. Overspray is controlled by dry fabric filters.	FGPOLYFOAM
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.		

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGPOLYFOAM	A polyurethane foam molding process consisting of ten (10) reaction injection mold lines.	EUPOLY1, EUPOLY2, EUPOLY3, EUPOLY4, EUPOLY5, EUPOLY6, EUPOLY7, EUPOLY8, EUPOLY9, EUPOLY10
FGFACILITY	All process equipment source-wide including equipment covered by other permits, grandfathered equipment and exempt equipment.	NA

The following conditions apply to: FGPLYFOAM

DESCRIPTION: A polyurethane foam molding process consisting of ten (10) reaction injection mold lines.

Emission Units: EUPOLY1, EUPOLY2, EUPOLY3, EUPOLY4, EUPOLY5, EUPOLY6, EUPOLY7, EUPOLY8, EUPOLY9, EUPOLY10

POLLUTION CONTROL EQUIPMENT: Dry fabric filters

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC, acetone, and methyl acetate combined	89.7 tpy	12-month rolling time period as determined at the end of each calendar month	FGPOLYFOAM	SC VI.2, SC VI.3	R 336.1702(a)
2. VOC	50.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUPOLY6 within FGPLYFOAM	SC VI.2, SC VI.3	R 336.1702(a)
3. VOC	47.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUPOLY2, EUPOLY3, EUPOLY5 each within FGPLYFOAM	SC VI.2, SC VI.3	R 336.1702(a)
4. VOC	43.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUPOLY7, EUPOLY9, EUPOLY10 each within FGPLYFOAM	SC VI.2, SC VI.3	R 336.1702(a)
5. VOC	36.0 tpy	12-month rolling time period as determined at the end of each calendar month	EUPOLY1, EUPOLY8 each within FGPLYFOAM	SC VI.2, SC VI.3	R 336.1702(a)
6. Dimethylformamide (CAS No. 68-12-2)	58.5 lb/day	Calendar day	EUPOLY4 and EUPOLY8 combined within FGPLYFOAM	SC VI.2, SC VI.4	R 336.1225(1)
7. Dimethylformamide (CAS No. 68-12-2)	20.9 lb/day	Calendar day	EUPOLY1 and EUPOLY8 combined within FGPLYFOAM	SC VI.2, SC VI.4	R 336.1225(1)

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Non-automotive paint coating	6.5 lb VOC/gal (minus water) ^a as applied	Instantaneous	FGPOLYFOAM	SC V.1	R 336.1702(a)
2. Mold release	6.4 lb VOC/gal (minus water) ^a as applied	Instantaneous	FGPOLYFOAM	SC V.1	R 336.1702(a)

^a The phrase “minus water” shall also include compounds which are used as organic solvents and which are excluded from the definition of volatile organic compound. **(R 336.1602(4))**

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall capture all waste materials and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1702(a))**
2. The permittee shall dispose of spent filters in a manner which minimizes the introduction of air contaminants to the outer air. **(R 336.1224, R 336.1370)**
3. The permittee shall handle all VOC and / or HAP containing materials in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
4. The permittee shall only apply paint coatings on EUPOLY1, EUPOLY4, EUPOLY5, EUPOLY7, and EUPOLY8. EUPOLY1 and EUPOLY5 shall only apply paint coatings if EUPOLY4 and/or EUPOLY7 are not operating. **(R 336.1224, R 336.1225, R 336.1702(a))**
5. The permittee shall not apply any paint coatings containing dimethylformamide (CAS No. 68-12-2) on EUPOLY5 and EUPOLY7. **(R 336.1225(1))**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall equip and maintain FGPOLYFOAM with HVLP applicators or comparable technology with equivalent transfer efficiency. For HVLP applicators, the permittee shall keep test caps available for pressure testing. **(R 336.1702(a))**
2. The permittee shall not operate FGPOLYFOAM unless all respective exhaust filters are installed, maintained and operated in a satisfactory manner. **(R 336.1224, R 336.1301, R 336.1910)**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content, and density of any paint coating, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer’s formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1702(a))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of the paint coatings and mold releases, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a monthly basis for FGPOLYFOAM:
 - a. Gallons (with water) of each VOC, acetone, and methyl acetate containing material used.
 - b. Where applicable, gallons or pounds of each VOC, acetone, and methyl acetate containing material reclaimed.
 - c. VOC content (minus water and with water), acetone content (with water), and methyl acetate content (with water) in pounds per gallon of each material as applied.
 - d. VOC, acetone, and methyl acetate combined mass emission calculations determining the monthly emission rate in tons per calendar month for each emission unit and the flexible group.
 - e. VOC, acetone, and methyl acetate combined mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month for each emission unit and the flexible group.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1224, R 336.1702(a))**

4. The permittee shall keep the following information on a daily basis for EUPOLY1, EUPOLY4, and EUPOLY8 within FGPOLYFOAM:
 - a. Gallons (with water) of each dimethylformamide containing material used.
 - b. Where applicable, gallons (with water) of each dimethylformamide containing material reclaimed.
 - c. The dimethylformamide content (with water) in pounds per gallon of each material used.
 - d. Dimethylformamide mass emission calculations determining the daily emission rate in pounds per calendar day for EUPOLY4 (or EUPOLY1) and EUPOLY8 combined.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1225(1))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter/ Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVPOLY1	18	44	R 336.1225, 40 CFR 52.21(c) & (d)
2. SVPOLY2	26	44	R 336.1225, 40 CFR 52.21(c) & (d)
3. SVPOLY3	26	44	R 336.1225, 40 CFR 52.21(c) & (d)
4. SVPOLY4	38	44	R 336.1225, 40 CFR 52.21(c) & (d)
5. SVPOLY5	26	44	R 336.1225, 40 CFR 52.21(c) & (d)
6. SVPOLY6	26	44	R 336.1225, 40 CFR 52.21(c) & (d)
7. SVPOLY7	24	44	R 336.1225, 40 CFR 52.21(c) & (d)
8. SVPOLY8	18	44	R 336.1225, 40 CFR 52.21(c) & (d)
9. SVPOLY9	24	44	R 336.1225, 40 CFR 52.21(c) & (d)
10. SVPOLY10	24	44	R 336.1225, 40 CFR 52.21(c) & (d)

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply Source-Wide to: FGFACILITY

POLLUTION CONTROL EQUIPMENT: NA

I. EMISSION LIMITS

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. Each Individual HAP	Less than 9.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1205(3)
2. Aggregate HAPs	Less than 22.5 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1205(3)
3. VOC	Less than 90.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(3)

II. MATERIAL LIMITS

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC containing materials	258,500 lb/yr	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.3	R 336.1205(1)(a) and (3)

III. PROCESS/OPERATIONAL RESTRICTIONS

NA

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any materials as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
 - a. Gallons or pounds of each HAP containing material used.
 - b. Where applicable, gallons or pounds of each HAP containing material reclaimed.
 - c. HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
 - d. Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
 - e. Individual and aggregate HAP emission calculations determining the cumulative emission rate of each during the first 12-months and the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

3. The permittee shall keep the following information on a monthly basis for FGFACILITY:
 - a. Pounds of each VOC containing material used.
 - b. Where applicable, pounds of each VOC containing material reclaimed.
 - c. VOC content, in pounds per gallon or pounds per pound, of each VOC containing material used.
 - d. VOC emission calculations determining the monthly emission rate in tons per calendar month.
 - e. VOC emission calculations determining the cumulative emission rate during the first 12-months and the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(1)(a) and (3))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA