

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

APRIL 27, 2021

**PERMIT TO INSTALL**  
158-16B

**ISSUED TO**  
SILICONATURE CORPORATION

**LOCATED AT**  
4255 68<sup>TH</sup> STREET SE  
CALEDONIA, MICHIGAN 49316

**IN THE COUNTY OF**  
KENT

**STATE REGISTRATION NUMBER**  
P0742

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>April 22, 2021</b>	
DATE PERMIT TO INSTALL APPROVED: <b>April 27, 2021</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

**PERMIT TO INSTALL**

**Table of Contents**

COMMON ACRONYMS .....2  
POLLUTANT / MEASUREMENT ABBREVIATIONS.....3  
GENERAL CONDITIONS .....4  
EMISSION UNIT SPECIAL CONDITIONS.....6  
    EMISSION UNIT SUMMARY TABLE .....6  
    EU-CoatingLine-01.....7  
FLEXIBLE GROUP SPECIAL CONDITIONS..... 11  
    FLEXIBLE GROUP SUMMARY TABLE ..... 11  
    FG-Tanks..... 12  
FG-FACILITY CONDITIONS ..... 14

## COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

**EMISSION UNIT SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU-TolueneTank	13,000 gallon toluene storage tank located within a building	July 2019	FG-Tanks
EU-HeptaneTank	10,000 heptane storage tank located within a building	July 2019	FG-Tanks
EU-MEKTank	8,000 gallon MEK storage tank located within a building	July 2019	FG-Tanks
EU-IPATank	8,000 gallon IPA storage tank located within a building	July 2019	FG-Tanks
EU-MixTanks	Solvent and Resin Mix Tanks: Used to prepare as-applied silicone resin coatings	July 2019	FG-Tanks
EU-CoatingLine-01	A silicone plastic film coating line consisting of a corona treatment unit, coaters, eight (8) drying ovens, and eight (8) curing ovens. The source of heat for the drying units is a natural gas fired boiler. The coaters and eight (8) drying ovens are controlled by a non-fugitive enclosure (NFE) and a regenerative thermal oxidizer (RTO No. 1). The associated purge and cleanup solvents are included.	July 2019	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EU-CoatingLine-01**  
**FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

A silicone plastic film coating line consisting of a corona treatment unit, coaters, eight (8) drying ovens, and eight (8) curing ovens. The source of heat for the drying units is a natural gas fired boiler. The coaters and eight (8) drying ovens are controlled by a non-fugitive enclosure (NFE) and a regenerative thermal oxidizer (RTO No. 1). The associated purge and cleanup solvents are included.

**Flexible Group:** NA

**POLLUTION CONTROL EQUIPMENT**

A coating line is controlled by a Non-Fugitive Enclosure (NFE) and a Regenerative Thermal Oxidizer (RTO) No. 1

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC	18.6 tpy	12-month rolling time period as determined at the end of each calendar month	EU-CoatingLine-01	SC VI. 1, SC VI. 2, SC VI. 3	R 336.1205(1)(a)(ii), R 336.1702(a)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall capture all waste coatings, reducers, clean-up solvents, etc. (materials) and store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1702(a))**
2. The permittee shall handle all VOC and / or HAP containing materials, including coatings, reducers, solvents, and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1205, R 336.1224, R 336.1702(a))**
3. The permittee shall not operate EU-CoatingLine-01 unless a malfunction abatement plan (MAP) as described in Rule 911(2), has been submitted within 60 days of commencement of trial operation, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
  - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1702(a), R 336.1910, R 336.1911, 40 CFR 52.21(c) and (d))**

4. The permittee shall maintain an average water pressure differential between the NFE and the adjacent area of negative (-) 0.007 inches on a continuous basis, as described in SC VI.4. **(R 336.1702(a), R 336.1910)**

#### **IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU-CoatingLine-01 unless RTO No. 1 is installed, maintained, and operated in a satisfactory manner. Satisfactory operation of EU-CoatingLine-01 includes a minimum NFE capture efficiency of 100 percent (by weight), a minimum destruction efficiency for RTO No. 1 of 99 percent (by weight), maintaining a minimum RTO No. 1 temperature of 1500°F, and a minimum retention time of RTO No. 1 0.5 seconds. **(R 336.1205(1)(a)(ii), R 336.1702, R 336.1910)**
2. The permittee shall install, calibrate, maintain, and operate, in a satisfactory manner, a temperature monitoring device to continuously monitor and record the combustion chamber temperature of RTO No. 1 during operation of EU-CoatingLine-01. **(R 336.1205, R 336.1225, R 336.1702)**
3. The permittee shall not operate EU-CoatingLine-01 unless the associated NFE is installed, maintained, and operated in a satisfactory manner. Satisfactory NFE operation requires that the NFE is operating at a pressure lower than all adjacent areas, so that air flows into the NFE through all natural draft openings (NDOs). NDO is defined as any opening that is not connected to a duct in which a fan or blower is installed. Satisfactory operation of the NFE is considered equivalent to a VOC capture efficiency of 100 percent. **(R 336.1702(a), R 336.1910)**
4. The permittee shall install, calibrate, maintain, and operate, in a satisfactory manner, differential pressure gauges to monitor the pressure differential between the NFE for EU-CoatingLine-01 and the adjacent area on a continuous basis during operation of any portion of EU-CoatingLine-01. **(R 336.1702(a), R 336.1910)**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the VOC content, water content, and density of any coating, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. **(R 336.1205, R 336.1702, R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**
2. Upon request from AQD District Supervisor, the permittee shall verify the VOC destruction efficiency of RTO No. 1 for EU-CoatingLine-01, by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in 40 CFR Part 60, Appendix A. An alternate method, or a modification to the approved EPA Method, may be specified in an AQD approved Test Protocol and must meet the requirements of the federal Clean Air Act, all applicable state and federal rules and regulations, and be within the authority of the AQD to make the change. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing. Verification of destruction efficiency includes the submittal of a complete report of the test results, including calculations demonstrating the destruction efficiency, to the AQD within 60 days following the last date of the test. **(R 336.1205, R 336.1702, R 336.2001, R 336.2003, R 336.2004)**

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a calendar month basis for EU-CoatingLine-01:
  - a) Gallons (with water) of each VOC containing coating, reducer, purge and clean-up solvents, etc. (material) used and reclaimed.
  - b) VOC content (with water) of each material as applied.
  - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1702(a))**

4. The permittee shall monitor and record, in a satisfactory manner, the pressure differential between the associated NFE for EU-CoatingLine-01 and the adjacent area, on a continuous basis, to verify that air is entering into NFE. Pressure differential data recordings shall consist of the average of the measurements made over each interval, and recorded at equally spaced intervals, not to exceed 10 minutes per interval. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1225, R 336.1702)**
5. The permittee shall monitor and record, in a satisfactory manner, the combustion chamber temperature of RTO No. 1 on a continuous basis in a manner and with instrumentation acceptable to the Air Quality Division. Temperature data recording shall consist of measurements made at equally spaced intervals, not to exceed 15 minutes per interval. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205, R 336.1225, R 336.1702)**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-1A (Line 1: Curing Ovens)	30	40	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-4A (RTO 1)	48	40	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-5A (Line 1: Corona Treatment)	12	40	R 336.1225, 40 CFR 52.21(c) & (d)

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

### FLEXIBLE GROUP SPECIAL CONDITIONS

#### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FG-Tanks	Four (4) solvents storage tanks and one (1) multiple mix tanks.	EU-TolueneTank, EU-HeptaneTank, EU-MEKTank, EU-IPATank, EU-MixTanks

<b>FG-Tanks</b> <b>FLEXIBLE GROUP CONDITIONS</b>
---

**DESCRIPTION**

Four (4) solvents storage tanks and one (1) multiple mix tanks.

**Emission Unit:** EU-TolueneTank, EU-HeptaneTank, EU-MEKTank, EU-IPATank, EU-MixTanks

**POLLUTION CONTROL EQUIPMENT**

Conservation vents and submerged fill pipes

**I. EMISSION LIMIT(S)**

NA

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall install, maintain, and operate in a satisfactory manner, conservation vent valves on each tank in FG-Tanks. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall handle all VOC and / or HAP containing solvents (materials), in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1205, R 336.1225, R 336.1702(a))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not fill any tank in FG-Tanks unless the tank is equipped with submerged fill piping. **(R 336.1205, R 336.1225, R 336.1702)**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702)**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**

3. The permittee shall keep records of the monthly and 12-month rolling time period, as determined at the end of each calendar month, throughput of each material for each tank in FG-Tanks. **(R 336.1205, R 336.1225, R 336.1702)**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

NA

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

## FG-FACILITY CONDITIONS

### DESCRIPTION:

The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment and exempt equipment.

### POLLUTION CONTROL EQUIPMENT

NA

#### I. EMISSION LIMIT(S)

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. Each Individual HAP	Less than 8.98 tpy	12-month rolling time period as determined at the end of each calendar month	FG-Facility	SC VI.3	R 336.1205(3)
2. Aggregate HAPs	22.4 tpy	12-month rolling time period as determined at the end of each calendar month	FG-Facility	SC VI.3	R 336.1205(3)
3. VOC	30.0 tpy	12-month rolling time period as determined at the end of each calendar month	FG-Facility	SC VI.4	R 336.1205(3)

#### II. MATERIAL LIMIT(S)

NA

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall determine the HAP content of any material as received and as applied, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. (R 336.1205(3), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))
2. The permittee shall determine the VOC content, water content, and density of any coating, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. (R 336.1205(3), R 336.1702(a), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5)).

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**
3. The permittee shall keep the following information on a calendar month basis for FG-Facility:
  - a) Gallons or pounds of each HAP containing material used.
  - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
  - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
  - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
  - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

4. The permittee shall keep the following information on a calendar month basis for FG-FACILITY:
  - a) Gallons or pounds of each VOC containing material used.
  - b) Where applicable, gallons or pounds of each VOC containing material reclaimed.
  - c) VOC content, in pounds per gallon or pounds per pound, of each VOC containing material used.
  - d) VOC emission calculations determining the monthly emission rate in tons per calendar month.
  - e) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1205(3))**

## **VII. REPORTING**

NA

## **VIII. STACK/VENT RESTRICTION(S)**

NA

## **IX. OTHER REQUIREMENT(S)**

### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).