

**MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY
AIR QUALITY DIVISION**

July 27, 2018

**PERMIT TO INSTALL
8-16A**

ISSUED TO
State Crushing, Inc.

LOCATED AT
2260 Auburn Road
Auburn Hills, Michigan

IN THE COUNTY OF
Oakland

STATE REGISTRATION NUMBER
N3171

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

June 19, 2018

DATE PERMIT TO INSTALL APPROVED:

July 27, 2018

SIGNATURE:

DATE PERMIT VOIDED:

SIGNATURE:

DATE PERMIT REVOKED:

SIGNATURE:

PERMIT TO INSTALL

Table of Contents

Section	Page
Alphabetical Listing of Common Abbreviations / Acronyms	2
General Conditions	3
Special Conditions	5
Emission Unit Summary Table.....	5
Special Conditions for EUPROCESS	6
Special Conditions for EUTRUCKTRAFFIC	9
Special Conditions for EUSTORAGE	11
Appendix A.....	13
Appendix B.....	14

Common Abbreviations / Acronyms

Common Acronyms		Pollutant / Measurement Abbreviations	
AQD	Air Quality Division	acfm	Actual cubic feet per minute
BACT	Best Available Control Technology	BTU	British Thermal Unit
CAA	Clean Air Act	°C	Degrees Celsius
CAM	Compliance Assurance Monitoring	CO	Carbon Monoxide
CEM	Continuous Emission Monitoring	CO _{2e}	Carbon Dioxide Equivalent
CFR	Code of Federal Regulations	dscf	Dry standard cubic foot
COM	Continuous Opacity Monitoring	dscm	Dry standard cubic meter
Department/ department	Michigan Department of Environmental Quality	°F	Degrees Fahrenheit
EU	Emission Unit	gr	Grains
FG	Flexible Group	HAP	Hazardous Air Pollutant
GACS	Gallons of Applied Coating Solids	Hg	Mercury
GC	General Condition	hr	Hour
GHGs	Greenhouse Gases	HP	Horsepower
HVLP	High Volume Low Pressure*	H ₂ S	Hydrogen Sulfide
ID	Identification	kW	Kilowatt
IRSL	Initial Risk Screening Level	lb	Pound
ITSL	Initial Threshold Screening Level	m	Meter
LAER	Lowest Achievable Emission Rate	mg	Milligram
MACT	Maximum Achievable Control Technology	mm	Millimeter
MAERS	Michigan Air Emissions Reporting System	MM	Million
MAP	Malfunction Abatement Plan	MW	Megawatts
MDEQ	Michigan Department of Environmental Quality	NMOC	Non-methane Organic Compounds
MSDS	Material Safety Data Sheet	NO _x	Oxides of Nitrogen
NA	Not Applicable	ng	Nanogram
NAAQS	National Ambient Air Quality Standards	PM	Particulate Matter
NESHAP	National Emission Standard for Hazardous Air Pollutants	PM ₁₀	Particulate Matter equal to or less than 10 microns in diameter
NSPS	New Source Performance Standards	PM _{2.5}	Particulate Matter equal to or less than 2.5 microns in diameter
NSR	New Source Review	pph	Pounds per hour
PS	Performance Specification	ppm	Parts per million
PSD	Prevention of Significant Deterioration	ppmv	Parts per million by volume
PTE	Permanent Total Enclosure	ppmw	Parts per million by weight
PTI	Permit to Install	psia	Pounds per square inch absolute
RACT	Reasonable Available Control Technology	psig	Pounds per square inch gauge
ROP	Renewable Operating Permit	scf	Standard cubic feet
SC	Special Condition	sec	Seconds
SCR	Selective Catalytic Reduction	SO ₂	Sulfur Dioxide
SNCR	Selective Non-Catalytic Reduction	TAC	Toxic Air Contaminant
SRN	State Registration Number	Temp	Temperature
TEQ	Toxicity Equivalence Quotient	THC	Total Hydrocarbons
USEPA/EPA	United States Environmental Protection Agency	tpy	Tons per year
VE	Visible Emissions	µg	Microgram
		µm	Micrometer or Micron
		VOC	Volatile Organic Compounds
		yr	Year

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to R 336.1210, operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to R 336.1219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of R 336.1219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of R 336.1301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with R 336.1303. **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.

12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in R 336.1370(2). **(R 336.1370)**

13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with R 336.2001 and R 336.2003, under any of the conditions listed in R 336.2001. **(R 336.2001)**

SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Process Equipment & Control Devices)	Flexible Group ID
EUPROCESS	A combination of process equipment (screens, crushers, feeders, conveyors, etc.) used to reduce larger materials down to smaller sizes, classify and sort materials into various product types, material handling and transporting of material to storage areas. Control methods include equipment enclosures or enclosed within a building, water sprays, drop chutes and/or pant legs for transfer points.	NA
EUTRUCKTRAFFIC	Truck traffic for delivery of material products to customers; truck traffic from quarry pit to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions from the quarry pit to the process area.	NA
EUSTORAGE	Open area stock piles of various material sizes and product types. Water spray of material products are used when necessary for material storage piles.	NA
Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1290.		

The following conditions apply to: EUPROCESS

DESCRIPTION: A combination of process equipment (screens, crushers, feeders, conveyors, etc.) used to reduce larger materials down to smaller sizes, classify and sort materials into various product types, material handling and transporting of material to storage areas.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Water Sprays

I. EMISSION LIMITS

1. Visible emissions from the drop point and transfer point portions of EUPROCESS shall not exceed 10 percent opacity. **(R 336.1301, 40 CFR 52.21 (c) & (d), 40 CFR 60.670)**

II. MATERIAL LIMITS

1. The permittee shall not process any asbestos tailing or asbestos containing waste materials in EUPROCESS pursuant to the National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 61 Subpart M. **(40 CFR Part 61 Subpart M)**
2. The permittee shall not process more than 2,250 tons of material per day nor 310,500 tons of material through EUPROCESS per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205, R 336.1901, 40 CFR 52.21 (c) & (d))**

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate any portion of EUPROCESS unless each portion of EUPROCESS meets the specific opacity limit listed in Appendix A of this permit. **(R 336.1301, R 336.2803, R 336.2804, 40 CFR 52.21 (c) & (d), 40 CFR 60.670)**
2. The permittee shall not operate EUPROCESS unless the nuisance minimization plan for fugitive dust for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. **(R 336.1371, R 336.1901)**
3. The permittee shall comply with all provisions of the federal Standards of Performance for New Stationary Sources as specified in 40 CFR Part 60 Subparts A and OOO, as they apply to EUPROCESS. **(40 CFR Part 60 Subparts A & OOO)**
4. The permittee shall perform periodic inspections of water sprays according to 40 CFR 60.674(b) and 60.676(b). **(40 CFR Part 60 Subparts A & OOO, 40 CFR Part 60.672(b) and Table 3)**
5. The permittee shall immediately cease the input feed to EUPROCESS, consistent with safe operating procedures, upon malfunction of any EUPROCESS equipment's control device specified in SC IV.1. Input feed to EUPROCESS shall not resume until the control device malfunction has been repaired and is operating in a satisfactory manner. **(R 336.1301, R 336.1901, R 336.1910, R 336.1911, 40 CFR 52.21 (c) & (d))**

IV. DESIGN/EQUIPMENT PARAMETERS

1. The permittee shall not operate any portion of EUPROCESS unless the equipment's specified control device is installed, maintained and operated in a satisfactory manner as listed in Appendix A. **(R 336.1901, R 336.1910, 40 CFR 52.21 (c) & (d))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. All new or additional equipment associated with EUPROCESS that is subject to the federal NSPS Subpart OOO, which has not been previously tested, shall comply with the testing requirements of the federal Standards of Performance for New Stationary Sources 40 CFR Part 60 Subparts A and OOO. The permittee must have prior approval from the AQD for visible emission observation procedures. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD within 45 days following the last date of the evaluation. **(R 336.1201(a), R 336.1301, R 336. 2001, 40 CFR Part 60 Subparts A & OOO)**
2. Within 180 days after issuance of this permit, the permittee shall comply with federal Standards of Performance for New Stationary Sources which require evaluation of visible emissions from EUPROCESS, at owner's expense, in accordance with 40 CFR Part 60 Subparts A and OOO. Visible emission observation procedures must have prior approval by the AQD Technical Programs Unit and District Office. No less than ten (10) days prior to the anticipated test date, the permittee shall notify the AQD District Supervisor of the test date. If after the anticipated test date has been submitted, there is a delay in conducting the test, the permittee shall submit to the AQD District Supervisor notice of the new test date. This notification shall take place a minimum of three (3) days prior to the rescheduled test taking place. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD Technical Programs Unit and District Office within 30 days following the last date of the test. **(R 336.1301, 40 CFR Part 60 Subparts A & OOO)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, 40 CFR 52.21 (c) & (d))**
2. The permittee shall keep daily and monthly records of the amount of material processed through EUPROCESS by tracking the amount of processed material moved each production day via wheel loader and converting that to tons per day. Further the permittee shall calculate on a monthly basis, the yearly throughput rate based upon the most recent 12-month rolling time period. The permittee shall keep records of the amount of material processed on file and make them available to the Department upon request. **(R 336.1205, 40 CFR 52.21 (c) & (d))**
3. The permittee shall verify compliance with the visible emission limit in SC I.1 by taking six-minute visible emission readings from EUPROCESS a minimum of once per calendar month during maximum routine operating conditions. A certified reader shall take each visible emission reading during maximum routine operating conditions. If the permittee observes any visible emissions above the permitted limits, the permittee shall immediately implement the following procedures:
 - a) The permittee shall perform the six-minute visible emission readings at least once every 30 minutes until emissions are no longer above the limit or until emissions above the limit have been observed for more than two hours. **(R 336.1301, R 336.1901)**
 - b) If visible emissions above the limit have been observed for more than two hours, a certified reader shall determine the opacity using Federal Reference Test Method 9 or other method as approved by the AQD District Supervisor. **(40 CFR Part 60, Appendix A).**
 - c) If the results of the Federal Reference Test Method 9 visible emission observation or other method as approved by the AQD District Supervisor indicate a violation of the opacity standard specified in SC I.1, the permittee shall immediately cease process operations and initiate corrective actions. **(R 336.1301, R 336.1303, R 336.1901)**
4. The permittee shall perform daily inspections and record the condition of the process equipment and associated control devices prior to process start-up each calendar operating day. **(R 336.1301, R 336.1910)**

5. The permittee shall keep, in a satisfactory manner (in a format acceptable to the AQD District Supervisor), records of all visible emission observation readings from EUPROCESS. At a minimum, the permittee shall record the date the visible emission readings were conducted, the name of the visible emission observer, the date the observer was certified, and the name of the certifying organization. The permittee shall also record the time, the production rate at the time of the readings, estimated distance to the emission location, approximate wind direction, estimated wind speed, description of the sky condition (presence and color of clouds), and plume background at the time opacity readings are initiated and completed. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1301, R 336.1303, 40 CFR 60.672)**
6. The permittee shall maintain a log of maintenance activities conducted and repairs made to EUPROCESS and control devices. Maintenance and daily inspection records for the EUPROCESS fugitive dust control equipment shall also be included. The permittee shall keep all records (in a format acceptable to the AQD District Supervisor) on file and make them available to the Department upon request. **(R 336.1301, R 336.1910, 40 CFR 52.21 (c) & (d))**

VII. REPORTING

1. The permittee shall provide written notification of construction and operation to comply with the federal Standards of Performance for New Stationary Sources, 40 CFR 60.7. The permittee shall submit this notification to the AQD District Supervisor within the time frames specified in 40 CFR 60.7. **(40 CFR 60.7)**

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

1. Within 45 days of issuance of this permit, the permittee shall label all equipment using the company ID Numbers in Appendix A, according to a method acceptable to the AQD District Supervisor. Labels shall be in a conspicuous location on the equipment. Within seven days of completing the labeling, the permittee shall notify the AQD District Supervisor, in writing, as to the date the labeling was completed. **(R 336.1201)**

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUTRUCKTRAFFIC

DESCRIPTION: Truck traffic for delivery of material products to customers; truck traffic from unloading area to processing area and loader traffic associated with processing equipment, storage pile handling and loading delivery trucks. All commercial truck areas and unpaved road portions.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Fugitive dust control plan

I. EMISSION LIMITS

1. Visible emissions from all wheel loaders and all truck traffic, operated in conjunction with EUTRUCKTRAFFIC, shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, 40 CFR 52.21(c) & (d))**

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUTRUCKTRAFFIC unless the nuisance minimization plan for fugitive dust for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. **(R 336.1371, R 336.1372, R 336.1901, Act 451 324.5524)**

IV. DESIGN/EQUIPMENT PARAMETERS

1. Not later than 90 days after the date of issuance of this Permit to Install, the permittee shall equip each truck exit from EUTRUCKTRAFFIC with rumble strips. The rumble strips shall be of sufficient length and width to effectively remove dirt from truck tires. **(R 336.1901, R 336.1910, 40 CFR 52.21 (c) & (d))**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Within 180 days after issuance of this permit, the permittee shall evaluate visible emissions from EUTRUCKTRAFFIC, at owner's expense, in accordance 40 CFR Part 60.11(b). Visible emission observation procedures must have prior approval by the AQD Technical Programs Unit and District Office. No less than ten (10) days prior to the anticipated test date, the permittee shall notify the AQD District Supervisor of the test date. If after the anticipated test date has been submitted, there is a delay in conducting the test, the permittee shall submit to the AQD District Supervisor notice of the new test date. This notification shall take place a minimum of three (3) days prior to the rescheduled test taking place. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD Technical Programs Unit and District Office within 30 days following the last date of the test. **(R 336.1301, 40 CFR Part 60 Subpart A)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify compliance with the visible emission limit in SC I.1 by taking six-minute visible emission readings from EUTRUCKTRAFFIC a minimum of once per calendar month during maximum routine operating conditions. A certified reader shall take each visible emission reading during maximum routine operating conditions. If the permittee observes any visible emissions above the permitted limits, the permittee shall immediately implement the following procedures:
 - a) The permittee shall perform the six-minute visible emission readings at least once every 30 minutes until emissions are no longer above the limit or until emissions above the limit have been observed for more than two hours. **(R 336.1301)**
 - b) If visible emissions above the limit have been observed for more than two hours, a certified reader shall determine the opacity using Federal Reference Test Method 9D or other method as approved by the AQD District Supervisor. **(R 336.1301, R 336.1303, 40 CFR Part 60, Appendix A).**
 - c) If the results of the Federal Reference Test Method 9D visible emission observation or other method as approved by the AQD District Supervisor indicate a violation of the opacity standard specified in SC I.1, the permittee shall immediately cease process operations and initiate corrective actions. **(R 336.1301, R 336.1303, R 336.1901)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

The following conditions apply to: EUSTORAGE

DESCRIPTION: Open area stock piles of various material sizes and product types

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT: Fugitive dust control plan

I. EMISSION LIMITS

1. Visible emissions from each of the material storage piles maintained under EUSTORAGE, shall not exceed five (5) percent opacity. Compliance shall be demonstrated using Test Method 9D as defined in Section 324.5525(j) of Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended (Act 451). **(R 336.1301, 40 CFR 52.21(c) & (d))**

II. MATERIAL LIMITS

NA

III. PROCESS/OPERATIONAL RESTRICTIONS

1. The permittee shall not operate EUSTORAGE unless the fugitive dust control plan for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix B has been implemented and is maintained. **(R 336.1371, R 336.1372, R 336.1901, Act 451 324.5524)**

IV. DESIGN/EQUIPMENT PARAMETERS

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Within 180 days after issuance of this permit, the permittee shall evaluate visible emissions from each of the material storage piles maintained under EUSTORAGE, at owner's expense, in accordance 40 CFR Part 60.11(b). Visible emission observation procedures must have prior approval by the AQD Technical Programs Unit and District Office. No less than ten (10) days prior to the anticipated test date, the permittee shall notify the AQD District Supervisor of the test date. If after the anticipated test date has been submitted, there is a delay in conducting the test, the permittee shall submit to the AQD District Supervisor notice of the new test date. This notification shall take place a minimum of three (3) days prior to the rescheduled test taking place. Verification of visible emissions includes the submittal of a complete report of opacity observations to the AQD Technical Programs Unit and District Office within 30 days following the last date of the test. **(R 336.1301, 40 CFR Part 60 Subpart A)**

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify compliance with the visible emission limit in SC I.1 by taking six-minute visible emission readings from each of the material storage piles maintained under EUSTORAGE a minimum of once per calendar month during maximum routine operating conditions. A certified reader shall take each visible emission reading during maximum routine operating conditions. If the permittee observes any visible emissions above the permitted limits, the permittee shall immediately implement the following procedures:
 - a) The permittee shall perform the six-minute visible emission readings at least once every 30 minutes until emissions are no longer above the limit or until emissions above the limit have been observed for more than two hours. **(R 336.1301)**
 - b) If visible emissions above the limit have been observed for more than two hours, a certified reader shall determine the opacity using Federal Reference Test Method 9D or other method as approved by the AQD District Supervisor. **(R 336.1301, R 336.1303, 40 CFR Part 60, Appendix A).**
 - c) If the results of the Federal Reference Test Method 9D visible emission observation or other method as approved by the AQD District Supervisor indicate a violation of the opacity standard specified in SC I.1, the permittee shall immediately cease process operations and initiate corrective actions. **(R 336.1301, R 336.1303, R 336.1901)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTIONS

NA

IX. OTHER REQUIREMENTS

NA

Footnotes:

¹This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

APPENDIX A

Equipment Description	ID Number	Opacity Limit (Percent)	Control Device
Primary Crusher - Telesmith 3055 portable crusher serial # 605M2495	1	12	Water sprays
Secondary Impact Crusher – Hazemag Model APS-1313/KH, Minus HAZtronic	9	12	Water sprays
36 inch x 120 foot radial stacking conveyor - serial # (no tag)	3	7	Residual moisture
30 inch x 80 foot radial stacking conveyor - serial # (no tag)	4	7	Residual moisture
42 inch x 72 foot discharge conveyor -serial # (no tag)	5	7	Residual moisture
65 foot transfer Conveyor – serial # (no tag)	7	7	Residual moisture
TCI Portable Screening/Crushing Plant for Terex 6' x 20' Screen and Customer's Hazemag APPH-1313 Crusher	10	12	Water sprays

APPENDIX B
Nuisance Minimization Plan
Fugitive Dust

I. Site Roadways / Plant Yard

- A. The dust on the site roadways and the plant yard shall be controlled by applications of water, calcium chloride or other acceptable and approved fugitive dust control compounds. Applications of dust suppressants shall be done as often as necessary to meet all applicable emission limits. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.
- B. All paved roadways and the plant yards shall be swept as needed between applications.
- C. Any material spillage on roads shall be cleaned up immediately.
- D. Speed of vehicles shall be posted conspicuously and limited to 5 miles per hour. Signs will be posted to advise drivers of the speed limit.

II. Plant

The drop distance at each transfer point shall be reduced to the minimum the equipment can achieve. The transfer point from the re-circulating belt to the feed belt shall be equipped with an enclosed chute.

III. Storage Piles

- A. Stockpiling of all nonmetallic minerals shall be performed to minimize drop distance and control potential dust problems.
- B. Stockpiles shall be watered on an as needed basis in order to meet the opacity limit of 5 percent. Equipment to apply water or dust suppressant shall be available at the site or on call for use at the site within a given operating day. A record of all watering/dust suppressant applications shall be kept on file and be made available to the AQD upon request.

IV. Truck Traffic

- A. On-site vehicles shall be loaded to prevent their contents from dropping, leaking, blowing or otherwise escaping. This shall be accomplished by loading so that no part of the load shall come in contact within 6 inches of the top of any side board, side panel or tailgate. Otherwise, the truck shall be tarped.
- B. Truckers will be notified to trim loads and clean wheels and truck bodies prior to exiting the site. Trimming of loads will be done manually. Cleaning of wheels will be accomplished with the use of rumble strips at each truck exit. The rumble strips shall be cleaned as needed to maintain their effectiveness, at least once per day.
- C. Speed limit signs shall be posted and should be visible to all truck traffic. The speed shall be limited to 5 miles per hour.

V. Process Equipment

Any fugitive emissions from malfunction(s) from any transfer system, storage bin, mixer or hopper shall be immediately corrected to prevent further fugitive emissions. The water spray systems (for the crusher unit and for controlling fugitive emissions from material handling) shall be modified or upgraded, as necessary, so that operation of such system is deemed acceptable as determined by the District Supervisor. The modified or upgraded water spray systems shall be in place within 30 days of issuance of this permit.

VI. Recordkeeping

Daily records (in a format acceptable to the AQD District Supervisor) of the fugitive dust control equipment inspections, dust control activities on travel surfaces and other surfaces where fugitive dust emissions occur shall be kept on file for a period of at least five years and made available to the Department upon request. The records will indicate the date, time, what was observed or the reason for the dust control activity (routine or other), and what action was taken.

VII. AQD/MDEQ Inspection

The provisions and procedures of this plan are subject to adjustment by written notification from the AQD if, following an inspection, the AQD finds the fugitive dust requirements and/or permitted emission limits are not being met.