

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

October 10, 2022

**PERMIT TO INSTALL**  
101-17A

**ISSUED TO**  
Multi Packaging Solutions, Inc.

**LOCATED AT**  
13 West 4<sup>th</sup> Street  
Holland, Michigan 49423

**IN THE COUNTY OF**  
Allegan

**STATE REGISTRATION NUMBER**  
N5214

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>September 6, 2022</b>	
DATE PERMIT TO INSTALL APPROVED: <b>October 10, 2022</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

### Table of Contents

COMMON ACRONYMS .....	2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....	3
GENERAL CONDITIONS .....	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE .....	6
EU-Press-05 .....	7
FLEXIBLE GROUP SPECIAL CONDITIONS.....	10
FLEXIBLE GROUP SUMMARY TABLE .....	10
FG-PrintingPakMfg.....	11
FGFACILITY CONDITIONS.....	14
<i>Appendix A</i> .....	16

### COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2e</sub>	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM <sub>10</sub>	Particulate Matter equal to or less than 10 microns in diameter
PM <sub>2.5</sub>	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

**EMISSION UNIT SPECIAL CONDITIONS**

**EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU-Press-01	Conventional sheet-fed offset lithographic printing press, Heidelberg CX-102 8+L, maximum sheet size 28" x 40". Automatic and/or manual blanket wash.	2011	FG-PrintingPakMfg
EU-Press-02	Conventional sheet-fed offset lithographic printing press, Heidelberg CX-102 8+L, maximum sheet size 28" x 40". Automatic and/or manual blanket wash.	2006	FG-PrintingPakMfg,
EU-Press-05	Conventional and UV sheet-fed offset lithographic printing press, Heidelberg CX-102 8+L, maximum sheet size 28" x 40". Automatic and/or manual blanket wash.	2019/PTI Issuance Date	NA
EU-Digital-01	Kirk Rudy IR inkjet labeler Model 882-1 2009	2009	FG-PrintingPakMfg
EU-Digital-02	Kirk Rudy IR inkjet labeler Model 882-1 2011	2011	FG-PrintingPakMfg
EU-DieCutter-01	B1-Sheet fed, unheated platen, non-blanking Bobst 1998 Model SP102-CERII	1998	FG-PrintingPakMfg
EU-DieCutter-02	B2-Sheet fed, blanking Bobst die cutter. 2001 Model SP102-EII	2001	FG-PrintingPakMfg
EU-DieCutter-03	B3-Sheet fed, non-blanking Bobst 2003 Model SP104-E	2003	FG-PrintingPakMfg
EU-DieCutter-04	B4-Sheet fed, blanking Bobst 2002 Model SP104-ER	2002	FG-PrintingPakMfg
EU-Folder-Gluer-01	FG01-Signature Model 90 Max blank size 36 inches wide	2006	FG-PrintingPakMfg
EU-Folder-Gluer-04	FG04-International Model 33 Max blank size 33 inches wide	1981	FG-PrintingPakMfg

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EU-Press-05  
EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Conventional and UV sheet-fed offset lithographic printing press, Heidelberg CX-102 8+L, maximum sheet size 28" x 40". Automatic and/or manual blanket wash.

Flexible Group ID: NA

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	15.0 tpy	12-month rolling time period as determined at the end of each calendar month	EU-Press-05	SC VI.3	R 336.1225, R 336.1702(a)

**II. MATERIAL LIMIT(S)**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC Content of the Fountain Solution	≤ 5.0 % By weight, as applied	Instantaneous	EU-Press-05	SC V.1, SC VI.1, SC VI.2, SC VI.3, Appendix A	R 336.1702(a)
2. Fountain Solution	1,000 lbs per month	Calendar Month	EU-Press-05	SC VI.1, SC VI.2, SC VI.3	R 336.1225
3. Sheets	50,000,000 units per 12-month rolling time period	12-month rolling time period as determined at the end of each calendar month	EU-Press-05	SC VI.1, SC VI.3	R 336.1205, R 336.1225, R 336.1702(a)

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. All VOC-containing inks, fountain solution, coatings, cleaning solvents such as blanket and roller washes, used shop towels, etc. (materials) shall be stored in closed containers and disposed of in an acceptable manner, in compliance with all applicable state rules and federal regulations. **(R 336.1225, R 336.1702(a))**

2. The permittee shall handle all VOC and/or HAP containing materials, including coatings, reducers, solvents and thinners, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1205(3), R 336.1224, R 336.1225, R 336.1702(a))**
3. All printing press-related cleaning solvents shall have VOC composite partial vapor pressures that do not exceed 10 mmHg @ 20°C (68°F). **(R 336.1702(a))**

#### **IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify the VOC content of any ink, coating, fountain solution *etc.* (material), as received and as applied, using federal Reference Test Method 24 or 24A pursuant to Rule 1040(5). Upon prior written approval by the AQD District Supervisor, VOC content may be determined from manufacturer's formulation data. If the Method 24 or 24A and the formulation values should differ, the Method 24 or 24A results shall be used to determine compliance. **(R 336.1702(a), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each VOC containing material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a calendar month basis for EU-Press-05:
  - a) The type of each VOC containing material used and reclaimed (ink, coating, blanket wash, roller wash, press wash, *etc.*)
  - b) The amount of fountain solution used in pounds.
  - c) The VOC content of each material as received and as applied (in percent by weight or pounds per gallon)
  - d) The number of sheets processed.
  - e) VOC mass emission calculations determining the monthly emission rate in tons per calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used, or an alternate factor approved by the AQD District Supervisor)
  - f) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used, or an alternate factor approved by the AQD District Supervisor)

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(a))**

4. The permittee shall calculate the VOC content of the fountain solution using the method detailed in Appendix A or an alternate method approved by the AQD District Supervisor. Calculations shall include both dampening

aid and wetting agent, as used, in percent by weight. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1702(a))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

1. The exhaust gases from EU-Press-05 shall be released only into the general in-plant environment. **(R 336.1225, 40 CFR 52.21(c) & (d))**

**IX. OTHER REQUIREMENT(S)**

1. Within 30 days of issuance of this permit, the permittee shall label the emission unit according to a method acceptable to the AQD District Supervisor. **(R 336.1201)**

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

### FLEXIBLE GROUP SPECIAL CONDITIONS

### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FG-PrintingPakMfg	Two sheet-fed offset lithographic printing presses. The printers are cleaned automatically and/or manually with blanket wash.	EU-Press-01, EU-Press-02,
	Two digital (inkjet) labelers	EU-Digital-01, EU-Digital-02
	Four die cutters	EU-DieCutter-01, EU-DieCutter-02, EU-DieCutter-03, EU-DieCutter-04
	Two folder/gluer	EU-Folder-Gluer-01, EU-Folder-Gluer-04

**FG-PrintingPakMfg  
 FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

Two sheet-fed offset lithographic printing presses and its associated two inkjet labelers, four die cutters, and two folder/gluer. The printers are cleaned automatically and/or manually with blanket wash.

**Emission Unit:** EU-Press-01, EU-Press-02, EU-Digital-01, EU-Digital-02, EU-DieCutter-01, EU-DieCutter-02, EU-DieCutter-03, EU-DieCutter-04, EU-Folder-Gluer-01, EU-Folder-Gluer-04

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMITS**

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOCs	22.1 tpy	12-month rolling time period as determined at the end of each calendar month	FG-PrintingPakMfg	SC VI.1, SC VI.2, SC VI.3	R 336.1225, R 336.1702(a)

**II. MATERIAL LIMITS**

Material	Limit	Time Period / Operating Scenario	Equipment	Testing / Monitoring Method	Underlying Applicable Requirements
1. VOC Content of the Fountain Solution	5.0 % By weight, as applied	Instantaneous	EU-Press-01, EU-Press-02	SC V.2, SC VI.1, SC VI.2, SC VI.3, Appendix A	R 336.1702(a)
2. VOC Content of Glue	2.9 % By weight, as applied	Instantaneous	EU-Folder-Gluer-01, EU-Folder-Gluer-04	SC VI.1, SC VI.2, SC VI.3	R 336.1702(a)
3. Fountain Solution	1,400 lbs per month	Monthly	FG-PrintingPakMfg	SC VI.1, SC VI.2, SC VI.3, SC VI.4	R 336.1225

### **III. PROCESS/OPERATIONAL RESTRICTIONS**

1. All VOC-containing inks, fountain solution, coatings, cleaning solvents such as blanket and roller washes, used shop towels, etc. (materials) shall be stored in closed containers and disposed of in an acceptable manner, in compliance with all applicable state rules and federal regulations. **(R 336.1224, R 336.1225, R 336.1702(a))**
2. The permittee shall handle all VOC and/or HAP containing materials, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1224, R 336.1225, R 336.1702(a))**
3. All printing press-related cleaning solvents shall have VOC composite partial vapor pressures that do not exceed 10 mmHg @ 20°C (68°F). **(R 336.1702(a))**

### **IV. DESIGN/EQUIPMENT PARAMETERS**

NA

### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall verify the VOC content of any ink, coating, etc. (material), as received and as applied, using federal Reference Test Method 24 or 24A pursuant to Rule 1040(5). Upon prior written approval by the AQD District Supervisor, VOC content may be determined from manufacturer's formulation data. If the Method 24 or 24A and the formulation values should differ, the Method 24 or 24A results shall be used to determine compliance. **(R 336.1702(a), R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**
2. The permittee shall verify the VOC content of the fountain solution as received and as applied, using federal Reference Test Method 24 or 24A pursuant to Rule 1040(5) on an annual basis. Upon prior written approval by the AQD District Supervisor, VOC content may be determined from manufacturer's formulation data. If the Method 24 or 24A and the formulation values should differ, the Method 24 or 24A results shall be used to determine compliance. **(R 336.225, R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))**

### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1225, R 336.1702(a))**
2. The permittee shall maintain a current listing from the manufacturer of the chemical composition of each VOC containing material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1225, R 336.1702)**
3. The permittee shall keep the following information on a calendar month basis for FG-PrintingPkgMfg:
  - a) The type of operation (type of press (sheet-fed or digital), die cutter, folder/gluer)
  - b) The type of each VOC containing material used and reclaimed (ink, coating, blanket wash, roller wash, press wash, etc.)
  - c) The amount of fountain solution used in pounds.
  - d) The VOC content of each material as received and as applied (in percent by weight or pounds per gallon)
  - e) VOC mass emission calculations determining the monthly emission rate in tons per calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress

Printing, EPA-453/R-06-002, September 2006 may be used, or an alternate factor approved by the AQD District Supervisor)

- f) VOC emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month. (Retention factors from Control Techniques Guidelines for Offset Lithographic Printing and Letterpress Printing, EPA-453/R-06-002, September 2006 may be used, or an alternate factor approved by the AQD District Supervisor)

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1702(a))**

4. The permittee shall calculate the VOC content of the fountain solution using the method detailed in Appendix A or an alternate method approved by the AQD District Supervisor. Calculations shall include both dampening aid and wetting agent, as used, in percent by weight. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1702(a))**

#### **VII. REPORTING**

NA

#### **VIII. STACK/VENT RESTRICTIONS**

1. The exhaust gases from FG-PrintPackMfg shall be released only into the general in-plant environment. **(R 336.1224, R 336.1225, 40 CFR 52.21(c) & (d))**

#### **IX. OTHER REQUIREMENTS**

1. The permittee shall label each emission unit according to a method acceptable to the AQD District Supervisor. **(R 336.1201)**

## FG FACILITY CONDITIONS

**DESCRIPTION:** All process equipment source-wide including equipment covered by other permits, grand-fathered equipment and exempt equipment.

### **I. EMISSION LIMITS**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period/ Operating Scenario</b>	<b>Equipment</b>	<b>Testing/ Monitoring Method</b>	<b>Underlying Applicable Requirements</b>
1. Each Individual HAP	8.9 tpy	12-month rolling time period as determined at the end of each calendar month	FG-Facility	SC VI.1, SC VI.2	R 336.1205(3)
2. Aggregate HAPs	22.4 tpy	12-month rolling time period as determined at the end of each calendar month	FG-Facility	SC VI.1, SC VI.2	R 336.1205(3)

### **II. MATERIAL LIMITS**

NA

### **III. PROCESS/OPERATIONAL RESTRICTIONS**

NA

### **IV. DESIGN/EQUIPMENT PARAMETERS**

NA

### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall determine the HAP content of any material as applied and as received, using manufacturer's formulation data. Upon request of the AQD District Supervisor, the permittee shall verify the manufacturer's HAP formulation data using EPA Test Method 311. **(R 336.1205(3))**

### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15<sup>th</sup> day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3))**

2. The permittee shall keep the following information for FG-Facility on a calendar month basis:
  - a) Gallons or pounds of each HAP containing material used.
  - b) Where applicable, gallons or pounds of each HAP containing material reclaimed.
  - c) HAP content, in pounds per gallon or pounds per pound, of each HAP containing material used.
  - d) Individual and aggregate HAP emission calculations determining the monthly emission rate of each in tons per calendar month.
  - e) Individual and aggregate HAP emission calculations determining the annual emission rate of each in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor and make them available to the Department upon request. **(R 336.1205(3))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTIONS**

NA

**IX. OTHER REQUIREMENTS**

NA

