MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY AIR QUALITY DIVISION

July 8, 2021

PERMIT TO INSTALL 37-21

ISSUED TO

Pharmacia & Upjohn Company LLC, a Subsidiary of Pfizer, Inc.

LOCATED AT

7000 Portage Road Kalamazoo, Michigan 49001

IN THE COUNTY OF

Kalamazoo

STATE REGISTRATION NUMBER B3610

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQ	DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:				
July 1, 2021					
DATE PERMIT TO INSTALL APPROVED:	SIGNATURE:				
July 8, 2021					
,					
DATE PERMIT VOIDED:	SIGNATURE:				
DATE PERMIT REVOKED:	SIGNATURE:				

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS	6
EMISSION UNIT SUMMARY TABLE	6
EUCR491COM-S3	7
Appendix A. Particle Size Categories	10
Appendix B. Recordkeeping	11
Appendix C. Particulate Control Equipment Operating Ranges	12

COMMON ACRONYMS

AQD Air Quality Division

BACT Best Available Control Technology

CAA Clean Air Act

CAM Compliance Assurance Monitoring
CEMS Continuous Emission Monitoring System

CFR Code of Federal Regulations

COMS Continuous Opacity Monitoring System

Department/department/EGLE Michigan Department of Environment, Great Lakes, and Energy

EU Emission Unit FG Flexible Group

GACS Gallons of Applied Coating Solids

GC General Condition
GHGs Greenhouse Gases

HVLP High Volume Low Pressure*

ID Identification

IRSLInitial Risk Screening LevelITSLInitial Threshold Screening LevelLAERLowest Achievable Emission RateMACTMaximum Achievable Control TechnologyMAERSMichigan Air Emissions Reporting System

MAP Malfunction Abatement Plan MSDS Material Safety Data Sheet

NA Not Applicable

NAAQS National Ambient Air Quality Standards

NESHAP National Emission Standard for Hazardous Air Pollutants

NSPS New Source Performance Standards

NSR New Source Review
PS Performance Specification

PSD Prevention of Significant Deterioration

PTE Permanent Total Enclosure

PTI Permit to Install

RACT Reasonable Available Control Technology

ROP Renewable Operating Permit

SC Special Condition

SCR Selective Catalytic Reduction
SNCR Selective Non-Catalytic Reduction

SRN State Registration Number

TBD To Be Determined

TEQ Toxicity Equivalence Quotient

USEPA/EPA United States Environmental Protection Agency

VE Visible Emissions

^{*}For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm Actual cubic feet per minute

BTU British Thermal Unit °C Degrees Celsius CO Carbon Monoxide

CO2e Carbon Dioxide Equivalent dscf Dry standard cubic foot dscm Dry standard cubic meter Personal Per

gr Grains

HAP Hazardous Air Pollutant

Hg Mercury hr Hour

HP Horsepower Hydrogen Sulfide

kW Kilowatt

Ib Pound

m Meter

mg Milligram

mm Millimeter

MM Million

MW Megawatts

NMOC Non-Methane Organic Compounds

NO_x Oxides of Nitrogen

ng Nanogram

PM Particulate Matter

PM10 Particulate Matter equal to or less than 10 microns in diameter PM2.5 Particulate Matter equal to or less than 2.5 microns in diameter

pph Pounds per hour ppm Parts per million

ppmv Parts per million by volume ppmw Parts per million by weight

psia Pounds per square inch absolute psig Pounds per square inch gauge

scf Standard cubic feet

 $\begin{array}{ccc} \text{sec} & \text{Seconds} \\ \text{SO}_2 & \text{Sulfur Dioxide} \end{array}$

TAC Toxic Air Contaminant

Temp Temperature

THC Total Hydrocarbons tpy Tons per year Microgram

μm Micrometer or Micron

VOC Volatile Organic Compounds

yr Year

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EUCR491COM-S3	All equipment in or around Building 91, commercial area, located in KAPI Region IV, which includes relocation and installation of equipment to operate the B91 9CPT process (91TANK3416-1, 91TANK3416-2, 91CLMN1011-9, and 91SILGELDROP). (PTI No. 37-21)	01-01-61/ 12-28-95/ 03-31-15 07-08-21	FGCRALLPART-S3 FGCRALLTOX-S3 FGCFUG-S3 FGPHARMAMACT-S3

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

EUCR491COM-S3 EMISSION UNIT CONDITIONS

DESCRIPTION

All equipment in or around Building 91, commercial area, located in KAPI Region IV, which includes relocation and installation of equipment to operate the B91 9CPT process (91TANK3416-1, 91TANK3416-2, 91CLMN1011-9, and 91SILGELDROP). (PTI No. 37-21)

Flexible Group ID: FGCRALLPART, FGCRALLTOX, FGCFUG, FGPHARMAMACT

POLLUTION CONTROL EQUIPMENT

HEPA Filters on DUST1010, EX27 filters1049 and 1056, EX117, EX118, EX119, Exhaust Fans on EX107, EX124; Condensers, connected to TOX; Scrubbers, connected to TOX.

I. EMISSION LIMIT(S)

Pollutant Limit		Time Period / Operating Limit Scenario Equipment		Monitoring / Testing Method	Underlying Applicable Requirements	
1	VOC	50 lbs per month 1	Calendar month	TANK1615 not	SC VI.3	R 336.1225
'-	VOO	oo iba per monur	Odichadi month	controlled by the	00 VI.0	R 336.1227(2)
				thermal oxidizer		11 000.1221(2)
2.	VOC	10 lbs per lot 1	Each lot	Unconnected VOC	SC VI.3	R 336.1225
				processes		R 336.1227(2)
3.	Methanol	0.1 pph ¹	Hourly	TANK1615 not	SC VI.3	R 336.1225
			-	controlled by the		R 336.1227(2)
				thermal oxidizer		
4.	Methylene	1 pph ¹	Hourly	TANK1615 not	SC VI.3	R 336.1225
	Chloride			controlled by the		R 336.1227(2)
				thermal oxidizer		
5.	Ozone	0.2 pph ¹	Hourly	TANK1615 not	SC VI.3	R 336.1225
				controlled by the		R 336.1227(2)
				thermal oxidizer		
6.	Particulate	90 lbs per month 1	Calendar month	All process vents	SC VI.2	R 336.1225
				combined		R 336.1227(2)
7.	Particulate	Limits in the table	Hourly	EUCR491COM	SC VI.2	R 336.1225
		below:				R 336.1331(c)

Exhaust ID		Lbs Particulate Per Hour By Size Category+ Lbs Particulate Per 1000 Lbs Of Dry Exhaust Gas				Maximum Gas Flow Rate		
	Α	В	С	Α	В	С	(dscfm)	
8. DUST1010	0.19	0.13	0.08	0.01	0.01	0.006	3,090	
9. EX-27	0.23	0.17	0.10	0.01	0.01	0.006	4,000	
10. EX-107	-	1.44	0.86	-	0.10	0.06	3,360	
11. EX-117	0.06	0.043	0.026	0.01	0.01	0.006	1,000	
12. EX-118	0.06	0.043	0.026	0.01	0.01	0.006	1,000	
13. EX-119	0.06	0.043	0.026	0.01	0.01	0.006	1,000	
14. EX-124	-	1.37	0.82	-	0.10	0.06	3,200	
+ See Appendix	See Appendix A for approved procedures for determination of the particle size category.							

II. MATERIAL LIMIT(S)

			Time Period / Operating		Monitoring / Testing	Underlying Applicable
	Material	Limit	Scenario	Equipment	Method	Requirements
1.	Lots of product produced in PM-emitting processes.	30 lots per month ¹	Calendar month	EUCR491COM	SC VI.2	R 336.1225 R 336.1227(2)
2.	Lots of VOC emitting product produced in equipment not controlled by the thermal oxidizer	5 lots per month ¹	Calendar month	EUCR491COM	SC VI.3	R 336.1225 R 336.1227(2)

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall not operate equipment located in EUCR491COM in vacuum service, while processing a VOC, unless a vacuum pump connected to the thermal oxidizer control is installed, maintained, and operated in a satisfactory manner acceptable to the AQD District Supervisor. (R 336.1224, R 336.1910)

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1225, R 336.1227(2), R 336.1331(c), R 336.1702(a))
- 2. The permittee shall calculate and record the actual particulate emission rates on a monthly basis using a method similar to that described in Appendix B. (R 336.1225, R 336.1227(2), R 336.1331(c))
- 3. The permittee shall calculate the actual VOC emissions from each process for unconnected VOC equipment for each calendar month using the method detailed in Appendix B. (R 336.1702(a))

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

	Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements				
1.	SVC91EX107	16	23	R 336.1225, 40 CFR 52.21(c)&(d)				
2.	SVC91EX117	10	23	R 336.1225, 40 CFR 52.21(c)&(d)				
3.	SVC91EX118	10	23	R 336.1225, 40 CFR 52.21(c)&(d)				
4.	SVC91EX119	10	23	R 336.1225, 40 CFR 52.21(c)&(d)				
5.	SVC91EX124	18	40	R 336.1225, 40 CFR 52.21(c)&(d)				
6.	SVC91EX27*	25 x 19	37	R 336.1225, 40 CFR 52.21(c)&(d)				
7.	SVC91DUST1010	24	62	R 336.1225, 40 CFR 52.21(c)&(d)				
*	may have an orientation 45° below horizontal							

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

Appendix A. Particle Size Categories

The permittee shall use the following approved procedures for determination of the particle size category and appropriate control equipment for the requirements referenced in EUCR491COM.

Category A Mean particle size by weight <100 microns

Category B Mean particle size by weight >100 microns but <200 microns

Category C Mean particle size by weight >200 microns

Control Device	Particle Size/Control Class	
Rotoclone	A, B, C	
Exhaust Fan	B, C	
Scrubber	A, B, C	
Baghouse	A, B, C	
Dust Collector	A, B, C	

Appendix B. Recordkeeping

The permittee shall use the following approved formats and procedures for the recordkeeping requirements referenced in EUCR491COM. Alternative formats must be approved by the AQD District Supervisor. An alternative format has been approved. All other provisions of Appendix 4-S3 of ROP# MI-ROP-B3610-2014h, revised July 24, 2018, remain applicable.

MONTHLY RECORDKEEPING FORMAT- REGION IV PM-EMITTING PROCESSES					
Process Building	Particulate Maximum (lbs/lot)	Actual Number of lots/month	Estimated Particulate Emissions (lbs/month)		
91 Commercial	2.5				

Appendix C. Particulate Control Equipment Operating Ranges

The following particulate control equipment operating ranges are applicable to control equipment in EUCR491COM-S3. All other provisions of Appendix 12-S3 of ROP# MI-ROP-B3610-2014h, revised July 24, 2018, remain applicable.

			Acceptable	Acceptable minimum	Acceptable min/max	Acceptable
D. t l /			min/max or	water	differential	minimum
Rotoclone/			min GPM	pressure	pressure (inches	water level
Scrubber	Fabric Filter	Emission Unit	water	(psi)	of water)	(inches)
	DUST1010	EUCR491COM			2.0/12.0	
	EX-27 1049	EUCR491COM			0.1/2.5	
	EX-27 1056	EUCR491COM			0.1/2.5	
	EX-117	EUCR491COM			0.1/3	
	EX-118	EUCR491COM			0.1/3	
	EX-119	EUCR491COM			0.1/3	