

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

September 28, 2022

**PERMIT TO INSTALL**  
129-22

**ISSUED TO**  
Beacon Recycling, Inc.

**LOCATED AT**  
1241 East Keating Avenue  
Muskegon, Michigan 49442

**IN THE COUNTY OF**  
Muskegon

**STATE REGISTRATION NUMBER**  
P1231

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>September 13, 2022</b>	
DATE PERMIT TO INSTALL APPROVED: <b>September 28, 2022</b>	SIGNATURE: <i>MaryAnn Dolichanty</i>
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

**PERMIT TO INSTALL**

**Table of Contents**

COMMON ACRONYMS .....2  
POLLUTANT / MEASUREMENT ABBREVIATIONS.....3  
GENERAL CONDITIONS .....4  
EMISSION UNIT SPECIAL CONDITIONS.....6  
    EMISSION UNIT SUMMARY TABLE .....6  
    EU001 .....7  
FGFACILITY CONDITIONS..... 14  
APPENDIX A ..... 16

## COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

## EMISSION UNIT SPECIAL CONDITIONS

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU001	Wendt Corp Model 6090 Scrap Metal Shredder capable of processing 60 gross tons of product per hour. Emissions from the shredder are controlled by a water injection system. The shredder and associated equipment run on electrical power. The shredder also has a feed conveyor, ferrous separation process, non-ferrous separation system, associated conveyors, material storage, and associated process activities including but not limited to management of materials from the shredding operations.	TBD	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EU001**  
**EMISSION UNIT CONDITIONS**

**DESCRIPTION**

Wendt Corp Model 6090 Scrap Metal Shredder capable of processing 60 gross tons of product per hour. Emissions from the shredder are controlled by a water injection system. The shredder and associated equipment run on electrical power. The shredder also has a feed conveyor, ferrous separation process, non-ferrous separation system, associated conveyors, material storage, and associated process activities including but not limited to management of materials from the shredding operations.

**Flexible Group ID:** NA

**POLLUTION CONTROL EQUIPMENT**

Water injection system on the shredder

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOC (as propane)	2.67 tpy <sup>a,3</sup>	12-month rolling time period as determined at the end of each calendar month	Shredder portion of EU001	SC VI.6	R 336.1702(a)
2. VOC (as propane)	3.85 tpy <sup>a,4</sup>	12-month rolling time period as determined at the end of each calendar month	Stack portion of EU001	SC VI.6	R 336.1702(a)
3. PM	0.05 lbs/ per 1000 lbs of exhaust gas <sup>b,4</sup>	Hourly	Stack portion of EU001	SC V.3	R 336.1331
4. PM2.5	3.69 lb/day <sup>a,3</sup>	Calendar Day	Shredder portion of EU001	SC VI.7	40 CFR 52.21 (c) & (d)
5. PM2.5	7.66 lb/day <sup>a,4</sup>	Calendar Day	Stack portion of EU001	SC VI.7	40 CFR 52.21 (c) & (d)
6. Lead	10.26 lb/yr <sup>a,3</sup>	12-month rolling time period as determined at the end of each calendar month	Shredder portion of EU001	SC VI.8	40 CFR 52.21 (c) & (d)
7. Lead	14.80 lb/yr <sup>a,4</sup>	12-month rolling time period as determined at the end of each calendar month	Stack portion of EU001	SC VI.8	40 CFR 52.21 (c) & (d)
8. Mercury	0.83 lb/yr <sup>a,3</sup>	12-month rolling time period as determined at the end of each calendar month	Shredder portion of EU001	SC VI.9	R 336.1225
9. Mercury	1.20 lb/yr <sup>a,4</sup>	12-month rolling time period as determined at the end of each calendar month	Stack portion of EU001	SC VI.9	R 336.1225

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
<sup>a</sup> Compliance with this limit will be demonstrated by multiplying the emission factor in SC VI.6, 7, 8, or 9 (or an alternate emission factor approved by the AQD District Supervisor) by the throughput.					
<sup>b</sup> Calculated on a dry gas basis					

10. Until an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the visible emissions from the shredder portion of EU001 shall not exceed a six-minute average of 20 percent opacity. **(R 336.1301, R 336.1303, R 336.1901, 40 CFR 52.21(c) & (d))**
11. On and after an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the visible emissions from the hood portion and from the stack portion of EU001 shall not exceed a six-minute average of 10 percent opacity. **(R 336.1301, R 336.1303, R 336.1901, 40 CFR 52.21(c) & (d))**
12. Visible emissions from the ferrous separation portion of EU001 shall not exceed a six-minute average of 10 percent opacity. **(R 336.1301, R 336.1303, R 336.1901, 40 CFR 52.21(c) & (d))**
13. Visible emissions from the non-ferrous portion of EU001 shall not exceed a six-minute average of 10 percent opacity. **(R 336.1301, R 336.1303, R 336.1901, 40 CFR 52.21(c) & (d))**
14. Visible emissions from the conveyors and transfer points of EU001 shall not exceed a six-minute average of 10 percent opacity. **(R 336.1301, R 336.1303, R 336.1901, 40 CFR 52.21(c) & (d))**

**II. MATERIAL LIMIT(S)**

1. Until an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the permittee shall not process more than 190 tons of material per calendar day and 69,350 tons of material per 12-month rolling time period as determined at the end of each calendar month through EU001. **(R 336.1224, R 336.1225, R 336.1901, 40 CFR 52.21(c) & (d))**
2. On and after an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the permittee shall not process more than 395 tons of material per calendar day and 100,000 tons of material per 12-month rolling time period as determined at the end of each calendar month through EU001. **(R 336.1224, R 336.1225, R 336.1901, 40 CFR 52.21(c) & (d))**
3. Until an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the permittee shall not process more than 20,805 tons of auto scrap material (of the 69,350 tons of material allowed in SC II.1) through EU001 per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1901, 40 CFR 52.21(c) & (d))**
4. On and after an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the permittee shall not process more than 30,000 tons of auto scrap material (of the 100,000 tons of material allowed in SC II.2) through EU001 per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1901, 40 CFR 52.21(c) & (d))**
5. The permittee shall not process any asbestos tailing or waste materials containing asbestos in EU001 pursuant to the National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 61, Subpart M. **(40 CFR Part 61 Subpart M)**
6. The permittee shall not process batteries in EU001.<sup>1</sup> **(R 336.1224, R 336.1225, R 336.1901)**
7. The permittee shall not process any gas tanks (including automotive gasoline tanks) or other tanks under pressure in EU001 unless they are flattened or punctured. **(R 336.1225, R 336.1702(a), R 336.1901)**

### **III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU001 unless the water injection system is installed, maintained, and operated in a satisfactory manner as described in the malfunction abatement plan (MAP), as described in SC III.10. **(R 336.1224, R 336.1225, R 336.1331, R 336.1901, R 336.1910, 40 CFR 52.21(c) & (d))**
2. The permittee shall properly remove and properly dispose of fluids from materials to be shredded as specified in the plan in SC III.7 (or inspect and/or document that removal has been performed). As specified in the materials management plan, materials include but are not limited to vehicles, appliances, and industrial machinery. As specified in the written plan for the management of materials, fluids shall include, at a minimum, gasoline, motor oil, antifreeze, transmission oil, brake oil, power steering fluid, hydraulic fluid, and differential fluid. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1901)**
3. The permittee shall properly remove and properly dispose of freon or other chlorofluorocarbons/hydrochlorofluorocarbons (CFCs/HCFCs) from materials to be shredded as specified in the plan in SC III.7 (or inspect and/or document that removal has been performed). As specified in the materials management plan, materials include but are not limited to air conditioning units in vehicles, appliances, and industrial machinery.<sup>1</sup> **(R 336.1224, R 336.1225, R 336.1901)**
4. The permittee shall properly remove and properly dispose of mercury-containing devices from materials to be shredded as specified in the plan in SC III.7 (or inspect and/or document that removal has been performed). As specified in the materials management plan, materials include but are not limited to vehicles, appliances, and industrial machinery.<sup>1</sup> **(R 336.1224, R 336.1225, R 336.1901)**
5. The permittee shall stage all non-metal and automotive shredder residue (e.g., fluff) generated by EU001 in a total volume not to exceed 2,000 cubic yards at any time. **(R 336.1301, R 336.1901)**
6. All fluids, non-metal, and waste materials generated by the EU001 shall be contained and disposed of or recycled in an acceptable manner in compliance with all applicable state and federal rules and regulations. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1901)**
7. Prior to commencement of operations, the permittee shall submit to the AQD District Supervisor an acceptable materials management plan for demonstrating compliance with SCs II.5, II.6, II.7, III.2, III.3, III.4, III.5, and III.6. The permittee shall not operate EU001 unless the plan, or an alternate plan, is implemented and maintained. Any changes to the plan by the permittee or as reasonably requested by the AQD shall be submitted to the AQD District Supervisor within 30 days. **(R 336.1224, R 336.1225, R 336.1301, R 336.1702(a), R 336.1901, 40 CFR Part 61 Subpart M)**
8. The permittee shall not operate EU001 unless the nuisance minimization plan for fire prevention for all material storage piles has been submitted within 45 days of permit issuance and is implemented and maintained. The nuisance minimization plan shall, at a minimum, specify the following:
  - a) An identification of all potential locations on-site for material storage piles.
  - b) An identification of all approved methods and materials for fire suppression.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a fire.Amendments to the nuisance minimization plan shall be submitted to the AQD District Supervisor for review and approval. **(R 336.1310, R 336.1901, 40 CFR 52.21(c) & (d))**
9. The permittee shall not operate EU001 unless the nuisance minimization plan for fugitive dust for all plant roadways, the plant yard, all material storage piles, and all material handling operations specified in Appendix A (or an amended plan approved by the AQD District Supervisor) has been implemented and is maintained.<sup>1</sup> **(R 336.1901, 40 CFR 52.21(c) & (d))**
10. The permittee shall not operate EU001 unless a MAP, as described in Rule 911(2), for EU001, has been submitted within 45 days of permit issuance, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
  - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description

- of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
- b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.
  - c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1224, R 336.1225, R 336.1301, R 336.1331, R 336.1910, R 336.1911, 40 CFR 52.21(c) & (d))**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

- 1. The permittee shall install, calibrate, maintain, and operate, in a satisfactory manner, devices to monitor the water injection rate and the shredder motor current on a continuous basis for EU001. **(R 336.1224, R 336.1225, R 336.1301, R 336.1910)**
- 2. The permittee shall not operate EU001 unless all conveyors that carry the dry non-metal and automotive shredder residue are covered and a chute at the discharge end of each conveyor is in place. **(R 336.1301, R 336.1303, R 336.1901)**

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

- 1. Within 180 days of the trial operation of the shredder, the permittee shall verify visible emissions from the shredder portion, ferrous separation portion, and the non-ferrous portion of EU001 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in the table below.

<b>Pollutant</b>	<b>Test Method Reference</b>
Visible Emission	40 CFR Part 51, Appendix M; 40 CFR Part 60, Appendix A

An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1301, R 336.1303, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

- 2. Upon request of the AQD District Supervisor, the permittee, shall determine the PM2.5, VOC, lead, and/or mercury emission factors (in lb/ton of material processed) from the shredder portion of EU001 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in the table below.

<b>Pollutant</b>	<b>Test Method Reference</b>
PM2.5	40 CFR Part 51, Appendix M
VOC	40 CFR Part 60, Appendix A
Lead	40 CFR Part 60, Appendix A
Mercury	40 CFR Part 60, Appendix A

An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1225, R 336.1331, R 336.1702, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

3. On and after an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed, the permittee, upon request of the AQD District Supervisor, shall determine the PM emission rate from the stack portion of EU001 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in the table below.

<b>Pollutant</b>	<b>Test Method Reference</b>
PM	40 CFR Part 60, Appendix A; Part 10 of the Michigan Air Pollution Control Rules

An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1225, R 336.1331, R 336.1702, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

4. Within 90 days of the completion of the installation of an exhaust hood and stack, meeting the requirements of SC VIII.1, the permittee shall determine the lead emission factor (in lb/ton of material processed) from the stack portion of EU001 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in the table below.

<b>Pollutant</b>	<b>Test Method Reference</b>
Lead	40 CFR Part 60, Appendix A

An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1225, R 336.1331, R 336.1702, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

## **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor and make them available by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901, 40 CFR 52.21(c) & (d))**
2. The permittee shall keep, in a satisfactory manner, daily records of the water injection rate and the shredder motor current for EU001. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(336.1224, R 336.1225, R 336.1301, R 336.1331, 40 CFR 52.21(c) & (d))**
3. The permittee shall monitor the shredder portion, ferrous separation portion, the non-ferrous portion, and all conveyors and transfer points of EU001 to verify compliance with the opacity limit by taking visible emission readings utilizing EPA's Method 9, a minimum of once per calendar week when the equipment is operating. If visible emissions are observed the permittee shall take corrective action as described in the MAP and document the corrective action taken. **(R 336.1301, R 336.1303, 40 CFR 52.21(c) & (d))**

4. The permittee shall keep, in a satisfactory manner, weekly records of all visible emission readings. At a minimum, records shall include the date, time, name of observer/reader, whether the reader is certified, status of visible emissions (percent opacity), and any corrective action taken. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1301, R 336.1303, 40 CFR 52.21(c) & (d))**
5. The permittee shall keep records of the amount of material (total) processed in EU001 in tons per calendar day, in tons per calendar month, and in tons per 12-month rolling time period as determined at the end of each calendar month and the amount of auto scrap material processed in EU001 in tons per 12-month rolling time period as determined at the end of each calendar month. The records shall be kept in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901, 40 CFR 52.21(c) & (d))**
6. The permittee shall keep the following information on a monthly basis for EU001:
  - a) VOC emission factor, in lb VOC/ton of material processed. The permittee shall use an emission factor of 0.077 lb VOC/ton of material processed unless an alternate emission factor has been approved by the AQD District Supervisor.
  - b) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - c) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1702(a))**

7. The permittee shall keep the following information on a calendar day basis for EU001:
  - a) PM2.5 emission factor, in lb PM2.5/ton of material processed. The permittee shall use an emission factor of 0.0194 lb PM2.5/ton of material processed unless an alternate emission factor has been approved by the AQD District Supervisor.
  - b) PM2.5 mass emission calculations determining the daily emission rate in pounds per calendar day.

The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(40 CFR 52.21(c) & (d))**

8. The permittee shall keep the following information on a monthly basis for EU001:
  - a) Lead emission factor, in lb lead/ton of material processed. The permittee shall use an emission factor of  $1.48 \times 10^{-4}$  lb lead/ton of material processed unless an alternate emission factor has been approved by the AQD District Supervisor.
  - b) Lead mass emission calculations determining the monthly emission rate in pounds per calendar month.
  - c) Lead mass emission calculations determining the annual emission rate in pounds per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(40 CFR 52.21(c) & (d))**

9. The permittee shall keep the following information on a monthly basis for EU001:
  - a) Mercury emission factor, in lb mercury/ton of material processed. The permittee shall use an emission factor of  $1.20 \times 10^{-5}$  lb mercury/ton of material processed unless an alternate emission factor has been approved by the AQD District Supervisor.
  - b) Mercury mass emission calculations determining the monthly emission rate in pounds per calendar month.
  - c) Mercury mass emission calculations determining the annual emission rate in pounds per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep all records on file at the facility and make them available to the Department upon request.<sup>1</sup> **(R 336.1225)**

10. The permittee shall keep daily records of the total volume of non-metal material and fluff staged. The records shall be kept in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1901, 40 CFR 52.21(c) & (d))**

11. The permittee shall keep records of all fire prevention activities as required by SC III.8. The permittee shall keep all records on file and make them available to the Department upon request. **(R 336.1310, R 336.1901)**
12. The permittee shall keep records of all fugitive dust control inspections and all dust control activities as required by Appendix A. The permittee shall keep all records on file and make them available to the Department upon request.<sup>1</sup> **(R 336.1901)**

## **VII. REPORTING**

1. Within 30 days after completion of the installation, construction, reconstruction, relocation, or modification authorized by this Permit to Install, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. Completion of the installation, construction, reconstruction, relocation, or modification is considered to occur not later than commencement of trial operation of EU001. **(R 336.1201(7)(a))**
2. Within 30 days after installation of the hood and stack on the shredder portion of EU001, the permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, in writing, of the completion of the activity. **(R 336.1201(7)(a))**

## **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV001	30 <sup>a</sup>	60 <sup>a</sup>	R 336.1225, 40 CFR 52.21(c) & (d)

<sup>a</sup> This parameter applies on and after installation of an exhaust hood and stack.

## **IX. OTHER REQUIREMENT(S)**

1. Within 18 months of the commencement of trial operation of EU001, the permittee, shall equip the shredder portion of EU001 with an exhaust hood and stack that meets the requirements of SC VIII.1. **(R 336.1224, R 336.1225, R 336.1702, R 336.1901, 40 CFR 52.21(c) & (d))**

### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

<sup>2</sup> This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

<sup>3</sup> This limit applies until an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed.

<sup>4</sup> This limit applies on and after the installation of an exhaust hood and stack that meets the requirements of SC VIII.1.

**FGFACILITY CONDITIONS**

**DESCRIPTION**

The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment and exempt equipment.

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. Hexavalent chromium (CAS No. 18540-29-9)	0.31 lb/yr <sup>1,3</sup>	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1225(2)
2. Hexavalent chromium (CAS No. 18540-29-9)	0.45 lb/yr <sup>1,4</sup>	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R 336.1225(2)

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

NA

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. Within 90 days of the completion of the installation of an exhaust hood and stack, meeting the requirements of SC VIII.1 in EU001, the permittee shall determine the hexavalent chromium emission factor (in lb/ton of material processed) from the stack portion of EU001 by testing at owner's expense, in accordance with Department requirements. Testing shall be performed using an approved EPA Method listed in the table below.

<b>Pollutant</b>	<b>Test Method Reference</b>
Hexavalent Chromium	40 CFR Part 60, Appendix A

An alternate method, or a modification to the approved EPA Method, may be specified in an AQD-approved Test Protocol. No less than 30 days prior to testing, the permittee shall submit a complete test plan to the AQD Technical Programs Unit and District Office. The AQD must approve the final plan prior to testing, including any modifications to the method in the test protocol that are proposed after initial submittal. The permittee must submit a complete report of the test results to the AQD Technical Programs Unit and District Office within 60 days following the last date of the test. **(R 336.1225, R 336.1331, R 336.1702, R 336.2001, R 336.2003, R 336.2004, 40 CFR 52.21(c) & (d))**

## **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1225(2))**
2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
  - a) Tons of hexavalent chromium (CAS No. 18540-29-9) containing material processed.
  - b) The Hexavalent chromium emission factor, in lbs hexavalent chromium/ton of metal processed (using an emission factor of  $4.48 \times 10^{-6}$  lb hexavalent chromium/ton of metal processed until the completion of a stack test, after which an emission factor based upon the most recent acceptable stack test shall be used. Alternatively, an emission factor acceptable to the AQD District Supervisor may be used).
  - c) Hexavalent chromium mass emission calculations determining the monthly emission rate in pounds per calendar month.
  - d) Hexavalent chromium mass emission calculations determining the annual emission rate in pounds per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records using mass balance or an alternate method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.<sup>1</sup> **(R 336.1225(2))**

## **VII. REPORTING**

NA

## **VIII. STACK/VENT RESTRICTION(S)**

NA

## **IX. OTHER REQUIREMENT(S)**

NA

### **Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

<sup>2</sup> This condition is federally enforceable and was established pursuant to Rule 201(1)(a).

<sup>3</sup> This limit applies until an exhaust hood and stack, meeting the requirements of SC VIII.1, is installed.

<sup>4</sup> This limit applies on and after the installation of an exhaust hood and stack that meets the requirements of SC VIII.1 in EU001.

## **APPENDIX A**

### **Nuisance Minimization Plan for Fugitive Dust**

#### **I. Plant/Shredder**

- a) The drop distance at each transfer point throughout the shredder shall be reduced to the minimum the equipment can reasonably achieve.
- b) Corrective actions and/or operational changes shall be undertaken to reduce opacity throughout the plant should opacity above 10% be observed.
- c) Records of all corrective actions and operational changes undertaken to reduce opacity.

#### **II. Truck Traffic**

- a) On-site vehicles shall be loaded to prevent their contents from dropping, leaking, blowing or otherwise escaping. This shall be accomplished by loading so that no part of the load shall come in contact within six inches of the top of any sideboard, side panel or tailgate, otherwise, the truck shall be tarped.
- b) Corrective actions and/or operational changes shall be undertaken to reduce opacity truck traffic should opacity above 20% be observed.
- c) Records of all corrective actions and operational changes undertaken to reduce opacity.

#### **III. Site Roadways and the Plant Yard**

- a) The dust on the site roadways and the plant yard shall be controlled by applications of water, calcium chloride or other acceptable and approved fugitive dust control compounds. Applications of dust suppressants shall be done as often as necessary to meet an opacity limit of 5% as determined by reference test method 9D.
- b) All paved roadways/plant yard shall be swept, as needed, between applications of dust suppressants.
- c) Any material spillage on roads shall be cleaned up in a timely manner.
- d) Corrective actions and/or operational changes shall be undertaken to reduce opacity from site roadways and throughout the plant yard should opacity above 5% be observed.
- e) A record of all applications of dust suppressants, and roadway and the plant yard sweepings shall be kept on file for the most recent five-year period and be made available to the AQD upon request.
- f) Records of all corrective actions and operational changes undertaken to reduce opacity.

#### **IV. Storage Piles**

- a) Stockpiling of all nonmetallic materials shall be performed to minimize drop distance and control potential dust problems.
- b) Stockpiles shall be watered on an as needed basis in order to meet an opacity limit of 20% as determined by reference test method 9D. Equipment to apply water or dust suppressant shall be available at the site, or on call for use at the site, within a given operating day.
- c) Corrective actions and/or operational changes shall be undertaken to reduce opacity from storage piles should opacity above 20% be observed.

- d) A record of all watering shall be kept on file for the most recent five-year period and be made available to the AQD upon request.
- e) Records of all corrective actions and operational changes undertaken to reduce opacity.

**V. AQD/EGLE Inspection**

The provisions and procedures of this plan are subject to adjustment by written notification from the AQD, if following an inspection, the AQD finds the fugitive dust requirements and/or the permitted opacity limits are not being met.