

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY
AIR QUALITY DIVISION**

August 24, 2023

**PERMIT TO INSTALL
72-22A**

**ISSUED TO
Seal Bond, Inc.**

**LOCATED AT
1251 East Mount Garfield Road
Norton Shores, Michigan 49441**

**IN THE COUNTY OF
Muskegon**

**STATE REGISTRATION NUMBER
P1262**

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: August 14, 2023	
DATE PERMIT TO INSTALL APPROVED: August 24, 2023	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....3
GENERAL CONDITIONS4
EMISSION UNIT SPECIAL CONDITIONS.....6
 EMISSION UNIT SUMMARY TABLE6
FLEXIBLE GROUP SPECIAL CONDITIONS.....8
 FLEXIBLE GROUP SUMMARY TABLE8
 FGADHESIVEMFG9
 FGVESSELCLEAN12
FGFACILITY CONDITIONS.....14

COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfuction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO ₂ e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H ₂ S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO _x	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO ₂	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EULARGEREYNOLDS	Blending vessel M1, nominal operating volume 185 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUROSS	Blending vessel M2, nominal operating volume 185 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUSMALLREYNOLDS	Blending vessel M3, nominal operating volume 46 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUSUPREYNOLDS	Blending vessel M4, nominal operating volume 295 gallons. Vacuum operations normally conducted at vacuum vent 2.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUHUGEST	Blending vessel M6, nominal operating volume 530 gallons. Vacuum operations normally conducted at vacuum vent 4.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUHOCKMEYER	Blending vessel M5, nominal operating volume 400 gallons. Vacuum operations normally conducted at vacuum vent 2.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUHOCKMEYER2	Blending vessel M7, nominal operating volume 500 gallons. Vacuum operations normally conducted at vacuum vent 3.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUMYERS	Blending vessel M8, nominal operating volume 35 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUFUSION1	Blending vessel M10, nominal operating volume 470 gallons. Vacuum operations normally conducted at vacuum vent 3.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUFUSION2	Blending vessel M11, nominal operating volume 500 gallons. Vacuum operations normally conducted at vacuum vent 5.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EUFUSION3	Blending vessel M12, nominal operating volume 500 gallons. Vacuum operations normally conducted at vacuum vent 5.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EULM1	R&D blending vessel LM1, nominal operating volume 1 gallon. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EULM2	R&D blending vessel LM2, nominal operating volume 4 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EULM3	Blending vessel LM3, nominal operating volume 4 gallons. Vacuum operations normally conducted at vacuum vent 1.	6-9-2022	FGADHESIVEMFG, FGVESSELCLEAN
EURA1	Blending vessel RA1, nominal operating volume 500 gallons. Operations vented through SV-STACK2.	TBD	FGADHESIVEMFG, FGVESSELCLEAN

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EURA2	Blending vessel RA2, nominal operating volume 300 gallons. Operations vented through SV-STACK2.	TBD	FGADHESIVEMFG FGVESSELCLEAN

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

FLEXIBLE GROUP SPECIAL CONDITIONS

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGADHESIVEMFG	Batch processes for manufacturing adhesives. Process steps include charging/adding materials, blending, mixing, heating, cooling, use of vacuum, and packaging.	EULARGEREYNOLDS, EUROSS, EUSMALLREYNOLDS, EUSUPREYNOLDS, EUHUGEST, EUHOCKMEYER, EUHOCKMEYER2, EUMYERS, EUFUSION1, EUFUSION2, EUFUSION3, EULM1, EULM2, EULM3, EURA1, EURA2
FGVESSELCLEAN	Use of clean-up solvent to remove product residue from blending vessels and mixer blades. Blending vessels are generally cleaned at the tub cleaning area and mixer blades are cleaned at the mixer location.	EULARGEREYNOLDS, EUROSS, EUSMALLREYNOLDS, EUSUPREYNOLDS, EUHUGEST, EUHOCKMEYER, EUHOCKMEYER2, EUMYERS, EUFUSION1, EUFUSION2, EUFUSION3, EULM1, EULM2, EULM3, EURA1, EURA2

**FGADHESIVEMFG
 FLEXIBLE GROUP CONDITIONS**

DESCRIPTION

Batch processes for manufacturing adhesives. Process steps include charging/adding materials, blending, mixing, heating, cooling, use of vacuum, and packaging.

Emission Unit: EULARGEREYNOLDS, EUROSS, EUSMALLREYNOLDS, EUSUPREYNOLDS, EUHUGEST, EUHOCKMEYER, EUHOCKMEYER2, EUMYERS, EUFUSION1, EUFUSION2, EUFUSION3, EULM1, EULM2, EULM3, EURA1, EURA2

POLLUTION CONTROL EQUIPMENT

Batches run with vinyl trimethoxysilane (VTMO) added in the beginning of the batch are controlled by a VTMO scrubber

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	3.3 tpy	12-month rolling time period as determined at the end of each calendar month	FGADHESIVEMFG	SC VI.4	R 336.1205(3), R 336.1702(a)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. Total dry solids material	12,500,000 lb used per year ¹	12-month rolling time period as determined at the end of each calendar month	FGADHESIVEMFG	SC VI.2	R 336.1225
2. Total liquid and paste material	8,820,142 lb used per year ¹	12-month rolling time period as determined at the end of each calendar month	FGADHESIVEMFG	SC VI.3	R 336.1205(3), R 336.1225, R 336.1702(a)

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall not operate FGADHESIVEMFG unless a malfunction abatement plan (MAP) as described in Rule 911(2), for the vinyl trimethoxysilane (VTMO) scrubber, has been submitted within 90 days of permit issuance, and is implemented and maintained. The MAP shall, at a minimum, specify the following:
 - a) A complete preventative maintenance program including identification of the supervisory personnel responsible for overseeing the inspection, maintenance, and repair of air-cleaning devices, a description of the items or conditions that shall be inspected, the frequency of the inspections or repairs, and an identification of the major replacement parts that shall be maintained in inventory for quick replacement.
 - b) An identification of the source and air-cleaning device operating variables that shall be monitored to detect a malfunction or failure, the normal operating range of these variables, and a description of the method of monitoring or surveillance procedures.

- c) A description of the corrective procedures or operational changes that shall be taken in the event of a malfunction or failure to achieve compliance with the applicable emission limits.

If at any time the MAP fails to address or inadequately addresses an event that meets the characteristics of a malfunction, the permittee shall amend the MAP within 45 days after such an event occurs. The permittee shall also amend the MAP within 45 days, if new equipment is installed or upon request from the District Supervisor. The permittee shall submit the MAP and any amendments to the MAP to the AQD District Supervisor for review and approval. If the AQD does not notify the permittee within 90 days of submittal, the MAP or amended MAP shall be considered approved. Until an amended plan is approved, the permittee shall implement corrective procedures or operational changes to achieve compliance with all applicable emission limits. **(R 336.1225, R 336.1910, R 336.1911)**

IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not introduce VTMO at the beginning of any batch in FGADHESIVEMFG unless the reactor exhausts to a VTMO scrubber system that is installed, maintained, and operated in a satisfactory manner acceptable to the AQD District Supervisor. **(R 336.1225, R 336.1910)**

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition.¹ **(R 336.1225)**
2. The permittee shall monitor and record, in a satisfactory manner, the amount of all dry solid materials used in FGADHESIVEMFG monthly, for the preceding 12-month rolling time period, using a method acceptable to the AQD District Supervisor. The permittee shall keep all records on file at the facility and make them available to the Department upon request.¹ **(R 336.1225)**
3. The permittee shall monitor and record, in a satisfactory manner, the amount of all liquid and paste materials used in FGADHESIVEMFG monthly, for the preceding 12-month rolling time period, using a method acceptable to the AQD District Supervisor. The permittee shall keep all records on file at the facility and make them available to the Department upon request.¹ **(R 336.1205(3), R 336.1225, R 336.1702(a))**
4. The permittee shall keep the following information on a monthly basis for FGADHESIVEMFG:
 - a) Amount of each VOC-containing material used.
 - b) VOC content of each VOC-containing material used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records on file at the facility, in a format acceptable to the AQD District Supervisor, and make them available to the Department upon request. **(R 336.1205(3), R 336.1702(a))**

5. The permittee shall keep records of the number of batches run with VTMO added in the beginning on a monthly basis in a satisfactory manner acceptable to the AQD District Supervisor. **(R 336.1225, R 336.1910)**
6. The permittee shall keep records of the date and time that the VTMO scrubber is operated on a monthly basis in a satisfactory manner acceptable to the AQD District Supervisor. **(R 336.1225, R 336.1910)**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVVACVENT1	3	23	R 336.1225, 40 CFR 52.21(c) and (d)
2. SVVACVENT2	3	23	R 336.1225, 40 CFR 52.21(c) and (d)
3. SVVACVENT3	3	23	R 336.1225, 40 CFR 52.21(c) and (d)
4. SVVACVENT4	3	23	R 336.1225, 40 CFR 52.21(c) and (d)
5. SVVACVENT5	3	23	R 336.1225, 40 CFR 52.21(c) and (d)
6 SV-STACK2	12	19	R 336.1225, 40 CFR 52.21(c) and (d)

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

**FGVESSELCLEAN
 FLEXIBLE GROUP CONDITIONS**

DESCRIPTION

Use of clean-up solvent to remove product residue from blending vessels and mixer blades. Blending vessels are generally cleaned at the tub cleaning area and mixer blades are cleaned at the mixer location.

Emission Unit: EULARGEREYNOLDS, EUROSS, EUSMALLREYNOLDS, EUSUPREYNOLDS, EUHUGEST, EUHOCKMEYER, EUHOCKMEYER2, EUMYERS, EUFUSION1, EUFUSION2, EUFUSION3, EULM1, EULM2, EULM3, EURA1, EURA2

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	28.63 tpy	12-month rolling time period as determined at the end of each calendar month	FGVESSELCLEAN	SC VI.3	R 336.1205(3), R 336.1702(a)

II. MATERIAL LIMIT(S)

Material	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. Net hydrotreated light distillates (CAS 64742-47-8) used*	7,000 gallons per year ¹	12-month rolling time period as determined at the end of each calendar month	FGVESSELCLEAN	SC VI.2	R 336.1205(3), R 336.1702(a)

* For each material, "Net used" refers to the amount of material used during a period minus the amount of material sent for recovery, recycling, reclaim, or disposal during the period.

III. PROCESS/OPERATIONAL RESTRICTION(S)

1. The permittee shall capture all waste clean-up solvents and shall store them in closed containers. The permittee shall dispose of all waste clean-up solvents in an acceptable manner in compliance with all applicable state rules and federal regulations. **(R 336.1702(a))**
2. The permittee shall handle all clean-up solvents and waste clean-up solvents in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. **(R 336.1225, R 336.1702(a))**

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205(3), R 336.1225, R 336.1702(a))**
2. The permittee shall keep the following information on a monthly basis for the use of hydrotreated light distillates (CAS 64742-47-8) as clean-up solvents in FGVESSEL CLEAN:
 - a) Gallons used, reclaimed, recycled, recovered and disposed.
 - b) Calculation determining the net amount of clean-up solvent used per month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request.¹ **(R 336.1205(3), R 336.1225)**

3. The permittee shall keep the following information on a monthly basis for FGVESSEL CLEAN:
 - a) Gallons of each clean-up solvent used, reclaimed, recycled, recovered, and disposed.
 - b) VOC content of each clean-up solvent used.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records on file at the facility, in a format acceptable to the AQD District Supervisor, and make them available to the Department upon request. **(R 336.1205(3), R 336.1702(a))**

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-STACK1	18	29	R 336.1225, 40 CFR 52.21(c) and (d)

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).

FGFACILITY CONDITIONS

DESCRIPTION

The following conditions apply source-wide to all process equipment including equipment covered by other permits, grand-fathered equipment, and exempt equipment.

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1. VOC	Less than 36.0 tpy	12-month rolling time period as determined at the end of each calendar month	FGFACILITY	SC VI.2	R336.1205(3)

II. MATERIAL LIMIT(S)

NA

III. PROCESS/OPERATIONAL RESTRICTION(S)

NA

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 30th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1205(3))
2. The permittee shall keep the following information on a monthly basis for FGFACILITY:
 - a) Amount of each VOC -containing material used, reclaimed, recycled, recovered, and disposed.
 - b) VOC content of each VOC-containing material used, reclaimed, recycled, recovered, and disposed.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records on file at the facility, in a format acceptable to the AQD District Supervisor, and make them available to the Department upon request. (R 336.1205(3))

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).