



Marathon Petroleum Company LP
1001 Oakwood
Detroit, MI 48217

RECEIVED

APR 12 2017

AIR QUALITY DIV.

REPORT ON COMPLIANCE TESTING


Performed for:
**MARATHON PETROLEUM COMPANY LP
DETROIT REFINERY**

FCCU REGENERATOR STACK (SVFCCU)


Client Reference No: 4101004604
CleanAir Project No: 13181-2
Revision R0: April 5, 2017

To the best of our knowledge, the data presented in this report are accurate, complete, error free, legible and representative of the actual emissions during the test program. Clean Air Engineering operates in conformance with the requirements of ASTM D7036-04 Standard Practice for Competence of Air Emission Testing Bodies.

Submitted by,


Andy Obuchowski
Midwest Engineering Group
Business Leader
aobuchowski@cleanair.com
(800) 627-0033 ext. 4537

Reviewed by,


Bill Ansell
Midwest Engineering Group
Technical Leader
bansell@cleanair.com
(800) 627-0033 ext. 4545

PROJECT OVERVIEW

1-1

INTRODUCTION

Marathon Petroleum Company LP (MPC) contracted Clean Air Engineering (CleanAir) to perform emission measurements at the Detroit Refinery for compliance purposes.

All testing was conducted in accordance with the regulations set-forth by the United States Environmental Protection Agency (USEPA) and the Michigan Department of Environmental Quality (DEQ). The permit limits are referenced in Michigan Department of Environmental Quality, Renewable Operating Permit No. MI-ROP-A9831-2012c.

Key Project Participants

Individuals responsible for coordinating and conducting the test program were:

Crystal Davis – MPC
Joe Reidy – MPC
Chad Eilering – CleanAir

Test Program Parameters

The testing was performed at the FCCU Regenerator Stack (Emission Unit ID No. EU11-FCCU-S1; Stack ID No. SVFCCU) on February 28 and March 1, 2017, and included the following emissions measurements:

- particulate matter (PM), assumed equivalent to non-sulfate filterable particulate matter (NSFPM)
- total particulate matter less than or equal to 10 microns (μm) in diameter (Total PM_{10}), assumed equivalent to the sum of the following constituents:
 - non-sulfate filterable particulate matter (NSFPM)
 - condensable particulate matter (CPM)
- ammonia (NH_3)
- sulfuric acid (H_2SO_4)
- volatile organic compounds (VOCs), assumed equivalent to total hydrocarbons (THC) minus the following constituents:
 - methane (CH_4)
 - ethane (C_2H_6)
- flue gas composition (e.g., O_2 , CO_2 , H_2O)
- flue gas flow rate
- flue gas velocity decay (wall-effects)

RECEIVED

APR 12 2017

AIR QUALITY DIV.

PROJECT OVERVIEW**TEST PROGRAM SYNOPSIS****Test Schedule**

The on-site schedule followed during the test program is outlined in Table 1-1.

**Table 1-1:
Schedule of Activities**

Run Number	Location	Method	Analyte	Date	Start Time	End Time
1	FCCU Regenerator Stack	USEPA Method 5F/202	NSFPM/CPM	02/28/17	10:35	12:11
2	FCCU Regenerator Stack	USEPA Method 5F/202	NSFPM/CPM	02/28/17	13:33	14:45
3	FCCU Regenerator Stack	USEPA Method 5F/202	NSFPM/CPM	02/28/17	15:57	17:08
1	FCCU Regenerator Stack	CTM-027	NH ₃	02/28/17	10:35	12:11
2	FCCU Regenerator Stack	CTM-027	NH ₃	02/28/17	13:33	14:45
3	FCCU Regenerator Stack	CTM-027	NH ₃	02/28/17	15:57	17:08
1	FCCU Regenerator Stack	USEPA Method 3A/18/25A	O ₂ /CO ₂ /CH ₄ /C ₂ H ₆ /THC	03/01/17	11:00	12:04
2	FCCU Regenerator Stack	USEPA Method 3A/18/25A	O ₂ /CO ₂ /CH ₄ /C ₂ H ₆ /THC	03/01/17	12:24	13:26
3	FCCU Regenerator Stack	USEPA Method 3A/18/25A	O ₂ /CO ₂ /CH ₄ /C ₂ H ₆ /THC	03/01/17	13:53	14:55
1	FCCU Regenerator Stack	Draft ASTM CCM	H ₂ SO ₄	03/01/17	10:53	11:53
2	FCCU Regenerator Stack	Draft ASTM CCM	H ₂ SO ₄	03/01/17	12:19	13:26
3	FCCU Regenerator Stack	Draft ASTM CCM	H ₂ SO ₄	03/01/17	13:46	14:46
1	FCCU Regenerator Stack	USEPA Method 2H	Wall Effects	02/27/17	13:40	13:59
1	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	02/28/17	07:37	07:53
2	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	02/28/17	12:24	12:40
3	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	02/28/17	14:54	15:04
4	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	02/28/17	17:25	17:42
5	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	03/01/17	10:50	11:03
6	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	03/01/17	12:14	12:27
7	FCCU Regenerator Stack	USEPA Method 2F	3-D Velocity & Flow Rate	03/01/17	13:43	13:54

032117 163107

PROJECT OVERVIEW**Results Summary**

Tables 1-2 through 1-4 and Figures 1-1 and 1-2 (on the following pages) summarize the results of the test program. A more detailed presentation of the test conditions and results of analysis are shown on pages 2-1 through 2-4.

**Table 1-2:
Summary of NSFPM, CPM and Total PM₁₀ Results (USEPA 5F/202)**

<u>FCCU Regenerator Stack</u>			NSFPM Rate (lb/Mlb coke)	CPM Rate (lb/Mlb coke)	Total PM ₁₀ Rate (lb/Mlb coke)
Test Dates: 2/28/17					
Coke Burn Rate (lb/hr)	24,666	Run 1	0.2	0.6	0.8
FCC Rate (bpd)	40,998	Run 2	0.2	0.6	0.8
Aqueous NH ₃ Injection (lb/hr)	31.0	Run 3	0.2	0.6	0.8
ESP Operation	Both/LPR				
		Average	0.2	0.6	0.8
		Limit	0.8		1.1

Note: Average includes 3 runs for all parameters.

3/21/2017 16:57

**Table 1-3:
Summary of NH₃ Results (USEPA CTM-027)**

<u>FCCU Regenerator Stack</u>			NH ₃ Conc. (ppmdv)	NH ₃ Slip (lb/hr)	NH ₃ Slip (lb/Mlb coke)
Test Dates: 2/28/17					
Coke Burn Rate (lb /hr)	24,666	Run 1	17	3.4	0.14
FCC Rate (bpd)	40,998	Run 2	16	3.3	0.13
Aqueous NH ₃ Injection (lb/hr)	31.0	Run 3	16	3.2	0.13
ESP Operation	Both/LPR				
		Average	16	3.3	0.13

Note: Average includes 3 runs for all parameters.

3/23/2017 16:58

**Table 1-4:
Summary of H₂SO₄ and VOC Results (Draft ASTM CCM & USEPA 18/25A)**

<u>Source</u>	Constituent (Units)	Sampling Method	Average Emission	Permit Limit ¹
<u>FCCU Regenerator Stack</u>				
	H ₂ SO ₄ (lb/Mlb coke)	Draft ASTM CCM	9.3E-03	N/A
	H ₂ SO ₄ (ppmdv)	Draft ASTM CCM	0.20	N/A
	VOC (Ton/yr)	USEPA 25A / 18	5.4	21
	VOC (lb/Mlb coke)	USEPA 25A / 18	0.050	N/A

¹ Permit limit obtained from MDEQ Permit No. MI-ROP-A9831-2012c.

032117 165723




Figure 1-1: NSFPM, CPM and Total PM₁₀ Results




Figure 1-2: CPM and NH₃ Results

PROJECT OVERVIEW

1-5

Discussion of Test Program***Flow Rate Measurements***

A wall-effects adjustment factor (WAF) was determined per EPA Method 2H prior to the start of the first test run.

3-D flow traverses per EPA Method 2F were performed before and after each EPA Method 5F/202 and CTM-027 test run and during each EPA Method 18/25A and Draft ASTM CCM test run.

NSFPM and CPM Testing - USEPA Method 5F/202

Three 60-minute Method 5F/202 test runs were performed on February 28.

For this test program, PM emission rate is assumed equivalent to NSFPM emission rate and PM₁₀ emission rate is assumed equivalent to the sum of NSFPM and CPM emission rates (units of lb/hr, ton/yr, or lb/Mlb coke for all constituents). For emissions inventory purposes, MPC applies a correction factor to NSFPM to eliminate particles with a diameter less than 10 microns. Application of that correction factor is not included in this test report.

The analytical procedures in EPA Method 202 include an ammonium titration of the inorganic sample fractions with pH less than 7.0 to neutralize acids with hygroscopic properties such as H₂SO₄ that may be present in the sample. This step speeds up the sample desiccation process and allows the samples to reach a constant weight prior to weighing. The weight of ammonium added to the sample as a result of the titration is subtracted from the analytical result.

CleanAir Analytical Services performed the gravimetric analysis and has determined that only samples with an initial pH less than 4.5 require a significant amount of ammonium neutralization, resulting in a correction in excess of 0.5 mg. Based on this observation, the laboratory has altered its procedures. Only samples with a pH lower than 4.5 are titrated.

All of the inorganic sample fractions analyzed from Runs 1 through 3 had a pH less than 4.5 and were titrated. The field train reagent blanks had a pH above 4.5 and were not titrated. The train blanks were observed to reach a constant weight without having to titrate the sample.

NH₃ Testing – USEPA Conditional Test Method (CTM)-027 - Stack

Three 60-minute CTM-027 test runs were performed on February 28. Each test run was performed concurrently with Method 5F/202 testing.

PROJECT OVERVIEW

1-6

H₂SO₄ Testing – Draft ASTM Controlled Condensation Method

Prior to the first official test run, a 60-minute sample conditioning run (Run 0) was performed in order to minimize the absorption capacity of the front-half components of the sample train (upstream of the H₂SO₄-collecting portion of the sample train). The conditioning run was recovered in the same manner as the official test runs, but was not analyzed or included in the final results.

Following the conditioning run on March 1, three official 60-minute test runs were performed. The results were expressed as the average of three official runs.

VOC Testing – USEPA Method 25A and Method 18

Three approximately 60-minute Method 25A test runs for THC were performed concurrently with three approximately 60-minute Method 18 integrated gas sample (IGS) collections for CH₄ and C₂H₆.

VOC emission rate is normally equivalent to THC emission rate, minus CH₄ and C₂H₆ emission rate (units of lb/hr, Ton/yr, or lb/Mlb coke for all constituents). For CH₄ and C₂H₆, a non-detectable result was obtained for Runs 1 through 3, so no correction was made to the THC results. Therefore, VOC emissions for Runs 1 through 3 were equivalent to THC emissions only. The final VOC results were expressed as the average of three runs.

Calculation of Final Results

Sample flow rates as determined by EPA Method 2, which is incorporated into Method 5F/202 and CTM-027, without the WAF corrections factor were used to calculate isokinetic sampling conditions.

Mass-based emission rates in units of pounds per hour (lb/hr) for Method 5F/202 and CTM-027 were calculated using the applicable average pre-run and post-run flow rate determined by Method 2F combined with the respective WAF correction factor. Mass-based emission rates in units of pounds per hour (lb/hr) for Method 18/25A and Draft ASTM CCM were calculated using the applicable concurrent flow rate determined by Method 2F combined with the respective WAF correction factor.

Emission rates in units of tons per year (Ton/yr) were calculated using an assumed capacity factor of 8,760 operating hours per year. Emission rates in units of pounds per 1,000 pounds of coke burn (lb/Mlb coke) were calculated using coke burn rate data provided by MPC.

Ammonia (NH₃) injection rates shown in Section 2 tables are the aqueous NH₃ (11FC2032) times a factor of 0.2.

End of Section 1 – Project Overview

RESULTS**Table 2-1:
NSFPM, CPM, and Total PM₁₀ (USEPA M5F/202)**

Run No.		1	2	3	Average
Date (2017)		Feb 28	Feb 28	Feb 28	
Start Time (approx.)		10:35	13:33	15:57	
Stop Time (approx.)		12:11	14:45	17:08	
Process Conditions					
R _P	Production rate (Mlb coke/hr)	24.7	24.6	24.7	24.7
P ₁	FCC charge rate (bpd)	40,992	40,997	41,006	40,998
P ₂	Ammonia Injection (lb/hr)	6.2	6.2	6.2	6.2
P ₃	ESP Operation	Both/LPR	Both/LPR	Both/LPR	
Cap	Capacity factor (hours/year)	8,760	8,760	8,760	8,760
Gas Conditions					
O ₂	Oxygen (dry volume %)	2.5	1.9	1.9	2.1
CO ₂	Carbon dioxide (dry volume %)	15.7	16.3	16.2	16.1
T _s	Sample temperature (°F)	522	523	522	522
B _w	Actual water vapor in gas (% by volume)	9.9	9.9	11.5	10.4
Gas Flow Rate¹					
Q _a	Volumetric flow rate, actual (acfm)	161,000	162,000	161,000	162,000
Q _s	Volumetric flow rate, standard (scfm)	85,100	85,700	84,900	85,200
Q _{std}	Volumetric flow rate, dry standard (dscfm)	76,700	77,300	75,100	76,300
Sampling Data					
V _{nsfld}	Volume metered, standard (dscf)	40.29	40.82	40.45	40.52
%I	Isokinetic sampling (%) ²	98.9	98.9	100.3	99.4
Laboratory Data					
m _n	Total NSFPM(g)	0.01517	0.01475	0.02174	
m _{CPM}	Total CPM(g)	0.06006	0.06111	0.05985	
NSFPM Results					
C _{sd}	Particulate Concentration (lb/dscf)	8.30E-07	7.97E-07	1.19E-06	9.37E-07
E _{lb/hr}	Particulate Rate (lb/hr)	3.82	3.69	5.34	4.28
E _{T/yr}	Particulate Rate (Ton/yr)	16.7	16.2	23.4	18.8
E _{Rp}	Particulate Rate - Production-based (lb/Mlb coke)	0.155	0.150	0.216	0.174
CPM Results					
C _{sd}	Particulate Concentration (lb/dscf)	3.29E-06	3.30E-06	3.26E-06	3.28E-06
E _{lb/hr}	Particulate Rate (lb/hr)	15.1	15.3	14.7	15.0
E _{T/yr}	Particulate Rate (Ton/yr)	66.2	67.0	64.4	65.9
E _{Rp}	Particulate Rate - Production-based (lb/Mlb coke)	0.612	0.622	0.595	0.610
Total Particulate Matter Results					
C _{sd}	Particulate Concentration (lb/dscf)	4.12E-06	4.10E-06	4.45E-06	4.22E-06
E _{lb/hr}	Particulate Rate (lb/hr)	18.9	19.0	20.0	19.3
E _{T/yr}	Particulate Rate (Ton/yr)	82.9	83.2	87.8	84.7
E _{Rp}	Particulate Rate - Production-based (lb/Mlb coke)	0.767	0.772	0.812	0.784

Average includes 3 runs.

040517 125809

¹ Gas flow rates obtained from bracketing Method 2F test runs combined with the WAF determined by Method 2H.² Sample flow rates as determined by EPA Method 2 were used to calculate isokinetic sampling conditions.

RESULTS**Table 2-2:
NH₃ (USEPA CTM-027)**

Run No.		1	2	3	Average
Date (2017)		Feb 28	Feb 28	Feb 28	
Start Time (approx.)		10:35	13:33	15:57	
Stop Time (approx.)		12:11	14:45	17:08	
Process Conditions					
R _p	Production rate - (Mlb coke/hr)	24.7	24.6	24.7	24.7
P ₁	FCC charge rate - (bpd)	40,992	40,997	41,006	40,998
P ₂	Ammonia Injection - (lb/hr)	6.2	6.2	6.2	6.2
P ₃	ESP Operation	Both/LPR	Both/LPR	Both/LPR	
Cap	Capacity factor (hours/year)	8,760	8,760	8,760	8,760
Gas Conditions					
O ₂	Oxygen (dry volume %)	2.4	3.2	3.8	3.1
CO ₂	Carbon dioxide (dry volume %)	15.8	15.1	14.2	15.0
T _s	Sample temperature (°F)	523	523	523	523
B _w	Actual water vapor in gas (% by volume)	10.35	10.36	10.29	10.33
Gas Flow Rate¹					
Q _a	Volumetric flow rate, actual (acfm)	161,000	162,000	161,000	162,000
Q _s	Volumetric flow rate, standard (scfm)	85,100	85,700	84,900	85,200
Q _{std}	Volumetric flow rate, dry standard (dscfm)	76,700	77,300	75,100	76,300
Sampling Data					
V _{mstd}	Volume metered, standard (dscf)	40.91	41.83	40.21	40.98
%I	Isokinetic sampling (%) ²	100.7	101.3	102.1	101.3
Laboratory Data					
m _n	Total NH ₃ collected (mg)	13.77	13.59	13.00	
Ammonia (NH₃) Results					
C _{sd}	Ammonia Concentration (lb/dscf)	7.42E-07	7.17E-07	7.13E-07	7.24E-07
C _{sd}	Ammonia Concentration (ppmdv)	16.8	16.2	16.1	16.4
E _{lb/hr}	Ammonia Rate (lb/hr)	3.42	3.32	3.21	3.32
E _{T/yr}	Ammonia Rate (Ton/yr)	15.0	14.5	14.1	14.5
E _{Rp}	Ammonia Rate - Production-based (lb/Mlb coke)	0.138	0.135	0.130	0.134

Average includes 2 runs.

032317 165849

¹ Gas flow rates obtained from bracketing Method 2F test runs combined with the WAF determined by Method 2H.² Sample flow rates as determined by EPA Method 2 were used to calculate isokinetic sampling conditions.

RESULTS**Table 2-3:
H₂SO₄ Emissions (Draft ASTM CCM)**

Run No.		1	2	3	Average
Date (2017)		Mar 1	Mar 1	Mar 1	
Start Time (approx.)		10:53	12:19	13:46	
Stop Time (approx.)		11:53	13:26	14:46	
Process Conditions					
R _P	Coke burn rate (lb/hr)	24.6	24.6	24.7	24.6
P ₁	FCC charge rate (bpd)	40,995	40,989	41,010	40,998
P ₂	NH ₃ Injection (lb/hr)	6.2	6.1	6.0	6.1
Cap	Capacity factor (hours/year)	8,760	8,760	8,760	8,760
Gas Conditions					
O ₂	Oxygen (dry volume %)	2.2	2.8	2.1	2.4
CO ₂	Carbon dioxide (dry volume %)	17.7	15.6	16.2	16.5
T _s	Sample temperature (°F)	522	521	519	520
B _w	Actual water vapor in gas (% by volume)	10.4	9.9	10.8	10.4
Gas Flow Rate¹					
Q _a	Volumetric flow rate, actual (acfm)	158,000	165,400	164,000	162,500
Q _s	Volumetric flow rate, standard (scfm)	82,000	85,800	85,200	84,300
Q _{std}	Volumetric flow rate, dry standard (dscfm)	73,500	77,300	75,900	75,600
Sampling Data					
V _{mstd}	Volume metered, standard (dscf)	25.66	25.82	25.51	25.66
Laboratory Data (Ion Chromatography)					
m _n	Total H ₂ SO ₄ collected (mg)	0.6757	0.3670	0.7298	
Sulfuric Acid Vapor (H₂SO₄) Results					
C _{std}	H ₂ SO ₄ Concentration (lb/dscf)	5.81E-08	3.13E-08	6.31E-08	5.08E-08
C _{std}	H ₂ SO ₄ Concentration (ppmdv)	0.228	0.123	0.248	0.200
E _{lb/hr}	H ₂ SO ₄ Rate (lb/hr)	0.256	0.145	0.287	0.230
E _{T/yr}	H ₂ SO ₄ Rate (Ton/yr)	1.12	0.637	1.26	1.01
E _{Rp}	H ₂ SO ₄ Rate - Production-based (lb/Mlb coke)	1.04E-02	5.91E-03	1.16E-02	9.32E-03

Average includes 3 runs.

032117 165556

¹ Gas flow rates obtained from concurrent Method 2F test runs combined with the WAF determined by Method 2H.

RESULTS**Table 2-4:
THC, CH₄, C₂H₆, and VOC Emissions (USEPA 25A/18)**

Run No.	1	2	3	Average
Date (2017)	Mar 1	Mar 1	Mar 1	
Start Time (approx.)	11:00	12:24	13:53	
Stop Time (approx.)	12:04	13:26	14:55	
Process Conditions				
R _p Coke burn rate (Mb/hr)	24.6	24.6	24.7	24.6
P ₁ FCC charge rate (bpd)	40,993	40,989	41,013	40,999
P ₂ NH ₃ injection (lb/hr)	6.1	6.1	6.0	6.1
Cap Capacity factor (hours/year)	8,760	8,760	8,760	8,760
Gas Conditions				
O ₂ Oxygen (dry volume %)	1.6	1.6	1.5	1.6
CO ₂ Carbon dioxide (dry volume %)	16.6	16.5	16.5	16.5
B _w Actual water vapor in gas (% by volume) ¹	10.4	9.9	10.8	10.4
Gas Flow Rate²				
Q _a Volumetric flow rate, actual (acfm)	158,000	165,000	164,000	162,000
Q _s Volumetric flow rate, standard (scfm)	82,000	85,800	85,200	84,300
Q _{std} Volumetric flow rate, dry standard (dscfm)	73,500	77,300	75,900	75,600
THC Results				
C _{sd} Concentration (ppmdv as C ₃ H ₈)	3.17	1.98	2.00	2.38
C _{sd} Concentration (lb/dscf)	3.62E-07	2.27E-07	2.29E-07	2.73E-07
E _{lb/hr} Emission Rate (lb/hr)	1.60	1.05	1.04	1.23
E _{T/yr} Emission Rate (Ton/yr)	7.00	4.61	4.57	5.39
E _{Rp} Emission Rate - Production-based (lb/Mb coke)	0.0650	0.0427	0.0422	0.0500
Methane Results				
C _{sd} Concentration (ppmdv)	<0.210	<0.210	<0.210	<0.210
C _{sd} Concentration (lb/dscf)	<8.74E-09	<8.74E-09	<8.74E-09	<8.74E-09
E _{lb/hr} Emission Rate (lb/hr)	<0.0385	<0.0406	<0.0398	<0.0397
E _{T/yr} Emission Rate (Ton/yr)	<0.169	<0.178	<0.174	<0.174
E _{Rp} Emission Rate - Production-based (lb/Mb coke)	<0.00157	<0.00165	<0.00161	<0.00161
Ethane Results				
C _{sd} Concentration (ppmdv)	<0.227	<0.227	<0.227	<0.227
C _{sd} Concentration (lb/dscf)	<1.77E-08	<1.77E-08	<1.77E-08	<1.77E-08
E _{lb/hr} Emission Rate (lb/hr)	<0.0781	<0.0822	<0.0807	<0.0803
E _{T/yr} Emission Rate (Ton/yr)	<0.342	<0.360	<0.354	<0.352
E _{Rp} Emission Rate - Production-based (lb/Mb coke)	<0.00318	<0.00334	<0.00327	<0.00326
VOC Results				
E _{lb/hr} Emission Rate (lb/hr)	1.60	1.05	1.04	1.23
E _{T/yr} Emission Rate (Ton/yr)	7.00	4.61	4.57	5.39
E _{Rp} Emission Rate - Production-based (lb/Mb coke)	0.0650	0.0427	0.0422	0.0500

Average includes 3 runs.

0804 0 154528

¹ Moisture data used for ppmwv to ppmdv correction obtained from nearly-concurrent Draft ASTM CCM runs.² Gas flow rates obtained from concurrent Method 2F test runs combined with the WAF determined by Method 2H. For methane and ethane, "<" indicates a measured response below the analytical detection limit determined by the laboratory.

For all calculated averages, "<" values are treated as the entire value of the detection limit.

End of Section 2 – Results