

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

March 30, 2022

**PERMIT TO INSTALL  
1-09B**

**ISSUED TO  
Devereaux Sawmill**

**LOCATED AT  
2872 North Hubbardston Road  
Pewamo, Michigan 48877**

**IN THE COUNTY OF  
Ionia**

**STATE REGISTRATION NUMBER  
N2157**

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203: <b>March 15, 2022</b>	
DATE PERMIT TO INSTALL APPROVED: <b>March 30, 2022</b>	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

## PERMIT TO INSTALL

### Table of Contents

COMMON ACRONYMS .....	2
POLLUTANT / MEASUREMENT ABBREVIATIONS.....	3
GENERAL CONDITIONS .....	4
EMISSION UNIT SPECIAL CONDITIONS.....	6
EMISSION UNIT SUMMARY TABLE .....	6
FLEXIBLE GROUP SPECIAL CONDITIONS.....	7
FLEXIBLE GROUP SUMMARY TABLE .....	7
FG-KILNS .....	8
FG-KILNS16-17-18 .....	11
FG-KILNS19-20-21 .....	13

## COMMON ACRONYMS

AQD	Air Quality Division
BACT	Best Available Control Technology
CAA	Clean Air Act
CAM	Compliance Assurance Monitoring
CEMS	Continuous Emission Monitoring System
CFR	Code of Federal Regulations
COMS	Continuous Opacity Monitoring System
Department/department/EGLE	Michigan Department of Environment, Great Lakes, and Energy
EU	Emission Unit
FG	Flexible Group
GACS	Gallons of Applied Coating Solids
GC	General Condition
GHGs	Greenhouse Gases
HVLP	High Volume Low Pressure*
ID	Identification
IRSL	Initial Risk Screening Level
ITSL	Initial Threshold Screening Level
LAER	Lowest Achievable Emission Rate
MACT	Maximum Achievable Control Technology
MAERS	Michigan Air Emissions Reporting System
MAP	Malfunction Abatement Plan
MSDS	Material Safety Data Sheet
NA	Not Applicable
NAAQS	National Ambient Air Quality Standards
NESHAP	National Emission Standard for Hazardous Air Pollutants
NSPS	New Source Performance Standards
NSR	New Source Review
PS	Performance Specification
PSD	Prevention of Significant Deterioration
PTE	Permanent Total Enclosure
PTI	Permit to Install
RACT	Reasonable Available Control Technology
ROP	Renewable Operating Permit
SC	Special Condition
SCR	Selective Catalytic Reduction
SNCR	Selective Non-Catalytic Reduction
SRN	State Registration Number
TBD	To Be Determined
TEQ	Toxicity Equivalence Quotient
USEPA/EPA	United States Environmental Protection Agency
VE	Visible Emissions

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO <sub>2</sub> e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H <sub>2</sub> S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NO <sub>x</sub>	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO <sub>2</sub>	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
µg	Microgram
µm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

### EMISSION UNIT SPECIAL CONDITIONS

#### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Emission Unit ID</b>	<b>Emission Unit Description (Including Process Equipment &amp; Control Device(s))</b>	<b>Installation Date / Modification Date</b>	<b>Flexible Group ID</b>
EU-KILN1	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF. (MBF is equivalent to one thousand board feet.)	1999 thru 2006	FG-KILNS
EU-KILN2	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN3	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN4	Indirect steam-heated lumber drying kiln. Charge capacity of 40 MBF.	1999 thru 2006	FG-KILNS
EU-KILN5	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN6	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN7	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN8	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN9	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN10	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN11	Indirect steam-heated lumber drying kiln. Charge capacity of 40 MBF.	1999 thru 2006	FG-KILNS
EU-KILN12	Indirect steam-heated lumber drying kiln. Charge capacity of 40 MBF.	1999 thru 2006	FG-KILNS
EU-KILN13	Indirect steam-heated lumber drying kiln. Charge capacity of 40 MBF.	1999 thru 2006	FG-KILNS
EU-KILN14	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN15	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	1999 thru 2006	FG-KILNS
EU-KILN16	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	November 2017	FG-KILNS16-17-18
EU-KILN17	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	November 2017	FG-KILNS16-17-18
EU-KILN18	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	November 2017	FG-KILNS16-17-18
EU-KILN19	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	TBD	FG-KILNS19-20-21
EU-KILN20	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	TBD	FG-KILNS19-20-21
EU-KILN21	Indirect steam-heated lumber drying kiln. Charge capacity of 60 MBF.	TBD	FG-KILNS19-20-21

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

### FLEXIBLE GROUP SPECIAL CONDITIONS

### FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

<b>Flexible Group ID</b>	<b>Flexible Group Description</b>	<b>Associated Emission Unit IDs</b>
FG-KILNS	Fifteen indirect steam-heated lumber drying kilns.	EU-KILN1, EU-KILN2, EU-KILN3, EU-KILN4, EU-KILN5, EU-KILN6, EU-KILN7, EU-KILN8, EU-KILN9, EU-KILN10, EU-KILN11, EU-KILN12, EU-KILN13, EU-KILN14, EU-KILN15
FG-KILNS16-17-18	Three indirect steam-heated lumber drying kilns.	EU-KILN16, EU-KILN17, EU-KILN18
FG-KILNS19-20-21	Three indirect steam-heated lumber drying kilns	EU-KILN19, EU-KILN20, EU-KILN21



**FG-KILNS  
 FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

Fifteen indirect steam-heated lumber drying kilns.

**Emission Unit:** EU-KILN1, EU-KILN2, EU-KILN3, EU-KILN4, EU-KILN5, EU-KILN6, EU-KILN7, EU-KILN8, EU-KILN9, EU-KILN10, EU-KILN11, EU-KILN12, EU-KILN13, EU-KILN14, EU-KILN15

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOCs (as carbon)	52.9 tpy*	12-month rolling time period as determined at the end of each calendar month	FG-KILNS	SC II.2, SC VI.2	R 336.1205, R 336.1702(a)

\* VOC calculations are based on the amount of wood dried (in thousand board feet, MBF) multiplied by its corresponding VOC emission factor in pounds carbon per thousand board feet (lbs C/MBF).

**II. MATERIAL LIMIT(S)**

1. The permittee shall only process hardwood in FG-KILNS. Hardwood is defined as the wood of a broad-leaved tree, either deciduous or evergreen. **(R 336.1225, R 336.1702(a))**
2. The permittee shall not dry more than 24,600 MBF of wood in FG-KILNS per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205, R 336.1224, R 336.1225, R 336.1301, R 336.1331, R 336.1702(a))**

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

NA

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1224, R 336.1225, R 336.1702)**

2. The permittee shall keep the following information on a monthly basis for FG-KILNS:
- The wood species and amount in MBF dried per calendar month.
  - The wood species and amount in MBF dried per 12-month rolling time period as determined at the end of each calendar month.
  - The VOC emission factor (in lbs C/MBF) for each wood species dried. (The worse-case VOC emission factor is assumed to be 4.3 lbs C/MBF. VOC emissions in general are based on emission factors from "Factors Affecting Lumber Kiln VOC Emissions," M.R. Milota, Oregon State University or an alternative method acceptable to the AQD District Supervisor.)
  - VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records shall be kept in a format acceptable to the AQD District Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1205, R 336.1225, R 336.1702(a))**

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter/ Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-KILN1F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-KILN1R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-KILN2F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
4. SV-KILN2R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
5. SV-KILN3F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
6. SV-KILN3R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
7. SV-KILN4F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
8. SV-KILN4R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
9. SV-KILN5F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
10. SV-KILN5R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
11. SV-KILN6F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
12. SV-KILN6R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter/ Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
13. SV-KILN7F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
14. SV-KILN7R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
15. SV-KILN8F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
16. SV-KILN8R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
17. SV-KILN9F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
18. SV-KILN9R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
19. SV-KILN10F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
20. SV-KILN10R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
21. SV-KILN11F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
22. SV-KILN11R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
23. SV-KILN12F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
24. SV-KILN12R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
25. SV-KILN13F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
26. SV-KILN13R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
27. SV-KILN14F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
28. SV-KILN14R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
29. SV-KILN15F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
30. SV-KILN15R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
* Vents are horizontal.			

**IX. OTHER REQUIREMENT(S)**

NA

**FG-KILNS16-17-18  
 FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

Three indirect steam-heated lumber drying kilns.

**Emission Unit:** EU-KILN16, EU-KILN17, EU-KILN18

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOCs (as carbon)	10.7 tpy*	12-month rolling time period as determined at the end of each calendar month	FG-KILNS16-17-18	SC II.2, SC VI.2	R 336.1205, R 336.1702(a)

\* VOC calculations are based on the amount of wood dried (in thousand board feet, MBF) multiplied by its corresponding VOC emission factor in pounds carbon per thousand board feet (lbs C/MBF).

**II. MATERIAL LIMIT(S)**

1. The permittee shall only process hardwood in FG-KILNS16-17-18. (Hardwood is defined as the wood of a broad-leaved tree, either deciduous or evergreen.) **(R 336.1225, R 336.1702(a))**
2. The permittee shall not dry more than 4,950 MBF of wood in FG-KILNS16-17-18 per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205, R 336.1224, R 336.1225, R 336.1702(a))**

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

NA

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

**V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1224, R 336.1225, R 336.1702)**

2. The permittee shall keep the following information on a monthly basis for FG- KILNS16-17-18:
  - a) The wood species and amount in MBF dried per calendar month.
  - b) The wood species and amount in MBF dried per 12-month rolling time period as determined at the end of each calendar month.
  - c) The VOC emission factor (in lbs C/MBF) for each wood species dried. If a VOC emission factor for each species is not available, the worst-case VOC emission factor is assumed to be 4.3 lbs C/MBF. VOC emissions in general are based on emission factors from "Factors Affecting Lumber Kiln VOC Emissions," M.R. Milota, Oregon State University. Other emission factors may be approved by the AQD District Supervisor.
  - d) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - e) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records shall be kept in a format acceptable to the AQD District Supervisor. All records shall be kept on file and made available to the Department upon request. (R 336.1205, R 336.1225, R 336.1702(a))

**VII. REPORTING**

NA

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-KILN16F (front exhaust, 1 vent) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-KILN16R (rear exhaust, 1 vent) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-KILN17F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
4. SV-KILN17R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
5. SV-KILN18F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
6. SV-KILN18R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
* Vents are horizontal.			

**IX. OTHER REQUIREMENT(S)**

NA

**FG-KILNS19-20-21  
FLEXIBLE GROUP CONDITIONS**

**DESCRIPTION**

Three indirect steam-heated lumber drying kilns.

**Emission Unit:** EU-KILN19, EU-KILN20, EU-KILN21

**POLLUTION CONTROL EQUIPMENT**

NA

**I. EMISSION LIMIT(S)**

<b>Pollutant</b>	<b>Limit</b>	<b>Time Period / Operating Scenario</b>	<b>Equipment</b>	<b>Monitoring / Testing Method</b>	<b>Underlying Applicable Requirements</b>
1. VOCs (as carbon)	10.7 tpy*	12-month rolling time period as determined at the end of each calendar month	FG-KILNS19-20-21	SC II.2, SC VI.2	R 336.1205, R 336.1702(a)

\* VOC calculations are based on the amount of wood dried (in thousand board feet, MBF) multiplied by its corresponding VOC emission factor in pounds carbon per thousand board feet (lbs C/MBF).

**II. MATERIAL LIMIT(S)**

1. The permittee shall only process hardwood in FG-KILNS19-20-21. (Hardwood is defined as the wood of a broad-leaved tree, either deciduous or evergreen.) **(R 336.1225, R 336.1702(a))**
2. The permittee shall not dry more than 4,950 MBF of wood in FG-KILNS19-20-21 per 12-month rolling time period as determined at the end of each calendar month. **(R 336.1205, R 336.1224, R 336.1225, R 336.1702(a))**

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

NA

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

NA

**V. TESTING/SAMPLING**

NA

**VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1205, R 336.1224, R 336.1225, R 336.1702)**

2. The permittee shall keep the following information on a monthly basis for FG-KILNS19-20-21:
  - a) The wood species and amount in MBF dried per calendar month.
  - b) The wood species and amount in MBF dried per 12-month rolling time period as determined at the end of each calendar month.
  - c) The VOC emission factor (in lbs C/MBF) for each wood species dried. If a VOC emission factor for each species is not available, the worst-case VOC emission factor is assumed to be 4.3 lbs C/MBF. VOC emissions in general are based on emission factors from "Factors Affecting Lumber Kiln VOC Emissions," M.R. Milota, Oregon State University. Other emission factors may be approved by the AQD District Supervisor.
  - d) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
  - e) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The records shall be kept in a format acceptable to the AQD District Supervisor. All records shall be kept on file and made available to the Department upon request. **(R 336.1205, R 336.1225, R 336.1702(a))**

**VII. REPORTING**

1. The permittee shall notify the Department if a change in land use occurs for property classified as industrial or as a public roadway, where this classification was relied upon to demonstrate compliance with Rule 225(1). The permittee shall submit the notification to the AQD District Supervisor, within 30 days of the actual land use change. Within 60 days of the land use change, the permittee shall submit to the AQD District Supervisor a plan for complying with the requirements of Rule 225(1). The plan shall require compliance with Rule 225(1) no later than one year after the due date of the plan submittal. **(R 336.1225(4))**

**VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

<b>Stack &amp; Vent ID</b>	<b>Maximum Exhaust Diameter / Dimensions (inches)</b>	<b>Minimum Height Above Ground (feet)</b>	<b>Underlying Applicable Requirements</b>
1. SV-KILN19F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
2. SV-KILN19R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
3. SV-KILN20F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
4. SV-KILN20R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
5. SV-KILN21F (front exhaust, 2 vents) *	NA	26.1	R 336.1225, 40 CFR 52.21(c) & (d)
6. SV-KILN21R (rear exhaust, 2 vents) *	NA	17.5	R 336.1225, 40 CFR 52.21(c) & (d)
* Vents are horizontal.			

**IX. OTHER REQUIREMENT(S)**

NA