MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY AIR QUALITY DIVISION

May 9, 2019

PERMIT TO INSTALL 45-09D

ISSUED TO

Pioneer Hi-Bred International, Inc.

LOCATED AT

1365 South Washington Street Constantine, Michigan

IN THE COUNTY OF Saint Joseph

STATE REGISTRATION NUMBER B7549

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:				
May 2, 2019				
DATE PERMIT TO INSTALL APPROVED:	SIGNATURE:			
May 9, 2019				
, i				
DATE PERMIT VOIDED:	SIGNATURE:			
DATE PERMIT REVOKED:	SIGNATURE:			
1				

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS	6
EMISSION UNIT SUMMARY TABLE	6
EUTREATER	7

COMMON ACRONYMS

AQD Air Quality Division

BACT Best Available Control Technology

CAA Clean Air Act

CAM Compliance Assurance Monitoring
CEMS Continuous Emission Monitoring System

CFR Code of Federal Regulations

COMS Continuous Opacity Monitoring System

Department/department Michigan Department of Environmental Quality

EU Emission Unit FG Flexible Group

GACS Gallons of Applied Coating Solids

GC General Condition
GHGs Greenhouse Gases

HVLP High Volume Low Pressure*

ID Identification

IRSL Initial Risk Screening Level
ITSL Initial Threshold Screening Level
LAER Lowest Achievable Emission Rate

MACT Maximum Achievable Control Technology
MAERS Michigan Air Emissions Reporting System

MAP Malfunction Abatement Plan

MDEQ Michigan Department of Environmental Quality

MSDS Material Safety Data Sheet

NA Not Applicable

NAAQS National Ambient Air Quality Standards

NESHAP National Emission Standard for Hazardous Air Pollutants

NSPS New Source Performance Standards

NSR New Source Review
PS Performance Specification

PSD Prevention of Significant Deterioration

PTE Permanent Total Enclosure

PTI Permit to Install

RACT Reasonable Available Control Technology

ROP Renewable Operating Permit

SC Special Condition

SCR Selective Catalytic Reduction
SNCR Selective Non-Catalytic Reduction
SRN State Registration Number

TBD To Be Determined

TEQ Toxicity Equivalence Quotient

USEPA/EPA United States Environmental Protection Agency

VE Visible Emissions

^{*}For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm Actual cubic feet per minute

BTU British Thermal Unit °C Degrees Celsius CO Carbon Monoxide

CO2e Carbon Dioxide Equivalent dscf Dry standard cubic foot dscm Dry standard cubic meter Pegrees Fahrenheit

gr Grains

HAP Hazardous Air Pollutant

Hg Mercury
hr Hour
HP Horsepo

HP Horsepower Hydrogen Sulfide

kW Kilowatt

Ib Pound

m Meter

mg Milligram

mm Millimeter

MM Million

MW Megawatts

NMOC Non-Methane Organic Compounds

NO_x Oxides of Nitrogen

ng Nanogram

PM Particulate Matter

PM10 Particulate Matter equal to or less than 10 microns in diameter PM2.5 Particulate Matter equal to or less than 2.5 microns in diameter

pph Pounds per hour ppm Parts per million

ppmv Parts per million by volume
ppmw Parts per million by weight
psia Pounds per square inch absolute
psig Pounds per square inch gauge

scf Standard cubic feet

 $\begin{array}{ccc} \text{sec} & \text{Seconds} \\ \text{SO}_2 & \text{Sulfur Dioxide} \end{array}$

TAC Toxic Air Contaminant

Temp Temperature
THC Total Hydrocarbons
tpy Tons per year

µg Microgram

µm Micrometer or Micron

VOC Volatile Organic Compounds

yr Year

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.

May 2, 2019 Page 5 of 8

- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.
- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
EU-TREATER	2,000 bushel per hour dual bowl seed treater	TBD	NA
	system used to apply fungicide and pesticide		
	to seed corn prior to bagging. The system		
	includes three 1,500 bushel per hour		
	aspirators. Emissions from the system are		
	controlled by two GS16 Farr Filters and an		
	activated carbon filter that are exhausted into		
	the building.		

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

May 2, 2019 Page 7 of 8

EUTREATER EMISSION UNIT CONDITIONS

DESCRIPTION

2,000 bushel per hour dual bowl seed treater system used to apply fungicide and pesticide to seed corn prior to bagging. The system includes three 1,500 bushel per hour aspirators.

Flexible Group ID: NA

POLLUTION CONTROL EQUIPMENT

Two GS16 Farr Filters and an activated carbon filter

I. EMISSION LIMIT(S)

	Pollutant	Limit	Time Period / Operating Scenario	Equipment	Monitoring / Testing Method	Underlying Applicable Requirements
1.	VOC	11.5 tpy	12-month rolling time period	EU-TREATER	SC V.1, VI.2,	R 336.1702(a)
			as determined at the end of		VI.3	
			each calendar month			
2.	Maleic Anhydride	0.0034 pph	Hourly	EU-TREATER	SC VI.4	R 336.1225

II. MATERIAL LIMIT(S)

			Time Period / Operating		Monitoring /	Underlying Applicable
	Material	Limit	Scenario	Equipment	Testing Method	Requirements
1.	VOC Content of	20% or less, by	Instantaneous	EU-TREATER	SC VI.4	R 336.1225,
	each treatment used	weight, as received				R 336.1702(a)

III. PROCESS/OPERATIONAL RESTRICTION(S)

- 1. The permittee shall capture all waste materials and shall store them in closed containers. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. (R 336.1225, R 336.1702(a))
- 2. The permittee shall handle all VOC and / or HAP containing materials, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers covered at all times except when operator access is necessary. (R 336.1225, R 336.1702(a))

IV. DESIGN/EQUIPMENT PARAMETER(S)

- 1. The permittee shall not operate EU-TREATER unless the two GS16 Farr Filters are installed, maintained, and operated in a satisfactory manner. (R 336.1331)
- 2. The permittee shall not operate EU-TREATER unless the activated carbon filter is installed, maintained, and operated in a satisfactory manner.¹ (R 336.1225)

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

1. The permittee shall determine the VOC content, water content and density of each treatment, as received, using federal Reference Test Method 24 or other test method approved by the Department. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's

May 2, 2019 Page 8 of 8

formulation data. If the Method 24 or other test method and the formulation values should differ, the permittee shall use the Method 24 or other test method results to determine compliance. (R 336.1225, R 336.1702, R 336.2001, R 336.2003, R 336.2004, R 336.2040(5))

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor by the 15th day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1225, R 336.1702)
- The permittee shall maintain a current listing from the manufacturer of the chemical composition of each treatment, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702)
- 3. The permittee shall keep the following information on a calendar month basis for EU-TREATER:
 - a) Gallons (with water) of each treatment used.
 - b) VOC content (with water) of each treatment as applied.
 - c) VOC mass emission calculations determining the monthly emission rate in tons per calendar month.
 - d) VOC mass emission calculations determining the annual emission rate in tons per 12-month rolling time period as determined at the end of each calendar month.

The permittee shall keep the records in a format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702)

4. The permittee shall maintain an up to date calculation of the hourly maleic anhydride emission rate from EU-TREATER based on current seed treatment compositions and seed treatment usage rates. This calculation shall be updated whenever there is a change to maleic anhydride containing seed treatments or an increase in the usage rate of a maleic anhydride containing seed treatment. The permittee shall keep all records on file and make them available to the Department upon request.¹ (R 336.1225)

VII. REPORTING

NA

VIII. STACK/VENT RESTRICTION(S)

NA

IX. OTHER REQUIREMENT(S)

NA

Footnotes:

¹ This condition is state only enforceable and was established pursuant to Rule 201(1)(b).