## MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

March 21, 2019

PERMIT TO INSTALL 190-18

**ISSUED TO**Rapids Tumble Finish, Inc.

LOCATED AT 1607 Hults Drive Eaton Rapids, Michigan

IN THE COUNTY OF Eaton

## STATE REGISTRATION NUMBER P0973

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

March 7, 2019	QUIRED BY RULE 203:
March 21, 2019	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

## **PERMIT TO INSTALL**

## **Table of Contents**

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	3
GENERAL CONDITIONS	
EMISSION UNIT SPECIAL CONDITIONS	
EMISSION UNIT SUMMARY TABLE	
EUFINLINE	7

#### **COMMON ACRONYMS**

AQD Air Quality Division

BACT Best Available Control Technology

CAA Clean Air Act

CAM Compliance Assurance Monitoring
CEMS Continuous Emission Monitoring System

CFR Code of Federal Regulations

COMS Continuous Opacity Monitoring System

Department/department Michigan Department of Environmental Quality

EU Emission Unit FG Flexible Group

GACS Gallons of Applied Coating Solids

GC General Condition GHGs Greenhouse Gases

HVLP High Volume Low Pressure\*

ID Identification

IRSLInitial Risk Screening LevelITSLInitial Threshold Screening LevelLAERLowest Achievable Emission RateMACTMaximum Achievable Control Technology

MAERS Michigan Air Emissions Reporting System
MAP Malfunction Abatement Plan

MDEQ Michigan Department of Environmental Quality

MSDS Material Safety Data Sheet

NA Not Applicable

NAAQS National Ambient Air Quality Standards

NESHAP National Emission Standard for Hazardous Air Pollutants

NSPS New Source Performance Standards

NSR New Source Review PS Performance Specification

PSD Prevention of Significant Deterioration

PTE Permanent Total Enclosure

PTI Permit to Install

RACT Reasonable Available Control Technology

ROP Renewable Operating Permit

SC Special Condition

SCR Selective Catalytic Reduction
SNCR Selective Non-Catalytic Reduction
SRN State Registration Number

TBD To Be Determined

TEQ Toxicity Equivalence Quotient

USEPA/EPA United States Environmental Protection Agency

VE Visible Emissions

<sup>\*</sup>For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig

## **POLLUTANT / MEASUREMENT ABBREVIATIONS**

acfm Actual cubic feet per minute

BTU British Thermal Unit °C Degrees Celsius CO Carbon Monoxide

CO2e Carbon Dioxide Equivalent dscf Dry standard cubic foot dscm Dry standard cubic meter Personal Per

gr Grains

HAP Hazardous Air Pollutant

Hg Mercury hr Hour

 $\begin{array}{ccc} \text{HP} & & \text{Horsepower} \\ \text{H}_2 \text{S} & & \text{Hydrogen Sulfide} \end{array}$ 

kW Kilowatt

lb Pound

m Meter

mg Milligram

mm Millimeter

MM Million

MW Megawatts

NMOC Non-Methane Organic Compounds

NO<sub>x</sub> Oxides of Nitrogen

ng Nanogram

PM Particulate Matter

PM10 Particulate Matter equal to or less than 10 microns in diameter PM2.5 Particulate Matter equal to or less than 2.5 microns in diameter

pph Pounds per hour ppm Parts per million

ppmv Parts per million by volume
ppmw Parts per million by weight
psia Pounds per square inch abso

psia Pounds per square inch absolute psig Pounds per square inch gauge

scf Standard cubic feet

 $\begin{array}{ccc} \text{sec} & \text{Seconds} \\ \text{SO}_2 & \text{Sulfur Dioxide} \end{array}$ 

TAC Toxic Air Contaminant

Temp Temperature

THC Total Hydrocarbons tpy Tons per year Microgram

µm Micrometer or Micron

VOC Volatile Organic Compounds

yr Year

Rapids Tumble Finish, Inc. (P0973)

March 21, 2019

Permit No. 190-18

March 21, 2019

#### **GENERAL CONDITIONS**

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

Rapids Tumble Finish, Inc. (P0973)
Permit No. 190-18

March 21, 2019 Page 5 of 8

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

#### **EMISSION UNIT SPECIAL CONDITIONS**

## **EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

	Emission Unit Description (Including Process Equipment & Control	Installation Date /	
Emission Unit ID	Device(s))	Modification Date	Flexible Group ID
EUFINLINE	Metal Finish / Cleaning Line: Various metal finishing activities such as washing, buffing, polishing, cleaning, and sandblasting. The line consists of a number of dip tanks (currently 27 tanks) equipped with an exhaust system of hoods and two stacks, one for each side of the line. The tank in the finish line contains acid and phosphate cleaners as well as rust prevention / inhibitor oils.	08-18-2004	NA

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

Rapids Tumble Finish, Inc. (P0973)

Permit No. 190-18

March 21, 2019

Page 7 of 8

# EUFINLINE EMISSION UNIT CONDITIONS

#### **DESCRIPTION**

Metal Finish / Cleaning Line: Various metal finishing activities such as washing, buffing, polishing, cleaning, and sandblasting. The line consists of a number of dip tanks (currently 27 tanks) equipped with an exhaust system of hoods and two stacks, one for each side of the line. The tank in the finish line contains acid and phosphate cleaners as well as rust prevention / inhibitor oils.

Flexible Group ID: NA

#### **POLLUTION CONTROL EQUIPMENT**

NA

I. EMISSION LIMIT(S)

NA

II. MATERIAL LIMIT(S)

NA

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

- 1. The permittee shall dispose of all waste materials in an acceptable manner in compliance with all applicable state rules and federal regulations. (R 336.1224, R 336.1225, R 336.1702(a)).
- 2. The permittee shall handle all VOC and/or HAP containing materials, in a manner to minimize the generation of fugitive emissions. The permittee shall keep containers (raw materials) covered at all times except when operator access is necessary. (R 336.1224, R 336.1225, R 336.1702(a))

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

1. The permittee shall not operate EUFINLINE unless all exhaust hoods are installed, maintained and operated in a satisfactory manner. (R 336.1224, R 336.1225, R 336.1910, 40 CFR 52.21(c) & (d))

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

 The permittee shall determine the VOC content, water content and density of any material, as applied and as received, using federal Reference Test Method 24. Upon prior written approval by the AQD District Supervisor, the permittee may determine the VOC content from manufacturer's formulation data. If the Method 24 and the formulation values should differ, the permittee shall use the Method 24 results to determine compliance. (R 336.1225, R 336.1702, R 336.2004)

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

 The permittee shall complete all required records in a format acceptable to the AQD District Supervisor by the 15<sup>th</sup> day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. (R 336.1224, R 336.1225, R 336.1702) Rapids Tumble Finish, Inc. (P0973)

Permit No. 190-18

March 21, 2019

Page 8 of 8

 The permittee shall maintain a current listing from the manufacturer of the chemical composition of each material, including the weight percent of each component. The data may consist of Material Safety Data Sheets, manufacturer's formulation data, or both as deemed acceptable by the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1224, R 336.1225, R 336.1702)

- 3. The permittee shall keep the following information on a calendar month basis for EUFINLINE:
  - a) Gallons (with water) of each material used and reclaimed for each container / tank.
  - b) VOC content (with water) of each material as applied (if applicable).

The permittee shall keep the records using mass balance, or an alternative method and format acceptable to the AQD District Supervisor. The permittee shall keep all records on file and make them available to the Department upon request. (R 336.1225, R 336.1702(a))

#### VII. REPORTING

NA

### VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVFINLINE-01	36.0	52.5	R 336.1225,
			40 CFR 52.21(c) & (d)
2. SVFINLINE-02	36.0	52.5	R 336.1225,
			40 CFR 52.21(c) & (d)

#### IX. OTHER REQUIREMENT(S)

NA

#### Footnotes:

<sup>&</sup>lt;sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).