MICHIGAN DEPARTMENT OF ENVIRONMENTAL QUALITY AIR QUALITY DIVISION

March 13, 2019

PERMIT TO INSTALL 44-19

ISSUED TO Milosch's Palace Chrysler Jeep Dodge Ram

> LOCATED AT 4800 South Lapeer Road Lake Orion, Michigan

IN THE COUNTY OF Oakland

STATE REGISTRATION NUMBER P0733

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environmental Quality. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:

February 28, 2019

DATE PERMIT TO INSTALL APPROVED: March 13, 2019	SIGNATURE:
DATE PERMIT VOIDED:	SIGNATURE:
DATE PERMIT REVOKED:	SIGNATURE:

PERMIT TO INSTALL

Table of Contents

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	3
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS	6
EMISSION UNIT SUMMARY TABLE	6
FLEXIBLE GROUP SPECIAL CONDITIONS	6
FLEXIBLE GROUP SUMMARY TABLE	6
FGHEATERS	7

COMMON ACRONYMS

AQD BACT CAA CAM CEMS CFR COMS Department/department EU FG GACS GC GHGS HVLP ID IRSL ITSL LAER MACT MAERS MAP MDEQ MSDS NA NAAQS NESHAP NSPS NSR PS PSD PTE PTI RACT ROP SC SCR SCR SCR SRN TBD TEQ USEPA/EPA VE	Air Quality Division Best Available Control Technology Clean Air Act Compliance Assurance Monitoring Continuous Emission Monitoring System Code of Federal Regulations Continuous Opacity Monitoring System Michigan Department of Environmental Quality Emission Unit Flexible Group Gallons of Applied Coating Solids General Condition Greenhouse Gases High Volume Low Pressure* Identification Initial Risk Screening Level Lowest Achievable Emission Rate Maximum Achievable Control Technology Michigan Air Emissions Reporting System Malfunction Abatement Plan Michigan Department of Environmental Quality Material Safety Data Sheet Not Applicable National Ambient Air Quality Standards National Ambient Air Quality Standards National Emission Standard for Hazardous Air Pollutants New Source Performance Standards New Source Review Performance Specification Prevention of Significant Deterioration Permanent Total Enclosure Permit to Install Reasonable Available Control Technology Renewable Operating Permit Special Condition Selective Catalytic Reduction State Registration Number To Be Determined Toxicity Equivalence Quotient United States Environmental Protection Agency Visible Emissions
VE	

POLLUTANT / MEASUREMENT ABBREVIATIONS

acfm	Actual cubic feet per minute
BTU	British Thermal Unit
°C	Degrees Celsius
CO	Carbon Monoxide
CO ₂ e	Carbon Dioxide Equivalent
dscf	Dry standard cubic foot
dscm	Dry standard cubic meter
°F	Degrees Fahrenheit
gr	Grains
HAP	Hazardous Air Pollutant
Hg	Mercury
hr	Hour
HP	Horsepower
H ₂ S	Hydrogen Sulfide
kW	Kilowatt
lb	Pound
m	Meter
mg	Milligram
mm	Millimeter
MM	Million
MW	Megawatts
NMOC	Non-Methane Organic Compounds
NOx	Oxides of Nitrogen
ng	Nanogram
PM	Particulate Matter
PM10	Particulate Matter equal to or less than 10 microns in diameter
PM2.5	Particulate Matter equal to or less than 2.5 microns in diameter
pph	Pounds per hour
ppm	Parts per million
ppmv	Parts per million by volume
ppmw	Parts per million by weight
psia	Pounds per square inch absolute
psig	Pounds per square inch gauge
scf	Standard cubic feet
sec	Seconds
SO ₂	Sulfur Dioxide
TAC	Toxic Air Contaminant
Temp	Temperature
THC	Total Hydrocarbons
tpy	Tons per year
hð	Microgram
μm	Micrometer or Micron
VOC	Volatile Organic Compounds
yr	Year

GENERAL CONDITIONS

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environmental Quality, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- 4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environmental Quality. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal conditions or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

Milosch's Palace Chrysler Jeep Dodge Ram (P0733) Permit No. 44-19

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
 - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
 - b) A visible emission limit specified by an applicable federal new source performance standard.
 - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (**R 336.1370**)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

EMISSION UNIT SPECIAL CONDITIONS

EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Flexible Group ID
EUHEATER1	Cleanburn waste oil heater with a heat input of 352,000 Btu/hr	FGHEATERS
EUHEATER2	Cleanburn waste oil heater with a heat input of 175,000 Btu/hr	FGHEATERS

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

FLEXIBLE GROUP SPECIAL CONDITIONS

FLEXIBLE GROUP SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGHEATERS	Waste oil heaters	EUHEATER1 EUHEATER2

FGHEATERS FLEXIBLE GROUP CONDITIONS

DESCRIPTION

Waste Oil Heaters

Emission Unit: EUHEATER1, EUHEATER2

POLLUTION CONTROL EQUIPMENT

NA

I. EMISSION LIMIT(S)

NA

II. MATERIAL LIMIT(S)

- 1. The permittee shall not burn any fuel in FGHEATERS other than those listed below.
 - a. No. 1 virgin fuel oil
 - b. No. 2 virgin fuel oil
 - c. Used oil (including crankcase, hydraulic, and transmission oils) with properties that do not exceed the standards specified in 40 CFR 279.11. "Used oil" is any oil that has been refined from crude oil, or any synthetic oil, that has been used and as result of such use is contaminated by physical or chemical impurities as defined in 40 CFR 279.1. This includes used oil generated by the permittee, household "do-it-yourselfer", and from used oil collection centers.

(R 336.1224, R336.1225, 40 CFR 279.11)

III. PROCESS/OPERATIONAL RESTRICTION(S)

 The permittee shall not burn waste oil or used oil fuel in FGHEATERS unless such waste oil or used oil fuel is pretreated (e.g. sedimentation, filtration, etc.) to reduce water and sediment. (R 336.1224(2)(b), R 336.1331)

IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- 1. The permittee shall keep, in a satisfactory manner, monthly records of fuel burned in FGHEATERS. The records shall demonstrate the following information for each 55-gal drum burned in FGHEATERS:
 - a. The type(s) of fuel, such as No. 1 and No. 2 virgin fuel oils, waste oil (including crankcase, hydraulic, and transmission oils), or used oil.
 - b. Whether the oil is generated by the permittee, either on-site or off-site, or by household "do-it-yourselfer" used oil generators.

The permittee shall keep all records on file at the facility and make them available to the Department upon request. (R 336.1224(2)(b), 40 CFR 279.23)

2. The permittee shall maintain documentation verifying that the design heat input capacity for EUFURNACE complies with SC II.1. The permittee shall keep records on file at the facility and make them available to the Department upon request. (R 336.1224(2)(b), 40 CFR 279.23)

VII. <u>REPORTING</u>

NA

VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SVHEATER1	8	21	R 336.1224(2)(b),
			40 CFR 279.23
2. SVHEATER2	8	21	R 336.1224(2)(b),
			40 CFR 279.23

IX. OTHER REQUIREMENT(S)

NA