

**MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY  
AIR QUALITY DIVISION**

May 14, 2021

**PERMIT TO INSTALL**  
151-20

**ISSUED TO**  
Dow Silicones Corporation

**LOCATED AT**  
Michigan Operation  
602 Building  
Midland, Michigan 48686

**IN THE COUNTY OF**  
Midland

**STATE REGISTRATION NUMBER**  
A4043

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

|  |            |
|--|------------|
| DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:<br><b>March 3, 2021</b> |            |
| DATE PERMIT TO INSTALL APPROVED:<br><b>May 14, 2021</b>                          | SIGNATURE: |
| DATE PERMIT VOIDED:  | SIGNATURE: |
| DATE PERMIT REVOKED:   | SIGNATURE: |

**PERMIT TO INSTALL**

**Table of Contents**

COMMON ACRONYMS ..... 2  
POLLUTANT / MEASUREMENT ABBREVIATIONS..... 3  
GENERAL CONDITIONS ..... 4  
EMISSION UNIT SPECIAL CONDITIONS..... 6  
    EMISSION UNIT SUMMARY TABLE ..... 6  
    EU602-07..... 7

## COMMON ACRONYMS

|                            |   |
|----------------------------|---|
| AQD                        | Air Quality Division  |
| BACT                       | Best Available Control Technology                           |
| CAA                        | Clean Air Act   |
| CAM                        | Compliance Assurance Monitoring                             |
| CEMS                       | Continuous Emission Monitoring System                       |
| CFR                        | Code of Federal Regulations                                 |
| COMS                       | Continuous Opacity Monitoring System                        |
| Department/department/EGLE | Michigan Department of Environment, Great Lakes, and Energy |
| EU                         | Emission Unit   |
| FG                         | Flexible Group  |
| GACS                       | Gallons of Applied Coating Solids                           |
| GC                         | General Condition   |
| GHGs                       | Greenhouse Gases  |
| HVLP                       | High Volume Low Pressure*                                   |
| ID                         | Identification  |
| IRSL                       | Initial Risk Screening Level                                |
| ITSL                       | Initial Threshold Screening Level                           |
| LAER                       | Lowest Achievable Emission Rate                             |
| MACT                       | Maximum Achievable Control Technology                       |
| MAERS                      | Michigan Air Emissions Reporting System                     |
| MAP                        | Malfunction Abatement Plan                                  |
| MSDS                       | Material Safety Data Sheet                                  |
| NA                         | Not Applicable  |
| NAAQS                      | National Ambient Air Quality Standards                      |
| NESHAP                     | National Emission Standard for Hazardous Air Pollutants     |
| NSPS                       | New Source Performance Standards                            |
| NSR                        | New Source Review   |
| PS                         | Performance Specification                                   |
| PSD                        | Prevention of Significant Deterioration                     |
| PTE                        | Permanent Total Enclosure                                   |
| PTI                        | Permit to Install   |
| RACT                       | Reasonable Available Control Technology                     |
| ROP                        | Renewable Operating Permit                                  |
| SC                         | Special Condition   |
| SCR                        | Selective Catalytic Reduction                               |
| SNCR                       | Selective Non-Catalytic Reduction                           |
| SRN                        | State Registration Number                                   |
| TBD                        | To Be Determined  |
| TEQ                        | Toxicity Equivalence Quotient                               |
| USEPA/EPA                  | United States Environmental Protection Agency               |
| VE                         | Visible Emissions   |

\*For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

### POLLUTANT / MEASUREMENT ABBREVIATIONS

|                   |  |
|-------------------|--|
| acfm              | Actual cubic feet per minute                                     |
| BTU               | British Thermal Unit   |
| °C                | Degrees Celsius  |
| CO                | Carbon Monoxide  |
| CO <sub>2</sub> e | Carbon Dioxide Equivalent  |
| dscf              | Dry standard cubic foot  |
| dscm              | Dry standard cubic meter   |
| °F                | Degrees Fahrenheit   |
| gr                | Grains   |
| HAP               | Hazardous Air Pollutant  |
| Hg                | Mercury  |
| hr                | Hour   |
| HP                | Horsepower   |
| H <sub>2</sub> S  | Hydrogen Sulfide   |
| kW                | Kilowatt   |
| lb                | Pound  |
| m                 | Meter  |
| mg                | Milligram  |
| mm                | Millimeter   |
| MM                | Million  |
| MW                | Megawatts  |
| NMOC              | Non-Methane Organic Compounds                                    |
| NO <sub>x</sub>   | Oxides of Nitrogen   |
| ng                | Nanogram   |
| PM                | Particulate Matter   |
| PM10              | Particulate Matter equal to or less than 10 microns in diameter  |
| PM2.5             | Particulate Matter equal to or less than 2.5 microns in diameter |
| pph               | Pounds per hour  |
| ppm               | Parts per million  |
| ppmv              | Parts per million by volume                                      |
| ppmw              | Parts per million by weight                                      |
| psia              | Pounds per square inch absolute                                  |
| psig              | Pounds per square inch gauge                                     |
| scf               | Standard cubic feet  |
| sec               | Seconds  |
| SO <sub>2</sub>   | Sulfur Dioxide   |
| TAC               | Toxic Air Contaminant  |
| Temp              | Temperature  |
| THC               | Total Hydrocarbons   |
| tpy               | Tons per year  |
| µg                | Microgram  |
| µm                | Micrometer or Micron   |
| VOC               | Volatile Organic Compounds                                       |
| yr                | Year   |

## GENERAL CONDITIONS

1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. **(R 336.1201(1))**
2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. **(R 336.1201(4))**
3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. **(R 336.1201(6)(b))**
4. The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. **(R 336.1201(8), Section 5510 of Act 451, PA 1994)**
5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. **(R 336.1219)**
6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. **(R 336.1901)**
7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). **(R 336.1912)**
8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). **(R 336.1301)**
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). **(R 336.1370)**
13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. **(R 336.2001)**

## EMISSION UNIT SPECIAL CONDITIONS

### EMISSION UNIT SUMMARY TABLE

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

| <b>Emission Unit ID</b> | <b>Emission Unit Description<br/>(Including Process Equipment &amp; Control<br/>Device(s))</b>  | <b>Installation<br/>Date /<br/>Modification<br/>Date</b> | <b>Flexible Group ID</b> |
|-------------------------|---|--|--------------------------|
| EU602-07                | <p>The 63 Unit is a continuous process making silicone gum. Condensers 6186 and 6168 control emissions from the reactor and from product stripping. This emission unit is subject to the miscellaneous organic chemical manufacturing NESHAP in 40 CFR Part 63, Subparts A and FFFF, and to the equipment leak provisions of Subpart UU.</p> <p>The most recent PTI for this emission unit is PTI No. 151-20.</p> | 2000<br>2021   | FGMONMACT                |

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

**EU602-07**  
**EMISSION UNIT CONDITIONS**

**DESCRIPTION**

The 63 Unit is a continuous process making silicone gum. Condensers 6186 and 6168 control emissions from the reactor and from product stripping. This emission unit is subject to the miscellaneous organic chemical manufacturing NESHAP in 40 CFR Part 63, Subparts A and FFFF, and to the equipment leak provisions of Subpart UU.

The most recent PTI for this emission unit is PTI No. 151-20.

**Flexible Group ID:** FGMONMACT

**POLLUTION CONTROL EQUIPMENT**

- Condenser 6186 (East IR Final Vent)
- Condenser 6168 (West IR Final Vent)

**I. EMISSION LIMIT(S)**

| <b>Pollutant</b>   | <b>Limit</b> | <b>Time Period / Operating Scenario</b>                                      | <b>Equipment</b> | <b>Monitoring / Testing Method</b> | <b>Underlying Applicable Requirements</b> |
|--|--------------|--|------------------|------------------------------------|---|
| 1. VOC   | 260 lbs/yr * | 12-month rolling time period as determined at the end of each calendar month | EU602-07         | SC VI.2, VI.4                      | R 336.1702(a)                             |
| * This emission limit does not include fugitive emissions (i.e., emissions from leaking valves, flanges, etc.) from the emission unit. |              |  |                  |                                    |   |

**II. MATERIAL LIMIT(S)**

NA

**III. PROCESS/OPERATIONAL RESTRICTION(S)**

1. The permittee shall not operate EU602-07 with products requiring vacuum stripping unless the exit gas temperature of condenser 6186 is 36°C or less. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**
2. The permittee shall not operate EU602-07 with products that do not require vacuum stripping unless the exit gas temperatures of condenser 6168 and condenser 6186 are both 36°C or less. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**

**IV. DESIGN/EQUIPMENT PARAMETER(S)**

1. The permittee shall not operate EU602-07 with products requiring vacuum stripping unless condenser 6186 is installed, maintained, and operated in a satisfactory manner acceptable to the AQD District Supervisor, which includes meeting the requirements of SC III.1. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**
2. The permittee shall not operate EU602-07 with products that do not require vacuum stripping unless condenser 6168 and condenser 6186 are installed, maintained, and operated in a satisfactory manner acceptable to the AQD District Supervisor, which includes meeting the requirements of SC III.2. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**



3. The permittee shall equip and maintain the condenser 6186 and condenser 6168 with exit gas temperature indicators. The permittee shall calibrate the exit temperature indicators in a satisfactory manner acceptable to the AQD District Supervisor. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**

#### **V. TESTING/SAMPLING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

NA

#### **VI. MONITORING/RECORDKEEPING**

Records shall be maintained on file for a period of five years. **(R 336.1201(3))**

1. The permittee shall complete all required calculations in a format acceptable to the AQD District Supervisor and make them available by the last day of the calendar month, for the previous calendar month, unless otherwise specified in any monitoring/recordkeeping special condition. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**
2. The permittee shall monitor and record, on a continuous basis, the exit gas temperatures of condenser 6186 and condenser 6168 with instrumentation acceptable to the AQD. For the purpose of this condition, "on a continuous basis" is defined as an instantaneous data point recorded at least once every 15 minutes. The permittee may record block average values for 15 minute or shorter periods calculated from all measured data values during each period. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**
3. The permittee shall keep a record of the time periods during which EU602-07 operates with products requiring vacuum stripping and during which EU602-07 operates with products that do not require vacuum stripping. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1224, R 336.1225, R 336.1702(a), R 336.1910)**
4. The permittee shall calculate and keep, in a satisfactory manner, records of monthly and 12-month rolling time period VOC emissions for EU602-07 using production records, operating records, and/or other data acceptable to the AQD District Supervisor. The permittee shall keep all records on file at the facility and make them available to the Department upon request. **(R 336.1702(a))**

#### **VII. REPORTING**

NA

#### **VIII. STACK/VENT RESTRICTION(S)**

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

| <b>Stack &amp; Vent ID</b>   | <b>Maximum Exhaust Diameter / Dimensions (inches)</b> | <b>Minimum Height Above Ground (feet)</b> | <b>Underlying Applicable Requirements</b> |
|--|---|---|---|
| 1. SV602-021 (63 Unit Dimethyl Cyclics Day Tank Vent) <sup>a</sup> | 1   | 43  | R 336.1225,<br>40 CFR 52.21(c)&(d)        |
| 2. SV602-026 (Condenser DV6186 - East IR Final Vent) <sup>a</sup>  | 4   | 43  | R 336.1225,<br>40 CFR 52.21(c)&(d)        |
| 3. SV602-027 (Condenser DV6168 - West IR Final Vent) <sup>a</sup>  | 4   | 43  | R 336.1225,<br>40 CFR 52.21(c)&(d)        |

<sup>a</sup> This vent is not required to discharge unobstructed vertically upwards.

**IX. OTHER REQUIREMENT(S)**

NA

**Footnotes:**

<sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).