## MICHIGAN DEPARTMENT OF ENVIRONMENT, GREAT LAKES, AND ENERGY AIR QUALITY DIVISION

November 20, 2023

PERMIT TO INSTALL 136-23

ISSUED TO
City of Marshall Power Plant

906 South Marshall Avenue Marshall, Michigan 49068

> IN THE COUNTY OF Calhoun

### STATE REGISTRATION NUMBER C6230

The Air Quality Division has approved this Permit to Install, pursuant to the delegation of authority from the Michigan Department of Environment, Great Lakes, and Energy. This permit is hereby issued in accordance with and subject to Section 5505(1) of Article II, Chapter I, Part 55, Air Pollution Control, of the Natural Resources and Environmental Protection Act, 1994 PA 451, as amended. Pursuant to Air Pollution Control Rule 336.1201(1), this permit constitutes the permittee's authority to install the identified emission unit(s) in accordance with all administrative rules of the Department and the attached conditions. Operation of the emission unit(s) identified in this Permit to Install is allowed pursuant to Rule 336.1201(6).

DATE OF RECEIPT OF ALL INFORMATION REQUIRED BY RULE 203:				
November 16, 2023				
DATE PERMIT TO INSTALL APPROVED:	SIGNATURE:			
November 20, 2023				
DATE PERMIT VOIDED:	SIGNATURE:			
DATE LEMMIT VOIDED.	GIONATORE.			
DATE PERMIT REVOKED:	SIGNATURE:			

## **PERMIT TO INSTALL**

## **Table of Contents**

COMMON ACRONYMS	2
POLLUTANT / MEASUREMENT ABBREVIATIONS	
GENERAL CONDITIONS	4
EMISSION UNIT SPECIAL CONDITIONS	6
EMISSION UNIT SUMMARY TABLE	6
FLEXIBLE GROUP SPECIAL CONDITIONS	7
FLEXIBLE GROUP SUMMARY TABLE	7
FGENGINES2,4	8

#### **COMMON ACRONYMS**

AQD Air Quality Division

BACT Best Available Control Technology

CAA Clean Air Act

CAM Compliance Assurance Monitoring
CEMS Continuous Emission Monitoring System

CFR Code of Federal Regulations

COMS Continuous Opacity Monitoring System

Department/department/EGLE Michigan Department of Environment, Great Lakes, and Energy

EU Emission Unit FG Flexible Group

GACS Gallons of Applied Coating Solids

GC General Condition
GHGs Greenhouse Gases

HVLP High Volume Low Pressure\*

ID Identification

IRSLInitial Risk Screening LevelITSLInitial Threshold Screening LevelLAERLowest Achievable Emission RateMACTMaximum Achievable Control TechnologyMAERSMichigan Air Emissions Reporting System

MAP Malfunction Abatement Plan MSDS Material Safety Data Sheet

NA Not Applicable

NAAQS National Ambient Air Quality Standards

NESHAP National Emission Standard for Hazardous Air Pollutants

NSPS New Source Performance Standards

NSR New Source Review
PS Performance Specification

PSD Prevention of Significant Deterioration

PTE Permanent Total Enclosure

PTI Permit to Install

RACT Reasonable Available Control Technology

ROP Renewable Operating Permit

SC Special Condition

SCR Selective Catalytic Reduction
SNCR Selective Non-Catalytic Reduction

SRN State Registration Number

TBD To Be Determined

TEQ Toxicity Equivalence Quotient

USEPA/EPA United States Environmental Protection Agency

VE Visible Emissions

<sup>\*</sup>For HVLP applicators, the pressure measured at the gun air cap shall not exceed 10 psig.

#### **POLLUTANT / MEASUREMENT ABBREVIATIONS**

acfm Actual cubic feet per minute

BTU **British Thermal Unit** °C **Degrees Celsius** CO Carbon Monoxide

CO<sub>2</sub>e Carbon Dioxide Equivalent dscf Dry standard cubic foot dscm Dry standard cubic meter °F Degrees Fahrenheit

Grains gr

HAP Hazardous Air Pollutant

Hg Mercury hr Hour

ΗP Horsepower  $H_2S$ Hydrogen Sulfide

kW Kilowatt lb Pound Meter m Milligram mg Millimeter mm MM Million MW Megawatts

NMOC Non-Methane Organic Compounds

 $NO_{x}$ Oxides of Nitrogen

Nanogram ng

PM Particulate Matter

Particulate Matter equal to or less than 10 microns in diameter PM10 Particulate Matter equal to or less than 2.5 microns in diameter PM2.5

Pounds per hour pph Parts per million ppm

ppmv Parts per million by volume ppmw Parts per million by weight

psia Pounds per square inch absolute Pounds per square inch gauge psig

Standard cubic feet scf

Seconds sec Sulfur Dioxide  $SO_2$ 

TAC **Toxic Air Contaminant** 

Temp Temperature

THC Total Hydrocarbons Tons per year tpy Microgram μg

μm Micrometer or Micron VOC Volatile Organic Compounds

Year yr

#### **GENERAL CONDITIONS**

- 1. The process or process equipment covered by this permit shall not be reconstructed, relocated, or modified, unless a Permit to Install authorizing such action is issued by the Department, except to the extent such action is exempt from the Permit to Install requirements by any applicable rule. (R 336.1201(1))
- 2. If the installation, construction, reconstruction, relocation, or modification of the equipment for which this permit has been approved has not commenced within 18 months, or has been interrupted for 18 months, this permit shall become void unless otherwise authorized by the Department. Furthermore, the permittee or the designated authorized agent shall notify the Department via the Supervisor, Permit Section, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy, P.O. Box 30260, Lansing, Michigan 48909-7760, if it is decided not to pursue the installation, construction, reconstruction, relocation, or modification of the equipment allowed by this Permit to Install. (R 336.1201(4))
- 3. If this Permit to Install is issued for a process or process equipment located at a stationary source that is not subject to the Renewable Operating Permit program requirements pursuant to Rule 210 (R 336.1210), operation of the process or process equipment is allowed by this permit if the equipment performs in accordance with the terms and conditions of this Permit to Install. (R 336.1201(6)(b))
- The Department may, after notice and opportunity for a hearing, revoke this Permit to Install if evidence indicates the process or process equipment is not performing in accordance with the terms and conditions of this permit or is violating the Department's rules or the Clean Air Act. (R 336.1201(8), Section 5510 of Act 451, PA 1994)
- 5. The terms and conditions of this Permit to Install shall apply to any person or legal entity that now or hereafter owns or operates the process or process equipment at the location authorized by this Permit to Install. If the new owner or operator submits a written request to the Department pursuant to Rule 219 and the Department approves the request, this permit will be amended to reflect the change of ownership or operational control. The request must include all of the information required by subrules (1)(a), (b), and (c) of Rule 219 and shall be sent to the District Supervisor, Air Quality Division, Michigan Department of Environment, Great Lakes, and Energy. (R 336.1219)
- 6. Operation of this equipment shall not result in the emission of an air contaminant which causes injurious effects to human health or safety, animal life, plant life of significant economic value, or property, or which causes unreasonable interference with the comfortable enjoyment of life and property. (R 336.1901)
- 7. The permittee shall provide notice of an abnormal condition, start-up, shutdown, or malfunction that results in emissions of a hazardous or toxic air pollutant which continue for more than one hour in excess of any applicable standard or limitation, or emissions of any air contaminant continuing for more than two hours in excess of an applicable standard or limitation, as required in Rule 912, to the Department. The notice shall be provided not later than two business days after start-up, shutdown, or discovery of the abnormal condition or malfunction. Written reports, if required, must be filed with the Department within 10 days after the start-up or shutdown occurred, within 10 days after the abnormal condition or malfunction has been corrected, or within 30 days of discovery of the abnormal condition or malfunction, whichever is first. The written reports shall include all of the information required in Rule 912(5). (R 336.1912)
- 8. Approval of this permit does not exempt the permittee from complying with any future applicable requirements which may be promulgated under Part 55 of 1994 PA 451, as amended or the Federal Clean Air Act.
- 9. Approval of this permit does not obviate the necessity of obtaining such permits or approvals from other units of government as required by law.
- 10. Operation of this equipment may be subject to other requirements of Part 55 of 1994 PA 451, as amended and the rules promulgated thereunder.

- 11. Except as provided in subrules (2) and (3) or unless the special conditions of the Permit to Install include an alternate opacity limit established pursuant to subrule (4) of Rule 301, the permittee shall not cause or permit to be discharged into the outer air from a process or process equipment a visible emission of density greater than the most stringent of the following. The grading of visible emissions shall be determined in accordance with Rule 303 (R 336.1303). (R 336.1301)
  - a) A six-minute average of 20 percent opacity, except for one six-minute average per hour of not more than 27 percent opacity.
  - b) A visible emission limit specified by an applicable federal new source performance standard.
  - c) A visible emission limit specified as a condition of this Permit to Install.
- 12. Collected air contaminants shall be removed as necessary to maintain the equipment at the required operating efficiency. The collection and disposal of air contaminants shall be performed in a manner so as to minimize the introduction of contaminants to the outer air. Transport of collected air contaminants in Priority I and II areas requires the use of material handling methods specified in Rule 370(2). (R 336.1370)
- 13. The Department may require the permittee to conduct acceptable performance tests, at the permittee's expense, in accordance with Rule 1001 and Rule 1003, under any of the conditions listed in Rule 1001. (R 336.2001)

## **EMISSION UNIT SPECIAL CONDITIONS**

## **EMISSION UNIT SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Emission Unit ID	Emission Unit Description (Including Process Equipment & Control Device(s))	Installation Date / Modification Date	Flexible Group ID
EU-ENG-2	Nordberg engine and generator using No. 2 fuel oil and natural gas. The unit is rated at 1130 KW.	1-1-53 TBD	FGENGINES2, 4
EU-ENG-4	Nordberg diesel engine and generator. The unit fires only No. 2 fuel oil. The unit is rated at 1000 KW.	1-1-42 TBD	FGENGINES2,4

Changes to the equipment described in this table are subject to the requirements of R 336.1201, except as allowed by R 336.1278 to R 336.1291.

## **FLEXIBLE GROUP SPECIAL CONDITIONS**

## **FLEXIBLE GROUP SUMMARY TABLE**

The descriptions provided below are for informational purposes and do not constitute enforceable conditions.

Flexible Group ID	Flexible Group Description	Associated Emission Unit IDs
FGEngines2,4	Two engine and generator units sharing the same fuel sampling requirements, and recordkeeping requirements.	EU-ENG-2, EU-ENG-4

# FGENGINES2,4 FLEXIBLE GROUP CONDITIONS

#### **DESCRIPTION**

Two engine and generator units sharing the same fuel sampling requirements, and recordkeeping requirements.

Emission Unit: EU-ENG-2, EU-ENG-4

#### POLLUTION CONTROL EQUIPMENT

NA

#### I. EMISSION LIMIT(S)

NA

#### II. MATERIAL LIMIT(S)

- 1. The permittee shall only use No. 2 fuel oil and/or pipeline grade sweet natural gas in FGEngines2,4. (R 336.1205, R 336.1225)
- 2. The permittee shall not burn more than 56 gallons of No. 2 fuel oil and 40 Mcf/hr of natural gas in EU-ENG-2, during the lifetime of this permit. (R 336.1205, R 336.1225)
- 3. The permittee shall not burn more than 344 gallons of No. 2 fuel oil in EU-ENG-4, during the lifetime of this permit. (R 336.1205, R 336.1225)

#### III. PROCESS/OPERATIONAL RESTRICTION(S)

- 1. The permittee shall not operate EU-ENG-2 and EU-ENG-4 simultaneously. (R 336.1205)
- 2. The permittee shall not operate EU-ENG-2 for more than 4 hours total, during the lifetime of this permit. Upon voidance of this permit, as referenced in SC IX.2, the permittee shall not operate EU-ENG-2.1 (R 336.1205, R 336.1225)
- 3. The permittee shall not operate EU-ENG-4 for more than 4 hours total, during the lifetime of this permit. Upon voidance of this permit, as referenced in SC IX.2, the permittee shall not operate EU-ENG-4.1 (R 336.1205, R 336.1225)

#### IV. DESIGN/EQUIPMENT PARAMETER(S)

NA

#### V. TESTING/SAMPLING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

NA

#### VI. MONITORING/RECORDKEEPING

Records shall be maintained on file for a period of five years. (R 336.1201(3))

- The permittee shall maintain purchase records for ASTM specification fuel oil, specifications or analyses
  provided by the vendor at the time of delivery, analytical results from laboratory testing or any other records
  adequate to demonstrate compliance with the material limit in SC II.1. (R 336.1402, R 336.2803, R 336.2804,
  40 CFR 52.21(c) & (d))
- 2. The permittee shall keep, in a satisfactory manner, records of the following while operating each engine in FGENGINES2,4:
  - a) The total number of hours in which each engine in FGENGINE2,4 has been in operation, since approval of this permit.<sup>1</sup>
  - b) The total amount of No. 2 Fuel oil, in gallons, that has been burned in each engine in FGENGINE2,4, since approval of this permit.<sup>1</sup>
  - c) The total amount of natural gas, in Mcf/hr, that has been burned in EU-ENG-2, since approval of this permit.<sup>1</sup> (R 336.1205, R 336.1225, 40 CFR 52.21 (c) & (d))

#### VII. REPORTING

1. The permittee or the authorized agent pursuant to Rule 204, shall notify the AQD District Supervisor, as well as the AQD Permit Section, upon commencement of, and cessation of, the testing operations of FGENGINES2,4. (R 336.1201(3))

#### VIII. STACK/VENT RESTRICTION(S)

The exhaust gases from the stacks listed in the table below shall be discharged unobstructed vertically upwards to the ambient air unless otherwise noted:

Stack & Vent ID	Maximum Exhaust Diameter / Dimensions (inches)	Minimum Height Above Ground (feet)	Underlying Applicable Requirements
1. SV-ENG-2 <sup>1</sup>	54	30	R 336.1225
			40 CFR 52.21 (c) & (d)
1. SV-ENG-4 <sup>1</sup>	48	34	R 336.1225
			40 CFR 52.21 (c) & (d)

#### IX. OTHER REQUIREMENT(S)

- 1. The permittee shall remove each engine in FGENGINES2,4 from operation immediately following the completion of the respective testing. To continue operation of FGENGINES2,4 at this site after this date, the permittee must apply for and receive a new PTI. (R 336.1205(1)(a) & (3))
- 2. After each engine in FGENGINES2,4 has completed the 4-hour testing operation this permit will be voided. (R 336.1205(1)(a) & (3))
- 3. The permittee shall comply with all applicable provisions of the National Emission Standards for Hazardous Air Pollutants, as specified in 40 CFR Part 63, Subpart A and Subpart ZZZZ, for Stationary Reciprocating Internal Combustion Engines. (40 CFR 63.6595, 40 CFR Part 63, Subparts A and ZZZZ)

#### Footnotes:

<sup>&</sup>lt;sup>1</sup> This condition is state only enforceable and was established pursuant to Rule 201(1)(b).