# FUGITIVE DUST CONTROL PROGRAM

FOR

#### MARTIN MARIETTA MAGNESIA SPECIALTIES LLC SRN: A3900

1800 Eastlake Road Manistee, Michigan 49660

Submitted To

## MICHIGAN DEPARTMENT OF EVIRONMENT, GREAT LAKES, AND ENERGY

Act 451 Part 55, Section 324.5524

Revised: 4/15/21

# TABLE OF CONTENTS

- 1.0 Introduction
- 2.0 Facility Description and Contact Information
- 3.0 Potential Sources of Fugitive Dust
- 4.0 Management of Potential Sources
- 5.0 Record Keeping
- 6.0 Plant Map

#### **1.0 INTRODUCTION**

The Martin Marietta Magnesia Specialties Renewable Operating Permit (ROP) requires the facility to implement and maintain a program for continuous fugitive emissions control for all plant roadways, the plant yard, all material storage piles, and all material handling operations as approved by the District Supervisor in compliance with Natural Resources and Environmental Protection Act 451 Part 55, Section 324.5524.

#### 2.0 FACILITY DESCRIPTION AND CONTACT INFORMATION

#### **2.1 Facility Location**

Martin Marietta Magnesia Specialties, LLC 1800 Eastlake Road Manistee, Michigan 49660

#### 2.2 Facility Contact

Jim Reithel, Vice President of Operations 1800 Eastlake Road Manistee, Michigan 49660

### 2.3 Activities at the Facility

The principle products of the Manistee Plant is Magnesium Oxide (MgO) and Magnesium Hydroxide slurry and powder Mg(OH)<sub>2</sub>. This material can range from a wet slurry to a fine white powder to a rock-hard tan briquette depending on the chemistry and degree of burn. Major process components are a rotary kiln, three vertical Herreshoff furnaces, and two vertical shaft kilns, three precision calciners, and three air-swept dryers.

#### 2.4 Site Map

(see attached map)

#### 3.0 POTENTIAL SOURCES OF FUGITIVE DUST

- 1. Paved roadways
- 2. Unpaved roadway
- 3. Buildings
- 4. Material Handling Operations

### 4.0 MANAGEMENT OF POTENTIAL SOURCES OF FUGITIVE DUST

#### 4.1 Paved Roadways

- a. Posted speed limit in plant is 17 miles per hour.
- b. A road sweeper is employed to clean all paved surfaces. Cleaning of paved surfaces is done by an outside contractor on an as needed basis. The cleaning is suspended from November into April for weather reasons and the limitations of the sweeper. The efficient operation of the sweeper requires spray water. When temperatures drop below freezing, the water lines must be drained to prevent damage to the sweeper.

### 4.2 Unpaved Roadways

The potential for emissions from unpaved roadways is dependent on weather conditions. Unpaved roadways will be treated with brine to control dust as necessary during the months of April through October. Most of the facility now has paved roadways.

### 4.3 Buildings

Material spilled on floors in the process buildings will be swept and returned to the process to minimize fugitive dust from being blown from the buildings.

### 4.4 Material Handling Operations

Dust is controlled at transfer points, screens, mills, loadouts, and silos by fabric filter dust collectors/bag houses. All dust transfer systems from bag houses are enclosed and are designed to return to the process.

Spot spills are remedied using a vac truck and routine housekeeping. Routine housekeeping is accomplished primarily by sweeping, returning most material to the process via belts and elevators designed to receive these materials.

The following emission units have requirements in the ROP regarding fugitive dust plan preventative procedures.

- a. EUN2SMILL: Dust from this unit is controlled by Pulse Jet Baghouse 25-0887. This equipment is monitored and maintained per requirements in the Malfunction Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping practices.
- EU88-SCRNR: Dust from this unit is controlled by Pulse Jet Baghouse 25-0890.
  This equipment is monitored and maintained per requirements in the Malfunction
  Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping practices.
- c. EUN2SMILLTRANS: Dust from this unit is controlled by Pulse Jet Baghouse 25-1020. This equipment is monitored and maintained per requirements in the Malfunction Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping.
- d. EUADDITIVE-DC: Dust from this unit is controlled by Pulse Jet Baghouse 25-0881. This equipment is monitored and maintained per requirements in the Malfunction Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping practices.
- EUHB-BINS: Dust from this unit is controlled by Pulse Jet Baghouse 25-0880.
  This equipment is monitored and maintained per requirements in the Malfunction Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping practices.
- f. EUC-LIME: Dust from this unit is controlled by Pulse Jet Baghouse 25-0873.
  This equipment is monitored and maintained per requirements in the Malfunction

Abatement Plan and the Renewable Operating Permit. Spot spills are cleaned up as needed using routine housekeeping practices.

# 5.0 RECORD KEEPING

Records of frequency of road sweeping and dust suppression application to unpaved roadways will be maintained for a period of five years.

# 6.0 PLANT MAP

