

**SOURCE TEST REPORT  
2021 HYDROGEN CHLORIDE COMPLIANCE  
TESTING  
UNITED STATES STEEL CORPORATION  
GREAT LAKES WORKS  
No. 5 PICKLE LINE  
ECORSE, MICHIGAN**

**RECEIVED**  
APR 08 2021  
AIR QUALITY DIVISION

Prepared For:

**UNITES STATES STEEL CORPORATION  
GREAT LAKES WORKS  
No. 1 QUALITY DRIVE  
ECORSE, MICHIGAN 48229**

For Submittal To:

**EGLE  
525 WEST ALLEGAN STREET  
LANSING, MICHIGAN 48933**

Prepared By:

**Montrose Air Quality Services, LLC  
4949 Fernlee Ave.  
Royal Oak, Michigan 48073**

Document Number: **M049AS-003571-RT-624**  
Test Date: **February 16, 2021**  
Submittal Date: **March 30, 2021**



### REVIEW AND CERTIFICATION

All work, calculations, and other activities and tasks performed and presented in this document were carried out by me or under my direction and supervision. I hereby certify that, to the best of my knowledge, Montrose operated in conformance with the requirements of the Montrose Quality Management System and ASTM D7036-04 during this test project.

Signature:  Date: 03 / 01 / 2021  
Name: Steven Smith Title: Client Project Manager

I have reviewed, technically and editorially, details, calculations, results, conclusions, and other appropriate written materials contained herein. I hereby certify that, to the best of my knowledge, the presented material is authentic, accurate, and conforms to the requirements of the Montrose Quality Management System and ASTM D7036-04.

Signature:  Date: 03 / 01 / 2021  
Name: Matthew Young Title: District Manager

**EXECUTIVE SUMMARY**

Montrose Air Quality Services, LLC (MAQS) was retained by United States Steel Corporation, Great Lakes Works (U. S. Steel) to evaluate Hydrogen Chloride (HCl) from the No. 5 Pickle Line Scrubber inlet and exhaust stacks at the U. S. Steel facility located at No. 1 Quality Drive in Ecorse, Michigan. The testing program was conducted on February 16, 2021.

The testing consisted of triplicate 60-minute test runs at each source. The results of the emission test program are summarized by Table I.

**Table I**  
**Executive Summary Table HCl Emission Rate Summary**

Unit	Emission Rate		Permit Limit	
	HCl (lb/hr)	HCl (PPMV, Dry)	HCl (lb/hr)	HCl (PPMV, Dry)
Pickle Line - Inlet	24.2	479.3		
Pickle Line - Outlet	1.96	38.7	1.64	18

RECEIVED  
 APR 08 2021  
 AIR QUALITY DIVISION

## TABLE OF CONTENTS

<u>SECTION</u>	<u>PAGE</u>
1.0 INTRODUCTION .....	6
1.a IDENTIFICATION, LOCATION, AND DATES OF TEST.....	6
1.b PURPOSE OF TESTING .....	6
1.c SOURCE DESCRIPTION .....	6
1.d TEST PROGRAM CONTACT .....	6
2.0 SUMMARY OF RESULTS .....	7
2.a OPERATING DATA .....	7
2.b APPLICABLE PERMIT .....	7
2.c RESULTS .....	7
2.d EMISSION REGULATION COMPARISON .....	8
3.0 SOURCE DESCRIPTION .....	8
3.a PROCESS DESCRIPTION .....	8
3.b RAW AND FINISHED MATERIALS.....	8
3.c PROCESS CAPACITY.....	8
3.d PROCESS INSTRUMENTATION .....	8
4.0 SAMPLING AND ANALYTICAL PROCEDURES .....	8
4.a SAMPLING TRAIN AND FIELD PROCEDURES.....	9
4.b RECOVERY AND ANALYTICAL PROCEDURES.....	9
4.c SAMPLING PORTS .....	10
4.d TRAVERSE POINTS .....	10
5.0 TEST RESULTS AND DISCUSSION.....	10
5.a RESULTS TABULATION .....	10
5.b DISCUSSION OF RESULTS .....	10
5.c SAMPLING PROCEDURE VARIATIONS .....	11
5.d PROCESS OR CONTROL DEVICE UPSETS.....	11
5.e CONTROL DEVICE MAINTENANCE.....	11
5.f AUDIT SAMPLE ANALYSIS .....	11
5.g CALIBRATION SHEETS.....	11
5.h SAMPLE CALCULATIONS .....	11
5.i FIELD DATA SHEETS .....	11
5.j LABORATORY DATA.....	11

**TABLES**

Table I	Executive Summary Table HCl Emission Rate Summary
Table 1	Testing Personnel Summary
Table 2	HCl Emission Rate Summary
Table 3	No. 5 Pickle Line Scrubber Inlet HCl Detailed Results Summary
Table 4	No. 5 Pickle Line Scrubber Exhaust HCl Detailed Results Summary

**FIGURES**

Figure 1	No. 5 Pickle Line Sampling Location Schematic
Figure 2	No. 5 Pickle Line Scrubber Exhaust Stack Diagram Drawing
Figure 3	USEPA Method 26 Sampling Train
Figure 4	USEPA Method 26A Sampling Train

**APPENDIX**

Appendix A	Field and Computer Generated Raw Data and Field Notes
Appendix B	Equipment Calibration
Appendix C	Example Calculations
Appendix D	Laboratory Results
Appendix E	Production Data

## 1.0 INTRODUCTION

Montrose Air Quality Services, LLC (MAQS) was retained by United States Steel Corporation (U.S. Steel) to conduct an evaluation of the hydrogen chloride (HCl) concentrations and emissions from the No. 5 Pickle Line Scrubber inlet and exhaust stacks. The scrubber is located at the U. S. Steel facility in Ecorse, Michigan. The evaluation consisted of triplicate 60-minute test runs at each sampling location. US EPA Methods 1, 2, 3, 4, 26, and 26A were utilized to perform the study.

All testing was performed in accordance with MAQS test plan PROJ-003571.

EGLI has published a guidance document entitled “Format for Submittal of Source Emission Test Plans and Reports” (November 2019). The following is a summary of the emissions test report in the format suggested by the EGLI test report format guide.

### 1.a IDENTIFICATION, LOCATION, AND DATES OF TEST

Sampling and analysis for the emission test program was conducted on February 16, 2021 at the U.S. Steel facility in Ecorse, Michigan. The test program included evaluation of HCl emissions from the No. 5 Pickle Line inlet and exhaust stacks.

### 1.b PURPOSE OF TESTING

Permit No. ROP 199600132d, issued by State of Michigan Division of Environmental Quality, governs this process.

The allowable HCl emission rate by permit is:

18 ppm HCl with a maximum emission rate of 1.64 pounds per hour or an overall removal efficiency of 97%.

### 1.c SOURCE DESCRIPTION

The No. 5 Pickle Line Scrubber captures and removes acid mist and vapors from the process line. All pickle line tubs are completely covered with capture hoods to evacuate the acid mist and fumes. Ductwork carries the fumes to the packed bed scrubber rated at 16,950 ACFM. The fumes are moved through the scrubber by an I.D. fan.

### 1.d TEST PROGRAM CONTACT

Mr. Todd Wessel  
Client Project Manager  
Montrose Air Quality Services  
4949 Fernlee Avenue  
Royal Oak, Michigan 48073  
Phone (616) 885-4013

Mr. Nathan Ganhs  
U. S. Steel Environmental  
United States Steel Corporation  
Great Lakes Works  
No. 1 Quality Drive  
Ecorse, Michigan 48229  
(313) 749-3857

**Table 1**  
**Testing Personnel Summary**

<b>Name and Title</b>	<b>Affiliation</b>	<b>Telephone</b>
Mr. Nathan Ganhs Environmental Department	U.S. Steel No. 1 Quality Drive Ecorse, Michigan 48229	(313) 749-3857
Mr. Matthew Young District Manager	MAQS 4949 Fernlee Avenue Royal Oak, MI 48073	(586) 744-9133
Mr. Steven Smith Client Project Manager	MAQS 4949 Fernlee Avenue Royal Oak, MI 48073	(248) 548-8072
Mr. Dave Trahan Field Project Manager	MAQS 4949 Fernlee Avenue Royal Oak, MI 48073	(248) 548-8072
Mr. David Koponen Field Technician	MAQS 4949 Fernlee Avenue Royal Oak, MI 48073	(248) 548-8072

## **2.0 SUMMARY OF RESULTS**

Sections 2.a through 2.d summarize the results of the emissions compliance test program.

### **2.a OPERATING DATA**

Operating data monitored included the start and end times of each production cycle and the weights of coiled steel processed.

### **2.b APPLICABLE PERMIT**

The applicable permit for this emissions test program is ROP No. 199600132d.

### **2.c RESULTS**

The overall results of the emission test program are summarized by Table 2 (see Section 5.a). Detailed results for each run can be found in Tables 3 and 4.

## **2.d EMISSION REGULATION COMPARISON**

The results are summarized in Table 2 (Section 5.a).

## **3.0 SOURCE DESCRIPTION**

Sections 3.a through 3.e provide a detailed description of the process.

### **3.a PROCESS DESCRIPTION**

The Pickling process uses a mineral acid (hydrochloric acid) to remove metal oxides formed when steel is hot rolled and cooled in the presence of oxygen. It is necessary to remove these oxides to provide a smooth clean surface for use as hot roll steel and/or to perform subsequent cold forming operations.

The No. 5 Pickle Line at U.S Steel consists of three pickle tubs in series. The fresh acid solution is introduced in the 3<sup>rd</sup> pickle tank. The acid solution then cascades from the 3<sup>rd</sup> tank to the 1<sup>st</sup> tank in a direction counter to the direction of the metal strip. By this countercurrent arrangement, the cleanest strip near the process exit is treated by the freshest acid, ensuring that the steel strip is as free of oxide scale as possible.

The No. 5 Pickle Line Scrubber captures and removes acid mist and vapors from the process line. All pickle line tubs are completely covered with capture hoods to evacuate the acid mist and fumes. Ductwork carries the fumes to the packed bed scrubber rated at 16,950 ACFM. The fumes are moved through the scrubber by an I.D. fan.

### **3.b RAW AND FINISHED MATERIALS**

Raw Material used is hydrochloric acid.

### **3.c PROCESS CAPACITY**

On a typical processing day, U.S Steels Pickle Line will process approximately 300 coils of steel which is approximately 9,000 tons of steel.

### **3.d PROCESS INSTRUMENTATION**

There is no process instrumentation relevant to the testing that was performed. U.S. Steel documented the start and end times of each production cycle and weights of coiled steel processed.

## **4.0 SAMPLING AND ANALYTICAL PROCEDURES**

Sections 4.a through 4.d provide a summary of the sampling and analytical procedures used.

#### 4.a SAMPLING TRAIN AND FIELD PROCEDURES

Measurement of exhaust gas velocity, molecular weight, and moisture content was conducted using the following reference test methods codified at Title 40, Part 60, Appendix A of the Code of Federal Regulations (40 CFR 60, Appendix A):

- Method 1 - "Location of the Sampling Site and Sampling Points"
- Method 2 - "Determination of Stack Gas Velocity and Volumetric Flowrate"
- Method 3 - "Determination of Molecular Weight of Dry Stack Gas"
- Method 4 - "Determination of Moisture Content in Stack Gases"
- Method 26 - "Determination of Hydrogen Halide and Halogen Emissions from Stationary Sources (Non-Isokinetic Method)"
- Method 26A - "Determination of Hydrogen Halide and Halogen Emissions from Stationary Sources (Isokinetic Method)"

Stack gas velocity traverses were conducted in accordance with the procedures outlined in Methods 1 and 2. Figure 1 presents the test port and traverse/sampling point locations used. A cyclonic flow evaluation was conducted at the outlet sampling location. An S-type pitot tube and thermocouple assembly calibrated in accordance with Method 2, Section 4.1.1 was used to measure exhaust gas velocity pressures and temperatures during testing. Because the pitot tube dimensions outlined in Sections 2.6 through 2.8 were within the specified limits, the baseline pitot tube coefficient of 0.84 (dimensionless) was assigned for this testing. Flow rates were not determined at the scrubber inlet. The inlet flow rate was assumed to be equal to the exhaust.

Molecular weight determinations were conducted according to Method 3. The equipment used for this evaluation consisted of a one-way squeeze bulb with connecting tubing and a set of Fyrite® combustion gas analyzers. Moisture content was determined from the condensate collected in the Method 26 and 26A sampling trains according to Method 4.

The Exhaust gas was measured using Method 26A (isokinetic sampling), and the inlet gas was measured using Method 26 (non-isokinetic sampling).

Method 26A was used to measure HCl concentrations and calculate emission rates from the exhaust stack (see Figure 2 for sampling train schematic diagram) MAQS Nutech® Model 2010 modular isokinetic stack sampling system consisted of (1) a Teflon coated stainless steel nozzle; (2) a heated borosilicate or quartz probe liner; (3) a heated borosilicate or quartz glass filter holder containing a pre-weighed 90-mm diameter washed teflon filter with Teflon filter support; (4) a set of two Greensburg-Smith (GS) impingers each of which contained 100 ml of 0.1 Normal Sulfuric Acid (0.1 N H<sub>2</sub>SO<sub>4</sub>), (5) a modified GS impinger that was empty as a knock out impinger, (6) a modified GS impinger containing a known weight of silica gel desiccant; (7) a length of sample line, and (8) a Nutech control case equipped with a pump, dry gas meter, and calibrated orifice.

The Method 26 inlet sampling train utilized an unheated Teflon line in place of a heated glass probe and nozzle. The sampling train was identical to the Method 26A train from the filter holder on back.

A sampling train and pitot tube leak test was conducted before and after each test run. Upon completion of the final leak check for each test run, the impinger train was carefully disassembled. The liquid volume of each impinger was measured gravimetrically and any volume increase was noted on field sheets. The impinger catch solution was then transferred to a pre-cleaned sample container. The impingers were then triple rinsed with deionized water (DI H<sub>2</sub>O), and the rinses added to the sample container. The container was labeled with the test number, test location, test date and the level of liquid was marked on the outside of each container. The samples were then placed in a sealed cooler for storage. In addition, blank samples of the 0.1N H<sub>2</sub>SO<sub>4</sub> and DI were collected. MAQS personnel shipped the samples to Bureau Veritas in Mississauga, Ontario for analysis. All appropriate QA/QC measures were strictly adhered to. Results of the laboratory tests are included in Appendix D.

**4.b RECOVERY AND ANALYTICAL PROCEDURES**

Recovery and analytical procedures were described in Section 4.a.

**4.c SAMPLING PORTS**

Sampling ports are located on the stack and meet method 1 criteria.

**4.d TRAVERSE POINTS**

Sampling port and traverse point locations for the No. 5 Pickle Line exhaust stack are illustrated by Figure 1.

**5.0 TEST RESULTS AND DISCUSSION**

Sections 5.a through 5.k provide a summary of the test results.

**5.a RESULTS TABULATION**

The results of the emissions test program are summarized by Table 2.

**TABLE 2  
 Test Program HCl Emission Rates Summary**

Unit	Emission Rate		Permit Limit	
	HCl (lb/hr)	HCl (PPMV, Dry)	HCl (lb/hr)	HCl (PPMV, Dry)
Pickle Line - Inlet	24.2	479.3		
Pickle Line - Outlet	1.96	38.7	1.64	18

Detailed data for each test run can be found in Tables 3 and 4.

**5.b DISCUSSION OF RESULTS**

Emission limitations for Permit No. 199600132d are summarized by section 1b. The results of the emissions test program are summarized by Table 2 (see section 5.a). Detailed results for each run are summarized by Tables 3 and 4.

**5.c SAMPLING PROCEDURE VARIATIONS**

There were no sampling procedure variations during the test program.

**5.d PROCESS OR CONTROL DEVICE UPSETS**

No upset conditions occurred during testing.

**5.e CONTROL DEVICE MAINTENANCE**

No maintenance was performed during the test program.

**5.f AUDIT SAMPLE ANALYSIS**

No audit samples were required.

**5.g CALIBRATION SHEETS**

Relevant equipment calibration documents are provided as Appendix B.

**5.h SAMPLE CALCULATIONS**

Sample Calculations are provided in Appendix C.

**5.i FIELD DATA SHEETS**

Field documents relevant to the emissions test program are presented in Appendix A.

**5.j LABORATORY DATA**

Laboratory results are presented in Appendix D.

# Tables

**TABLE 3  
 HCl EMISSIONS RESULTS -  
 SCRUBBER INLET**

Run Number	1	2	3	Average
Date	2/16/2021	2/16/2021	2/16/2021	--
Time	10:42-12:10	12:25-13:25	13:38-14:57	--
<b>Flue Gas Parameters</b>				
O <sub>2</sub> , % volume dry	21.0	21.0	21.0	21.0
CO <sub>2</sub> , % volume dry	0.0	0.0	0.0	0.0
moisture content, % volume	15.81	16.56	15.63	16.00
volumetric flow rate, dscfm	8,834	8,897	8,972	8,901
<b>HCl</b>				
ppmvd	517.3	469.0	451.6	479.3
lb/hr	25.9	23.7	23.0	24.2

**TABLE 4  
 HCl EMISSIONS AND RE RESULTS -  
 SCRUBBER EXHAUST**


Run Number	1	2	3	Average
Date	2/16/2021	2/16/2021	2/16/2021	--
Time	10:42-12:16	12:25-13:30	13:38-14:59	--
<b>Process Data*</b>				
charged steel, tons	175	204	202	194
<b>Flue Gas Parameters</b>				
O <sub>2</sub> , % volume dry	21.0	21.0	21.0	21.0
CO <sub>2</sub> , % volume dry	0.0	0.0	0.0	0.0
flue gas temperature, °F	102.8	105.1	102.2	103.3
moisture content, % volume	6.91	7.71	6.43	7.02
volumetric flow rate, dscfm	8,834	8,897	8,972	8,901
<b>HCl</b>				
ppmvd	34.9	34.8	46.3	38.7
lb/hr	1.75	1.76	2.36	1.96
<b>HCl Removal Efficiency (RE)</b>				
%	93.3	92.6	89.7	91.9

\* Process data was provided by US Steel Corporation - Great Lakes Works personnel

† Displayed Run 2 moisture content values are saturated for the respective stack gas temperature and pressure.

# Figures

### EG5-PICKLE-LINE SAMPLING LOCATION SCHEMATIC



**EG5-PICKLE-LINE SCRUBBER EXHAUST TRAVERSE POINT LOCATION DRAWING**





FIGURE 2

FIGURE 3  
US EPA METHOD 26 SAMPLING TRAIN



**FIGURE 4**  
**US EPA METHOD 26A (HALIDES) SAMPLING TRAIN**

